

Highway Maintenance Manual

Chapter 05 Traffic Services and Safety

Section 01 Truck Safety

Subject 05 Maintenance Truck Lighting

Bureau of Highway Operations

November 2022

1.0 Authority/Statutory Provisions/Administrative Code Rules

The following Wisconsin State Statutes and Wisconsin Administrative Codes relate to highway maintenance truck lighting requirements:

Wisconsin State Statute Chapter 347 - Equipment of Vehicles, Lighting Equipment

- s. 347.06 When lighted lamps are required.
- s. 347.07 Special restrictions on lamps and the use thereof.
- s. 347.09 Headlamps on motor vehicles.
- s. 347.10 Headlamps specifications for motor vehicles.
- s. 347.23 Lamps on highway maintenance equipment.
- s. 347.26 Restrictions on certain optional lighting equipment.
- s. 347.26(6) Warning lamps on tow trucks and service vehicles.
- s. 347.26(7) Warning lamps on certain highway vehicles.
- s. 347.26(11) Flashing warning lamps.

Wisconsin Administrative Rule Trans 305 - Standards for Vehicle Equipment

- Trans 305.075 Auxiliary lamps.
- Trans 305.08 Back up lamps.
- Trans 305.09 Direction signal lamps.
- Trans 305.11 Headlamps.
- Trans 305.48 Subchapter IV-Heavy Trucks.

Wisconsin Administrative Rule Trans 327 - Motor Carrier Safety

 Trans 327.03(4) - Federal regulations adopted - Federal Motor Carrier Safety Regulations. Volume I -Driver Regulations, 49CFR, Part 393 - Parts and Accessories Necessary for Safe Operation.

2.0 Definitions

<u>Auxiliary Lamp</u> - Any lamp mounted on a maintenance truck with a bulb having wattage in excess of 10 watts and is not required equipment under Wisconsin State Statute Ch. 347 or Trans 305, except a spotlight.

<u>Back Up Lamp</u> - Any lamp designed to provide road illumination to the rear of a maintenance truck when the vehicle is in reverse gear.

<u>All-Directional Lamp</u> - An auxiliary lamp mounted at the highest practicable point on a maintenance truck to give an adequate warning of the presence of the truck and to show safe clearance for passing or overtaking the truck.

<u>Heavy Truck</u> - A motor truck, truck tractor, or road tractor with a gross vehicle weight rating or actual gross weight of more than 10,000 pounds.

Maintenance Truck - A highway maintenance truck used for winter maintenance operations.

November 2022 Page 1

<u>Plow Lamp</u> - An auxiliary, or replacement, headlamp mounted on a maintenance truck used during snow plowing or salting operations.

<u>Safety Lamp</u> - An auxiliary lamp on a maintenance truck mounted to be able to warn vehicles approaching from the rear of the truck.

3.0 Required Maintenance Truck Lighting

The following lamps are required on highway winter maintenance trucks in accordance with Wisconsin State Statutes and Wisconsin Administrative Codes:

- Headlamps In accordance with ss. 347.09 and 347.10, Wis. Stats., and Trans 305.11.
- Plow Lamps In accordance with ss. 347.09(1)(a) and 347.09(2), Wis. Stats., and Trans 305.075.
- All-Directional Lamps In accordance with ss. 347.23(4) and 347.26(7), Wis. Stats.

Snow and ice control equipment operating on the state highway system are required to have all-directional lamp(s) with the following minimum lighting specifications for standard identification:

- 1. Mount all-directional lamp(s) located on the truck cab either on a self-leveling bracket on the front end of the truck box body or in a rubber seat on the cab protector (optional) so the light is visible when the truck body is in a raised position.
- 2. Amber or green in color and visible from all directions (360°).
 - a. All-directional lamps shall be a flashing (strobe) type or a revolving (beacon) type. If a flashing (strobe) type, the number of flashes per minute shall be 60 to 120 flashes per minute. If a revolving (beacon) type, the number of revolutions shall be 45 to 90 rpm. Flashing (strobe) type shall be high intensity with a wide-angle pattern.
 - b. Minimum light intensity shall be:
 - 1. Flashing (strobe) type = 500,000 candle power (c.p.)
 - 2. Revolving (beacon) types = two bulbs @ 35,000 c.p. each. (light emitting diode or LED type lamps recommended)
- 3. Rear safety lamps in accordance with ss. 347.26(7) and 347.26(11), Wis. Stats.
 - a. All snow and ice control maintenance trucks operating on the state highway system shall have, in addition to the all-directional lamp(s), flashing (strobe), amber or green safety lamps mounted to provide warning to vehicles approaching from the rear of the truck. Mount lamps so they are clearly visible to approaching traffic and functional when the truck box is in the raised position.
 - b. Alternating, flashing (strobe) safety lamps shall be wide-angle, fog, 8,800 c.p. each, mounted in or on the truck box corner post, type model. An alternative model is the flashing (strobe) high-intensity or LED model with a wide-angle (or vertical 180°) pattern. The number of flashes shall be 60 to 120 flashes per minute.
- 4. Auxiliary lamps in accordance with ss. 347.07 and 347.26, Wis. Stats., and Trans 305.075.

Equip maintenance trucks used on high volume (>25,000 AADT) highway winter patrol sections including Interstate, or four-lane, or more, freeways or expressway type highways with the following auxiliary lamps:

- a. High intensity discharge (HID) plow lamps that comply with s. 347.26(2), Wis. Stats. Bulb should be a 35-watt, xenon lamp using xenon gas and no filament. Color temperature should be a minimum of 4,100 degrees K.
- b. Wing plow (left or right) lamp(s) and wing-end marker to be used to warn approaching vehicles of the presence of the wing plow when in operation. A self-contained LED, red lamp is recommended. All LED lamps shall meet the appropriate federal regulations for its design.

November 2022 Page 2

Notes:

- 1. A string of lights (PVC tube totally encasing mini-lamps, spaced at one inch (1") intervals that produce a glowing neon-like appearance) outlining the top and outer edge of the wing plow is an acceptable alternative for the wing plow lamp.
- 2. A white lamp mounted on the rearview mirror and aimed at the extreme edge of the wing plow will assist the snow plow operator with seeing the end of the plow but is not an acceptable alternative for the wing plow lamp and/or wing-end marker.

4.0 Optional Truck Lighting

The following lamps are optional on all highway winter maintenance trucks:

- 1. Salt spreader auxiliary lamp(s) used to illuminate the spreader for the benefit of the operator shall be in accordance with s. 347.07(2), Wis. Stats. (referenced to color) and s. 347.13(3), Wis. Stats. (referenced to visible distance).
- 2. Amber or white color lamps may be mounted and aimed to shine on the salt spreader and not visible to the rear at a distance greater than fifty (50) feet.
- 3. Suggested mounting locations are the rear corner of the truck box or the side of the salt spreader unit.

The following lamps are optional on patrol trucks normally assigned to winter patrol sections on low volume (<25,000 AADT), two lane state highways:

- a. High intensity discharge (HID) lamps refer to HMM 05-01-05, Section 3.4 for guidelines.
- Wing plow (left or right) lamp(s) and wing end marker refer to HMM 05-01-05, Section 3.4 for guidelines.

5.0 Supplemental Truck Lighting Information and References.

- 1. Effective Date: maintenance trucks purchased after January 1, 2005 used for winter maintenance activities on state highways shall meet the truck lighting requirements contained within this chapter.
- 2. Trucks normally assigned to low volume (<25,000 AADT) state highway winter patrol sections that assist on high volume (>25,000 AADT) state highway winter patrol sections during extreme winter weather conditions shall meet the required truck lighting section (Section 3) of this chapter.
- 3. Winter patrol sections or county highway winter patrol sections assisting on high volume (>25,000 AADT) state highway winter patrol sections during extreme winter weather conditions shall meet the required truck lighting section (Section 3) of this chapter.
- 4. The installation of signage on the rear of winter maintenance trucks is at the discretion of the county highway departments. Signage, such as "Stay Back 200 Feet", is appropriate. Guidelines for sign size, letter size, thickness and spacing, and exact wording are available from the department.
- 5. Guidelines for Truck Conspicuity Marking can be found in HMM 05-01-06.

November 2022 Page 3