



Wisconsin Department of Transportation

February 4, 2016

Division of Transportation Systems Development

Bureau of Project Development
4802 Sheboygan Avenue, Rm 601
P O Box 7916
Madison, WI 53707-7916

Telephone: (608) 266-1631
Facsimile (FAX): (608) 266-8459

NOTICE TO ALL CONTRACTORS:

Proposal #05: 1071-02-60
La Crosse - Tomah
W County Line to USH 12
IH 90
Monroe County

Letting of February 9, 2016

This is Addendum No. 01, which provides for the following:

Special Provisions

Revised Special Provisions	
Article No.	Description
10	Culvert Pipe Liners, 18-Inch, Item 520.9700.S.01; Culvert Pipe Liners, 24-Inch, Item 520.9700.S.02; Culvert Pipe Liners, 30-Inch, Item 520.9700.S.03; Cleaning Culvert Pipes for Liner Verification, Item 520.9750.S.01.

The responsibility for notifying potential subcontractors and suppliers of these changes remains with the prime contractor.

Sincerely,

Mike Coleman

Proposal Development Specialist
Proposal Management Section

ADDENDUM NO. 01

1071-02-60

February 4, 2015

Special Provisions

- 10. Culvert Pipe Liners, 18-Inch, Item 520.9700.S.01; Culvert Pipe Liners, 24-Inch, Item 520.9700.S.02; Culvert Pipe Liners, 30-Inch, Item 520.9700.S.03; Cleaning Culvert Pipes for Liner Verification, Item 520.9750.S.01.**

*Replace entire section titled **B.1 General** with the following:*

B.1 General

Provide flow calculations at the preconstruction conference. Use contractor-proposed liner properties, the Manning's coefficients listed on the department's approved products list, and base calculations on existing culvert sizes and liner sizes the plans show. Ensure that pipes when lined have a capacity within $\pm 5\%$ of the original full flow capacity of the pipe with the exception of the following:

- The culvert at sta. 1835+00A shall be lined with a product on the department's approved products list and have an inside diameter of 18 inches \pm half an inch.
- The culvert at sta. 1840+00 shall be lined with a product on the department's approved products list and have an inside diameter of 24 inches \pm half an inch.
- The culvert at sta. 1844+70A shall be lined with a product on the department's approved products list and have an inside diameter of 18 inches \pm half an inch.

END OF ADDENDUM