



# Wisconsin Department of Transportation

March 7, 2017

## Division of Transportation Systems Development

Bureau of Project Development  
4802 Sheboygan Avenue, Rm 601  
P O Box 7916  
Madison, WI 53707-7916

Telephone: (608) 266-1631  
Facsimile (FAX): (608) 266-8459

### NOTICE TO ALL CONTRACTORS:

**Proposal #28:** 1180-00-63  
Brule - Ino  
Sznaider Road to CTH A  
USH 2  
Bayfield County

1540-00-60  
River Falls – New Richmond  
USH 12 to CTH G  
STH 65  
St. Croix County

1550-01-60  
C Cumberland, Elm ST and 2<sup>nd</sup> Ave  
West Junction STH 48 to Charrie Ln  
USH 63  
Barron County

8070-00-60  
Amery – Millton  
York Park Entrance to USH 8  
STH 46  
Polk County

8120-00-60  
Mckinley – Rice Lake  
STH 25 to West Avenue  
STH 48  
Barron County

8510-01-60  
Port Wing - Superior  
East County Line to CTH F  
STH 13  
Douglas County

### Letting of March 14, 2017

This is Addendum No. 01, which provides for the following:

#### Special Provisions:

Revised Special Provisions	
Article No.	Description
13	Fog Seal, SPV.0180.03

The responsibility for notifying potential subcontractors and suppliers of these changes remains with the prime contractor.

Sincerely,

*Mike Coleman*

Proposal Development Specialist  
Proposal Management Section

**ADDENDUM NO. 01**

**1180-00-63, 1540-00-60, 1550-01-60, 8070-00-60, 8120-00-60, 8510-01-60**

**March 7, 2017**

**Special Provisions**

**13. Fog Seal, SPV.0180.03**

*Replace entire section titled **B.1 Asphaltic Material** with the following:*

**B.1 Asphaltic Material**

Provide CSS-1H or CQS-1H, asphaltic material for fog seal. The CSS-1H and CQS-1H, asphaltic material for fog sealing, shall meet the following requirements for the type and grade specified. Only Asphaltic Material supplied from a certified source is approved for use.

Emulsified asphalt compatibility with aggregate shall be verified prior to construction. This shall be done through documentation for material provider.

Emulsified Asphalt

The emulsified asphalt shall meet the requirements of AASHTO M-316 subject to the following modification:

- CSS-1H and CQS-1H shall be produced by using polymer modified base asphalt only. The use of Latex modification shall not be allowed. Any emulsion not meeting this requirement shall not be used.

END OF ADDENDUM