


ORDER OF SHEETS

Section No.	1	Title
Section No.	2	Typical Sections and Details
Section No.	3	Estimate of Quantities
Section No.	3	Miscellaneous Quantities
Section No.	4	Right of Way Plat
Section No.	5	Plan and Profile
Section No.	6	Standard Detail Drawings
Section No.	7	Sign Plates
Section No.	8	Structure Plans
Section No.	9	Computer Earthwork Data
Section No.	9	Cross Sections

TOTAL SHEETS = 90



DESIGN DESIGNATION

A.A.D.T.	2022	=	1140
A.A.D.T.	2042	=	1390
D.H.V.	(2042)	=	174
D.D.		=	50/50
T.		=	5.8%
DESIGN SPEED		=	40 MPH
ESALS		=	170,000

CONVENTIONAL SYMBOLS

PLAN	PROFILE
CORPORATE LIMITS	GRADE LINE
PROPERTY LINE	ORIGINAL GROUND
LOT LINE	MARSH OR ROCK PROFILE (To be noted as such)
LIMITED HIGHWAY EASEMENT	SPECIAL DITCH
EXISTING RIGHT OF WAY	GRADE ELEVATION
PROPOSED OR NEW R/W LINE	CULVERT (Profile View)
SLOPE INTERCEPT	UTILITIES
REFERENCE LINE	ELECTRIC
EXISTING CULVERT	FIBER OPTIC
PROPOSED CULVERT (Box or Pipe)	GAS
COMBUSTIBLE FLUIDS	SANITARY SEWER
MARSH AREA	STORM SEWER
WOODED OR SHRUB AREA	TELEPHONE
	WATER
	UTILITY PEDESTAL
	POWER POLE
	TELEPHONE POLE

STATE OF WISCONSIN  
DEPARTMENT OF TRANSPORTATION

PLAN OF PROPOSED IMPROVEMENT


PORTAGE COUNTY LINE - CTH G

SOUTH BR LITTLE WOLF RIVER BRIDGE

CTH B

WAUPACA COUNTY

STATE PROJECT NUMBER  
**6832-11-70**



TOTAL NET LENGTH OF CENTERLINE = 0.047 MI.

HORIZONTAL POSITIONS SHOWN ON THIS PLAN ARE WISCONSIN COORDINATE REFERENCE SYSTEM (WISCRS), WAUPACA COUNTY, NAD83 (2011), IN U.S. SURVEY FEET. POSITIONS SHOWN ARE GRID COORDINATES, GRID BEARINGS, AND GRID DISTANCES. GRID DISTANCES ARE THE SAME AS GROUND DISTANCES. ELEVATIONS ARE REFERENCED TO NAVD 88 (2012). GPS DERIVED ELEVATIONS ARE BASED ON GEOID 12B.

STATE PROJECT	FEDERAL PROJECT	
	PROJECT	CONTRACT
6832-11-70	WISC 2022130	1

ACCEPTED FOR  
WAUPACA COUNTY

7-15-2021 *Craig H. B...*  
DATE COUNTY HIGHWAY COMMISSIONER

ORIGINAL PLANS PREPARED BY  
**AYRES**

WISCONSIN  
PHILLIP J. VERVILLE III  
E36336  
GREEN BAY, WI  
PROFESSIONAL ENGINEER  
7/14/21  
(Date)

STATE OF WISCONSIN  
DEPARTMENT OF TRANSPORTATION

PREPARED BY \_\_\_\_\_ AYRES  
Designer \_\_\_\_\_ AYRES  
Project Manager \_\_\_\_\_ JASON SCHAEFFER  
Regional Supervisor \_\_\_\_\_ ROBIN STAFFORD

APPROVED FOR THE DEPARTMENT  
DATE 7/22/2021 *Phillip J. Verville III*  
(Signature)

E

**GENERAL NOTES**

THE LOCATION OF EXISTING UTILITY FACILITIES AS SHOWN ON THE PLANS ARE APPROXIMATE. THERE MAY BE OTHER UTILITY FACILITIES WITHIN THE PROJECT AREA THAT ARE NOT SHOWN.

NO TREES OR SHRUBS ARE TO BE REMOVED WITHOUT APPROVAL OF THE ENGINEER.

BEARINGS SHOWN ON THIS PLAN ARE TRUE BEARINGS TO THE NEAREST SECOND.

ALL TIES ON THIS PLAN ARE HORIZONTAL UNLESS DESCRIBED OTHERWISE.

EROSION CONTROL LOCATIONS AS SHOWN ON THE EROSION CONTROL PLAN ARE APPROXIMATE. THE EXACT LOCATIONS WILL BE DETERMINED BY THE ENGINEER IN THE FIELD.

DISTURBED AREAS WITHIN THE RIGHT OF WAY, EXCEPT THE AREAS WITHIN THE FINISHED SUBGRADE SHOULDER POINTS ARE TO BE SEEDED AND EROSION MAT AS DIRECTED BY THE ENGINEER.

WISDOT WILL FURNISH A BENCHMARK MONUMENT TO BE SET BY THE CONTRACTOR.

SAW CUT LOCATIONS SHOWN ON THE PLAN ARE SUBJECT TO ADJUSTMENT BY THE ENGINEER IN THE FIELD. THE LINE OF SUCH SAW CUTS WILL BE NEATLY DELINEATED THROUGH THE ASPHALT WITHOUT ANY DAMAGE TO THE REMAINING PORTION OF THE EXISTING PAVEMENT.

**UTILITIES**

**ELECTRICITY & GAS/PETROLUM**

**ALLIANT ENERGY**  
708 NE 7th STREET  
MARION, WI 54950  
ATTENTION: SCOTT FISHER  
E-MAIL: scottfisher@alliantenergy.com

TELEPHONE 715-824-3510

**ELECTRICITY - TRANSMISSION**

ATC

PO BOX 47  
WAUKESHA, WI 53187  
ATTENTION: TONY MARCINIAK  
E-MAIL: amarciniak@atcllc.com

TELEPHONE 262-506-6814

**SANITARY SEWER**

VILLAGE OF SCANDINAVIA

PO BOX 24  
SCANDINAVIA, WI 54977  
ATTENTION: RENEE SMITH  
E-MAIL: villageofscandiclerk@tds.net

TELEPHONE 715-467-0036

**COMMUNICATION LINE**

AMHERST COMMUNICATIONS

120 MILL STREET  
PO BOX 279  
AMHERST, WI 54406  
ATTENTION: TOM IVERSON  
E-MAIL: tiverson@tvalleycom.com

TELEPHONE 715-824-2006  
CELL 715-572-5630

**SOLARUS**

440 EAST GRAND AVENUE  
WISCONSIN RAPIDS, WI 54494  
ATTENTION: DENNIS PIERCE  
E-MAIL: pierce@solarus.net

TELEPHONE 715-572-0152

**TDS TELECOM**

525 JUNCTION ROAD  
MADISON, WI 53717  
ATTENTION: MATT SCHULTE  
E-MAIL: matt.schulte@tdstelecom.com

TELEPHONE 262-754-3063

**MEDIACOM**

1240 HIGHWAY 52 SOUTH  
CHATFIELD, MN 55923  
ATTENTION: CRAIG EGGERT  
E-MAIL: ceggert@mediacomcc.com

TELEPHONE 563-419-5160

\*-NOT A MEMBER OF DIGGERS HOTLINE

**RUNOFF COEFFICIENT TABLE**


	HYDROLOGIC SOIL GROUP											
	A			B			C			D		
	SLOPE RANGE (PERCENT)			SLOPE RANGE (PERCENT)			SLOPE RANGE (PERCENT)			SLOPE RANGE (PERCENT)		
LAND USE:	0-2	2-6	6 & OVER									
ROW CROPS	.08 .22	.16 .30	.22 .38	.12 .26	.20 .34	.27 .44	.15 .30	.24 .37	.33 .50	.19 .34	.28 .41	.38 .56
MEDIAN STRIP-TURF	.19 .24	.20 .26	.24 .30	.19 .25	.22 .28	.26 .33	.20 .26	.23 .30	.30 .37	.20 .27	.25 .32	.30 .40
SIDE SLOPE-TURF			.25 .32			.27 .34			.28 .36			.30 .38
PAVEMENT:												
ASPHALT	.70 - .95											
CONCRETE	.80 - .95											
BRICK	.70 - .80											
DRIVES, WALKS	.75 - .85											
ROOFS	.75 - .95											
GRAVEL ROADS, SHOULDERS	.40 - .60											

TOTAL AREA EXPECTED TO BE DISTURBED BY CONSTRUCTION ACTIVITIES = 0.45 ACRES  
SOIL GROUP C

**STANDARD ABBREVIATIONS**


ADT	AVERAGE DAILY TRAFFIC	NC	NORMAL CROWN
AC	ASPHALT CEMENT	PT	POINT OF TANGENCY
AGG	AGGREGATE	PC	POINT OF CURVATURE
ASPH	ASPHALT	PI	POINT OF INTERSECTION
BM	BENCH MARK	PE	PRIVATE ENTRANCE
C/L	CENTERLINE	R	RADIUS
CONC	CONCRETE	REM	REMOVE
CMP	CORRUGATED METAL PIPE	R/L OR RL	REFERENCE LINE
CR.	CREEK	RCCP	REINFORCED CONCRETE CULVERT PIPE
D	DEGREE OF CURVE	RCPSS	REINFORCED CONCRETE PIPE STORM SEWER
DHV	DESIGN HOUR VOLUME	R.O.	RUNOUT
ESALS	EQUIVALENT SINGLE AXIS LOADS	R/W	RIGHT-OF-WAY
EXIST	EXISTING	STA	STATION
FE	FIELD ENTRANCE	SE	SUPER ELEVATION
HYD	HYDRANT	SS	STORM SEWER
IP	IRON PIPE OR PIN	T	TANGENT
L	LENGTH OF CURVE	TEL	TELEPHONE
LC	LONG CHORD OF CURVE	TLE	TEMPORARY LIMITED EASEMENT
LR	LENGTH OF RUNOFF	T	TRUCKS
MH	MANHOLE	VC	VERTICAL CURVE
		W	WELL





**EXISTING TYPICAL SECTION FOR CTH B**



STA. 7+55.2 - STA. 12+87.2





**FINISHED TYPICAL SECTION FOR CTH B**

STA. 7+55.2 - STA. 8+00 RT  
STA. 7+86 - STA. 8+00 LT  
STA. 10+44 - STA. 10+75 LT  
STA. 10+50 - STA. 12+87.2 RT


\*\* GUARDRAIL TO BE INSTALLED  
STA. 10+50 TO 11+78.8 RT









**TYPICAL INSTALLATION FOR EROSION MAT  
DITCH LINING**  
(SEE MISCELLANEOUS QUANTITIES FOR LOCATIONS)




**EROSION MAT AT END OF PIPE**  
(CONCRETE OR METAL)  
(SEE MISCELLANEOUS QUANTITIES FOR LOCATIONS)



**TOP VIEW**  
**ROCK BAGS USED FOR SILT FENCE RELIEF DETAIL**




**SIDE VIEW (SINGLE LAYER)**



\* LENGTH AND NUMBER OF BAGS MAY VARY  
DEPENDING ON DESIRED DEPTH OF WATER POOL


**SIDE VIEW (MULTIPLE LAYER)**

**ROCK BAGS DITCH CHECK**  
PAID AS ROCK BAGS




NOTE: BACKFILL QUANTITIES COMPUTED FROM POINT "d" TO COMPENSATE FOR PROBABLE DISPLACED MARSH AREA.

**TYPICAL SECTION-MARSH EXCAVATION**



NOTE:  
SILT FENCE POSTS FOR THE TURN-AROUND SHOULD BE ON THE OUTSIDE OF THE TURN-AROUND.

PLAN VIEW



SIDE VIEW


**SILT FENCE TURN-AROUND DETAIL**



LEGEND

- EROSION MAT URBAN CLASS I, TYPE B
- ##### EROSION MAT CLASS II, TYPE C
- SILT FENCE
- ◄— TURBIDITY BARRIER
- - - SLOPE INTERCEPT
- ~ SURFACE WATER FLOW
- OOO CULVERT PIPE CHECK
- [R] ROCK BAGS
- [ASPH] ASPHALTIC FLUME

CONSTRUCTION LIMITS  
STA. 31+50



STA. 9+16.50 CTH B=  
STA. 30+00.00 CTH G  
Y = 380739.931  
X = 519006.734

Estimate Of Quantities

6832-11-70

Line	Item	Item Description	Unit	Total	Qty
0002	201.0105	Clearing	STA	3.000	3.000
0004	201.0205	Grubbing	STA	3.000	3.000
0006	203.0100	Removing Small Pipe Culverts	EACH	2.000	2.000
0008	203.0260	Removing Structure Over Waterway Minimal Debris (structure) 01. B-68-15	EACH	1.000	1.000
0010	204.0165	Removing Guardrail	LF	15.000	15.000
0012	205.0100	Excavation Common	CY	753.000	753.000
0014	205.0400	Excavation Marsh	CY	45.000	45.000
0016	206.1000	Excavation for Structures Bridges (structure) 01. B-68-148	LS	1.000	1.000
0018	208.1100	Select Borrow	CY	69.000	69.000
0020	210.1500	Backfill Structure Type A	TON	440.000	440.000
0022	213.0100	Finishing Roadway (project) 01. 6832-11-70	EACH	1.000	1.000
0024	305.0110	Base Aggregate Dense 3/4-Inch	TON	125.000	125.000
0026	305.0120	Base Aggregate Dense 1 1/4-Inch	TON	1,290.000	1,290.000
0028	455.0605	Tack Coat	GAL	61.000	61.000
0030	465.0105	Asphaltic Surface	TON	280.000	280.000
0032	465.0315	Asphaltic Flumes	SY	25.000	25.000
0034	502.0100	Concrete Masonry Bridges	CY	244.000	244.000
0036	502.3200	Protective Surface Treatment	SY	265.000	265.000
0038	505.0400	Bar Steel Reinforcement HS Structures	LB	5,390.000	5,390.000
0040	505.0600	Bar Steel Reinforcement HS Coated Structures	LB	32,950.000	32,950.000
0042	513.4061	Railing Tubular Type M	LF	52.200	52.200
0044	513.7084	Railing Steel Type NY4	LF	77.300	77.300
0046	516.0500	Rubberized Membrane Waterproofing	SY	20.000	20.000
0048	522.2414	Culvert Pipe Reinforced Concrete Horizontal Elliptical Class HE-IV 14x23-Inch	LF	172.000	172.000
0050	522.2614	Apron Endwalls for Culvert Pipe Reinforced Concrete Horizontal Elliptical 14x23-Inch	EACH	4.000	4.000
0052	550.0500	Pile Points	EACH	16.000	16.000
0054	550.2106	Piling CIP Concrete 10 3/4 X 0.365-Inch	LF	680.000	680.000
0056	601.0411	Concrete Curb & Gutter 30-Inch Type D	LF	145.000	145.000
0058	602.0405	Concrete Sidewalk 4-Inch	SF	150.000	150.000
0060	606.0300	Riprap Heavy	CY	170.000	170.000
0062	612.0406	Pipe Underdrain Wrapped 6-Inch	LF	180.000	180.000
0064	614.2300	MGS Guardrail 3	LF	88.000	88.000
0066	614.2500	MGS Thrie Beam Transition	LF	78.000	78.000
0068	614.2610	MGS Guardrail Terminal EAT	EACH	2.000	2.000
0070	619.1000	Mobilization	EACH	1.000	1.000
0072	624.0100	Water	MGAL	14.000	14.000
0074	625.0100	Topsoil	SY	1,150.000	1,150.000
0076	628.1504	Silt Fence	LF	950.000	950.000
0078	628.1520	Silt Fence Maintenance	LF	1,900.000	1,900.000
0080	628.1905	Mobilizations Erosion Control	EACH	5.000	5.000
0082	628.1910	Mobilizations Emergency Erosion Control	EACH	3.000	3.000
0084	628.2008	Erosion Mat Urban Class I Type B	SY	1,000.000	1,000.000
0086	628.2027	Erosion Mat Class II Type C	SY	150.000	150.000
0088	628.6005	Turbidity Barriers	SY	200.000	200.000
0090	628.7555	Culvert Pipe Checks	EACH	10.000	10.000
0092	628.7570	Rock Bags	EACH	40.000	40.000
0094	629.0210	Fertilizer Type B	CWT	1.000	1.000
0096	630.0120	Seeding Mixture No. 20	LB	35.000	35.000
0098	630.0500	Seed Water	MGAL	25.000	25.000

Estimate Of Quantities

6832-11-70

Line	Item	Item Description	Unit	Total	Qty
0100	634.0614	Posts Wood 4x6-Inch X 14-FT	EACH	11.000	11.000
0102	637.2210	Signs Type II Reflective H	SF	33.680	33.680
0104	637.2230	Signs Type II Reflective F	SF	20.000	20.000
0106	638.2102	Moving Signs Type II	EACH	1.000	1.000
0108	638.2602	Removing Signs Type II	EACH	20.000	20.000
0110	638.3000	Removing Small Sign Supports	EACH	21.000	21.000
0112	642.5001	Field Office Type B	EACH	1.000	1.000
0114	643.0420	Traffic Control Barricades Type III	DAY	3,360.000	3,360.000
0116	643.0705	Traffic Control Warning Lights Type A	DAY	5,040.000	5,040.000
0118	643.0900	Traffic Control Signs	DAY	2,310.000	2,310.000
0120	643.5000	Traffic Control	EACH	1.000	1.000
0122	645.0111	Geotextile Type DF Schedule A	SY	120.000	120.000
0124	645.0120	Geotextile Type HR	SY	315.000	315.000
0126	646.1020	Marking Line Epoxy 4-Inch	LF	1,400.000	1,400.000
0128	650.4500	Construction Staking Subgrade	LF	619.000	619.000
0130	650.5000	Construction Staking Base	LF	619.000	619.000
0132	650.5500	Construction Staking Curb Gutter and Curb & Gutter	LF	145.000	145.000
0134	650.6000	Construction Staking Pipe Culverts	EACH	1.000	1.000
0136	650.6500	Construction Staking Structure Layout (structure) 01. B-68-148	LS	1.000	1.000
0138	650.9910	Construction Staking Supplemental Control (project) 01. 6832-11-70	LS	1.000	1.000
0140	650.9920	Construction Staking Slope Stakes	LF	619.000	619.000
0142	690.0150	Sawing Asphalt	LF	332.000	332.000
0144	715.0502	Incentive Strength Concrete Structures	DOL	1,464.000	1,464.000
0146	999.2000.S	Installing and Maintaining Bird Deterrent System (station) 01. 10+00	EACH	1.000	1.000
0148	ASP.1T0A	On-the-Job Training Apprentice at \$5.00/HR	HRS	300.000	300.000
0150	ASP.1T0G	On-the-Job Training Graduate at \$5.00/HR	HRS	600.000	600.000

CLEARING AND GRUBBING

CATEGORY	STATION	TO	STATION	LOCATION	201.0105 CLEARING STA	201.0205 GRUBBING STA
0010	8+00	-	11+00	CTH B	3	3
TOTAL 0010					3	3

REMOVING CULVERTS

CATEGORY	STATION	LOCATION	203.0100 REMOVING SMALL PIPE CULVERTS EACH	REMARKS
0010	8+35	CTH B, RT	1	18" CMP
TOTAL 0010			1	
0030	30+40	CTH G	1	18" CMP
TOTAL 0030			1	
PROJECT TOTAL			2	

REMOVING GUARDRAIL

CATEGORY	STATION	TO	STATION	LOCATION	204.0165 REMOVING GUARDRAIL LF
0010	9+70	-	9+85	CTH B, RT	15
TOTAL 0010					15

EARTHWORK SUMMARY

CATEGORY	STATION	TO	STATION	LOCATION	205.0100 EXCAVATION COMMON CUT (1)	205.0400 EXCAVATION MARSH (2)	208.1100 SELECT BORROW FACTOR 1.50 (3)	UNEXPANDED FILL	EXPANDED FILL FACTOR 1.30 (4)	MASS ORDINATE +/- (5)
0010	10+28.27	-	10+50	CTH B (EAST OF STRUCTURE)	38	15	23	13	17	21
0010	10+50	-	10+75	CTH B - NE QUADRANT	5	0	0	7	9	-4
0010	10+50	-	12+87.2	CTH B - SE QUADRANT	57	21	32	24	31	26
TOTAL 0010					100	36	55	44	57	43
0030	7+55.2	-	8+00	CTH B - SW QUADRANT	15	0	0	0	0	15
0030	7+85.9	-	8+00	CTH B - NW QUADRANT	5	0	0	0	0	5
0030	8+00	-	9+77.73	CTH B (WEST OF STRUCTURE)	316	9	14	56	73	243
0030	30+13	-	31+50	CTH G	317	0	0	2	3	314
TOTAL 0030					653	9	14	58	76	577
PROJECT TOTAL					753	45	69	102	133	620

- 1) Cut = Available Material
- 2) Marsh Excavation to be backfilled with Select Borrow material as shown in cross sections.
- 3) Expanded Marsh Backfill = Select Borrow Material, item 208.1100
- 4) Expanded Fill = Unexpanded Fill \* Fill Factor
- 5) Mass Ordinate + or - quantity calculated for the Category. Plus indicates an excess of material. Minus indicates a shortage of material.

3

BASE AGGREGATE DENSE

CATEGORY	STATION	TO	STATION	LOCATION	305.0110	305.0120	624.0100	REMARKS
					BASE AGGREGATE DENSE 3/4-INCH TON	BASE AGGREGATE DENSE 1 1/4-INCH TON	WATER MGAL	
0010	10+28	-	12+87	CTH B	40	230	3	
TOTAL 0010					40	230	3	
0030	7+55	-	9+78	CTH B	50	600	6	
0030	30+13	-	31+50	CTH G	35	460	5	
TOTAL 0030					85	1,060	11	
PROJECT TOTAL					125	1,290	14	

ASPHALTIC SURFACE ITEMS

CATEGORY	STATION	TO	STATION	LOCATION	455.0605	465.0105	465.0315	REMARKS
					TACK COAT GAL	ASPHALTIC SURFACE TON	ASPHALTIC FLUMES SY	
0010	10+28	-	12+87	CTH B	5	24	10	
TOTAL 0010					5	24	10	
0030	7+55	-	9+78	CTH B	31	142	-	
0030	30+13	-	31+50	CTH G	25	114	15	
TOTAL 0030					56	256	15	
PROJECT TOTAL					61	280	25	

3

CULVERT PIPES AND APRON ENDWALLS

CATEGORY	STATION	LOCATION	522.2414	522.2614	650.6000	STATION & OFFSET		END OF PIPE INVERT	
			CULVERT PIPE REINFORCED CONCRETE HORIZONTAL ELLIPTICAL CLASS HE-IV 14X23-INCH LF	APRON ENDWALLS FOR CULVERT PIPE REINFORCED CONCRETE HORIZONTAL ELLIPTICAL 14X23-INCH EACH	CONSTRUCTION STAKING PIPE CULVERTS EACH	INLET	OUTLET	INLET	OUTLET
0010	8+75	CTH B, RT	124	2	-	8+00.7, 26.7' RT	9+25.0, 20' RT	931.0	927.5
TOTAL 0010			124	2	0				
0030	30+46	CTH G	48	2	1	30+46.6, 22.0' LT	30+46.6, 26.0' RT	929.0	928.0
TOTAL 0030			48	2	1				
PROJECT TOTAL			172	4	1				

NOTE: STATION, OFFSET AND ELEVATION TO END OF PIPE

CONCRETE CURB AND GUTTER AND SIDEWALK

CATEGORY	STATION	TO	STATION	LOCATION	601.0411	602.0405
					CONCRETE CURB & GUTTER 30-INCH TYPE D LF	CONCRETE SIDEWALK 4-INCH SF
0010	10+30	-	10+40	CTH B, LT	25	150
TOTAL 0010					25	150
0030	30+15	-	30+60	CTH G, LT & RT	120	-
TOTAL 0030					120	0
PROJECT TOTAL					145	150

RIPRAP AND GEOTEXTILE FABRIC

CATEGORY	STATION	LOCATION	* 606.0300 RIPRAP HEAVY CY	* 645.0120 GEOTEXTILE TYPE HR SY
			0010	10+45
TOTAL 0010			10	15

MGS GUARDRAIL

CATEGORY	STATION TO	STATION	LOCATION	614.2300 MGS GUARDRAIL 3 LF	614.2500 MGS THRIE BEAM TRANSITION LF	614.2610 MGS GUARDRAIL TERMINAL EAT EACH
				0010	8+59	- 9+75
0010	10+26	- 11+79	CTH B, RT	63	39	1
TOTAL 0010				88	78	2

SILT FENCE

CATEGORY	STATION TO	STATION	LOCATION	628.1504 SILT FENCE LF	628.1520 SILT FENCE MAINTENANCE LF
				0010	8+35
0010	10+25	- 12+90	CTH B, LT & RT	320	640
0010	UNDISTRIBUTED			100	200
TOTAL 0010				560	1,120
0030	7+85	- 8+60	CTH B, LT	90	180
0030	30+25	- 31+50	CTH G, LT & RT	250	500
0030	UNDISTRIBUTED			50	100
TOTAL 0030				390	780
PROJECT TOTAL				950	1,900

LANDSCAPING ITEMS

CATEGORY	STATION TO	STATION	LOCATION	625.0100 TOPSOIL SY	628.2008 EROSION MAT URBAN CLASS I TYPE B SY	628.2027 EROSION MAT CLASS II TYPE C SY	629.0210 FERTILIZER TYPE B CWT	630.0120 SEEDING MIXTURE NO. 20 LB	630.0500 SEED WATER MGAL
				0010	7+55	- 9+78	CTH B, RT	250	210
0010	10+28	- 10+75	CTH B, LT	40	-	40	-	1	1
0010	10+28	- 12+87	CTH B, RT	320	320	-	0.2	9	7
0010	UNDISTRIBUTED			80	60	20	0.1	3	1
TOTAL 0010				690	590	100	0.5	20	15
0030	7+85	- 8+60	CTH B, LT	70	70	-	0.1	2	2
0030	30+13	- 31+50	CTH G, LT & RT	340	300	40	0.2	9	7
0030	UNDISTRIBUTED			50	40	10	0.2	4	1
TOTAL 0030				460	410	50	0.5	15	10
PROJECT TOTAL				1,150	1,000	150	1.0	35	25

TURBIDITY BARRIERS

CATEGORY	LOCATION	628.6005 TURBIDITY BARRIERS SY
0010	WEST ABUTMENT	100
0010	EAST ABUTMENT	100
TOTAL 0010		200

CULVERT PIPE CHECKS

CATEGORY	STATION	LOCATION	628.7555 CULVERT PIPE CHECKS EACH
0010	8+25	CTH B, RT	3
0010	UNDISTRIBUTED		2
TOTAL 0010			5
0030	30+45	CTH G, LT	3
0030	UNDISTRIBUTED		2
TOTAL 0030			5
PROJECT TOTAL			10

ROCK BAGS

CATEGORY	STATION	LOCATION	628.7570 ROCK BAGS EACH
0010	9+75	CTH B, LT & RT	10
0010	10+30	CTH B, LT & RT	10
0010	11+75	CTH B, RT	5
0010	UNDISTRIBUTED		15
TOTAL 0010			40

MOBILIZATIONS EROSION CONTROL

CATEGORY	LOCATION	628.1905 MOBILIZATIONS EROSION CONTROL EACH	628.1910 MOBILIZATIONS EMERGENCY EROSION CONTROL EACH
0010	PROJECT LIMITS	5	3
TOTAL 0010		5	3

TYPE II SIGNS AND SUPPORTS

CATEGORY	STATION	LOCATION	SIGN CODE	W	X	H	634.0614	637.2210	637.2230	638.2102	638.2602	638.3000	REMARKS
							POSTS WOOD 4X6-INCH X 14-FT EACH	SIGNS TYPE II REFLECTIVE H SF	SIGNS TYPE II REFLECTIVE F SF	MOVING SIGNS TYPE II EACH	REMOVING SIGNS TYPE II EACH	REMOVING SMALL SIGN SUPPORTS EACH	
0010	8+75	CTH B, RT	J13-1	24"	X	45"	1	7.50	-	-	1	1	COUNTY G, LEFT ARROW
0010	9+25	CTH B, RT	W1-7	48"	X	24"	1	-	8.00	-	1	1	
0010	9+70	CTH B, LT	J13-1	24"	X	45"	1	7.50	-	-	1	1	COUNTY G, RIGHT ARROW
0010	9+70	CTH B, LT	W5-52L	12"	X	36"	1	-	3.00	-	1	1	
0010	9+75	CTH B, RT	W5-52R	12"	X	36"	1	-	3.00	-	1	1	
0010	10+25	CTH B, RT	W5-52L	12"	X	36"	1	-	3.00	-	1	1	
0010	10+45	CTH B, LT	W5-52R	12"	X	36"	1	-	3.00	-	1	1	
0010	11+25	CTH B, RT	J4-1	24"	X	36"	1	6.00	-	-	1	1	EAST, COUNTY B
0010		PROJECT LIMITS		--	X	--	-	-	-	-	8	8	NARROW BRIDGE, WEIGHT POSTING, OBJECT MARKERS
0010	EAST AND WEST OF PROJECT LIMITS			--	X	--	-	-	-	-	2	2	WEIGHT POSTING XX MILES AHEAD
TOTAL 0010							8	21.00	20.00	0	18	18	
0030	30+55	CTH G, RT	R1-1	30"	X	30"	1	5.18	-	-	1	1	STOP
0030	30+55	CTH G, RT	J13-1	24"	X	45"	1	7.50	-	-	1	1	COUNTY B, DOUBLE ARROW
0030	31+35	CTH G, RT	R12-53	24"	X	30"	1	-	-	1	-	1	
TOTAL 0030							3	12.68	0	1	2	3	
PROJECT TOTAL							11	33.68	20.00	1	20	21	

TRAFFIC CONTROL SUMMARY

CATEGORY	LOCATION	DAYS	643.0420 BARRICADES TYPE III		643.0705 WARNING LIGHTS TYPE A		643.0900 SIGNS		REMARKS
			NO. IN SERVICE	DAY	NO. IN SERVICE	DAY	NO. IN SERVICE	DAY	
0010	CTH B / GILMAN RD	70	2	140	4	280	3	210	BRIDGE OUT 3 MILES AHEAD - SEE BARRICADES AND SIGNS FOR MAINLINE CLOSURES DETAIL C
0010	CTH B / ACADEMY DR	70	2	140	4	280	3	210	BRIDGE OUT 0.1 MILES AHEAD - SEE BARRICADES AND SIGNS FOR MAINLINE CLOSURES DETAIL C
0010	CTH G / NOTTLESON RD	70	2	140	4	280	3	210	ROAD CLOSED 0.4 MILES AHEAD LOCAL TRAFFIC ONLY - SEE BARRICADES AND SIGNS FOR MAINLINE CLOSURES DETAIL C
0010	NORTH OF WORK ZONE LIMITS	70	7	490	10	700	4	280	SEE BARRICADES AND SIGNS FOR MAINLINE CLOSURES DETAIL C
0010	WEST OF WORK ZONE LIMITS	70	7	490	10	700	4	280	SEE BARRICADES AND SIGNS FOR MAINLINE CLOSURES DETAIL C
0010	EAST OF WORK ZONE LIMITS	70	7	490	10	700	4	280	SEE BARRICADES AND SIGNS FOR MAINLINE CLOSURES DETAIL C
0010	NORTH WORK ZONE LIMITS	70	7	490	10	700	4	280	SEE BARRICADES AND SIGNS FOR MAINLINE CLOSURES DETAIL D
0010	WEST WORK ZONE LIMITS	70	7	490	10	700	4	280	SEE BARRICADES AND SIGNS FOR MAINLINE CLOSURES DETAIL D
0010	EAST WORK ZONE LIMITS	70	7	490	10	700	4	280	SEE BARRICADES AND SIGNS FOR MAINLINE CLOSURES DETAIL D
TOTAL 0010				3,360		5,040		2,310	

NOTE:  
DETOUR WILL BE SIGNED AND MAINTAINED BY WAUPACA COUNTY HIGHWAY DEPARTMENT.

MARKING LINE

CATEGORY	STATION	TO	STATION	LOCATION	646.1020 MARKING LINE EPOXY 4-INCH LF
0010	7+85	-	8+55	CTH B, LT	70
0010	8+00	-	10+50	CTH B	500
0010	7+55	-	12+85	CTH B, RT	530
0010	9+75	-	10+75	CTH B, LT	100
TOTAL 0010					1,200
0030	30+50	-	31+50	CTH G	200
TOTAL 0030					200
PROJECT TOTAL					1,400

CONSTRUCTION STAKING

CATEGORY	STATION	TO	STATION	LOCATION	650.4500 SUBGRADE LF	650.5000 BASE LF	650.5500 CURB GUTTER AND CURB & GUTTER LF	650.6500.01 STRUCTURE LAYOUT (B-68-148) LS	650.9910.01 SUPPLEMENTAL CONTROL (6832-11-70) LS	650.9920 SLOPE STAKES LF
0010	7+55	-	12+87	CTH B	-	-	-	-	1	-
0010	10+28	-	12+87	CTH B	259	259	25	-	-	259
TOTAL 0010					259	259	25	0	1	259
0020	9+78	-	10+28	CTH B	-	-	-	1	-	-
TOTAL 0020					0	0	0	1	0	0
0030	7+55	-	9+78	CTH B	223	223	-	-	-	223
0030	30+13	-	31+50	CTH G	137	137	120	-	-	137
TOTAL 0030					360	360	120	0	0	360
PROJECT TOTAL					619	619	145	1	1	619

SAWING

CATEGORY	STATION	TO	STATION	LOCATION	690.0150 SAWING ASPHALT LF
0010	7+55	-	8+00	CTH B	80
0010	10+50	-	12+25	CTH B	230
TOTAL 0010					310
0030	31+50	-		CTH G	22
TOTAL 0030					22
PROJECT TOTAL					332

# VILLAGE

NE-SW  
15-23-11

NW-SE  
15-23-11

## SCHEDULE OF LANDS AND INTERESTS REQUIRED

PARCEL NUMBER	OWNER(S)	INTEREST REQUIRED	TLE SQ. FT.
1	D&S ERICKSON FAMILY OF SCANDINAVIA, LLC	TLE	561
2	COREY A. AND JESSICA R. PAULSEN	TLE	3473
50	ALLIANT ENERGY-ELECTRIC	TEMP. RELEASE	---
51	ALLIANT ENERGY-GAS	TEMP. RELEASE	---

OWNER'S NAMES ARE SHOWN FOR REFERENCE PURPOSES ONLY AND ARE SUBJECT TO CHANGE PRIOR TO THE TRANSFER OF LAND INTERESTS TO THE COUNTY

- 50** ALLIANT ENERGY-ELECTRIC  
VOL. 281 RECORDS, PAGE 159  
DOC. NO. 266108 - PARCEL 1  
VOL. 283 RECORDS, PAGE 507  
DOC. NO. 267982 - PARCEL 1
- 51** ALLIANT ENERGY-GAS  
VOL. 396 RECORDS, PAGE 380  
DOC. NO. 317103 - PARCEL 1

JAY R. MORK

JAY R. AND MARY A. MORK  
LOT 1 CSM 7550

FOUND BERNTSEN NAIL  
Y = 382128.057  
X = 518964.975

CONSTRUCTION LIMITS  
STA. 31+50

BURIED TELEPHONE LINE  
(APPROXIMATE LOCATION)

CONSTRUCTION LIMITS  
STA. 7+55.2

EXISTING RW

BEGIN PROJECT  
STA. 8+00

STA. 8+00

Y = 380754.429  
X = 518891.140

Y = 380754.429  
X = 518891.140

TOWN AND VILLAGE OF SCANDINAVIA

STRUCTURE B-68-148  
REQ'D.

BURIED FIBER OPTIC  
(APPROXIMATE LOCATION)

BURIED TELEPHONE LINE  
(APPROXIMATE LOCATION)

CONSTRUCTION LIMITS  
STA. 12+87.2

CTH B  
CURVE DATA

PI STA = 5+55.70

Y = 380786.289

X = 518648.373

DELTA = 5°49'13"

D = 0°54'34"

T = 320.27'

L = 639.99'

R = 6300.00'

PC STA = 2+35.44

Y = 380794.955

X = 518328.222

PT STA = 8+75.42

Y = 380745.201

X = 518965.994

BK = S88°26'58.1"E

AH = S82°37'44.6"E

CP#401

STA. 15+63.19-45.35' LT.

3/4" REBAR W/ CAP NE QUAD.

MAIN ST. AND ACADEMY DR.

25' W. OF PP#23-11-15.4

Y = 380701.945

X = 519653.899

CTH G  
CURVE DATA

PI STA = 30+86.35

Y = 380825.563

X = 519017.811

DELTA = 12°47'52"

D = 11°07'31"

T = 57.76'

L = 115.03'

R = 515.00'

PC STA = 30+28.59

Y = 380768.285

X = 519010.401

PT STA = 31+43.62

Y = 380883.061

X = 519012.349

BK = N07°22'15.4"E

AH = N05°25'36.5"W

SW-SE  
15-23-11

COREY A. AND JESSICA R. PAULSEN


2

LOT 1 CSM 5416  
VOL. 18, PAGE 86, DOC. NO. 614621

SCANDINAVIA

5

5



STA. 10+00  
REMOVE STRUCTURE B-68-0015  
SINGLE SPAN STEEL DECK GIRDER BRIDGE  
29.0 FEET LONG  
26.5 FOOT CLEAR ROADWAY


STA. 10+00  
STRUCTURE B-68-148 REQ'D.  
SINGLE SPAN, CONCRETE FLAT SLAB BRIDGE  
50.5 FEET LONG  
30 FOOT CLEAR ROADWAY

PROJECT NO: 6832-11-70	HWY: CTH B	COUNTY: WAUPACA	PLAN AND PROFILE:	SHEET	E
------------------------	------------	-----------------	-------------------	-------	---

5


5

### CTH G PROFILE




## Standard Detail Drawing List


08D01-22A	CONCRETE CURB & GUTTER
08D01-22B	CONCRETE CURB, TIES AND CURB AND GUTTER APPLICATIONS
08D04-05	CONCRETE SURFACE DRAINS & ASPHALTIC FLUMES
08D21-01	DRIVEWAYS WITHOUT CURB & GUTTER
08E09-06	SILT FENCE
08E11-02	TURBIDITY BARRIER
08E15-01	CULVERT PIPE CHECK
08F02-01	APRON ENDWALLS FOR PIPE ARCH AND ELLIPTICAL PIPE
08F04-07	JOINT TIES FOR CONCRETE PIPE AND CONCRETE COLLAR DETAIL
12A03-10	NAME PLATE (STRUCTURES)
13C19-03	HMA LONGITUDINAL JOINTS
14B42-07A	MIDWEST GUARDRAIL SYSTEM (MGS) GUARDRAIL
14B42-07B	MIDWEST GUARDRAIL SYSTEM (MGS) GUARDRAIL
14B42-07C	MIDWEST GUARDRAIL SYSTEM (MGS) GUARDRAIL
14B42-07D	MIDWEST GUARDRAIL SYSTEM (MGS) GUARDRAIL
14B44-04A	MIDWEST GUARDRAIL SYSTEM ENERGY ABSORBING TERMINAL (MGS)
14B44-04B	MIDWEST GUARDRAIL SYSTEM ENERGY ABSORBING TERMINAL (MGS)
14B44-04C	MIDWEST GUARDRAIL SYSTEM ENERGY ABSORBING TERMINAL (MGS)
14B45-05A	MIDWEST GUARDRAIL SYSTEM THRIE BEAM TRANSITION (MGS)
14B45-05B	MIDWEST GUARDRAIL SYSTEM THRIE BEAM TRANSITION (MGS)
14B45-05C	MIDWEST GUARDRAIL SYSTEM THRIE BEAM TRANSITION (MGS)
14B45-05H	MIDWEST GUARDRAIL SYSTEM THRIE BEAM TRANSITION (MGS)
15C02-08A	BARRICADES AND SIGNS FOR MAINLINE CLOSURES
15C02-08B	BARRICADES AND SIGNS FOR VARIOUS CLOSURES
15C06-09	SIGNING & MARKING FOR TWO LANE BRIDGES
15C08-20A	LONGITUDINAL MARKING (MAINLINE)
15C11-09B	CHANNELIZING DEVICES DRUMS, CONES, BARRICADES AND VERTICAL PANELS
15C35-04A	PAVEMENT MARKING (INTERSECTIONS)




TYPES A<sup>①</sup> & D




6" SLOPED CURB TYPES G<sup>①</sup> & J




4" SLOPED CURB TYPES G<sup>①</sup> & J




TYPES K<sup>①</sup> & L  
(OPTIONAL CURB SHAPE)




TYPES K<sup>①</sup> & L  
CONCRETE CURB AND GUTTER 30"




TYPES A<sup>①</sup> & D  
CONCRETE CURB AND GUTTER 18"



6" SLOPED CURB TYPES A<sup>①</sup> & D




4" SLOPED CURB TYPES A<sup>①</sup> & D  
CONCRETE CURB AND GUTTER 36"



4" SLOPED CURB TYPES R<sup>①</sup> & T


TBT & TBTT	X
30"	22"
36"	28"



TYPES TBT & TBTT<sup>①</sup>  
CONCRETE CURB AND GUTTER


PAVEMENT THICKNESS  
AND MAXIMUM CONCRETE  
PANEL WIDTH TABLE

PAVEMENT THICKNESS	MAXIMUM PANEL WIDTH
LESS THAN 10"	12'
10" & ABOVE	15'



PARTIAL SECTION OF PAVEMENT \*  
WITH INTEGRAL CURB AND GUTTER

\* BIKE LANE IS NOT SHOWN



REVERSE SLOPE GUTTER<sup>⑥</sup>  
(TYPICAL FOR ALL CURB & GUTTER TYPES)

GENERAL NOTES


DETAILS OF CONSTRUCTION AND WORKMANSHIP NOT SHOWN ON THIS DRAWING SHALL CONFORM TO THE PERTINENT REQUIREMENTS OF THE CONTRACT.

PAVEMENT TIES AND TIE BARS SHALL BE EPOXY COATED IN CONFORMANCE WITH SUBSECTION 505.2.6.2 OF THE STANDARD SPECIFICATIONS.


INTEGRAL CURB AND GUTTER SHALL CONFORM TO THE DETAILS SHOWN FOR CONCRETE CURB AND GUTTER INCLUDING THE TRANSVERSE GUTTER SLOPE.

UNLESS OTHERWISE SHOWN ON THE TYPICAL CROSS SECTIONS, THE BASE AGGREGATE AND COMMON EXCAVATION LIMITS ARE 2' - 0" BEHIND THE BACK OF CURBS.

- ① TIE BARS ARE REQUIRED FOR CURB AND GUTTERS TYPES A, G, K, R, AND TBTT.
- ② THE BOTTOM OF CURB AND GUTTER MAY BE CONSTRUCTED EITHER LEVEL OR PARALLEL TO THE SLOPE OF THE SUBGRADE OR BASE AGGREGATE PROVIDED A 6" MINIMUM GUTTER THICKNESS IS MAINTAINED.
- ③ USE 8" MINIMUM GUTTER THICKNESS WHEN USED WITH AN ADJACENT CONCRETE TRUCK APRON PLACED BEHIND BACK OF CURB.
- ④ THE BOTTOM OF CURB AND GUTTER MAY BE CONSTRUCTED EITHER LEVEL OR PARALLEL TO THE SLOPE OF THE SUBGRADE OR BASE AGGREGATE PROVIDED A 8" MINIMUM GUTTER THICKNESS IS MAINTAINED.
- ⑤ UNLESS OTHERWISE NOTED, FOR STAKING PURPOSES THE FACE OF CURB IS 6" FROM THE BACK OF CURB.
- ⑥ WHEN REVERSE SLOPE GUTTER IS REQUIRED, THE LOCATION(S) WILL BE SHOWN ELSEWHERE IN THE PLAN.
- ⑦ USE 4% GUTTER CROSS SLOPE UNLESS OTHERWISE NOTED IN THE PLANS.
- ⑧ INCLUDE LONGITUDINAL JOINT AND TIE BARS ALONG LANE EDGE WHEN CONCRETE PANEL WIDTH EXCEEDS THE MAXIMUM WIDTH PER TABLE BELOW. LONGITUDINAL JOINT(S) ARE NOT ALLOWED WITHIN TRAFFIC LANES AND BIKE LANES. LONGITUDINAL JOINT MAY BE SAWED.
- ⑨ CONCRETE CURB AND GUTTER 4-INCH SLOPED 30-INCH TYPE "R" AND "T" = 17 INCHES  
CONCRETE CURB AND GUTTER 4-INCH SLOPED 36-INCH TYPE "R" AND "T" = 23 INCHES



**END SECTION CURB AND GUTTER**



**DETAIL OF CURB AND GUTTER AT INLETS**  
(TYPICAL H INLET COVER SHOWN)


**GENERAL NOTES**

DETAILS OF CONSTRUCTION AND WORKMANSHIP NOT SHOWN ON THIS DRAWING SHALL CONFORM TO THE PERTINENT REQUIREMENTS OF THE CONTRACT.


PAVEMENT TIES AND TIE BARS SHALL BE EPOXY COATED IN CONFORMANCE WITH SUBSECTION 505.2.6.2 OF THE STANDARD SPECIFICATIONS.

UNLESS OTHERWISE SHOWN ON THE TYPICAL CROSS SECTIONS, THE BASE AGGREGATE AND COMMON EXCAVATION LIMITS ARE 2' - 0" BEHIND THE BACK OF CURBS.


- ① TIE BARS ARE REQUIRED FOR CURB AND GUTTERS TYPES A, G, K, R, AND TBTT.
- ② THE BOTTOM OF CURB AND GUTTER MAY BE CONSTRUCTED EITHER LEVEL OR PARALLEL TO THE SLOPE OF THE SUBGRADE OR BASE AGGREGATE PROVIDED A 6" MINIMUM GUTTER THICKNESS IS MAINTAINED.
- ⑨ REFER TO SDD 08D18 AND 08D19 FOR ADDITIONAL DRIVEWAY ENTRANCE CURB DETAILS.



**TYPICAL TIE BAR LOCATION** ①




**TYPES A ① & D**




**TYPES G ① & J**

**CONCRETE CURB**




**PLAN VIEW**



**SECTION A - A**

**TIE BARS DRILLED INTO EXISTING PAVEMENT**



**DRIVEWAY ENTRANCE CURB** ⑨  
(WHEN DIRECTED BY THE ENGINEER)

**CONCRETE CURB, TIES AND CURB AND GUTTER APPLICATIONS**

STATE OF WISCONSIN  
DEPARTMENT OF TRANSPORTATION


APPROVED  
February 2021 /S/ Rodney Taylor  
DATE ROADWAY STANDARDS DEVELOPMENT  
ENGINEER

FHWA


**ASPHALTIC FLUME**

NOTE: TAPER CURB ENDS TO GUTTER IN 1'-0"


INCREASE  $\phi$  FROM RIGHT ANGLE TO BEST FIT FIELD CONDITIONS



**PLAN VIEW FLUME AT CURB END**



**SECTION B-B**





**GENERAL NOTES**

DETAILS OF CONSTRUCTION, MATERIALS AND WORKMANSHIP NOT SHOWN ON THIS DRAWING SHALL CONFORM TO PERTINENT REQUIREMENTS OF THE STANDARD SPECIFICATIONS AND APPLICABLE SPECIAL PROVISIONS.


WELDED STEEL WIRE FABRIC SHALL BE IN ACCORDANCE WITH AASHTO SPECIFICATION M55.

- ① JOINTS SHALL BE 1/8 TO 1/4 INCH WIDE BY 1 1/2 INCHES DEEP AND SPACED AT UNIFORM INTERVALS OF APPROXIMATELY 4 FEET.
- ② GEOTEXTILE FABRIC TYPE "R" SHALL UNDERLAY THE FULL LENGTH AND WIDTH OF THE CONCRETE SURFACE DRAIN AND RIPRAP.
- ③ CONCRETE SURFACE DRAIN WITHOUT CURB AND GUTTER MAY BE USED ON BACKSLOPES WHEN SPECIFIED

**③ CONCRETE SURFACE DRAIN**




**SECTION D-D**



**CONCRETE SURFACE DRAINS & ASPHALTIC FLUMES**

STATE OF WISCONSIN  
DEPARTMENT OF TRANSPORTATION


APPROVED  
9-4-08 /S/ Jerry H. Zogg  
DATE ROADWAY STANDARDS DEVELOPMENT ENGINEER  
FHWA



**PLAN VIEW**  
(UNPAVED SHOULDER ON HIGHWAY)

**PLAN VIEW**  
(PAVED SHOULDER ON HIGHWAY)


**RURAL DRIVEWAY INTERSECTION DETAIL  
(NO CURB AND GUTTER OR SIDEWALK)**




**TYPICAL CROSS SECTION FOR  
PRIVATE DRIVE OR FIELD ENTRANCE  
AGGREGATE SURFACE**

\*\* SLOPE CAN VARY WITH SPEED. SEE 11-45-30.6.2

POSTED SPEED MPH	MAX. SLOPE
<35	4:1
≥ 35 TO < 60	6:1
≥60	10:1




**TYPICAL DRIVEWAY PROFILES**




**TYPICAL CROSS SECTION FOR  
PRIVATE DRIVE OR FIELD ENTRANCE  
ASPHALTIC SURFACE**

<b>DRIVEWAYS WITHOUT CURB AND GUTTER</b>	
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION	
APPROVED December 2017 DATE	/S/ Rodney Taylor ROADWAY STANDARDS DEVELOPMENT UNIT SUPERVISOR
FHWA	



PLAN VIEW  
TYPICAL APPLICATION OF SILT FENCE




SITUATION 1 SITUATION 2  
PLAN VIEW  
SILT FENCE AT MEDIAN SURFACE DRAINS

**GENERAL NOTES**


DETAILS OF CONSTRUCTION NOT SHOWN ON THIS DRAWING SHALL CONFORM TO THE PERTINENT REQUIREMENTS OF THE STANDARD SPECIFICATIONS AND APPLICABLE SPECIAL PROVISIONS.

- ① HORIZONTAL BRACE REQUIRED WITH 2" X 4" WOODEN FRAME OR EQUIVALENT AT TOP OF POSTS.
- ② FOR MANUAL INSTALLATIONS THE TRENCH SHALL BE A MINIMUM OF 4" WIDE & 6" DEEP TO BURY AND ANCHOR THE GEOTEXTILE FABRIC. FOLD MATERIAL TO FIT TRENCH AND BACKFILL & COMPACT TRENCH WITH EXCAVATED SOIL.
- ③ WOOD POSTS SHALL BE A MINIMUM SIZE OF 1 1/8" X 1 1/8" OF OAK OR HICKORY.
- ④ SILT FENCE TO EXTEND ACROSS THE TOP OF THE PIPE.
- ⑤ CONSTRUCT SILT FENCE FROM A CONTINUOUS ROLL IF POSSIBLE BY CUTTING LENGTHS TO AVOID JOINTS. IF A JOINT IS NECESSARY USE ONE OF THE FOLLOWING TWO METHODS; A) OVERLAP THE END POSTS AND TWIST, OR ROTATE, AT LEAST 180 DEGREES, B) HOOK THE END OF EACH SILT FENCE LENGTH.




TRENCH DETAIL

NOTE: ADDITIONAL POST DEPTH OR TIE BACKS MAY BE REQUIRED IN UNSTABLE SOILS




SILT FENCE

\* NOTE: 8'-0" POST SPACING ALLOWED IF A WOVEN GEOTEXTILE FABRIC IS USED.




JOINING TWO LENGTHS OF SILT FENCE ⑤




SILT FENCE TIE BACK  
(WHEN REQUIRED BY THE ENGINEER)

<b>SILT FENCE</b>	
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION	
APPROVED 4-29-05 DATE	/S/ Beth Canestra CHIEF ROADWAY DEVELOPMENT ENGINEER
FHWA	




**SECTION B - B**

**TURBIDITY BARRIER - FLOAT ALTERNATIVE  
CAUTION - SEE NOTE 6**




**PLAN VIEW**



**SECTION A - A**

**TURBIDITY BARRIER - STANDARD POST INSTALLATION**



**PLAN VIEW**


**TURBIDITY BARRIER PLACEMENT DETAILS**

**GENERAL NOTES**


DETAILS OF CONSTRUCTION, MATERIALS AND WORKMANSHIP NOT SHOWN ON THIS DRAWING SHALL CONFORM TO THE PERTINENT REQUIREMENTS OF THE STANDARD SPECIFICATIONS AND THE APPLICABLE SPECIAL PROVISIONS.

TURBIDITY BARRIER MAY BE REMOVED AT THE ENGINEERS DISCRETION, WHEN PERMANENT EROSION CONTROL MEASURES HAVE BEEN ESTABLISHED.

- ① DRIVEN STEEL POSTS, PIPES, OR CHANNELS. LENGTH SHALL BE SUFFICIENT TO SECURELY SUPPORT BARRIER AT HIGH WATER ELEVATIONS.
- ② SAND BAGS TO BE USED AS ADDITIONAL BALLAST WHEN ORDERED BY THE ENGINEER TO MEET ADVERSE FIELD CONDITIONS. SPACE AS APPROPRIATE FOR SITE CONDITIONS.
- ③ WHEN BARRIER HEIGHT "H" EXCEEDS 8 FEET, POST SPACING MAY NEED TO BE DECREASED.
- ④ IN WATERWAYS SUBJECT TO FLUCTUATING WATER ELEVATIONS, PROVISIONS SHOULD BE MADE TO ALLOW THE WATER TO EQUALIZE ON EACH SIDE OF THE BARRIER. THIS MAY BE ACCOMPLISHED BY LEAVING A PORTION OF THE BARRIER OPEN ON THE UPSTREAM END.
- ⑤ ESTIMATED HIGH WATER ELEVATION DURING CONSTRUCTION PERIOD. MINIMUM BARRIER HEIGHT SHALL BE 2' GREATER THAN EITHER THE Q2 ELEVATION OR THE ESTIMATED HIGH WATER ELEVATION DURING CONSTRUCTION, WHICHEVER IS GREATER.
- ⑥ FLOAT ALTERNATIVE WILL ONLY BE ALLOWED WITH WRITTEN APPROVAL OF THE ENGINEER, AND IS MEANT FOR LOCATIONS WHERE BEDROCK PREVENTS THE INSTALLATION OF POSTS.
- ⑦ ALLOW SUFFICIENT SLACK VERTICALLY AND HORIZONTALLY SO THAT SEDIMENT BUILD UP WILL NOT SEPARATE OR LOWER THE TURBIDITY BARRIER.
- ⑧ USE AS DIRECTED BY COAST GUARD OR DNR PERMIT WHEN WORKING IN NAVIGABLE WATERWAYS.



**PLAN VIEW**



**SECTION C - C**


**TURBIDITY BARRIER DETAIL SHOWING  
TYPICAL PLACEMENT AT STRUCTURES**

**TURBIDITY BARRIER**


STATE OF WISCONSIN  
DEPARTMENT OF TRANSPORTATION

APPROVED  
6/4/02 DATE /S/ Beth Cannestra  
DATE CHIEF ROADWAY DEVELOPMENT  
ENGINEER

FHWA




END VIEW




SIDE VIEW

**CULVERT PIPE CHECK**  
 (INSTALL ON INLET END ONLY)


<b>CULVERT PIPE CHECK</b>	
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION	
APPROVED May 2019 DATE	/S/ Daniel Schave EROSION CONTROL ENGINEER
<small>FHWA</small>	



END VIEW




PLAN VIEW




LONGITUDINAL SECTION

CONCRETE ENDWALLS




PLAN VIEW


END CORNER PLATES MAY BE FASTENED TO APRON PROPER BY BOLTS, RIVETS, OR RESISTANCE SPOT WELDS WHICH WILL HOLD THE SURFACES TIGHTLY TOGETHER



END VIEW



SIDE ELEVATION  
METAL ENDWALLS



SECTION A-A

2- 2/3" X 1/2" CORRUGATIONS													
EQUIV. DIA. (Inches)	(Inches)		MIN. THICK. (Inches)		DIMENSIONS (Inches)							APPROX. SLOPE	BODY
	SPAN	RISE	STEEL	ALUM.	A (±1")	B (MAX.)	H (±1")	L (±1 1/2")	L1 (±1")	L2 (±1")	W (±2")		
15	17	13	.064	.060	7	9	6	19	14	16	30	2 1/2 to 1	1 Pc.
18	21	15	.064	.060	7	10	6	23	14	19 3/8	36	2 1/2 to 1	1 Pc.
21	24	18	.064	.060	8	12	6	28	18	21 3/4	42	2 1/2 to 1	1 Pc.
24	28	20	.064	.060	9	14	6	32	18	27 1/2	48	2 1/2 to 1	1 Pc.
30	35	24	.079	.075	10	16	6	39	18	37 5/8	60	2 1/2 to 1	1 Pc.
36	42	29	.079	.075	12	18	8	46	24	45 3/8	75	2 1/2 to 1	1 Pc.
42	49	33	.109	.105	13	21	9	53	24	54 3/4	85	2 1/2 to 1	2 Pc.
48	57	38	.109	.105	18	26	12	63	24	68	90	2 1/2 to 1	3 Pc.
54	64	43	.109	.105	18	30	12	70	24	72 3/4	102	2 1/4 to 1	3 Pc.
60	71	47	.109*	.105*	18	33	12	77	30	82 1/4	114	2 1/4 to 1	3 Pc.
66	77	52	.109*	.105*	18	36	12	77	—	—	126	2 to 1	3 Pc.
72	83	57	.109*	.105*	18	39	12	77	—	—	138	2 to 1	3 Pc.

3" X 1" CORRUGATIONS													
EQUIV. DIA. (Inches)	(Inches)		MIN. THICK. (Inches)		DIMENSIONS (Inches)							APPROX. SLOPE	BODY
	SPAN	RISE	STEEL	ALUM.	A (±1")	B (MAX.)	H (±1")	L (±1 1/2")	L1 (±1")	L2 (±1")	W (±2")		
48	53	41	.109	.105	18	26	12	63	24	72 3/4	90	2 1/2 to 1	2 Pc.
54	60	46	.109	.105	18	30	12	70	30	82 1/4	102	2 to 1	2 Pc.
60	66	51	.109*	.105*	18	33	12	77	—	—	114	1 1/2 to 1	3 Pc.
66	73	55	.109*	.105*	18	36	12	77	—	—	126	1 1/2 to 1	3 Pc.
72	81	59	.109*	.105*	18	39	12	77	—	—	138	2 to 1	3 Pc.
78	87	63	.109*	.105*	22	38	12	77	—	—	148	1 1/2 to 1	3 Pc.
84	95	67	.109*	.105*	22	34	12	77	—	—	162	1 1/2 to 1	3 Pc.
90	103	71	.109*	.105*	22	38	12	77	—	—	174	1 1/2 to 1	3 Pc.
96	112	75	.109*	.105*	24	40	12	77	—	—	174	1 1/2 to 1	3 Pc.

NOTE: ALL SPLICES TO BE LAP RIVETED OR BOLTED. \* EXCEPT CENTER PANEL SEE GENERAL NOTES

REINFORCED CONCRETE PIPE ARCH										
EQUIV. DIA. (Inches)	DIMENSIONS (Inches)									APPROX. SLOPE
	**SPAN	**RISE	T	A	B	C	D	E		
24	29	18	3	8 1/2	39	33	72	48	3 to 1	
30	36	22	3 1/2	9 1/2	50	46	96	60	3 to 1	
36	44	27	4	11 1/8	60	36	96	72	3 to 1	
42	51	31	4 1/2	15 1/8	60	36	96	78	3 to 1	
48	58	36	5	21	60	36	96	84	3 to 1	
54	65	40	5 1/2	25 1/2	60	36	96	90	3 to 1	
60	73	45	6	31	60	36	96	96	3 to 1	
72	88	54	7	31	60	39	99	120	2 to 1	
84	102	62	8	28 1/2	83	19	102	144	2 to 1	

REINFORCED CONCRETE ELLIPTICAL PIPE										
EQUIV. DIA. (Inches)	DIMENSIONS (Inches)									APPROX. SLOPE
	**SPAN	**RISE	T	A	B	C	D	E		
24	30	19	3 1/4	8 1/2	39	33	72	48	3 to 1	
30	38	24	3 3/4	9 1/2	54	18	72	60	3 to 1	
36	45	29	4 1/2	11 1/8	60	24	84	72	2 1/2 to 1	
42	53	34	5	15 3/4	60	36	96	78	2 1/2 to 1	
48	60	38	5 1/2	21	60	36	96	84	2 1/2 to 1	
54	68	43	6	25 1/2	60	36	96	90	2 1/2 to 1	
60	76	48	6 1/2	30	60	36	96	96	2 1/2 to 1	

\*\*NOMINAL SIZE

GENERAL NOTES

DETAILS OF CONSTRUCTION, MATERIALS AND WORKMANSHIP NOT SHOWN ON THIS DRAWING SHALL CONFORM TO THE PERTINENT REQUIREMENTS OF THE STANDARD SPECIFICATIONS AND THE APPLICABLE SPECIAL PROVISIONS.

CONCRETE APRON ENDWALLS MAY NOT BE USED WITH GALVANIZED STEEL OR ALUMINUM CULVERT PIPE OR VISE VERSA. GALVANIZED STEEL OR ALUMINUM APRON ENDWALLS SHALL NORMALLY BE INSTALLED ON CULVERT PIPE OF THE SAME METAL.

ALL THREE PIECE STEEL APRON ENDWALLS FOR 66" X 51" PIPE ARCH AND LARGER SHALL HAVE 0.109" SIDES AND 0.138" CENTER PANELS. ALL THREE PIECE ALUMINUM APRON ENDWALLS FOR 66" X 51" PIPE ARCH AND LARGER SHALL HAVE 0.105" SIDES AND 0.134" CENTER PANELS. THE WIDTH OF CENTER PANELS SHALL BE GREATER THAN 20 PERCENT OF THE PIPE ARCH PERIMETER.

LAP SEAMS SHALL BE TIGHTLY JOINED BY GALVANIZED RIVETS OR BOLTS FOR STEEL UNITS AND ALUMINUM RIVETS AND BOLTS FOR ALUMINUM UNITS. FOR THE 77" X 52" THROUGH 112" X 75" APRON ENDWALL SIZES, THE REINFORCED EDGES AND CENTER PANEL SEAMS SHALL BE FURTHER REINFORCED WITH GALVANIZED STEEL OR ALUMINUM STIFFENER ANGLES. THE ANGLES SHALL BE ATTACHED BY GALVANIZED NUTS AND BOLTS FOR STEEL UNITS AND ALUMINUM NUTS AND BOLTS FOR ALUMINUM UNITS.


WHERE TWO OR MORE PIPES WITH APRON ENDWALLS ARE LAID ADJACENT TO EACH OTHER, THEY SHALL BE SEPARATED BY A DISTANCE SUFFICIENT TO PROVIDE A MINIMUM CLEARANCE OF 6 INCHES BETWEEN APRON ENDWALLS.

① FOR PIPE ARCH SIZES UP TO 73" X 55" A 180° ROLLED EDGE MAY BE USED INSTEAD OF STEEL ROD REINFORCEMENT. SEE SECTION A-A.




TYPE 2

FOR 17" X 13" THRU 112" X 75" PIPE ARCH



TYPE 3

FOR 64" X 43" THRU 112" X 75" PIPE ARCH



TYPE 5

ALTERNATE FOR:  
ALL SIZES CORRUGATED PIPE ARCHES


NOTE: DIMPLED BAND FITS OVER OUTSIDE OF ENDWALL, AND CORRUGATED BAND FITS INSIDE ENDWALL.

CONNECTION DETAILS

APRON ENDWALLS FOR  
PIPE ARCH AND  
ELLIPTICAL PIPE


STATE OF WISCONSIN  
DEPARTMENT OF TRANSPORTATION

APPROVED  
11/30/94 /S/ Rory L. Rhinesmith  
DATE CHIEF ROADWAY DEVELOPMENT ENGINEER  
FHWA



EYE BOLTS AND TIE ROD

EYE BOLT AND TIE ROD ASSEMBLY (ALTERNATE NO. 1)



(CAST-IN-PLACE THREADED INSERT)  
LONGITUDINAL SECTIONS

GENERAL NOTES


DETAILS OF CONSTRUCTION, MATERIALS, AND WORKMANSHIP NOT SHOWN ON THIS DRAWING SHALL CONFORM TO THE PERTINENT REQUIREMENTS OF THE STANDARD SPECIFICATIONS AND APPLICABLE SPECIAL PROVISIONS.

CONCRETE CULVERT AND STORM SEWER PIPE SHALL BE TIED TOGETHER IN THE MANNER ILLUSTRATED BY THIS DETAIL AT LOCATIONS DESIGNATED IN THE STANDARD SPECIFICATIONS AND THE PLAN. THE CONTRACTOR MAY USE EITHER ALTERNATE 1, 2 OR 3 FOR DRAINAGE STRUCTURES. ONLY ALTERNATE 1 AND 3 MAY BE USED FOR CATTLE PASSES, UNLESS OTHERWISE STATED IN THE CONTRACT. THE MATERIALS, FABRICATION AND WORK NECESSARY TO TIE THE PIPE BY THIS DETAIL WILL BE CONSIDERED INCIDENTAL TO THE PIPE AND APRON ENDWALLS IF REQUIRED.


DETAILED DRAWINGS FOR PROPOSED ALTERNATE DESIGNS FOR JOINT TIES SHALL BE SUBMITTED TO THE ENGINEER FOR APPROVAL.

JOINT TIES TO BE HOT-DIP GALVANIZED PER ASTM A 153.

- ①  $\phi$  OF TONGUE AND GROOVE OR BELL AND SPIGOT JOINTS.
- ② THE INSIDE OF THE THREADED INSERTS SHALL BE CLEAN TO ALLOW THE INSERTION OF THREADED EYE BOLTS.
- ③ HOLES SHALL BE CAST-IN-PLACE OR DRILLED 12 INCHES FROM  $\phi$  OF TONGUE AND GROOVE.
- ④ BOLT PROJECTION INSIDE OF PIPE SHALL NOT EXCEED 2 INCHES.
- ⑤ OPENING TO BE ROD DIAMETER PLUS 1 INCH.
- ⑥ LENGTH ADEQUATE TO EXTEND TO WITHIN  $\frac{1}{2}$  INCH OF THE INNER SURFACE OF THE PIPE.



(TONGUE & GROOVE PIPE)



(MODIFIED BELL PIPE)  
LONGITUDINAL SECTION


EYE BOLT DIMENSION TABLE

PIPE SIZE	L = LENGTH	
	TONGUE & GROOVE PIPE	MODIFIED BELL PIPE
18" TO 24"	4 1/2"	6 1/4"
30"	5"	7"
36"	5 1/2"	7"
42"	6"	
48"	6 1/2"	
60"	7 1/2"	
66"	8"	


ADJUSTABLE TIE ROD TABLE

PIPE DIAMETER	TIE ROD DIAMETER	D	L1	N
12-60	5/8	5/8	5	1/2
66-84	3/4	3/4	5	1/2
90-108	1	1	7	1 1/6

DIMENSIONS SHOWN ARE IN INCHES




TAPERED PLAIN  
RIGHT AND LEFT THREADS  
SLEEVE NUTS




PLACEMENT OF (2) CAST-IN-PLACE INSERTS OR HOLES DURING FABRICATION FOR PIPE SECTIONS REQUIRING TIE RODS

TRANSVERSE SECTION




EYE BOLT

NOTE: TWO EYE BOLTS MAY BE USED WITH A 30" LONG THREADED ROD IN LIEU OF THE 90° BENT TIE ROD.




EYE BOLT AND TIE ROD

(JOINT TIES FOR 18" TO 66" DIA. CONCRETE PIPE)  
EYE BOLT AND TIE ROD ASSEMBLY (ALTERNATE NO. 2)



LONGITUDINAL SECTION

(JOINT TIES FOR 12" TO 108" DIA. CONCRETE PIPE)  
ADJUSTABLE TIE ROD (ALTERNATE NO. 3)




SECTION A-A

CONCRETE COLLAR DETAIL

JOINT TIES FOR CONCRETE PIPE AND CONCRETE COLLAR DETAIL

STATE OF WISCONSIN  
DEPARTMENT OF TRANSPORTATION

APPROVED  
6/5/2012 /S/ Jerry H. Zogg  
DATE ROADWAY STANDARDS DEVELOPMENT ENGINEER  
FHWA




**TYPICAL NAME PLATE**  
(BRIDGES, CULVERTS, AND RETAINING WALLS)

**GENERAL NOTES**


NAME PLATES TO BE INSTALLED ON BRIDGES, CULVERTS, AND RETAINING WALLS SHALL CONFORM TO THE REQUIREMENTS OF SECTION 502.3.11 OF THE STANDARD SPECIFICATIONS.

THE BRIDGE NUMBER AND YEAR BUILT SHOWN ON THIS DRAWING ARE EXAMPLES ONLY. SEE CONSTRUCTION PLANS FOR INDIVIDUAL NUMBERING AND YEAR BUILT.


- ① EPOXY RESIN SHALL BE FROM AN APPROVED MANUFACTURER AND USED IN ACCORDANCE WITH MANUFACTURER'S RECOMMENDATIONS.
- ② REHABILITATION OF AN EXISTING STRUCTURE SHOULD USE THE DATE OF ORIGINAL STRUCTURE CONSTRUCTION.



**SECTION A-A**




**ALTERNATE LUG**




**NUMBERING DESIGNATION  
MULTI-UNIT STRUCTURES**

- ① ADHERE ANCHOR LUG TO PRECAST RETAINING WALL WITH EPOXY RESIN.




**ALTERNATE LUG**  
(FOR ATTACHMENT TO PRECAST STRUCTURES)


<b>NAME PLATE (STRUCTURES)</b>	
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION	
APPROVED DATE 3/26/10	/S/ Scot Becker CHIEF STRUCTURAL DEVELOPMENT ENGINEER
FHWA	



**TYPICAL PAVEMENT CROSS SECTION  
NOTCHED WEDGE JOINT**



**TYPICAL PAVEMENT CROSS SECTION  
VERTICAL JOINT**



**TYPICAL PAVEMENT CROSS SECTION  
VERTICAL JOINT (MILLED)**

**GENERAL NOTES**


IN ADDITION TO THE DETAILS PROVIDED IN THIS DRAWING, CONFORM TO STANDARD SPECIFICATION 450.3.2.8 FOR WHEN A NOTCHED WEDGE JOINT IS REQUIRED AND FOR GENERAL JOINT CONSTRUCTION REQUIREMENTS.

FOR ALL LONGITUDINAL JOINTS, ENSURE THE PAVER SCREED OVERLAPS THE PREVIOUSLY PLACED PAVEMENT BY  $1" \pm 0.5"$  AND THE HOT SIDE OF THE JOINT REMAINS HIGHER THAN THE COLD SIDE BY APPROXIMATELY 0.1" AFTER FINAL COMPACTION. (IT WILL BE FLUSH WHEN PAVING IN ECHELON.)

ONLY REMOVE THE LONGITUDINAL NOTCHED WEDGE JOINT FOR SMA PAVEMENT OR AS DIRECTED BY THE ENGINEER TO ADDRESS SPECIFIC LENGTHS OF JOINT DAMAGED BY TRAFFIC.

WHEN MILLING BACK OR REMOVING ANY LONGITUDINAL JOINT, LIMIT THE MATERIAL REMOVED TO 2" FROM THE TOP NOTCH OR FROM THE VERTICAL JOINT EDGE ON THE COLD SIDE OF THE JOINT.

USE LONGITUDINAL MILLED JOINT AS PLANS SHOW OR THE AS THE ENGINEER DIRECTS.



**OVERLAP DETAIL (TYPICAL)**

6


6

SDD 13C19 - 03


SDD 13C19 - 03

<b>HMA LONGITUDINAL JOINTS</b>	
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION	
APPROVED November 2020 DATE	/S/ Steven Hefel HMA PAVEMENT ENGINEER
FHWA	






**FRONT VIEW  
POST SPACING STANDARD INSTALLATION**




**FRONT VIEW  
MID-SPAN BEAM SPLICE**

**GENERAL NOTES**


- ⑧ DO NOT INSTALL REFLECTORS ON THE FIRST 50 FEET OF THE APPROACH END OF THE ENERGY ABSORBING TERMINAL.
  - ⑨ 25 FEET OF HALF POST SPACING IS REQUIRED ON APPROACH AND DEPARTURE ENDS OF QUARTER POST SPACING.
- POST BOLTS ARE A 3/8" DIAMETER ASTM A307 GUARDRAIL BOLT. A POST BOLT REQUIRES 3/4" DIAMETER A563A DOUBLE RECESSED (DR) HEAVY HEX NUT AND 3/8" DIAMETER F844 FLAT WASHER. POST BOLTS MAY BE LONGER IF MULTIPLE BLOCKOUTS ARE BEING USED.
- GUARD RAIL SPLICE BOLTS ARE A 3/8" DIAMETER ASTM A307 GUARDRAIL HEAD BOLT. A GUARDRAIL SPLICE BOLT REQUIRES 3/8" DIAMETER A563A DOUBLE RECESSED (DR) HEAVY HEX NUT.




**FRONT VIEW  
HALF POST SPACING (HS) AND  
HALF POST SPACING WITH LONGER POSTS (K)**




**FRONT VIEW AT STEEL POST**




**FRONT VIEW AT WOOD POST**



**SECTION THRU W-BEAM RAIL**



**FRONT VIEW  
QUARTER POST SPACING (QS)**



**ONE SIDED REFLECTOR DETAIL  
AND TYPICAL INSTALLATION**

6


6

SDD 14B42 - 07b

SDD 14B42 - 07b

**MIDWEST GUARDRAIL SYSTEM  
(MGS) GUARDRAIL**

STATE OF WISCONSIN  
DEPARTMENT OF TRANSPORTATION




**DETAIL FOR 16" BLOCKOUT DEPTH**

IT IS ACCEPTABLE TO USE BLOCKOUTS UP TO 16" DEEP TO INCREASE THE POST OFFSET TO AVOID UNDERGROUND OBSTACLES. THERE IS NO LIMIT TO THE NUMBER OF POSTS THAT CAN HAVE ADDITIONAL BLOCKOUTS UP TO 16" DEEP.


**NOTE:**

1. ALL FILLETS SHALL HAVE A MINIMUM RADIUS OF 3/16".
2. IF THE BOLT EXTENDS MORE THAN 1/4" FROM THE NUT THE BOLT SHOULD BE TRIMMED BACK.




**POST BOLT TABLE**


L	T (MIN.)
1 1/4"	1 1/8"
2"	1 3/4"
10"	4"
14"	4 1/16"
18"	4"
21"	4 1/16"
25"	4"




**ALTERNATE BOLT HEAD**



**PLAN VIEW  
BEAM LAPPING DETAIL**




**POST DRIVING FOR CONTINUOUS  
UNDERGROUND OBSTRUCTION**




**DETAIL FOR 36" BLOCKOUT DEPTH**

NOTES: UNDER SPECIAL CIRCUMSTANCES, SUCH AS AVOIDING OBSTACLES THAT ARE NOT RELOCATED, IT IS ACCEPTABLE TO INSTALL ADDITIONAL BLOCKOUTS TO OBTAIN UP TO 36" DEPTH FOR ONE OR TWO POSTS IN A SECTION OF GUARDRAIL.  
DO NOT USE 16" OR 36" BLOCKOUTS IF IT CAUSES THE POST TO BE DRIVEN BEYOND SHOULDER HINGE POINT OR CAUSES A FIXED OBJECT TO BE WITHIN THE DEFLECTION DISTANCE OF THE BARRIER.



**POST BOLT, SPLICE BOLT  
AND RECESS NUT**




**ALTERNATE WOOD  
BLOCKOUT DETAIL**


6 WHEN USING STEEL POST AND WOOD BLOCKOUTS, INSTALL FOUR 16D GALVANIZED NAILS. INSTALL NAILS AT THE BACK CORNERS OF THE BLOCK AND BEND THE NAILS OVER THE FLANGE OF THE STEEL POST.

**MIDWEST GUARDRAIL SYSTEM  
(MGS) GUARDRAIL**


STATE OF WISCONSIN  
DEPARTMENT OF TRANSPORTATION




**MISSING POST IN MGS GUARDRAIL**




**MISSING POST IN MGS GUARDRAIL NEAR EAT**




**MISSING POST IN MGS GUARDRAIL NEAR AN APPROACH TRANSITION**



**MISSING POST IN MGS GUARDRAIL NEAR FLARED BEAM GUARD**




**MISSING POST IN MGS GUARDRAIL NEAR A TYPE 2 END TERMINAL**




**MISSING POST IN SHORT SPAN MGS GUARDRAIL NEAR CURB (SL)**

- 400 MAX SPAN 12' - 6"
- 401 2' MIN.
- 402 MGS GUARDRAIL 3
- 403 NESTING BEAM GUARD
- 404 ASYMMETRIC TRANSITION
- 405 SOIL WELL DRAINED AND COMPACTED
- 406 SEE OTHER DRAWINGS IN THIS SDD
- 407 SEE OTHER DRAWINGS FOR MIN. SPACING BETWEEN SPANS
- 408 SEE SDD 14B44
- 409 SEE SDD 14B45
- 410 SEE SDD 14B47
- 411 MINIMUM DISTANCE BETWEEN MISSING POST SPANS.



**SECTION A - A**




**SECTION B - B**

<b>MIDWEST GUARDRAIL SYSTEM (MGS) GUARDRAIL</b>	
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION	
APPROVED May 2021 DATE	/S/ Rodney Taylor ROADWAY STANDARDS DEVELOPMENT UNIT SUPERVISOR
<small>FHWA</small>	




**BILL OF MATERIALS**


PART NO.	DESCRIPTION MATERIALS PROVIDED BY MGS EAT MANUFACTURER. SEE MANUFACTURER'S DETAILS FOR MORE INFORMATION.
①	UPPER POST NO. 1 6" X 6" TUBE
②	LOWER POST NO. 1
③	WOOD CRT
④	WOOD BLOCKOUT
⑤	PIPE SLEEVE
⑥	BEARING PLATE
⑦	BCT CABLE ASSEMBLY
⑧	ANCHOR CABLE BOX
⑨	GROUND STRUT
⑩	PERFORATED W-BEAM RAIL END PANEL, 12'-6" LONG.
⑪	STANDARD W-BEAM RAIL. MULTIPLE SECTIONS REQUIRED. SECTIONS VARY IN LENGTH.
⑫	IMPACT HEAD
⑬	EAT MARKER POST - YELLOW (SEE APPROVED PRODUCTS LIST)
⑭	SOIL PLATE
⑮	UPPER POST NO. 2
⑯	LOWER POST NO. 2



**GENERIC GROUND STRUT** ⑨ ⑤



**GENERIC ANCHOR CABLE BOX** ⑨ ⑤



**BEARING PLATE** ⑥ ⑤

6


6

SDD 14B44 - 04b


SDD 14B44 - 04b

**MIDWEST GUARDRAIL SYSTEM  
ENERGY ABSORBING TERMINAL  
(MGS)**


STATE OF WISCONSIN  
DEPARTMENT OF TRANSPORTATION




UPPER POST NO. 1 <sup>(1)</sup> (E)




LOWER POST NO. 1 <sup>(2)</sup> (E)




WOOD CRT POST <sup>(3)</sup> (E)  
POSTS NUMBER 3-9



UPPER POST NO. 2 <sup>(15)</sup> (E)




LOWER POST NO. 2 <sup>(16)</sup> (E)



WOOD BLOCKOUT <sup>(4)</sup>  
REQ'D. AT ALL POSTS EXCEPT POST NO'S 1 & 2


6




REFLECTIVE SHEETING DETAIL <sup>(E)</sup>

TYPE H  
YELLOW REFLECTIVE  
SHEETING 3" X 9".  
SEE STANDARD  
SPECIFICATION 637.


E.A.T. MARKER  
POST (YELLOW)



FRONT VIEW SIDE VIEW  
E.A.T. MARKER POST <sup>(13)</sup>



SIDE VIEW



TOP VIEW


ALTERNATE WOOD  
BLOCKOUT DETAIL

6


**MIDWEST GUARDRAIL SYSTEM  
ENERGY ABSORBING TERMINAL  
(MGS)**

STATE OF WISCONSIN  
DEPARTMENT OF TRANSPORTATION

APPROVED  
7/2018 DATE /S/ Rodney Taylor  
ROADWAY STANDARDS DEVELOPMENT  
UNIT SUPERVISOR



**TWO WAY TRAFFIC**



**ONE WAY TRAFFIC**

Ⓣ THRIE BEAM CONNECTION

Ⓜ W-BEAM CONNECTION WHEN REQUIRED

**TYPICAL LOCATIONS OF THRIE BEAM AND W-BEAM CONNECTIONS TO BRIDGE**

**GENERAL NOTES**


IF ROCK IS ENCOUNTERED, REMOVE ROCK TO FULL DEPTH OF POST PLUS 2 1/2", AND 12" DIAMETER AROUND POST. SEE 14B42 FOR MORE DETAILS.

TRANSITION USES STEEL POSTS ONLY.


SEE STANDARD DETAIL DRAWING 14 B 42 FOR MORE INFORMATION.

POST 2 THROUGH 17 USES STEEL POST ONLY

- ① BRIDGE RAILING TYPE "W" DOES NOT REQUIRE A TERMINAL CONNECTOR.
- ② OPTIONAL CURB AND GUTTER OR DRAINAGE FEATURE SEE PLAN FOR INFORMATION.
- ⑬ STEEL OR WOOD POST IS ACCEPTABLE AT POST 1. SEE SDD14B42



**PLAN VIEW**



**ELEVATION VIEW**


**MIDWEST GUARDRAIL SYSTEM THRIE BEAM TRANSITION**

**MIDWEST GUARDRAIL SYSTEM  
THRIE BEAM TRANSITION (MGS)**


STATE OF WISCONSIN  
DEPARTMENT OF TRANSPORTATION

**GENERAL NOTES**


- ② OPTIONAL CURB AND GUTTER OR DRAINAGE FEATURE SEE PLAN FOR INFORMATION.
- ③ WHEN USING STEEL POSTS AND WOOD BLOCKOUTS INSTALL FOUR 10D GALVANIZED NAILS. INSTALL NAILS AT THE BACK CORNERS OF THE BLOCK AND BEND THE NAILS OVER THE FLANGE OF THE STEEL POST.
- ④ TOLERANCE FOR TOP OF W-BEAM RAIL IS ± 1".
- ⑬ STEEL OR WOOD POST IS ACCEPTABLE AT POST 1. SEE SDD 14B42




**SECTION A-A  
POSTS 1-5**




**SECTION B-B  
POST 6**




**SECTION C-C  
POSTS 7-11**




**PLATE WASHER DETAIL**



**SPLICE DETAIL**




**THRIE BEAM  
TERMINAL CONNECTOR**




**SECTION THRU THRIE  
BEAM RAIL ELEMENT**

**MIDWEST GUARDRAIL SYSTEM  
THRIE BEAM TRANSITION (MGS)**


STATE OF WISCONSIN  
DEPARTMENT OF TRANSPORTATION




**W-BEAM TO THRIE BEAM TRANSITION SECTION**




**6'-3\"/>**




**12'-6\"/>**




**ALTERNATE WOOD BLOCKOUT DETAIL**




**STEEL POSTS 1-5**




**STEEL POSTS 6-17**




**TOP VIEW**



**FRONT VIEW  
BLOCKOUT  
POSTS 1-5**



**TOP VIEW**



**FRONT VIEW  
BLOCKOUT  
POSTS 6-17**

**GENERAL NOTES**

- STEEL POSTS ARE W6X9 OR W6X8.5.
- BOLT HOLES FOR POST ARE ON FRONT AND OF SIDE OF POST.
- (3) WHEN USING STEEL POSTS AND WOOD BLOCKOUTS INSTALL FOUR 16D GALVANIZED NAILS. INSTALL NAILS AT THE BACK CORNERS OF THE BLOCK AND BEND THE NAILS OVER THE FLANGE OF THE STEEL POST.
- (5) WOOD BLOCKS MAY BE CONSTRUCTED OUT OF 2 WOOD BLOCKS. SEE ALTERNATE WOOD BLOCK DETAIL.
- (13) STEEL OR WOOD POST IS ACCEPTABLE AT POST 1. SEE SDD 14B42.

**MIDWEST GUARDRAIL SYSTEM  
THRIE BEAM TRANSITION (MGS)**

STATE OF WISCONSIN  
DEPARTMENT OF TRANSPORTATION

6


6

S.D.D. 14 B 45-5c


S.D.D. 14 B 45-5c

**GENERAL NOTES**


(4) TOLERANCE FOR TOP OF W-BEAM RAIL IS ± 1".



**FRONT VIEW**




**PLAN VIEW  
BACK-UP PLATE DETAIL, TYPE "M"**




**FRONT VIEW**

**ANCHOR  
PLATE DETAIL,  
TYPE "M"**




**SECTION M-M**



**SECTION L-L**


**FRONT VIEW**

**ANCHOR AND BACK-UP PLATE MOUNTING TO BRIDGE RAILING, TYPE "M"**



**FRONT VIEW**

**M**




**PLAN VIEW**

**THRIE BEAM CONNECTION TO TUBULAR RAILING, TYPE "M"**

**MIDWEST GUARDRAIL SYSTEM  
THRIE BEAM TRANSITION (MGS)**

STATE OF WISCONSIN  
DEPARTMENT OF TRANSPORTATION

APPROVED  
DATE 07/2018 /S/ Rodney Taylor  
ROADWAY STANDARDS DEVELOPMENT  
UNIT SUPERVISOR  
FHWA



**DETAIL A  
MAINLINE CLOSURE WITH POSTED DETOUR**

WORK ZONE GREATER THAN OR EQUAL TO 1/2 MILE FROM  
DETOUR ROUTE ( 1000 FEET IF URBAN )

**DETAIL B  
MAINLINE CLOSURE WITH POSTED DETOUR**


WORK ZONE LESS THAN 1/2 MILE FROM  
DETOUR ROUTE ( 1000 FEET IF URBAN )

**LEGEND**

- SIGN ON PERMANENT SUPPORT
- TYPE III BARRICADE
- TYPE III BARRICADE WITH ATTACHED SIGN
- TYPE "A" WARNING LIGHT (FLASHING)
- WORK AREA
- FLAGS, 16" X 16" MIN. (ORANGE)

SPEED LIMIT (MPH)	"STOP AHEAD" ADVANCE WARNING DISTANCE (FT)
25	200
30	200
35	350
40	350
45	500
50	550
55	750

- M4 - 8
- M3 - X
- M1 - 4
- M1 - 6
- M1 - 5A
- M05 - 1
- M06 - 1




**DETAIL C  
MAINLINE CLOSURE, NO POSTED DETOUR**

SEE SDD 15C2-SHEET "b"  
FOR GENERAL NOTES  
AND FOOTNOTES ① THROUGH ⑦


**BARRICADES AND SIGNS  
FOR MAINLINE CLOSURES**

STATE OF WISCONSIN  
DEPARTMENT OF TRANSPORTATION

APPROVED  
February 2020 /S/ Andrew Heidtke  
DATE WORK ZONE ENGINEER  
FHWA



**DETAIL D  
ROAD CLOSURE BARRICADE DETAIL  
APPROACH VIEW**



**DETAIL E  
LANE CLOSURE BARRICADE DETAIL  
APPROACH VIEW**

SEE SDD 15C2 - SHEET "a" FOR LEGEND

**GENERAL NOTES**

THE EXACT NUMBER, LOCATION, AND SPACING OF ALL SIGNS AND BARRICADES SHALL BE ADJUSTED TO FIT FIELD CONDITIONS AS APPROVED BY THE ENGINEER.

ANY SIGNS TEMPORARY OR EXISTING, WHICH CONFLICT WITH TRAFFIC CONTROL "IN USE", SHALL BE REMOVED OR COVERED AS NEEDED AND AS APPROVED BY THE ENGINEER.

THE SPACING BETWEEN TRAFFIC CONTROL SIGNS SHOULD BE ADJUSTED TO NOT CONFLICT WITH AND SHOULD PROVIDE A DESIRABLE MINIMUM OF 200 FEET CLEARANCE TO EXISTING SIGNS THAT WILL REMAIN IN PLACE.

BARRICADES THAT MUST BE MOVED FOR A WORK OPERATION SHALL BE IMMEDIATELY RE-ESTABLISHED UPON COMPLETION OF THE OPERATION, OR FOR CONTINUING OPERATIONS, AT THE END OF EACH WORKING DAY.

SIGNS THAT WILL BE IN PLACE LESS THAN 7 CONTINUOUS DAYS AND NIGHTS MAY BE MOUNTED ON PORTABLE SUPPORTS.

ALL TYPE III BARRICADES SHALL HAVE RAILS REFLECTORIZED ON BOTH FACES. STRIPES SHALL BE PROPERLY SLOPED DOWN TOWARD THE TRAFFIC SIDE OR AS SHOWN IN THE ROAD CLOSURE BARRICADE DETAIL "D" FOR FULL ROAD CLOSURES.

TYPE "A" LOW - INTENSITY FLASHING WARNING LIGHTS SHALL BE VISIBLE ON BOTH SIDES OF THE BARRICADE.

THE R11 - 2, R11 - 3, M4 - 9, R11 - 4, AND R10 - 61 SIGNS PLACED ON THE BARRICADES SHALL COVER NO MORE THAN THE TOP RAIL. THE SIGNS SHALL NOT COVER ANY PORTION OF THE MIDDLE RAIL OR BOTTOM RAILS.

"WO" AND "MO" SIGNS ARE THE SAME AS "W" AND "M" SIGNS EXCEPT THE BACKGROUND IS ORANGE.

ALL SIGNS SHALL BE 48" X 48" UNLESS OTHERWISE NOTED BELOW:

- R11 - 2 SHALL BE 48" X 30"
- R11 - 3 SHALL, R11 - 4 AND R10 - 61 SHALL BE 60" X 30"
- M4 - 9 SHALL BE 30" X 24"
- M3 - X SHALL BE 24" X 12" (36" X 18" IF NEEDED TO MATCH EXISTING SIGNS)
- M4 - 8 SHALL BE 24" X 12" (36" X 18" IF NEEDED TO MATCH EXISTING SIGNS)
- M1 - 4, M1 - 5A AND M1 - 6 SHALL BE 24" X 24" (36" X 36" IF NEEDED TO MATCH EXISTING SIGNS)
- MO5 - 1 AND MO6 - 1 SHALL BE 21" X 21" (30" X 30" IF NEEDED TO MATCH EXISTING SIGNS)
- D1 - X SHALL BE AS SHOWN ON SPECIFIC PROJECT SIGNING DETAIL SHEETS.
- R1 - 1 SHALL BE 36" X 36"

- ① TWO WARNING LIGHTS SHALL BE PROVIDED ON THE CENTER BARRICADE AND A MINIMUM OF ONE WARNING LIGHT SHALL BE PROVIDED ON EACH OF THE OTHER BARRICADES WITHIN THE ROADWAY LIMITS. SPACING OF THE WARNING LIGHTS SHALL BE UNIFORM TO THE EDGE OF ROADWAY AS SHOWN (APPROX. 8 FOOT LIGHT SPACING).
- ② THESE SIGNS AND BARRICADES ARE NOT REQUIRED IF ROAD CLOSURE BEGINS AT AN INTERSECTION.
- ③ FOR ROAD CLOSURE WITHOUT LOCAL ACCESS TO PROJECT, SEE ROAD CLOSURE BARRICADE DETAIL "D".
- ④ FOR ROAD CLOSURE WITH LOCAL ACCESS TO PROJECT, SEE ROAD CLOSURE BARRICADE DETAIL "E".
- ⑤ FOR BRIDGE OR CULVERT REPLACEMENTS, SUBSTITUTE "BRIDGE OUT" INSTEAD OF "ROAD CLOSED" ON R11 - 2 AND R11 - 3 SIGNS.
- ⑥ INSTALL DETOUR AND COMMUNITY GUIDE SIGNS AND ARROWS ONLY IF SPECIFIED IN THE CONTRACT. IF THERE ARE EXISTING ROUTE MARKER ASSEMBLIES THAT WILL REMAIN IN PLACE, ADJUST THE LOCATION OF THE DETOUR ROUTE SIGNS TO CORRESPOND WITH THE EXISTING ASSEMBLIES. MODIFY EXISTING SIGNS WHERE POSSIBLE. SEE SPECIFIC PROJECT DETOUR SIGNING DETAIL SHEETS. IF DETOUR SIGNS ARE BEING INSTALLED BY OTHERS, PLACE THE CONTRACTED TRAFFIC CONTROL SIGNS TO ALLOW FOR PLACEMENT OF ALL WARNING, DETOUR AND GUIDE SIGNS AS SHOWN.
- ⑦ "EAST" CARDINAL DIRECTION MARKERS AND RIGHT TURN ARROWS ARE SHOWN. USE OTHER CARDINAL DIRECTIONS AND ARROWS AS APPROPRIATE.

**BARRICADES AND SIGNS  
FOR  
VARIOUS CLOSURES**

STATE OF WISCONSIN  
DEPARTMENT OF TRANSPORTATION

APPROVED  
February 2020 /S/ Andrew Heidtke  
DATE WORK ZONE ENGINEER

### GENERAL NOTES


DETAILS OF TRAFFIC CONTROL DEVICES AND INSTALLATION NOT SHOWN ON THIS DRAWING SHALL CONFORM TO THE PERTINENT REQUIREMENTS OF THE STANDARD SPECIFICATIONS, THE SPECIAL PROVISIONS, AND THE MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES.

LOCATE W5-52 SIGN POST(S) BEHIND GUARDRAIL WHEN PRESENT.

PLACE THE EDGE OF THE W5-52 SIGN IN LINE WITH FACE OF CURB OR PARAPET.


① OMIT ON ONE-WAY TRAVELLED WAYS.

➡ DIRECTION OF TRAFFIC



### SITUATION 1

WARRANTING CRITERIA:  
BRIDGE WIDTH IS AT LEAST 16 FEET BUT LESS THAN 24 FEET.



### SITUATION 2

WARRANTING CRITERIA:  
1. BRIDGE WIDTH IS AT LEAST 24 FEET AND  
2. BRIDGE SHOULDER WIDTH IS LESS THAN 6 FEET.


DISTANCE TABLE

POSTED OR 85th PERCENTILE SPEED	DISTANCE "A"
25	150'
30	200'
35	250'
40	300'
45	400'
50	550'
55	750'


### SIGNING & MARKING FOR TWO LANE BRIDGES

STATE OF WISCONSIN  
DEPARTMENT OF TRANSPORTATION

APPROVED  
June 2017 /S/ Matthew R. Rauch  
DATE STATE SIGNING AND MARKING ENGINEER  
FHWA




**TWO WAY TRAFFIC**




**ONE WAY TRAFFIC**

**PERMANENT PAVEMENT MARKING**



**TWO WAY TRAFFIC**



**ONE WAY TRAFFIC**

**TEMPORARY PAVEMENT MARKING**


**GENERAL NOTES**

DETAILS OF CONSTRUCTION NOT SHOWN ON THIS DRAWING SHALL CONFORM TO STANDARD SPECIFICATIONS AND SPECIAL PROVISIONS.

- ① LOCATE THE NO PASSING ZONE W14-3 SIGN WITHIN 50 FEET OF THE "T" MARKING
- ② MEASURE FROM EDGE OF MARKING TO JOINT LINE. THIS DOES NOT INCLUDE SPACE NEEDED FOR GROOVING OPERATIONS.

**LEGEND**


- "T" MARKING
- SIGN ON PERMANENT SUPPORT
- DIRECTION OF TRAFFIC




**LONGITUDINAL MARKING  
(MAINLINE)**

STATE OF WISCONSIN  
DEPARTMENT OF TRANSPORTATION

APPROVED  
February 2020 /S/ Matthew Rauch  
DATE STATEWIDE SIGNING AND MARKING  
ENGINEER



**DRUM**




**42" CONE**

DO NOT USE IN TAPERS  
1/2 SPACING OF DRUMS


**GENERAL NOTES**

- ① REFLECTIVE SHEETING SHALL FOLLOW THE REQUIREMENTS IN THE APPROVED PRODUCTS LISTING FOR SIGN SHEETING.
- ② LOCATION OF WARNING LIGHTS WHEN SHOWN ON THE PLAN.




**VERTICAL PANEL**

THE STRIPES SHALL SLOPE DOWNWARD TO THE TRAFFIC SIDE FOR CHANNELIZATION.



**TYPE II BARRICADE**

FOR RAILS LESS THAN 36" LONG, 4" WIDE STRIPES MAY BE USED. ALL STRIPES SHALL SLOPE DOWNWARD TO THE TRAFFIC SIDE FOR CHANNELIZATION.



**TYPE III BARRICADE**

IF SIGN MOUNTED, DO NOT COVER MORE THAN 50% OF THE TOP TWO RAILS OR 33% OF THE TOTAL AREA OF THE THREE RAILS.

\* IF USED FOR A PERMANENT APPLICATION USE RED SHEETING.

**CHANNELIZING DEVICES  
DRUMS, CONES, BARRICADES  
AND VERTICAL PANELS**

STATE OF WISCONSIN  
DEPARTMENT OF TRANSPORTATION

APPROVED  
May 2021 /S/ Andrew Heidtke  
DATE WORK ZONE ENGINEER


**GENERAL NOTES**

OMIT EDGE LINES THROUGH INTERSECTIONS. CONTINUE EDGE LINES THROUGH DRIVEWAYS.


- ① WHEN DISTANCE "A" IS LESS THAN 250 FEET, OMIT LANE LINE.
- ② WHEN DISTANCE "B" IS LESS THAN 100 FEET, OMIT CHANNELIZING LANE LINE.
- ③ BARRIER LINE ENDS AT SIDE ROAD PAVEMENT / SURFACE EDGE EXTENSION.
- ④ BARRIER LINE STARTS 500 FEET PRIOR TO THE BYPASS TAPER.

**LEGEND**


➡ DIRECTION OF TRAVEL



**MINOR INTERSECTION**



**INTERSECTION ON OUTSIDE OF CURVE**




**MAJOR INTERSECTIONS  
(INTERSECTION WITH FULL RIGHT TURN LANE OR BYPASS LANE)**

**PAVEMENT MARKING  
(INTERSECTIONS)**


STATE OF WISCONSIN  
DEPARTMENT OF TRANSPORTATION

URBAN AREA


RURAL AREA (See Note 2)




White Edgeline Location



Outside Edge of Gravel



White Edgeline Location



Outside Edge of Gravel

POST EMBEDMENT DEPTH

Area of Sign Installation ( Sq. Ft. )	D ( Min )
20 or Less	4'
Greater than 20	5'

GENERAL NOTES

1. Signs wider than 4 feet or 20 sq.ft or larger, shall be mounted on multiple posts. Refer to plate A4-4.
2. If signs are mounted on or behind barrier wall, see A4-10 sign plate.  
The Double Arrow sign (W12-1D) shall be mounted at a height of 2'-3" (±). The Chevron sign (W1-8), Roundabout Chevron panel (R6-4B), Enhanced Reference Markers, Clearance Markers (W5-52), Mile Markers (D10 series), In Road Object Markers (W5-54) & End of Road Markers (W5-56) shall be mounted at a height of 4'-3" (±).
3. For expressways and freeways, mounting height is 7'- 3" (±) or 6'-3" (±) depending upon existence of a sub-sign.
4. Minimum mounting height for signs mounted on traffic signal poles is 5'- 3" (±).
5. Offset distance shall be consistent with existing signs or consistent throughout length of project.
6. The (±) tolerance for mounting height is 3 inches.
7. Folding signs shall be mounted at a height of 5'-3" (±) or as directed by the Engineer.

\* \* The existence of curb and gutter does not in itself mandate the vertical clearance illustrated. That height is typically measured where there is sidewalk adjacent to the roadway or parking is permitted. In the absence of sidewalk vertical clearance is measured from the top of the curb. Offset of signs is measured from the flow line.


\* 6 feet from edge of a paved shoulder or 12 feet from the edge of pavement (edge line location) or 2 feet from outside edge of gravel, whichever is greater unless directed by project engineer.

TYPICAL INSTALLATION OF PERMANENT TYPE II SIGNS ON SINGLE POSTS

WISCONSIN DEPT OF TRANSPORTATION

APPROVED *Matthew R. Rauch*  
for State Traffic Engineer

DATE 5/13/2020 PLATE NO. A4-3.22



Nuts, bolts and lags used for mounting signs shall have hexagonal heads and shall be either :



- Hot dip galvanized in accordance with ASTM Designation: A 153, Class D, or SC 3
- Electro-galvanized in accordance with ASTM Designation : B 633, TYPE III, SC 3.

Threads on bolts and nuts shall be manufactured with sufficient allowance for the cadmium plate or galvanized coating to permit the nuts to run freely on the bolts.

- STRINGER BOLTING TO ALUMINUM SIGNS (SEE SIGN PLATE A4-18)
- MACHINE BOLTS -  $\frac{5}{16}$ " X 1-3/4" Length w/ lock nuts
- WOOD POSTS (4" x 6")
- LAG SCREWS -  $\frac{3}{8}$ " X 3" (NO STRINGERS ON BACK OF SIGN)  
 $\frac{3}{8}$ " X 4" (STRINGERS ON BACK OF SIGN)
- SQUARE STEEL POSTS (2" x 2")
- MACHINE BOLTS -  $\frac{3}{8}$ " X 3-1/4" Length w/ nuts (NO STRINGER ON BACK OF SIGN)  
 $\frac{3}{8}$ " X 5" Length w/ nuts (STRINGERS ON BACK OF SIGN)
- RIVETS -  $\frac{9}{32}$ " (6605-9-6) BULB-TITE, TRI-FOLD, ALUMINUM BODY/MANDREL  
 O.D. FLANGE .720-.765 INCH, GRIP RANGE .042-.375 INCH
- WASHERS (ALL POSTS) -
- 1-1/4" O.D. X  $\frac{3}{8}$ " I.D. X  $\frac{1}{16}$ " STEEL
- 1-1/4" O.D. X  $\frac{3}{8}$ " I.D. X .080 NYLON

\* Two different fastening systems are shown for illustration purposes. On any individual sign, either one or the other system shall be used. Actual number of fasteners per sign varies with the sign area, but normally there are two. For a single post installation, all signs greater than 9 sq. ft. require the use of 3 fasteners.

ATTACHMENT OF SIGNS TO POSTS	
WISCONSIN DEPT OF TRANSPORTATION	
APPROVED	<i>Matthew R Rauch</i> For State Traffic Engineer
DATE 4/1/2020	PLATE NO. A4-8.9



GENERAL NOTES

1. All 4 x 6 Wood Posts shall be modified by having two 1½" diameter holes drilled perpendicular to the roadway centerline.


7

7




<b>4 X 6 WOOD POST MODIFICATIONS</b>	
<i>WISCONSIN DEPT OF TRANSPORTATION</i>	
APPROVED	<i>Chester J. Spang</i> for State Traffic Engineer
DATE <u>3/27/97</u>	PLATE NO. <u>A4-11.2</u>

**NOTES**

1. Sign is Type II - see Note 7 - reference WIS DOT Standard Specification for HIGHWAY and STRUCTURE CONSTRUCTION latest edition.
2. Color:  
Background - White & Black - See Note 7  
Message - Black
3. Message Series - see Note 5
4. Corners may be square or rounded when base material is plywood but borders shall be rounded as shown. When base material is metal, the corners and borders shall be rounded.
5. Message Series E for 1 letter.  
Message Series D for 2 letters unless message is too big then Series C.  
Message Series C for 3 letters unless message is too big then Series B.
6. Substitute appropriate letters & optically center to achieve proper balance.
7. Permanent Signs  
Background - Type H Reflective  
Detour or temporary Signs  
Background - Reflective



M1-5A



7

7

SIZE	A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q	R	S	T	U	V	W	X	Y	Z	Area sq. ft.
1																											
2	24		1 1/2			10	3	5 1/8	4 1/8	9 1/4	9 5/8	2	11 1/2	10 1/8	9 3/8	2 1/4		6 5/8									4.0
3	36		2 1/4			16	4	7 5/8	5 5/8	12 1/4	12 7/8	3	17 1/8	15 1/4	14	3 3/8		10									9.0
4	36		2 1/4			16	4	7 5/8	5 5/8	12 1/4	12 7/8	3	17 1/8	15 1/4	14	3 3/8		10									9.0
5	36		2 1/4			16	4	7 5/8	5 5/8	12 1/4	12 7/8	3	17 1/8	15 1/4	14	3 3/8		10									9.0

**CTH MARKER**  
**M1-5A FOR ASSEMBLIES**

WISCONSIN DEPT OF TRANSPORTATION


APPROVED *Matthew R. Raub*  
For State Traffic Engineer

DATE 9/27/11 PLATE NO. MI-5A.8


PROJECT NO: \_\_\_\_\_ HWY: \_\_\_\_\_ COUNTY: \_\_\_\_\_ SHEET NO: **E**

NOTES


- All Signs Type II - Type H
- Color:
  - Background - See note 5
  - Message - See note 5
- Message Series - C
- Corners may be square or rounded when base material is plywood but borders shall be rounded as shown. When base material is metal, the corners and borders shall be rounded.
- M3-1 thru M3-4 Background - White  
 Message - Black  
 MB3-1 thru MB3-4 Background - Blue  
 Message - White  
 MK3-1 thru MK3-4 Background - Green  
 Message - White  
 MM3-1 thru MM3-4 Background - White  
 Message - Green  
 MN3-1 thru MN3-4 Background - Brown  
 Message - White  
 MP3-1 thru MP3-4 Background - White  
 Message - Blue
- Note the first letter of each direction is larger than the remainder of the message.




M3-1  
MM3-1  
MP3-1




MB3-1  
MK3-1  
MN3-1




M3-2  
MM3-2  
MP3-2




MB3-2  
MK3-2  
MN3-2




M3-3  
MM3-3  
MP3-3



MB3-3  
MK3-3  
MN3-3



M3-4  
MM3-4  
MP3-4



MB3-4  
MK3-4  
MN3-4

7


SIZE	A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q	R	S	T	U	V	W	X	Y	Z	Area sq. ft.
1																											
2	24	12	1 1/8	3/8	3/8	6	7	2 1/4	2 3/4	10 1/4	7 7/8	8 3/8	10 1/4	9 3/4	8 3/4			1 1/2									2.00
3	36	18	1 1/8	3/8	1/2	9	10	3 3/4	4 1/4	14 3/8	12	12 1/8	14	14 1/8	13			1 1/2									4.5
4	36	18	1 1/8	3/8	1/2	9	10	3 3/4	4 1/4	14 3/8	12	12 1/8	14	14 1/8	13			1 1/2									4.5
5	36	18	1 1/8	3/8	1/2	9	10	3 3/4	4 1/4	14 3/8	12	12 1/8	14	14 1/8	13			1 1/2									4.5

STANDARD SIGNS  
M3-1 thru M3-4  
SERIES


WISCONSIN DEPT OF TRANSPORTATION

APPROVED *Matthew R. Rauch*  
for State Traffic Engineer


DATE 10/15/15 PLATE NO. M3-1.14




M6-1  
MM6-1  
M06-1  
MP6-1




M6-2  
MM6-2  
M06-2  
MP6-2



MB6-1  
MK6-1  
MN6-1  
MR6-1



MB6-2  
MK6-2  
MN6-2  
MR6-2



NOTES

- Signs are Type II - Type H except as Shown
- Color:  
Background - See note 4  
Message - See note 4
- Corners may be square or rounded when base material is plywood but borders shall be rounded as shown. When base material is metal, the corners and borders shall be rounded.
- M6-1 and M6-2 Background - White  
Message - Black  
MB6-1 and MB6-2 Background - Blue  
Message - White  
MK6-1 and MK6-2 Background - Green  
Message - White  
MM6-1 and MM6-2 Background - White  
Message - Green  
MN6-1 and MN6-2 Background - Brown  
Message - White  
M06-1 and M06-2 Background - Orange - Type F Reflective  
Message - Black  
MP6-1 and MP6-2 Background - White  
Message - Blue  
MR6-1 and MR6-2 Background - Brown  
Message - Yellow

7


SIZE	A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q	R	S	T	U	V	W	X	Y	Z	Area sq. ft.
1																											
2	21		1 1/8	3/8	3/8		7 1/2	7 1/8	5 5/8	5	4 1/4	5 1/4	3	2 5/8	1/2						1 1/2	1/2					3.06
3	30		1 3/8	1/2	5/8		10 3/4	10 1/4	8	7 1/4	6	7 1/2	4 1/4	3 3/4	3/4						1 7/8	1/2					6.25
4	30		1 3/8	1/2	5/8		10 3/4	10 1/4	8	7 1/4	6	7 1/2	4 1/4	3 3/4	3/4						1 7/8	1/2					6.25
5	30		1 3/8	1/2	5/8		10 3/4	10 1/4	8	7 1/4	6	7 1/2	4 1/4	3 3/4	3/4						1 7/8	1/2					6.25

STANDARD SIGN  
M6-1 & M6-2  
SERIES


WISCONSIN DEPT OF TRANSPORTATION

APPROVED *Matthew R. Rauch*  
for State Traffic Engineer


DATE 10/15/15 PLATE NO. M6-1.15




M6-4  
MM6-4  
M06-4  
MP6-4



M6-6  
MM6-6  
M06-6  
MP6-6




MB6-4  
MK6-4  
MN6-4  
MR6-4



MB6-6  
MK6-6  
MN6-6  
MR6-6

NOTES

- Signs are Type II - Type H except as Shown
- Color:  
Background - See Note 4  
Message - See Note 4
- Corners may be square or rounded when base material is plywood but borders shall be rounded as shown. When base material is metal, the corners and borders shall be rounded.
- M6-4 and M6-6 Background - White  
Message - Black  
MB6-4 and MB6-6 Background - Blue  
Message - White  
MK6-4 and MK6-6 Background - Green  
Message - White  
MM6-4 and MM6-6 Background - White  
Message - Green  
MN6-4 and MN6-6 Background - Brown  
Message - White  
M06-4 and M06-6 Background - Orange - Type F Reflective  
Message - Black  
MP6-4 and MP6-6 Background - White  
Message - Blue  
MR6-4 and MR6-6 Background - Brown  
Message - Yellow
- M6-6R same as M6-6L except arrow points ahead and right.



7

SIZE	A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q	R	S	T	U	V	W	X	Y	Z	Area sq. ft.
1																											
2	21		1 1/8	3/8	3/8		7 1/2	8 3/4	4 1/4			5 1/4	3	2 5/8	1/2						1 1/2	1/2					3.06
3	30		1 3/8	1/2	5/8		10 3/4	12 1/2	6 3/4			7 1/2	4 1/4	3 3/4	3/4						1 7/8	1/2					6.25
4	30		1 3/8	1/2	5/8		10 3/4	12 1/2	6 3/4			7 1/2	4 1/4	3 3/4	3/4						1 7/8	1/2					6.25
5	30		1 3/8	1/2	5/8		10 3/4	12 1/2	6 3/4			7 1/2	4 1/4	3 3/4	3/4						1 7/8	1/2					6.25

STANDARD SIGN  
M6-4 & M6-6  
SERIES


WISCONSIN DEPT OF TRANSPORTATION

APPROVED *Matthew R. Rauch*  
for State Traffic Engineer

DATE 10/15/15 PLATE NO. M6-4.10

NOTES

1. Sign is Type II - Type H Reflective - reference WIS DOT Standard Specification for HIGHWAY and STRUCTURE CONSTRUCTION latest edition.
2. Color:  
Background - Red  
Message - White
3. Message Series - C



R1-1

SIZE	A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q	R	S	T	U	V	W	X	Y	Z	Area sq. ft.
1	30				5/8	10	12 1/2	45°		12 3/4																	5.18
2S	30				5/8	10	12 1/2	45°		12 3/4																	5.18
2M	36				3/4	12	15	45°		15 3/8																	7.46
3	36				3/4	12	15	45°		15 3/8																	7.46
4	48				1	16	20	45°		20 1/2																	13.25
5	48				1	16	20	45°		20 1/2																	13.25
6	18				3/8	6	7 3/4	45°		7 3/4																	1.86
7	12				1/4	4	5	45°		5 1/8																	0.78

STANDARD SIGN  
R1-1

WISCONSIN DEPT OF TRANSPORTATION


APPROVED *Matthew R. Rauch*  
for State Traffic Engineer

DATE 11/12/15 PLATE NO. R1-1.13

PROJECT NO: \_\_\_\_\_ HWY: \_\_\_\_\_ COUNTY: \_\_\_\_\_ SHEET NO: **E**

NOTES

1. Sign is Type II - Type H Reflective - reference WIS DOT Standard Specification for HIGHWAY and STRUCTURE CONSTRUCTION latest edition.
2. Color:
  - Background - White
  - Message - Black
3. Message Series - D
4. Corners may be square or rounded when base material is plywood but borders shall be rounded as shown. When base material is metal, the corners and borders shall be rounded.



R11-2B

7

7

SIZE	A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q	R	S	T	U	V	W	X	Y	Z	Area sq. ft.
1																											
2S	48	30	1 3/8	1/2	5/8	8	5	4	19 3/4	9 3/4	9 7/8																10.0
2M	48	30	1 3/8	1/2	5/8	8	5	4	19 3/4	9 3/4	9 7/8																10.0
3	48	30	1 3/8	1/2	5/8	8	5	4	19 3/4	9 3/4	9 7/8																10.0
4	48	30	1 3/8	1/2	5/8	8	5	4	19 3/4	9 3/4	9 7/8																10.0
5	48	30	1 3/8	1/2	5/8	8	5	4	19 3/4	9 3/4	9 7/8																10.0

**STANDARD SIGN**  
R11-2B

*WISCONSIN DEPT OF TRANSPORTATION*


APPROVED *Matthew R. Rauch*  
For State Traffic Engineer

DATE 4/1/11 PLATE NO. R11-2B.2

PROJECT NO: \_\_\_\_\_ SHEET NO: \_\_\_\_\_ E


NOTES

1. Sign is Type II - Type H Reflective
2. Color:  
Background - White  
Message - Black
3. Message Series - C
4. Corners may be square or rounded when base material is plywood but borders shall be rounded as shown. When base material is metal, the corners and borders shall be rounded.
5. Substitute appropriate numerals to nearest quarter mile and optically adjust spacing to achieve proper balance.



R11-3

\*\* See Note 5



SIZE	A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q	R	S	T	U	V	W	X	Y	Z	Area sq. ft.
1	36	18	1 1/4	3/8	3/8	4	3	2	11 1/4	3	1 1/8	15 3/8	2	3 3/4	8 1/4	5/8		1 3/8	13 1/4	8 3/8	7/8	10 1/2	7 1/8			4.5	
2S	60	30	1 3/8	1/2	5/8	6	5	3 1/2	16 7/8	5	1 3/8	23 1/4	3	6 1/4	13 5/8	1 1/8		1 7/8	22 1/8	14	1 1/2	17 1/2	11 7/8			12.5	
2M	60	30	1 3/8	1/2	5/8	6	5	3 1/2	16 7/8	5	1 3/8	23 1/4	3	6 1/4	13 5/8	1 1/8		1 7/8	22 1/8	14	1 1/2	17 1/2	11 7/8			12.5	
3																											
4																											
5																											

STANDARD SIGN  
R11-3


WISCONSIN DEPT OF TRANSPORTATION

APPROVED *Matthew R. Rauch*  
for State Traffic Engineer


DATE 6/14/2021 PLATE NO. R11-3.9

NOTES

1. Sign is Type II - Type H Reflective
2. Color:  
Background - White  
Message - Black
3. Message Series - C
4. Corners may be square or rounded when base material is plywood but borders shall be rounded as shown. When base material is metal, the corners and borders shall be rounded.
5. Substitute appropriate numerals to nearest quarter mile and optically adjust spacing to achieve proper balance.



R11-3C      \*\* See Note 5



SIZE	A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q	R	S	T	U	V	W	X	Y	Z	Area sq. ft.
1	36	15	1 3/8	1/2	5/8	4	3	2 1/2	13 1/4	2 1/4	3	8	8	1 1/2	2	10 3/4		7 1/8									3.75
2S	60	24	1 3/8	1/2	5/8	6	5	4	20 1/8	3	5	12	13 1/4	1 3/4	3	17 3/8		11 7/8									10.0
2M	60	24	1 3/8	1/2	5/8	6	5	4	20 1/8	3	5	12	13 1/4	1 3/4	3	17 3/8		11 7/8									10.0
3																											
4																											
5																											

STANDARD SIGN  
R11-3C


WISCONSIN DEPT OF TRANSPORTATION

APPROVED *Matthew R. Rauch*  
For State Traffic Engineer

DATE 7/28/16      PLATE NO. R11-3C.3

**NOTES**

1. Sign is Type II - Type F Reflective - reference WIS DOT Standard Specification for HIGHWAY and STRUCTURE CONSTRUCTION latest edition.
2. Color:  
Background - Yellow  
Message - Black
3. Corners may be square or rounded when base material is plywood but borders shall be rounded as shown. When base material is metal, the corners and borders shall be rounded.



W1-7

7

7

SIZE	A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q	R	S	T	U	V	W	X	Y	Z	Area sq. ft.
1	36	18	1 1/8	3/8	1/2	5	2 1/2	5 3/4	3/4	15 5/8	10 1/8																4.5
2S	48	24	1 3/8	1/2	5/8	6 1/2	3 1/4	7 1/2	1	20 1/2	13 1/4																8.0
2M	48	24	1 3/8	1/2	5/8	6 1/2	3 1/4	7 1/2	1	20 1/2	13 1/4																8.0
3	60	30	1 3/8	1/2	5/8	8	4	9 1/4	1 1/4	25 3/8	16 1/4																12.5
4	60	30	1 3/8	1/2	5/8	8	4	9 1/4	1 1/4	25 3/8	16 1/4																12.5
5	96	48	2 1/4	3/4	1	13	6 1/2	15	2	41	26 1/2																32.0


**STANDARD SIGN**  
W1-7

WISCONSIN DEPT OF TRANSPORTATION


APPROVED *Matthew R. Rauch*  
For State Traffic Engineer

DATE 6/7/10 PLATE NO. W1-7.7

PROJECT NO: \_\_\_\_\_ HWY: \_\_\_\_\_ COUNTY: \_\_\_\_\_ SHEET NO: \_\_\_\_\_ E



W5-52L



W5-52R

NOTES

1. Sign is Type II - Type F Reflective - reference WIS DOT Standard Specification for HIGHWAY and STRUCTURE CONSTRUCTION latest edition.
2. Color:  
Background - Yellow  
Message - Black
3. Corners may be square or rounded when base material is plywood but borders shall be rounded as shown. When base material is metal, the corners and borders shall be rounded.
4. Alternate colors of stripes as shown.

7

7

SIZE	A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q	R	S	T	U	V	W	X	Y	Z	Area sq. ft.
1																											
2S	12	36				4 3/8	3 1/2	5 5/8	45°	4	4																3.0
2M	12	36				4 3/8	3 1/2	5 5/8	45°	4	4																3.0
3	18	54				6	5 1/2	8 1/2	45°	6	6 9/16																6.75
4																											
5																											


STANDARD SIGN  
W5-52L & W5-52R

WISCONSIN DEPT OF TRANSPORTATION


APPROVED *Matthew R. Rauch*  
for State Traffic Engineer

DATE 5/29/12 PLATE NO. W5-52.9


PROJECT NO: \_\_\_\_\_ HWY: \_\_\_\_\_ COUNTY: \_\_\_\_\_ SHEET NO: \_\_\_\_\_ E




W20-3A



W20-3D



W20-3C



W20-3B



W20-3G



W20-3F

**NOTES**

1. Sign is Type II - Type F Reflective - reference WIS DOT Standard Specification for HIGHWAY and STRUCTURE CONSTRUCTION latest edition.
2. Color:  
Background - Orange  
Message - Black
3. Message Series - see note 5
4. Corners may be square or rounded when base material is plywood but borders shall be rounded as shown. When base material is metal, the corners and borders shall be rounded.
5. Lines 1 and 2 are Series D.  
Line 3 is Series D for AHEAD and Series C for all other distances.

7

7

SIZE	A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q	R	S	T	U	V	W	X	Y	Z	Area sq. ft.
1	36		1 5/8	5/8	3/4	5	3 3/8	3 1/2	1 1/8	4	8 3/8	8 7/8	12 1/2	11	9	6	10 1/8	2 1/2	1 7/8	5 5/8	8	1 3/8	4 1/2	3 1/2	10 3/4	1 3/4	9.0
2S	48		2 1/4	3/4	1	7	4 1/2	4 3/4	1 1/2	5 1/4	11 3/4	12 1/2	17 1/4	14 5/8	12	8	13 1/2	3 3/8	2 5/8	7 1/2	10 5/8	1 7/8	6	4 5/8	14 3/8	2 3/8	16.0
2M	48		2 1/4	3/4	1	7	4 1/2	4 3/4	1 1/2	5 1/4	11 3/4	12 1/2	17 1/4	14 5/8	12	8	13 1/2	3 3/8	2 5/8	7 1/2	10 5/8	1 7/8	6	4 5/8	14 3/8	2 3/8	16.0
3	48		2 1/4	3/4	1	7	4 1/2	4 3/4	1 1/2	5 1/4	11 3/4	12 1/2	17 1/4	14 5/8	12	8	13 1/2	3 3/8	2 5/8	7 1/2	10 5/8	1 7/8	6	4 5/8	14 3/8	2 3/8	16.0
4	48		2 1/4	3/4	1	7	4 1/2	4 3/4	1 1/2	5 1/4	11 3/4	12 1/2	17 1/4	14 5/8	12	8	13 1/2	3 3/8	2 5/8	7 1/2	10 5/8	1 7/8	6	4 5/8	14 3/8	2 3/8	16.0
5	48		2 1/4	3/4	1	7	4 1/2	4 3/4	1 1/2	5 1/4	11 3/4	12 1/2	17 1/4	14 5/8	12	8	13 1/2	3 3/8	2 5/8	7 1/2	10 5/8	1 7/8	6	4 5/8	14 3/8	2 3/8	16.0


**STANDARD SIGN**  
W20-3A, B, C, D, F & G

WISCONSIN DEPT OF TRANSPORTATION

APPROVED *Matthew R. Rauch*  
For State Traffic Engineer

DATE 3/18/11 PLATE NO. W20-3.7

PROJECT NO: \_\_\_\_\_ HWY: \_\_\_\_\_ COUNTY: \_\_\_\_\_ SHEET NO: \_\_\_\_\_ E



**LIST OF DRAWINGS**


1. GENERAL PLAN
2. TYPICAL SECTION AND DESIGN DATA
3. QUANTITIES AND NOTES
4. SUBSURFACE EXPLORATION
5. WEST ABUTMENT
6. WEST ABUTMENT WING 1 DETAILS
7. WEST ABUTMENT WING 2 DETAILS
8. WEST ABUTMENT PILE LAYOUT & BILL OF BARS
9. EAST ABUTMENT
10. EAST ABUTMENT WING 3 DETAILS
11. EAST ABUTMENT WING 4 DETAILS
12. EAST ABUTMENT PILE LAYOUT & BILL OF BARS
13. SUPERSTRUCTURE
14. SUPERSTRUCTURE PLAN
15. SUPERSTRUCTURE DETAILS
16. TUBULAR STEEL RAILING TYPE 'M'
17. RAILING STEEL TYPE NY4
18. END POST DETAILS FOR RAILING STEEL TYPE NY4

\* ANCHOR ASSEMBLY FOR THRIE BEAM TYPE GUARDRAIL.  
 ○ DENOTES WING NUMBER

▨ COST OF EXCAVATION IN THE HATCHED AREAS SHALL BE INCLUDED IN THE CONTRACT LUMP SUM PRICE FOR "EXCAVATION FOR STRUCTURES BRIDGES B-68-148".

**PLAN**  
 SINGLE SPAN CONCRETE FLAT SLAB BRIDGE

FOR TYPICAL SECTION AND DESIGN DATA SEE SHEET 2



**ELEVATION**

(NORMAL TO C OF CREEK)

REMOVE EXISTING SUBSTRUCTURE UNITS AS NEEDED. COST CONSIDERED INCIDENTAL TO "REMOVING STRUCTURE" ITEM. TYPICAL AT ALL SUBSTRUCTURES.



08/23/2021

BRIDGE OFFICE CONTACT:  
 AARON BONK  
 (608) 261-0261  
 CONSULTANT CONTACT:  
 ARLEN BEAUDETTE  
 (715) 834-3161

7/6/2021  
 PENTABLE:Breau\_shd\_util.tbi

DATE: DATE:  
 CHECKED BY: BACK CHECKED BY:  
 CORRECTED BY:

8

8

NO.	DATE	REVISION	BY
ORIGINAL PLANS PREPARED BY			
<b>AVRES</b> 3433 Oakwood Hills Parkway Eau Claire, WI 54701 www.AyresAssociates.com			
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
ACCEPTED	SDR 08/24/21		DATE
CHIEF STRUCTURES DESIGN ENGINEER			
<b>STRUCTURE B-68-148</b>			
CTH B OVER SOUTH BRANCH LITTLE WOLF RIVER			
COUNTY	WAUPACA	TOWN/CITY/VILLAGE	SCANDANAVIA
DESIGN SPEC. AASHTO LRFD BRIDGE DESIGN SPECIFICATIONS			
DESIGNED BY	JLB	DESIGN CK'D.	CJM
DRAWN BY	JLB	PLANS CK'D.	AEB
<b>GENERAL PLAN</b>			SHEET 1 OF 18

**DESIGN DATA**

**LIVE LOAD:**

DESIGN LOADING: HL-93  
 INVENTORY RATING FACTOR: 1.08  
 OPERATING RATING FACTOR: 1.40  
 WISCONSIN STANDARD PERMIT VEHICLE (WIS-SPV) = 250 KIPS

STRUCTURE IS DESIGNED FOR A FUTURE WEARING SURFACE OF 20" S.F.

**MATERIAL PROPERTIES:**

CONCRETE MASONRY { SUPERSTRUCTURE  $f'_c = 4,000$  p.s.i.  
 ALL OTHER  $f'_c = 3,500$  p.s.i.  
 HIGH STRENGTH BAR STEEL REINFORCEMENT (GRADE 60)  $f_y = 60,000$  p.s.i.

**HYDRAULIC DATA:**

**100 YEAR FREQUENCY**

$Q_{100} = 1,170$  c.f.s.  
 VEL. = 8.7 f.p.s.  
 HW<sub>100</sub> = EL. 927.80  
 WATERWAY AREA = 135 sq. ft.  
 DRAINAGE AREA = 50.3 sq. mi.  
 ROADWAY OVERTOPPING = N/A  
 SCOUR CRITICAL CODE = 8  
 DATUM = NAVD88

**2 YEAR FREQUENCY**

$Q_2 = 410$  c.f.s.  
 VEL. = 8.0 f.p.s.  
 HW<sub>2</sub> = EL. 924.88

**FOUNDATION DATA:**


WEST ABUTMENT TO BE SUPPORTED ON 10 3/4"  $\phi$  x 0.365" CIP CONCRETE PILING (WITH PILE POINTS) DRIVEN TO A REQUIRED DRIVING RESISTANCE OF 150 TONS  $\pm$  PER PILE AS DETERMINED BY THE MODIFIED GATES DYNAMIC FORMULA. ESTIMATED LENGTH 50'-0".

EAST ABUTMENT TO BE SUPPORTED ON 10 3/4"  $\phi$  x 0.365" CIP CONCRETE PILING (WITH PILE POINTS) DRIVEN TO A REQUIRED DRIVING RESISTANCE OF 150 TONS  $\pm$  PER PILE AS DETERMINED BY THE MODIFIED GATES DYNAMIC FORMULA. ESTIMATED LENGTH 35'-0".

\*THE FACTORED AXIAL RESISTANCE OF PILES IN COMPRESSION USED FOR DESIGN IS THE REQUIRED DRIVING RESISTANCE MULTIPLIED BY A RESISTANCE FACTOR OF 0.5 USING MODIFIED GATES TO DETERMINE DRIVEN PILE CAPACITY.


**TRAFFIC DATA:**

A.A.D.T. = 1,275 (2022)  
 A.A.D.T. = 1,400 (2042)  
 R.D.S. = 35 M.P.H.



▲  $\pm 0.5\%$  CONSTRUCTION TOLERANCE IN SIDEWALK CROSS SLOPE. THE SIDEWALK CROSS SLOPE SHALL NOT EXCEED 2% WITHOUT PRIOR APPROVAL FROM THE ENGINEER.


**TYPICAL SECTION THRU BRIDGE**  
(LOOKING EAST)



**PILE SPlice DETAIL**

CAST-IN-PLACE PILE SHELL MATERIAL SHALL BE IN ACCORDANCE WITH THE STANDARD SPECIFICATIONS.

**CIP PILE WELD DETAIL**



**END PLATE DETAIL FOR CIP PILING**

\$PRNAME\$ I:\42\45-0487.00 - Waupaca Co. CTH B Structures\CADD\Final\450487 gp.dgn

8

8

NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
<b>STRUCTURE B-68-148</b>			
DRAWN BY		JLB	PLANS CK'D. AEB
<b>TYPICAL SECTION AND DESIGN DATA</b>			SHEET 2 OF 18

ORIGINAL PLANS PREPARED BY  
**AYRES** 3433 Oakwood Hills Parkway  
 Eau Claire, WI 54701  
 www.AyresAssociates.com


**TOTAL ESTIMATED QUANTITIES**

BID ITEM NUMBER	BID ITEMS	UNIT	W. ABUT.	E. ABUT.	SUPER.	TOTAL
203.0260	REMOVING STRUCTURE OVER WATERWAY MINIMAL DEBRIS B-68-15	EACH	-----	-----	-----	1
206.1000	EXCAVATION FOR STRUCTURES BRIDGES B-68-148	LS	-----	-----	-----	1
210.1500	BACKFILL STRUCTURE TYPE A	TON	220	220	-----	440
502.0100	CONCRETE MASONRY BRIDGES	CY	34	34	176	244
502.3200	PROTECTIVE SURFACE TREATMENT	SY	-----	-----	265	265
505.0400	BAR STEEL REINFORCEMENT HS STRUCTURES	LB	2,700	2,690	-----	5,390
505.0600	BAR STEEL REINFORCEMENT HS COATED STRUCTURES	LB	1,730	1,730	29,490	32,950
513.4061	RAILING TUBULAR TYPE M	LF	-----	-----	52.2	52.2
513.7084	RAILING STEEL TYPE NY4	LF	13.4	13.4	50.5	77.3
516.0500	RUBBERIZED MEMBRANE WATERPROOFING	SY	10	10	-----	20
550.0500	PILE POINTS	EACH	8	8	-----	16
550.2106	PILING CIP CONCRETE 10 3/4 x 0.365-INCH	LF	400	280	-----	680
606.0300	RIPRAP HEAVY	CY	80	80	-----	160
612.0406	PIPE UNDERDRAIN WRAPPED 6-INCH	LF	90	90	-----	180
645.0111	GEOTEXTILE TYPE DF SCHEDULE A	SY	60	60	-----	120
645.0120	GEOTEXTILE TYPE HR	SY	150	150	-----	300
NON-BID ITEMS						
	FILLER	SIZE	-----	-----	-----	1/2" & 3/4"

**GENERAL NOTES**

DRAWINGS SHALL NOT BE SCALED.  
 BAR STEEL REINFORCEMENT SHALL BE EMBEDDED 2" CLEAR UNLESS SHOWN OR NOTED OTHERWISE.  
 THE FIRST DIGIT OF A THREE DIGIT BAR NO. AND THE FIRST TWO DIGITS OF A FOUR DIGIT BAR NO. SIGNIFIES THE BAR SIZE. JOINT FILLER SHALL CONFORM TO THE REQUIREMENTS OF A.A.S.H.T.O. DESIGNATION M 153, TYPE I, II OR III OR A.A.S.H.T.O. DESIGNATION M 213.  
 THE SLOPE OF THE FILL IN FRONT OF THE ABUTMENTS SHALL BE COVERED WITH RIPRAP HEAVY AND GEOTEXTILE TYPE HR TO THE EXTENT SHOWN ON THE GENERAL PLAN SHEET AND IN THE ABUTMENT DETAILS.  
 SLAB FALSEWORK SHALL BE SUPPORTED ON PILES OR THE SUBSTRUCTURE UNLESS AN ALTERNATIVE METHOD IS APPROVED BY THE ENGINEER.  
 THE UPPER LIMITS OF "EXCAVATION FOR STRUCTURES BRIDGES B-68-148" SHALL BE THE EXISTING GROUNDLINE.  
 THE EXISTING STRUCTURE, B-68-15, TO BE REMOVED, IS A SINGLE SPAN STEEL DECK GIRDER BRIDGE ON TIMBER ABUTMENTS, 28 FEET LONG WITH A 24 FOOT CLEAR ROADWAY WIDTH.  
 PROTECTIVE SURFACE TREATMENT IS TO BE APPLIED AS SHOWN IN DETAILS ON THIS SHEET.  
 BEVEL EXPOSED EDGES OF CONCRETE 3/4" UNLESS NOTED OTHERWISE.  
 EXCAVATION BELOW THE ABUTMENT AND ABUTMENT BEDDING MATERIALS REQUIRES ENGINEER APPROVAL. GEOTEXTILE SHALL BE SET AT THE BOTTOM OF EXCAVATION AND EXTEND 2'-0" ABOVE BOTTOM OF ABUTMENT.  
 THE BACKFILL QUANTITIES ARE BASED ON THE PAY LIMITS SHOWN ON THE PLANS AND MAY NOT REFLECT ACTUAL PLACED QUANTITIES. "BACKFILL STRUCTURE TYPE A" REQUIRED DIRECTLY BEHIND ABUTMENTS AND ABUTMENT WINGS FOR 3 FEET. BACKFILL PLACED BEYOND PAY LIMITS OR EXCEEDING PLAN QUANTITIES SHALL BE INCIDENTAL TO EXCAVATION FOR STRUCTURES.  
 AT ABUTMENTS, CONCRETE POURED UNDERWATER WILL BE ALLOWED AND SHALL BE DONE IN ACCORDANCE WITH SECTION 502.3.5.3 OF THE STANDARD SPECIFICATIONS.  
 EXTENT OF BELOW GRADE SUBSTRUCTURES SHOWN ON PLANS ARE BASED ON AS BUILT PLANS. REMOVE EXISTING SUBSTRUCTURES AS NEEDED TO BUILD NEW SUBSTRUCTURES. COST OF SUBSTRUCTURE REMOVAL IS CONSIDERED INCIDENTAL TO "REMOVING STRUCTURE" BID ITEM.  
 AT THE BACK FACE OF ABUTMENTS AND AT EXISTING ABUTMENT REMOVALS, ALL VOLUME WHICH CANNOT BE PLACED BEFORE ABUTMENT CONSTRUCTION AND IS NOT OCCUPIED BY THE NEW STRUCTURE SHALL BE BACKFILLED WITH BACKFILL STRUCTURE TYPE A.


\$PRNAME\$ I:\42\45-0487.00 - Waupaca Co. CTH B=Structures=CADD\Final\450487 gp.dgn




**BACKFILL STRUCTURE LIMITS**

BACKFILL PAY LIMITS. BACKFILL BEYOND BACKFILL PAY LIMITS SHALL BE INCIDENTAL TO EXCAVATION FOR STRUCTURES. LIMITS OF EXCAVATION SHALL BE DETERMINED BY THE CONTRACTOR.

PIPE UNDERDRAIN WRAPPED 6-INCH. SLOPE 0.5% MIN. TO SUITABLE DRAINAGE. ATTACH RODENT SHIELD AT ENDS OF PIPE UNDERDRAIN AS DETAILED ON SHEET 7.



**PROTECTIVE SURFACE TREATMENT DETAILS**



**TYPICAL FILL SECTION AT WING TIPS 2 AND 3**

8

8



NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
<b>STRUCTURE B-68-148</b>			
DRAWN BY JLB		PLANS CK'D. AEB	
<b>QUANTITIES AND NOTES</b>			SHEET 3 OF 18

ORIGINAL PLANS PREPARED BY  
**AYRES** 3433 Oakwood Hills Parkway  
 Eau Claire, WI 54701  
 www.AyresAssociates.com

BORING #	DATE COMPLETED	NORTHING (Y)	EASTING (X)
1	3/26/2020	380739.77	519070.30
2	3/26/2020	380718.15	519112.76

BORINGS COMPLETED BY: ECS MIDWEST, LLC  
 REPORT COMPLETED BY: ECS MIDWEST, LLC  
 ALL COORDINATES REFERENCED TO WCCS WAUPACA COUNTY

SOUTH BRACNH LITTLE  
WOLF RIVER




STATE PROJECT NUMBER

6832-11-70

MATERIAL SYMBOLS

ASPHALT	TOPSOIL	PEAT
CONCRETE	FILL	GRAVEL
SAND	CLAY	SILT
BOULDERS OR COBBLES	LIMESTONE	BEDROCK (UNKNOWN)
SHALE	SANDSTONE	IGNEOUS/META

LEGEND OF BORING



(1) UNCONFINED STRENGTH, AS DETERMINED BY A POCKET PENETROMETER (TSF)

(2) UNLESS OTHERWISE, SPECIFIED THE SPT 'N' VALUE IS BASED ON AASHTO T-206, STANDARD PENETRATION TEST. THE SPT 'N' VALUE PRESENTED HAS NOT BEEN CORRECTED FOR OVERBURDEN PRESSURE OR HAMMER EFFICIENCY.

GROUND WATER ELEVATION

- ▽ AT TIME OF DRILLING
- ▽ END OF DRILLING
- ▽ AFTER DRILLING

ABBREVIATIONS

F-FINE M-MEDIUM C-COARSE ST-SHELBY TUBE

SUBSURFACE EXPLORATION FOR FOUNDATION DESIGN AND BIDDERS INFORMATION

BORINGS WERE COMPLETED AT POINTS APPROXIMATELY AS INDICATED ON THIS DRAWING TO OBTAIN INFORMATION CONCERNING THE CHARACTER OF SUBSURFACE MATERIALS FOUND AT THE SITE, BECAUSE THE INVESTIGATED DEPTHS ARE LIMITED AND THE AREA OF THE BORINGS IS VERY SMALL IN RELATION TO THE ENTIRE SITE, THE WISCONSIN DEPARTMENT OF TRANSPORTATION DOES NOT WARRANT SIMILAR SUBSURFACE CONDITIONS BELOW, BETWEEN, OR BEYOND THESE BORINGS. VARIATIONS IN SOIL CONDITIONS SHOULD BE EXPECTED AND FLUCTUATIONS IN GROUNDWATER LEVELS MAY OCCUR.


NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
<b>STRUCTURE B-68-148</b>			
DRAWN BY JLB		PLANS CKD. AEB	
<b>SUBSURFACE EXPLORATION</b>			SHEET 4 OF 18

\$PRNAME\$ I:\42\45-0487.00 - Waupaca Co. CTH B Structures\CADD\Final\450487 soil.dgn


8

8

NOTE: SEAL ALL EXPOSED HORIZONTAL AND VERTICAL SURFACES OF 1/2" FILLER WITH NON-STAINING GRAY NON-BITUMINOUS JOINT SEALER. (1" DEEP AND HOLD 1/8" BELOW SURFACE OF CONCRETE.)



**ELEVATION**  
(LOOKING WEST)




**SECTION F**

- ▲ 3/4" CORK FILLER ON VERTICAL FACE ONLY.
- ⊖ PIPE UNDERDRAIN WRAPPED 6-INCH. SLOPE 0.5% MIN. TO SUITABLE DRAINAGE. ATTACH RODENT SHIELD AT ENDS OF PIPE UNDERDRAIN AS DETAILED ON SHEET 7. RODENT SHIELD TO BE INCIDENTAL TO BID PRICE OF "PIPE UNDERDRAIN WRAPPED 6-INCH".
- ⊞ VERTICAL 18" RUBBERIZED MEMBRANE WATERPROOFING TO EXTEND FROM BRIDGE SEAT TO TOP OF WINGWALL.
- 18" RUBBERIZED MEMBRANE WATERPROOFING TO EXTEND FROM BRIDGE SEAT TO TOP OF WING.
- OPT. KEYED CONST. JOINT - FORMED BY A SURFACED BEVELED 2" x 6" WITH RUBBERIZED MEMBRANE WATERPROOFING ON B.F. (RUBBERIZED MEMBRANE WATERPROOFING INCIDENTAL TO BID ITEM "CONCRETE MASONRY BRIDGES" IF CONST. JOINT IS USED).

FOR PILE SPLICE DETAIL SEE SHEET 2.

B.F. DENOTES BACK FACE

F.F. DENOTES FRONT FACE



**PLAN**

7/6/2021 PENTABLE:BRReou\_shd\_util.tbl

8


8

NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
<b>STRUCTURE B-68-148</b>			
DRAWN BY		CLP	PLANS CK'D. AEB
<b>WEST ABUTMENT</b>			SHEET 5 OF 18


ORIGINAL PLANS PREPARED BY

**AYRES**


3433 Oakwood Hills Parkway  
Eau Claire, WI 54701  
www.AyresAssociates.com




**ELEVATION - WING I**



**SECTION A**



**SECTION B**



**SECTION C**

- ▣ RUBBERIZED MEMBRANE WATERPROOFING IF CONST. JOINT IS USED (COST INCIDENTAL TO BID ITEM "CONCRETE MASONRY BRIDGES")
- OPT. KEYED CONST. JOINT - FORMED BY A SURFACED BEVELED 2" x 6" WITH RUBBERIZED MEMBRANE WATERPROOFING ON B.F. (RUBBERIZED MEMBRANE WATERPROOFING INCIDENTAL TO BID ITEM "CONCRETE MASONRY BRIDGES" IF CONST. JOINT IS USED).
- ⊕ 3/4" 'V' GROOVE ON F.F. OF WING WALL NOT REQUIRED IF CONST. JT. IS NOT USED.
- ▣ 18" RUBBERIZED MEMBRANE WATERPROOFING TO EXTEND FROM BRIDGE SEAT TO TOP OF WING.

FOR PILE SPLICE DETAIL SEE SHEET 2.

B.F. DENOTES BACK FACE

E.F. DENOTES EACH FACE

F.F. DENOTES FRONT FACE

7/6/2021 PENTABLE:BRReou\_shd\_util.tbl

8




8

NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
<b>STRUCTURE B-68-148</b>			
DRAWN BY		CLP	PLANS CK'D. AEB
<b>WEST ABUTMENT WING 1 DETAILS</b>			SHEET 6 OF 18

ORIGINAL PLANS PREPARED BY

**AYRES**

3433 Oakwood Hills Parkway  
Eau Claire, WI 54701  
www.AyresAssociates.com



\* DIMENSIONS ARE APPROXIMATE. THE GRATE IS SIZED TO FIT INTO A PIPE COUPLING. ORIENT SO SLOTS ARE VERTICAL.

THE RODENT SHIELD, PIPE COUPLING AND SCREWS SHALL BE CONSIDERED INCIDENTAL TO THE BID ITEM "PIPE UNDERDRAIN WRAPPED 6-INCH".

THE RODENT SHIELD SHALL BE PVC GRATE SIMILAR TO THIS DETAIL. THE GRATE IS COMMERCIALY AVAILABLE AS A FLOOR STRAINER. A PIPE COUPLING IS REQUIRED FOR THE ATTACHMENT OF THIS SHIELD TO THE EXPOSED END OF THE PIPE UNDERDRAIN. THE SHIELD SHALL BE FASTENED TO THE PIPE COUPLING WITH TWO OR MORE NO. 10 x 1-INCH SHEET METAL SCREWS.

**RODENT SHIELD DETAIL**

⊕ 3/4" "V" GROOVE ON FRONT FACE OF WINGWALL. ONLY REQUIRED IF OPTIONAL CONSTRUCTION JOINT IS USED.

● OPT. CONST. JOINT FORMED BY A BEVELED 2" x 6" KEYWAY WITH MEMBRANE ON BACKFACE.

⊞ 18" RUBBERIZED MEMBRANE WATERPROOFING. SEAL ALL HOIRZONTAL AND VERTICAL JOINTS ON BACKFACE.

B.F. DENOTES BACK FACE.

F.F. DENOTES FRONT FACE.

E.F. DENOTES EACH FACE.


7/6/2021  
PENTABLE:BRou\_shd\_util.tbl

8

8


NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
<b>STRUCTURE B-68-148</b>			
DRAWN BY		CLP	PLANS CK'D. AEB
<b>WEST ABUTMENT WING 2 DETAILS</b>			SHEET 7 OF 18

ORIGINAL PLANS PREPARED BY  
**AYRES** 3433 Oakwood Hills Parkway  
Eau Claire, WI 54701  
www.AyresAssociates.com



**TYPICAL SECTION THRU BODY**

NOTE: DO NOT PLACE FILL ABOVE THREE FEET FROM BOTTOM OF ABUTMENT UNTIL SUPERSTRUCTURE IS IN PLACE.



**BILL OF BARS**

BAR NO.	COATED BAR	NO. REQ'D.	LENGTH	BENT BAR	BUNDLED	BAR SERIES	1,730' COATED 2,700' UNCOATED	
							LOCATION	
A501		86	6-1	X			BODY VERT. E.F.	
A502		9	42-7				BODY HORIZ. F.F.	
A803		9	24-0	X			BODY HORIZ. B.F. @ WING 1	
A804		9	26-0	X			BODY HORIZ. B.F. @ WING 2	
A405		33	2-10	X			BODY TIES	
A506		43	6-1	X			BODY VERT. TOP	
A507		17	4-11	X			BODY VERT. TOP	
A408		3	16-6				BODY HORIZ. TOP	
A409		2	31-4				BODY HORIZ. @ TOP NOTCH	
A410		21	3-9	X			BODY VERT. @ TOP NOTCH	
A411	X	22	9-0	X			WING 1 VERT. E.F.	
A412	X	4	10-2	X			WING 1 VERT. E.F.	
A513	X	9	11-7	X			WING 1 HORIZ. F.F.	
A814	X	9	13-2	X			WING 1 HORIZ. B.F.	
A415	X	2	10-3				WING 1 HORIZ. E.F.	
A416	X	2	8-8				WING 1 HORIZ. E.F.	
A417	X	2	6-8				WING 1 HORIZ. E.F.	
A418	X	2	4-8				WING 1 HORIZ. E.F.	
A419	X	2	10-8	X			WING 1 DIAG. E.F.	
A420	X	5	8-11	X			WING 1 HORIZ.	
A421	X	7	4-3				WING 1 VERT.	
A522	X	12	15-8	X			WING 2 VERT.	
A523	X	6	14-5				WING 2 HORIZ. F.F.	
A624	X	11	13-7				WING 2 HORIZ. B.F. & TOP	
A625	X	17	11-9	X			WING 2 VERT.	
A426	X	8	11-8				WING 2 HORIZ. E.F.	
A627	X	17	4-10	X			WING 2 VERT.	
A628	X	2	11-8				WING 2 HORIZ. E.F.	
A429	X	4	4-7				BODY VERT. END @ WING 2	

BENDING DIMENSIONS ARE OUT TO OUT OF BARS.  
 ⊗ LENGTH SHOWN FOR BAR IS AN AVERAGE LENGTH AND SHOULD ONLY BE USED FOR BAR WEIGHT CALCULATIONS. SEE BAR SERIES TABLE FOR ACTUAL LENGTHS.

**BAR SERIES TABLE**

BAR MARK	NO. REQ'D.	LENGTH
A411	2 SERIES OF 11	7'-10" TO 10'-2"

BUNDLE AND TAG EACH SERIES SEPARATELY.

▣ ABUTMENT TO BE SUPPORTED ON 10 3/4" φ x 0.365" CIP CONCRETE PILING (WITH PILE POINTS) DRIVEN TO A REQ'D. DRIVING RESISTANCE OF 150 TONS PER PILE ESTIMATED LENGTH 50'-0".

⊗ STEEL TROWEL TOP SURFACE OF ABUTMENT. PLACE MULTIPLE LAYERS OF POLYETHYLENE SHEETS OVER ENTIRE ABUTMENT TOP BEFORE PLACING SUPERSTRUCTURE. TOTAL THICKNESS OF SHEETS SHALL BE AT LEAST 0.03".

⊖ PIPE UNDERDRAIN WRAPPED 6-INCH. SLOPE 0.5% MIN. TO SUITABLE DRAINAGE. ATTACH RODENT SHIELD AT ENDS OF PIPE UNDERDRAIN AS DETAILED ON SHEET 7. RODENT SHIELD TO BE INCIDENTAL TO BID PRICE OF "PIPE UNDERDRAIN WRAPPED 6-INCH".


FOR PILE SPLICE DETAIL SEE SHEET 2.

B.F. DENOTES BACK FACE

E.F. DENOTES EACH FACE

F.F. DENOTES FRONT FACE


ORIGINAL PLANS PREPARED BY  
**AYRES** 3433 Oakwood Hills Parkway  
 Eau Claire, WI 54701  
 www.AyresAssociates.com




**PILE LAYOUT**

NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
<b>STRUCTURE B-68-148</b>			
DRAWN BY		CLP	PLANS CK'D. AEB
<b>WEST ABUTMENT PILE LAYOUT &amp; BILL OF BARS</b>			SHEET 8 OF 18

NOTE: SEAL ALL EXPOSED HORIZONTAL AND VERTICAL SURFACES OF 1/2" FILLER WITH NON-STAINING GRAY NON-BITUMINOUS JOINT SEALER. (1" DEEP AND HOLD 1/8" BELOW SURFACE OF CONCRETE.)




**ELEVATION**  
(LOOKING EAST)



**SECTION F**

- ▲ 3/4" CORK FILLER ON VERTICAL FACE ONLY.
  - ⊖ PIPE UNDERDRAIN WRAPPED 6-INCH. SLOPE 0.5% MIN. TO SUITABLE DRAINAGE. ATTACH RODENT SHIELD AT ENDS OF PIPE UNDERDRAIN AS DETAILED ON SHEET 7. RODENT SHIELD TO BE INCIDENTAL TO BID PRICE OF "PIPE UNDERDRAIN WRAPPED 6-INCH".
  - ⊞ VERTICAL 18" RUBBERIZED MEMBRANE WATERPROOFING TO EXTEND FROM BRIDGE SEAT TO TOP OF WINGWALL.
  - 18" RUBBERIZED MEMBRANE WATERPROOFING TO EXTEND FROM BRIDGE SEAT TO TOP OF WING.
  - OPT. KEYED CONST. JOINT - FORMED BY A SURFACED BEVELED 2" x 6" WITH RUBBERIZED MEMBRANE WATERPROOFING ON B.F. (RUBBERIZED MEMBRANE WATERPROOFING INCIDENTAL TO BID ITEM "CONCRETE MANSIONRY BRIDGES" IF CONST. JOINT IS USED).
- FOR PILE SPLICE DETAIL SEE SHEET 2.
- B.F. DENOTES BACK FACE  
F.F. DENOTES FRONT FACE



**PLAN**


7/6/2021 PENTABLE:BRReou\_shd\_util.tbl

8


8

NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
<b>STRUCTURE B-68-148</b>			
DRAWN BY		CLP	PLANS CK'D. AEB
<b>EAST ABUTMENT</b>			SHEET 9 OF 18

ORIGINAL PLANS PREPARED BY  
**AYRES** 3433 Oakwood Hills Parkway  
Eau Claire, WI 54701  
www.AyresAssociates.com



**ELEVATION - WING 3**



**SECTION D**

- ⊕ 3/4" "V" GROOVE ON FRONT FACE OF WINGWALL. ONLY REQUIRED IF OPTIONAL CONSTRUCTION JOINT IS USED.
  - OPT. CONST. JOINT FORMED BY A BEVELED 2" x 6" KEYWAY WITH MEMBRANE ON BACKFACE.
  - ⊞ 18" RUBBERIZED MEMBRANE WATERPROOFING. SEAL ALL HORIZONTAL AND VERTICAL JOINTS ON BACKFACE.
- B.F. DENOTES BACK FACE.  
 F.F. DENOTES FRONT FACE.  
 E.F. DENOTES EACH FACE.


7/6/2021 PENTABLE:BRReou\_shd\_util.tbl

8


8

NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
<b>STRUCTURE B-68-148</b>			
DRAWN BY		CLP	PLANS CK'D. AEB
<b>EAST ABUTMENT WING 3 DETAILS</b>			SHEET 10 OF 18


ORIGINAL PLANS PREPARED BY  
**AYRES** 3433 Oakwood Hills Parkway  
 Eau Claire, WI 54701  
 www.AyresAssociates.com




**ELEVATION - WING 4**



**SECTION A**



**SECTION B**



**SECTION C**

- ▣ RUBBERIZED MEMBRANE WATERPROOFING IF CONST. JOINT IS USED (COST INCIDENTAL TO BID ITEM "CONCRETE MANSIONRY BRIDGES")
- OPT. KEYED CONST. JOINT - FORMED BY A SURFACED BEVELED 2" x 6" WITH RUBBERIZED MEMBRANE WATERPROOFING ON B.F. (RUBBERIZED MEMBRANE WATERPROOFING INCIDENTAL TO BID ITEM "CONCRETE MANSIONRY BRIDGES" IF CONST. JOINT IS USED).
- ⊕ 3/4" 'V' GROOVE ON F.F. OF WING WALL NOT REQUIRED IF CONST. JT. IS NOT USED.
- ▣ 18" RUBBERIZED MEMBRANE WATERPROOFING TO EXTEND FROM BRIDGE SEAT TO TOP OF WING.

FOR PILE SPLICE DETAIL SEE SHEET 2.

B.F. DENOTES BACK FACE

E.F. DENOTES EACH FACE

F.F. DENOTES FRONT FACE


7/6/2021 PENTABLE:BRReou\_shd\_util.tbl

8

8



NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
<b>STRUCTURE B-68-148</b>			
DRAWN BY		CLP	PLANS CK'D. AEB
<b>EAST ABUTMENT WING 4 DETAILS</b>			SHEET 11 OF 18

ORIGINAL PLANS PREPARED BY  
**AYRES** 3433 Oakwood Hills Parkway  
Eau Claire, WI 54701  
www.AyresAssociates.com



**TYPICAL SECTION THRU BODY**

NOTE: DO NOT PLACE FILL ABOVE THREE FEET FROM BOTTOM OF ABUTMENT UNTIL SUPERSTRUCTURE IS IN PLACE.



BAR NO.	DIM. 'A'	DIM. 'B'
B804	1'-0 3/4"	1'-0 3/4"
B521	1'-0 3/4"	1'-0 3/4"
B822	1'-0 3/4"	1'-0 3/4"
B427	8'-0"	2'-5"

**BILL OF BARS**

BAR NO.	COATED BAR	NO. REQ'D.	LENGTH	BENT BAR	BUNDLED BAR SERIES	1,730* COATED 2,690* UNCOATED	
						LOCATION	
B501		86	6-1	X			BODY VERT. E.F.
B502		9	41-8				BODY HORIZ. F.F.
B803		9	26-0	X			BODY HORIZ. B.F. @ WING 3
B804		9	24-0	X			BODY HORIZ. B.F. @ WING 4
B405		33	2-10	X			BODY TIES
B506		43	6-1	X			BODY VERT. TOP
B507		17	4-11	X			BODY VERT. TOP
B408		3	16-6				BODY HORIZ. TOP
B409		2	31-4				BODY HORIZ. @ TOP NOTCH
B410		21	3-9	X			BODY VERT. @ TOP NOTCH
B511	X	12	15-8	X			WING 3 VERT.
B512	X	6	14-5				WING 3 HORIZ. F.F.
B613	X	11	13-7				WING 3 HORIZ. B.F. & TOP
B614	X	17	11-9	X			WING 3 VERT.
B415	X	8	11-8				WING 3 HORIZ. E.F.
B616	X	17	4-10	X			WING 3 VERT.
B617	X	2	11-8				WING 3 HORIZ. E.F.
B418	X	3	4-7				BODY VERT. END @ WING 3
B419	X	22	9-0	X			WING 4 VERT. E.F.
B420	X	4	10-2	X			WING 4 VERT. E.F.
B521	X	9	11-7	X			WING 4 HORIZ. F.F.
B822	X	9	13-2	X			WING 4 HORIZ. B.F.
B423	X	2	10-3				WING 4 HORIZ. E.F.
B424	X	2	8-8				WING 4 HORIZ. E.F.
B425	X	2	6-8				WING 4 HORIZ. E.F.
B426	X	2	4-8				WING 4 HORIZ. E.F.
B427	X	2	10-8	X			WING 4 DIAG. E.F.
B428	X	5	8-2	X			WING 4 HORIZ.
B429	X	7	4-3				WING 4 VERT.

BENDING DIMENSIONS ARE OUT TO OUT OF BARS.  
 ⊗ LENGTH SHOWN FOR BAR IS AN AVERAGE LENGTH AND SHOULD ONLY BE USED FOR BAR WEIGHT CALCULATIONS. SEE BAR SERIES TABLE FOR ACTUAL LENGTHS.

**BAR SERIES TABLE**


BAR MARK	NO. REQ'D.	LENGTH
B419	2 SERIES OF 11	7'-10" TO 10'-2"

BUNDLE AND TAG EACH SERIES SEPARATELY.

▣ ABUTMENT TO BE SUPPORTED ON 10 3/4" φ x 0.365" CIP CONCRETE PILING (WITH PILE POINTS) DRIVEN TO A REQ'D. DRIVING RESISTANCE OF 150 TONS PER PILE ESTIMATED LENGTH 35'-0".

⊗ STEEL TROWEL TOP SURFACE OF ABUTMENT. PLACE MULTIPLE LAYERS OF POLYETHYLENE SHEETS OVER ENTIRE ABUTMENT TOP BEFORE PLACING SUPERSTRUCTURE. TOTAL THICKNESS OF SHEETS SHALL BE AT LEAST 0.03".

⊖ PIPE UNDERDRAIN WRAPPED 6-INCH. SLOPE 0.5% MIN. TO SUITABLE DRAINAGE. ATTACH RODENT SHIELD AT ENDS OF PIPE UNDERDRAIN AS DETAILED ON SHEET 7. RODENT SHIELD TO BE INCIDENTAL TO BID PRICE OF "PIPE UNDERDRAIN WRAPPED 6-INCH".



**PILE LAYOUT**

FOR PILE SPLICE DETAIL SEE SHEET 2.

B.F. DENOTES BACK FACE

E.F. DENOTES EACH FACE

F.F. DENOTES FRONT FACE

ORIGINAL PLANS PREPARED BY

**AYRES** 3433 Oakwood Hills Parkway  
 Eau Claire, WI 54701  
 www.AyresAssociates.com

NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
<b>STRUCTURE B-68-148</b>			
DRAWN BY		CLP	PLANS CK'D. AEB
<b>EAST ABUTMENT PILE LAYOUT &amp; BILL OF BARS</b>			SHEET 12 OF 18


TOP TRANSVERSE BARS IN SLAB SHALL BE SUPPORTED BY INDIVIDUAL BAR CHAIRS AT APPROXIMATELY 3'-0" CENTERS EACH WAY. BOTTOM LONGITUDINAL BARS SHALL BE SUPPORTED BY CONTINUOUS BAR CHAIRS AT APPROXIMATELY 4'-0" CENTERS.

ALL SLAB THICKNESS DIMENSIONS ARE MINIMUM. ANY TOLERANCES NECESSARY TO CORRECT CONSTRUCTION DISCREPANCIES ARE TO BE PLUS (+).


**BILL OF BARS**

BAR NO.	COATED BAR	NO. REQ'D.	LENGTH	BENT BAR	BUNDLED	BAR SERIES	29,490* COATED
							LOCATION
S401	X	62	3-3	X			SLAB @ ABUT. NOTCH
S402	X	4	31-4				SLAB @ ABUT. NOTCH
S503	X	80	6-1	X			SLAB @ ABUT.
S504	X	80	3-0	X			SLAB @ ABUT.
S1105	X	75	44-3	X			SLAB LONG. BOT.
S506	X	79	39-8				SLAB TRANS. BOT.
S507	X	51	39-8				SLAB TRANS. TOP
S508	X	40	50-2				SLAB LONG. TOP
S409	X	101	4-0	X			SLAB @ SDWK. @ EDGE OF SLAB
S410	X	101	3-8	X			SLAB @ SDWK. @ CURB
S411	X	22	25-11				SDWK. LONG. TOP
S512	X	151	8-2	X			SDWK. TRANS. TOP
S613	X	14	12-0	X			SLAB @ RAIL POSTS
S614	X	24	6-0				SLAB @ INT. RAIL POSTS
S615	X	8	6-0	X			SLAB @ END RAIL POSTS
S616	X	2	12-0	X			SLAB @ END RAIL POSTS
S617	X	16	12-0	X			SLAB @ RAIL POSTS
S618	X	28	6-0				SLAB @ INT. RAIL POSTS
S619	X	8	6-0	X			SLAB @ END RAIL POSTS
S620	X	2	12-0	X			SLAB @ END RAIL POSTS

BENDING DIMENSIONS ARE OUT TO OUT OF BARS.




**TYPICAL SECTION THRU BRIDGE**





**TYPICAL SECTION THRU SIDEWALK**

WIRE BARS TOGETHER @ 2'-0" CENTERS




**BUNDLING DETAIL**



▲ ±0.5% CONSTRUCTION TOLERANCE IN OBSERVATION PLATFORM CROSS SLOPE. THE OBSERVATION PLATFORM CROSS SLOPE SHALL NOT EXCEED 2% WITHOUT PRIOR APPROVAL FROM THE ENGINEER.

☐ CONST. JOINT - STRIKE OFF AS SHOWN AND LEAVE ROUGH. FOR DECK POUR, MATCH BRIDGE X-SLOPE.

⊙ 3/4" V-GROOVE. EXTEND V-GROOVE TO 6" FROM FRONT FACE OF ABUTMENTS - TYP.



**S512**


7/6/2021  
PENTABLE:BRReou\_shd\_util.tbl

8

8

ORIGINAL PLANS PREPARED BY  
**AYRES** 3433 Oakwood Hills Parkway  
Eau Claire, WI 54701  
www.AyresAssociates.com

NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
<b>STRUCTURE B-68-148</b>			
DRAWN BY CLP		PLANS CK'D. AEB	
<b>SUPERSTRUCTURE</b>			SHEET 13 OF 18



**PLAN**

**SURVEY TOP OF SLAB ELEVATIONS**

LOCATION	€ OF W. ABUT.	5/10 PTS.	€ OF E. ABUT.
N. EDGE OF SLAB			
€ OF STRUCTURE			
S. EDGE OF SLAB			

PRIOR TO RELEASING SLAB FALSEWORK, TAKE TOP OF DECK ELEVATIONS AT THE € OF ABUTMENTS AND AT 5/10 PTS. TO VERIFY CAMBER. TAKE ELEVATIONS ALONG EDGE OF SLAB AND CROWN OR €. RECORD THE ELEVATIONS IN THE ABOVE TABLE FOR THE "AS BUILT" PLANS.


**TOP OF DECK ELEVATIONS**

LOCATION	€ OF W. ABUT.	0.1	0.2	0.3	0.4	0.5	0.6	0.7	0.8	0.9	€ OF E. ABUT.
N. EDGE OF SLAB	931.12	931.07	931.03	930.99	930.94	930.90	930.85	930.81	930.77	930.72	930.68
INSIDE FACE OF SDWK	931.29	931.25	931.21	931.16	931.12	931.07	931.03	930.99	930.94	930.90	930.86
€ OF STRUCTURE	931.62	931.57	931.53	931.49	931.44	931.40	931.36	931.31	931.27	931.22	931.18
S. EDGE OF SLAB	931.32	931.28	931.23	931.19	931.14	931.10	931.06	931.01	930.97	930.92	930.88

ELEVATIONS SHOWN ARE FINISHED DECK AND DO NOT INCLUDE ALLOWANCES OF DEAD LOAD DEFLECTION AND FUTURE CREEP.


NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
<b>STRUCTURE B-68-148</b>			
DRAWN BY CLP		PLANS CK'D. AEB	
<b>SUPERSTRUCTURE PLAN</b>			SHEET 14 OF 18

ORIGINAL PLANS PREPARED BY  
**AYRES** 3433 Oakwood Hills Parkway  
Eau Claire, WI 54701  
www.AyresAssociates.com



**PART LONGITUDINAL SECTION**

- 18" RUBBERIZED MEMBRANE WATERPROOFING
- ▲ DIMENSIONS MEASURED NORMAL TO CL OF SUBSTRUCTURE.
- DIMENSIONS MEASURED ALONG CL OF CTH B.



**CAMBER DIAGRAM**

CAMBER SPAN AS SHOWN TO PROVIDE FOR DEAD LOAD DEFLECTION & FUTURE CREEP. CAMBER DOES NOT INCLUDE ALLOWANCE FOR FORM SETTLEMENT.


7/6/2021 PENTABLE:BRou\_shd\_util.tbl

8


8

NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
<b>STRUCTURE B-68-148</b>			
DRAWN BY		CLP	PLANS CK'D. AEB
<b>SUPERSTRUCTURE DETAILS</b>			SHEET 15 OF 18


ORIGINAL PLANS PREPARED BY  
**AYRES** 3433 Oakwood Hills Parkway  
 Eau Claire, WI 54701  
 www.AyresAssociates.com




SECTION THRU RAILING ON DECK




FIELD ERECTION JOINT DETAIL




SHOP RAIL SPLICE DETAIL



ANCHOR BOLTS




SECTION THRU POST WEB




SECTION THRU RAIL


TYPICAL RAIL TO POST CONNECTIONS




TOP VIEW AT END POST




SECTION C-C




DETAIL AT END POST




SECTION D-D




SECTION A-A



ANCHOR PLATE AT BEAM GUARD ATTACHMENT



BACK-UP PLATE DETAIL



ANCHOR PLATE AT RAIL TO DECK CONNECTION

LEGEND

- ① W6 x 25 WITH 1/8" X 1/2" HORIZ. SLOTS ON EACH SIDE OF POST FOR BOLT NO. 6. CUT BOTTOM OF POST TO MATCH CROSS SLOPE OF ROADWAY. PLACE POST VERTICAL. PLACE POSTS NORMAL TO GRADE LINE.
- ② PLATE 1/4" X 11 3/4" X 1'-8" WITH 1 7/16" DIA. OVERSIZED HOLES FOR ANCHOR BOLTS NO. 3. WELD TO NO. 1 AS SHOWN.
- ③ ASTM A449 - 1/8" DIA. ANCHOR BOLTS WITH NUT AND HARDENED WASHER (ALL GALVANIZED), 5 REQ'D. PER POST. THREAD 3" AND PLACE NORMAL TO PLATE NO. 2. CHAMFER TOP OF BOLTS BEFORE THREADING. USE 1'-9" LONG IN ABUTMENT WINGS. AT POSTS ON CONCRETE SLAB SUPERSTRUCTURES WHERE THE SLAB THICKNESS IS > 16" USE 1'-3" LONG. USE 10 3/4" LONG AT ALL OTHER LOCATIONS. (AN EQUIVALENT THREADED ROD WITH NUTS AND HARDENED WASHERS MAY BE SUBSTITUTED FOR ANCHOR BOLTS IN WINGS IF REQ'D. FOR CONSTRUCTABILITY.)
- ④ 5/8" x 11" x 1'-8" ANCHOR PLATE (GALVANIZED) WITH 1 3/16" DIA. HOLES FOR ANCHOR BOLTS NO. 3
- ⑤ TS 5 x 4 x 0.25 STRUCTURAL TUBING. ATTACH TO NO. 1 WITH NO. 6.
- ⑤A TS 5 x 5 x 0.25 STRUCTURAL TUBING. ATTACH TO NO. 1 WITH NO. 6.
- ⑥ 7/8" DIA. A325 SLOTTED ROUND HEAD BOLT WITH NUT, 3/16" X 1 5/8" X 1 5/8" MIN. WASHER, AND LOCK WASHER (2 REQ'D. AT EACH RAIL TO POST LOCATION.)
- ⑦ 1/2" THK. BACK-UP PLATE WITH 2 - 7/8" X 1/2" THREADED SHOP WELDED STUDS (NO. 12). BOLT TO RAIL AS SHOWN IN DETAIL. REQUIRED AT THREE BEAM GUARD RAIL ATTACHMENTS ONLY. PLACE SYMMETRICALLY ABOUT TUBES NO. 5A.
- ⑧ 1" DIA. HOLES IN PLATE NO. 7 & TUBES NO. 5A FOR 7/8" DIA. A325 BOLTS WITH HEX NUTS AND WASHERS. 6 HOLES IN TUBES AND PLATE NO. 7.
- ⑨ SPLICE SLEEVE FABRICATED FROM 1/4" PLATE. PROVIDE "SLIDING FIT".
- ⑩ 3/8" X 3 5/8" X 2'-4" PLATE. 2 PER RAIL. USED IN NO. 5 & 5A.
- ⑩A 3/8" X 2 5/8" X 2'-4" PLATE USED IN NO. 5, 3/8" X 3 5/8" X 2'-4" PLATE USED IN NO. 5A. 2 PER RAIL.
- ⑪ 7/8" DIA. A325 ROUND HEAD BOLT WITH NUT, WASHER, AND LOCK WASHER. USE 1 5/8" X 1 1/4" LONGIT. SLOTTED HOLES IN PLATE NO. 10A. AT FIELD JOINTS AND 1 1/8" X 2 1/2" MIN. LONGIT. SLOTTED HOLES AT EXP. JOINTS IN PLATE NO. 10A. PROVIDE 5/16" DIA. ROUND HOLES IN TUBES NO. 5 AND NO. 5A.
- ⑫ 7/8" DIA. X 1 1/2" LONG THREADED SHOP WELDED STUDS (2 REQ'D).
- ⑬ 3/8" X 8" X 1'-6" PLATE. BOLT TO RAIL AS SHOWN IN DETAIL. REQ'D. AT THREE BEAM GUARD RAIL ATTACHMENTS ONLY. PLACE SYM. ABOUT TUBES NO. 5A.
- ⑭ 7/8" DIA. X 2" LONG A325 HEX BOLT WITH NUT AND WASHER (5 REQ'D.).
- ⑮ 1" DIA. HOLES IN TUBES NO. 5A FOR 7/8" DIA. A325 ROUND HEAD BOLT WITH NUT, WASHER AND LOCK WASHER (4 REQ'D.). 4 HOLES IN TUBES.

GENERAL NOTES

1. BID ITEM SHALL BE "RAILING TUBULAR TYPE M" WHICH INCLUDES ALL ITEMS SHOWN.
2. RAIL POST AND BASE PLATES SHALL CONFORM TO THE REQUIREMENTS OF ASTM A709 GRADE 50. HOLLOW RAILING STRUCTURAL TUBING SHALL CONFORM TO THE REQUIREMENTS OF ASTM A500 GRADE B OR C AT A CERTIFIED FY = 50 KSI. ANCHOR PLATES, AND SPLICE TUBE PLATES SHALL CONFORM TO THE REQUIREMENTS OF ASTM A709 GRADE 36.
3. THE NUT SECURING THE POST BASE PLATE TO THE CONCRETE SHALL BE TIGHTENED TO A SNUG FIT AND GIVEN AN ADDITIONAL 1/8" TURN.
4. RAILS SHALL BE CONTINUOUS OVER A MINIMUM OF THREE (3) POSTS WITHOUT SPLICES WHERE POSSIBLE. RAILS SHALL BE SPLICED IN A PANEL OVER EXPANSION JOINTS.
5. ENDS OF TUBE SECTIONS SHALL BE SAWED. GRIND SMOOTH EXPOSED EDGES. ALL CUT ENDS SHALL BE TRUE AND SMOOTH.
6. WELD IS THE SAME ON BOTH FLANGES. FLANGE WELD DOES NOT REQUIRE MAGNETIC PARTICLE TESTING.
7. FILL BOLT SLOT OPENINGS IN POST SHIMS AND PLATE NO. 2 AND CAULK AROUND PERIMETER OF PLATE NO. 2 WITH NON-STAINING GRAY NON-BITUMINOUS JOINT SEALER. STEEL POST SHIMS MAY BE USED UNDER POSTS WHERE REQ'D. FOR ALIGNMENT.
8. POST BASE PLATES SHALL BE FLAT WITH ALL SURFACES SMOOTH AND FREE FROM WARP AND ALL EDGES SMOOTH, STRAIGHT AND VERTICAL. ALL PLATE CUTS SHALL BE MACHINE OR MACHINE FLAME CUT.
9. ALL MATERIAL SHALL BE GALVANIZED AFTER FABRICATION. PRIOR TO GALVANIZING, ALL STEEL RAILING POSTS & STEEL TUBING SHALL BE GIVEN A NO. 6 BLAST CLEANING BY SSPC SPECIFICATIONS.

▲ TIE TO TOP MAT OF STEEL.

\* ANCHOR BOLT ASSEMBLY MAY BE TACK WELDED, EITHER IN THE SHOP, OR IN THE FIELD AFTER THE ANCHOR PLATE IS PLACED.


ORIGINAL PLANS PREPARED BY  
**AYRES** 3433 Oakwood Hills Parkway  
Eau Claire, WI 54701  
www.AyresAssociates.com

NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
<b>STRUCTURE B-68-148</b>			
DRAWN BY		CLP	PLANS CK'D. AEB
<b>TUBULAR STEEL RAILING TYPE 'M'</b>			SHEET 16 OF 18



8

8


\$PRNAME\$ I:\42-45-0487-00 - Waupaca Co. CTH B=Structures=CADD=Final\450487 NY4 RAIL.DGN




**SECTION THRU RAILING ON SIDEWALK**  
\*NORMAL TO BASE PLATE




**FIELD ERECTION JOINT DETAIL**




**SPLICE TUBE**




**SECTION A-A**  
BASE PLATE DETAIL




**SPLICE BAR**




**PART ELEVATION OF RAILING AT POST**  
INTERIOR ELEVATION



**PART ELEVATION OF RAILING**  
INTERIOR ELEVATION  
(WING 3 SHOWN, WING 2 SIMILAR)



**ANCHOR BOLTS**  
FOR ANCHOR BOLTS IN WINGS, TACK WELD MAY BE USED IN FIELD AFTER ANCHOR PLATE IS IN POSITION IF REQ'D FOR CONSTRUCTIBILITY.



**SHOP RAIL SPLICE DETAIL**  
(LOCATION MUST BE SHOWN ON SHOP DRAWINGS)


**LEGEND**

- ① W6 X 25 WITH 1/8" X 1 3/8" HORIZONTAL SLOTTED HOLES ON EACH SIDE OF POST FOR BOLT NO. 6 AT TOP TWO RAILS. USE 1" DIA. HOLES FOR BOLTS NO. 6 AT BOTTOM NO. 5A & FOR BOLT NO. 6A AT NO. 7. CUT BOTTOM OF POST TO MATCH CROSS SLOPE OF ROADWAY. PLACE POST VERTICAL. PLACE POSTS NORMAL TO GRADE LINE.
- ② PLATE 1/4" X 10" X 1'-2" WITH 1/8" X 1 1/8" SLOTTED HOLES FOR ANCHOR BOLTS NO. 3. PLACE POST VERTICAL. PLACE POSTS NORMAL TO SHORT SIDE OF PLATE.
- ③ ASTM A449 - 1" DIA. ANCHOR BOLTS WITH HEAVY HEX NUT AND 2" O.D. HARDENED WASHER (ALL GALVANIZED). 4 REQUIRED PER POST. THREAD 3" AND PLACE NORMAL TO PLATE NO. 2. CHAMFER TOP OF BOLTS BEFORE THREADING. USE 1 1/2" LONG BOLT FOR CONCRETE DECK. ON CONCRETE SLAB SUPERSTRUCTURES, USE 1'-3" LONG BOLT FOR SLAB THICKNESS > 16" AND 1 1/2" LONG FOR THICKNESS < 16". USE 1'-9" LONG IN ABUTMENT WINGS. (AN EQUIVALENT THREADED ROD WITH HEAVY HEX NUTS AND HARDENED WASHERS MAY BE SUBSTITUTED FOR ANCHOR BOLTS IN WINGS IF REQUIRED FOR CONSTRUCTIBILITY.)
- ④ 3/8" X 10" X 1'-2" ANCHOR PLATE (GALVANIZED) WITH 1/8" DIA. HOLES FOR ANCHOR BOLTS NO. 3.
- ⑤ TS 6 X 6 X 3/8" STRUCTURAL TUBING. USE 1" DIA. HOLES FOR BOLT NO. 6 (FRONT & BACK) & 7/8" DIA. HOLES FOR BOLT NO. 6A (TOP & BOTTOM).
- ⑤A TS 5 X 3 X 1/4" STRUCTURAL TUBING. USE 1" DIA. HOLES FOR BOLT NO. 6 IN TOP RAIL (FRONT & BACK). USE 1/8" X 1 3/8" HORIZONTAL SLOTTED HOLES FOR BOLT NO. 6 IN BOTTOM RAIL (FRONT & BACK) AND A 2" O.D. WASHER UNDER RAIL HEAD.
- ⑥ 7/8" DIA. A325 SLOTTED ROUND HEAD BOLT WITH HEX NUT, 3/16" X 1 3/4" X 1 3/4" WASHER, AND SPRING LOCK WASHER (2 REQUIRED AT RAIL TO POST LOCATIONS SHOWN).
- ⑥A 3/4" DIA. A325 BOLT WITH HEX NUT AND SPRING LOCK WASHER (1 REQUIRED AT RAIL TO ANGLE AND 2 REQUIRED AT ANGLE TO POST LOCATIONS SHOWN WITH 3/16" X 1 3/4" X 1 3/4" WASHER).
- ⑦ L 5 X 5 X 5/8" STRUCTURAL ANGLE. ATTACH TO NO. 1 AND NO. 5 AS SHOWN.
- ⑧ TS 5 X 5 X 3/8" X 2'-4" LONG SPLICE TUBE. 1 PER RAIL. USED IN NO. 5.
- ⑧A 1/4" X 2 1/8" X 2'-4" LONG SPLICE BAR. 1 PER RAIL. USED IN NO. 5A.
- ⑨ 3/4" DIA. A325 FULLY THREADED BOLTS, 7/2" LONG, WITH 2 WASHERS AND HEAVY HEX NUT ON EACH BOLT. NUT TO BE FINGER TIGHT. (4 REQUIRED PER SPLICE). USE 1" X 4" SLOTTED HOLES IN TOP AND BOTTOM OF NO. 5.
- ⑨A 3/4" DIA. A325 FULLY THREADED BOLTS, 4 1/2" LONG, WITH 2 WASHERS AND HEAVY HEX NUT ON EACH BOLT. NUT TO BE FINGER TIGHT. (4 REQUIRED PER SPLICE). USE 1" X 4" SLOTTED HOLES IN TOP AND BOTTOM OF NO. 5A.
- ⑩ SPLICE SLEEVE FABRICATED FROM 1/4" PLATE. PROVIDE "SLIDING FIT".


- ▲ PROTRUSIONS CAUSED BY WELDING OR GALVANIZING ARE NOT PERMITTED ON THE ADJOINING SURFACES OF THE RAILS, SPLICE TUBES AND FILL PLATES.
- TIE TO TOP MAT OF STEEL.

**NOTES**

- BID ITEM SHALL BE "RAILING STEEL TYPE NY4, WHICH INCLUDES ALL ITEMS SHOWN.
- RAILING SHALL BE CONTINUOUS OVER A MINIMUM OF THREE (3) POSTS WITHOUT SPLICES WHERE POSSIBLE.
- POST BASE PLATES SHALL BE FLAT WITH ALL SURFACES SMOOTH AND FREE FROM WARP AND ALL EDGES SMOOTH, STRAIGHT, AND VERTICAL. ALL PLATE CUTS SHALL BE MACHINE OR MACHINE FLAME CUT.
- ALL MATERIAL SHALL BE GALVANIZED AFTER FABRICATION. PRIOR TO GALVANIZING, ALL STEEL RAILING POSTS, ANGLES, SPLICE TUBES, SPLICE BARS AND STEEL TUBING SHALL BE GIVEN A NO. 6 BLAST CLEANING PER SSPC SPECIFICATIONS.
- RAIL POST, BASE PLATES, SPLICE BAR, ANGLES AND SPLICE PLATES SHALL CONFORM TO THE REQUIREMENTS OF ASTM A709 GRADE 50. STRUCTURAL TUBING SHALL CONFORM TO THE REQUIREMENTS OF ASTM A500 GRADE B OR C WITH A CERTIFIED fy=50 KSI. ANCHOR PLATES & SHIMS SHALL CONFORM TO THE REQUIREMENTS OF ASTM A709 GRADE 36.
- THE NUT SECURING THE POST BASE PLATE TO THE CONCRETE SHALL BE TIGHTENED TO A SNUG FIT AND GIVEN AN ADDITIONAL 1/8 TURN.
- FILL BOLT SLOT OPENINGS IN POST SHIMS AND PLATE NO. 2 WITH NON-STAINING GRAY NON-BITUMINOUS JOINT SEALER. CAULK AROUND PERIMETER OF NO. 2 WITH NON-STAINING GRAY NON-BITUMINOUS JOINT SEALER.
- STEEL SHIMS SHALL BE PROVIDED & USED UNDER PLATE NO. 2 WHERE REQUIRED FOR ALIGNMENT, AND SHALL BE GALVANIZED.
- WORK THIS SHEET WITH "END POST DETAILS FOR RAILING STEEL TYPE NY4" SHEET.



**SECTION D-D**



**POST SHIM DETAIL**

ORIGINAL PLANS PREPARED BY

**AYRES** 3433 Oakwood Hills Parkway  
Eau Claire, WI 54701  
www.AyresAssociates.com

NO.	DATE	REVISION	BY

STATE OF WISCONSIN  
DEPARTMENT OF TRANSPORTATION

**STRUCTURE B-68-148**

DRAWN BY	CLP	PLANS CK'D.	AEB

**RAILING STEEL TYPE NY4**

SHEET 17 OF 18


**LEGEND**

- ① W6 X 25 WITH 1/8" X 1 3/8" HORIZONTAL SLOTTED HOLES ON SIDE OF POST FOR BOLT NO. 6 AT NO. 5 & AT TOP RAIL NO. 5A. USE 1" DIA. HOLE FOR BOLT NO. 6 AT NO. 5A BOTTOM RAIL. CUT BOTTOM OF POST TO MATCH CROSS SLOPE OF ROADWAY. PLACE POST VERTICAL. PLACE POSTS NORMAL TO GRADE LINE.
- ② PLATE 1/4" X 10" X 1-2". SEE SHEET "RAILING STEEL TYPE NY4" FOR MORE INFORMATION.
- ⑤ TS 6 X 6 X 3/8" STRUCTURAL TUBING. USE 7/8" DIA. HOLES IN TOP AND BOTTOM OF RAILS FOR BOLT NO. 13 AS SHOWN IN PLAN DETAILS. USE 1" DIA. HOLES IN FRONT AND BACK OF RAILS FOR BOLTS NO. 6 & NO. 14 AS SHOWN IN ELEVATION DETAILS.
- ⑤A TS 5 X 3 X 1/4" STRUCTURAL TUBING. USE 1" DIA. HOLES FOR TOP RAIL NO. 5A (FRONT & BACK). USE 1/8" X 1 3/8" HORIZONTAL SLOTTED HOLES FOR BOLT NO. 6 IN BOTTOM RAIL (FRONT & BACK) AND A 2" O.D. WASHER UNDER BOLT HEAD.
- ⑥ 7/8" DIA. A325 SLOTTED ROUND HEAD BOLT WITH HEX NUT, 3/8" X 1 3/4" X 1 3/4" WASHER, AND SPRING LOCK WASHER (1 REQUIRED AT RAIL NO. 5 TO POST NO. 1 CONNECTION LOCATIONS SHOWN, 2 REQUIRED AT RAIL NO. 5A TO POST NO. 1 CONNECTION LOCATIONS SHOWN).
- ⑪ TS 6 X 6 X 3/8" STRUCTURAL TUBING. USE 1" DIA. HOLES IN FRONT AND BACK FOR BOLT NO. 14 & 7/8" DIA. HOLES IN TOP & BOTTOM FOR BOLT NO. 13.
- ⑫ L 6 X 6 X 1/2" STRUCTURAL ANGLE. USE 7/8" DIA. HOLES IN TOP FLANGE FOR BOLT NO. 13.
- ⑬ 3/4" DIA. A325 FULLY THREADED BOLTS, 2 WASHERS AND A HEAVY HEX NUT, ON EACH BOLT. NUT TO BE FINGER TIGHT. 3 BOLTS AT EACH END POST.
- ⑭ 7/8" DIA. A325 SLOTTED ROUND HEAD BOLT WITH HEX NUT AND 3/8" X 2" X 2" WASHER FOR CONNECTION OF THRIE BEAM (4 REQUIRED)



**NOTES**

STRUCTURAL TUBING SHALL CONFORM TO THE REQUIREMENTS OF ASTM A500 GRADE B OR C WITH A CERTIFIED  $f_y = 50$  KSI. STRUCTURAL ANGLE SHALL CONFORM TO THE REQUIREMENTS OF ASTM A709 GRADE 50.




WORK THIS SHEET WITH "RAILING STEEL TYPE NY4" SHEET.





**TOP RAIL ⑤ DETAILS**






**TUBE ⑪ DETAILS**




**BOTTOM RAIL ⑤ DETAILS**



**ANGLE ⑫ DETAILS**




**BOTTOM RAIL ⑤A DETAILS**




**SECTION THRU RAILING END POST**


THIS FACE TO BE VERTICAL




**ELEVATION DETAIL AT END POST INTERIOR ELEVATION**




**ELEVATION OF DETAIL AT END POST THRIE BEAM RAIL ATTACHMENT**




**PLAN OF DETAIL AT END POST**



**PLAN OF DETAIL AT END POST THRIE BEAM RAIL ATTACHMENT**



**TOP RAIL ⑤A DETAILS**



7/6/2021 PENTABLE:BRReou\_shd\_util.tbl

8

8

NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
<b>STRUCTURE B-68-148</b>			
DRAWN BY		CLP	PLANS CK'D. AEB
<b>END POST DETAILS FOR RAILING STEEL TYPE NY4</b>			SHEET 18 OF 18

ORIGINAL PLANS PREPARED BY  
**AYRES** 3433 Oakwood Hills Parkway  
 Eau Claire, WI 54701  
 www.AyresAssociates.com

EARTHWORK - SW QUADRANT (CATEGORY 0030)

STATION	AREA (SF)			INCREMENTAL VOL (CY) (UNADJUSTED)			CUMULATIVE VOL (CY)			MASS ORDINATE
	CUT	FILL	MARSH EXC	CUT	FILL	MARSH EXC	CUT	EXPANDED FILL	EXPANDED MARSH BACKFILL	
7+55.2	9.48	0.20	0.00	0	0	0	0	0	0	0
7+85.9	8.48	0.20	0.00	10	0	0	10	0	0	10
8+00	8.91	1.47	0.00	5	0	0	15	0	0	15

15      0      0

EARTHWORK - NW QUADRANT (CATEGORY 0030)

STATION	AREA (SF)			INCREMENTAL VOL (CY) (UNADJUSTED)			CUMULATIVE VOL (CY)			MASS ORDINATE
	CUT	FILL	MARSH EXC	CUT	FILL	MARSH EXC	CUT	EXPANDED FILL	EXPANDED MARSH BACKFILL	
7+85.9	10.48	0.00	0.00	0	0	0	0	0	0	0
8+00	10.14	0.21	0.00	5	0	0	5	0	0	5

5      0      0

EARTHWORK - CTH B (CATEGORY 0030)

STATION	AREA (SF)			INCREMENTAL VOL (CY) (UNADJUSTED)			CUMULATIVE VOL (CY)			MASS ORDINATE
	CUT	FILL	MARSH EXC	CUT	FILL	MARSH EXC	CUT	EXPANDED FILL	EXPANDED MARSH BACKFILL	
8+00	48.79	1.47	0.00	0	0	0	0	0	0	0
8+32.9	72.43	0.26	0.00	73	1	0	73	1	0	72
8+59.4	44.12	11.20	0.00	57	6	0	130	9	0	121
8+84.4	44.09	13.48	0.00	41	11	0	171	23	0	148
9+00	44.40	9.45	0.00	26	7	0	197	33	0	165
9+09.4	43.32	10.11	0.00	15	3	0	212	36	0	176
9+25.1	42.59	3.98	0.00	25	4	0	237	42	0	195
9+50	39.13	7.62	0.00	38	5	0	275	48	0	227
9+71	39.54	25.81	17.00	31	13	7	306	65	11	241
9+77.73	39.54	25.81	0.00	10	6	2	316	73	14	243

316      56      9

<b>Notes:</b>	
1 - Cut	Cut includes Unusable Pavement Material
3 - Fill	Does not include Unusable Pavement Exc volume
4 - Expanded Marsh Backfill	Will be backfilled with Select Borrow
8 - Mass Ordinate	Cut - (Fill * Fill Factor)
8 - Mass Ordinate	Does not include Marsh Excavation

9

9

EARTHWORK - CTH B (CATEGORY 0010)

STATION	AREA (SF)			INCREMENTAL VOL (CY) (UNADJUSTED)			CUMULATIVE VOL (CY)			MASS ORDINATE
	CUT	FILL	MARSH EXC	CUT	FILL	MARSH EXC	CUT	EXPANDED FILL	EXPANDED MARSH BACKFILL	
10+28.27	46.54	16.57	0.00	0	0	0	0	0	0	0
10+32.0	46.54	16.57	0.00	6	2	0	6	3	0	3
10+50	49.75	15.79	45.00	32	11	15	38	17	23	21

38 13 15

EARTHWORK - NE QUADRANT (CATEGORY 0010)

STATION	AREA (SF)			INCREMENTAL VOL (CY) (UNADJUSTED)			CUMULATIVE VOL (CY)			MASS ORDINATE
	CUT	FILL	MARSH EXC	CUT	FILL	MARSH EXC	CUT	EXPANDED FILL	EXPANDED MARSH BACKFILL	
10+50	5.28	14.12	0.00	0	0	0	0	0	0	0
10+75	5.09	0.00	0.00	5	7	0	5	9	0	-4

5 7 0

EARTHWORK - SE QUADRANT (CATEGORY 0010)

STATION	AREA (SF)			INCREMENTAL VOL (CY) (UNADJUSTED)			CUMULATIVE VOL (CY)			MASS ORDINATE
	CUT	FILL	MARSH EXC	CUT	FILL	MARSH EXC	CUT	EXPANDED FILL	EXPANDED MARSH BACKFILL	
10+50	5.57	0.18	45.00	0	0	0	0	0	0	0
10+74.9	5.79	0.02	0.00	5	0	21	5	0	32	5
11+13.1	5.48	0.09	0.00	8	0	0	13	0	32	13
11+28.8	5.46	1.12	0.00	3	0	0	16	0	32	16
11+53.8	6.76	7.01	0.00	6	4	0	22	5	32	17
11+78.8	7.15	8.45	0.00	6	7	0	28	14	32	14
12+00	7.32	3.91	0.00	6	5	0	34	21	32	13
12+50	6.87	2.74	0.00	13	6	0	47	29	32	18
12+87.2	8.29	0.00	0.00	10	2	0	57	31	32	26

57 24 21

<b>Notes:</b>	
1 - Cut	Cut includes Unusable Pavement Material
3 - Fill	Does not include Unusable Pavement Exc volume
4 - Expanded Marsh Backfill	Will be backfilled with Select Borrow
8 - Mass Ordinate	Cut - (Fill * Fill Factor)
8 - Mass Ordinate	Does not include Marsh Excavation

9

9


EARTHWORK - CTH G (CATEGORY 0030)

STATION	AREA (SF)			INCREMENTAL VOL (CY) (UNADJUSTED)			CUMULATIVE VOL (CY)			MASS ORDINATE
	CUT	FILL	MARSH EXC	CUT	FILL	MARSH EXC	CUT	EXPANDED FILL	EXPANDED MARSH BACKFILL	
30+13	151.51	0.00	0.00	0	0	0	0	0	0	0
30+50	57.03	7.98	0.00	143	5	0	143	7	0	137
31+00	46.47	0.18	0.00	96	8	0	239	17	0	222
31+50	37.94	2.30	0.00	78	2	0	317	20	0	298
				317	15	0				

Notes:	
1 - Cut	Cut includes Unusable Pavement Material
3 - Fill	Does not include Unusable Pavement Exc volume
4 - Expanded Marsh Backfill	Will be backfilled with Select Borrow
8 - Mass Ordinate	Cut - (Fill * Fill Factor)
8 - Mass Ordinate	Does not include Marsh Excavation

9

9




9

9

PROJECT NO: 6832-11-70      HWY: CTH B      COUNTY: WAUPACA      CROSS SECTIONS: CTH B      SHEET      E

FILE NAME : I:\45450487 WAUPACA CTH B\C3D\SHEETSPLAN\090201 XS.DWG      PLOT DATE : 7/30/2021 5:57 AM      PLOT BY : SOUFAL, KEVIN      PLOT NAME :      PLOT SCALE : 1 IN:10 FT HORZ. / 1 IN:10 FT VERT.      WISDOT/CADD SHEET 49

LAYOUT NAME - 090201 xs




9

9

PROJECT NO: 6832-11-70      HWY: CTH B      COUNTY: WAUPACA      CROSS SECTIONS: CTH B      SHEET      E

FILE NAME: I:\45\450487 WAUPACA CTH B\C3D\SHEETSPLAN\090201 XS.DWG      PLOT DATE: 7/30/2021 5:57 AM      PLOT BY: SOUFAL, KEVIN      PLOT NAME:      PLOT SCALE: 1 IN:10 FT HORZ. / 1 IN:10 FT VERT.      WISDOT/CADD SHEET 49



PROJECT NO: 6832-11-70


HWY: CTH B

COUNTY: WAUPACA

CROSS SECTIONS: CTH B

SHEET

E



9



9

PROJECT NO: 6832-11-70      HWY: CTH B      COUNTY: WAUPACA      CROSS SECTIONS: CTH B      SHEET      E


FILE NAME: I:\45450487 WAUPACA CTH B\C3D\SHEETS\PLAN\090201 XS.DWG      PLOT DATE: 7/30/2021 5:57 AM      PLOT BY: SOUFAL, KEVIN      PLOT NAME:      PLOT SCALE: 1 IN:10 FT HORZ. / 1 IN:10 FT VERT.      WISDOT/CADD SHEET 49

LAYOUT NAME - 090204 xs

CONSTRUCTION LIMITS  
STA. 12+87




PROJECT NO: 6832-11-70	HWY: CTH B	COUNTY: WAUPACA	CROSS SECTIONS: CTH B	SHEET	E
------------------------	------------	-----------------	-----------------------	-------	---



PROJECT NO: 6832-11-70      HWY: CTH B      COUNTY: WAUPACA      CROSS SECTIONS: CTH G      SHEET 9

# Notes



## ***Wisconsin Department of Transportation***

Dedicated people creating transportation solutions through innovation and exceptional service.

<http://www.dot.wisconsin.gov>