

FEB 13, 2024

ORDER OF SHEETS

SECTION NO. 1	TITLE
SECTION NO. 2	TYPICAL SECTIONS AND DETAILS
SECTION NO. 3	ESTIMATE OF QUANTITIES
SECTION NO. 3	MISCELLANEOUS QUANTITIES
SECTION NO. 4	RIGHT OF WAY PLAN
SECTION NO. 5	PLAN AND PROFILE
SECTION NO. 6	STANDARD DETAIL DRAWINGS
SECTION NO. 7	SIGN PLATES
SECTION NO. 8	STRUCTURE PLANS
SECTION NO. 9	COMPUTER EARTHWORK DATA

TOTAL: 100



15



STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION

PLAN OF PROPOSED IMPROVEMENT

C MILWAUKEE, N HOLTON ST PHASE I I

BR OVER MILW RVR, COMMERCE, WATER

P-40-0875

LOCAL STREET
MILWAUKEE COUNTY

STATE PROJECT NUMBER
2984-12-74

DESIGN DESIGNATION

A.D.T. (2016)	=	10,059
A.D.T. (2058)	=	10,803
D.H.V.	=	967
D.	=	54%
T.	=	N/A
DESIGN SPEED	=	30 M.P.H.
ESALS	=	N/A

CONVENTIONAL SYMBOLS

PLAN

COUNTY LINE	---
TOWNSHIP OR RANGE LINE	----
SECTION LINE	-----
CORPORATE OR CITY LIMITS	-----
PROPERTY LINE	-----
STANDARD BENCH MARK	●
EXISTING RIGHT OF WAY LINE	— R/W —
PROPOSED SEWER LATERAL	— (SIZE) —
BASE OF SURVEY LINE	—
CONCRETE WALK/DWY. REMOVAL	▨
LIMITS OF CONCRETE PAVEMENT REMOVAL	X X X X X X
CATCH BASIN OR INLET	⊕
EXISTING	⊞
PROPOSED	⊞

COMBUSTIBLE FLUIDS
UNDER PRESSURE

RAILROADS

FENCE

FIRE & POLICE CALL BOX

LIGHT POLE

POWER POLE

TELEPHONE OR TELEGRAPH POLE

TRAFFIC SIGNAL

TRAFFIC SIGNAL CONTROL BOX

HYDRANT

GAS OR WATER GATE VALVE

MANHOLES - SEWER ○ UTILITY (TYPE) □

TREES - EXISTING ● TO BE REMOVED ✕

STRUCTURE P-40-0875

LAYOUT

SCALE: 1 INCH = 1/2 MILE

TOTAL NET LENGTH OF CENTERLINE = 0.184 MI (URBAN)

POSITIONS SHOWN ON THIS PLAN ARE WISCONSIN COORDINATE REFERENCE SYSTEM COORDINATES (WISCRS), MILWAUKEE COUNTY, NAD 83-2011 IN US SURVEY FEET. VALUES SHOWN ARE GRID COORDINATES, GRID BEARINGS, AND GRID DISTANCES. GRID DISTANCES MAYBE USED AS GROUND DISTANCES.

ELEVATIONS SHOWN ON THIS PLAN ARE REFERENCED TO THE CITY OF MILWAUKEE DATUM.

TO CONVERT ELEVATIONS SHOWN ON THIS PLAN TO NATIONAL GEODESIC VERTICAL DATUM OF 1929, ADD 580.603 TO ELEVATIONS SHOWN ON THIS PLAN.

STATE PROJECT

2984-12-74

FEDERAL PROJECT

PROJECT

WISC 2024227

CONTRACT

1

Accepted For
City of Milwaukee

10/26/2023
(Date)

Commissioner of Public Works

Original Plans Prepared By



(Date)

City Engineer

STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION

PREPARED BY	CITY OF MILWAUKEE
SURVEYOR	CITY OF MILWAUKEE
DESIGNER	GREGORY HAFEMAN
PROJECT MANAGER	
DISTRICT EXAMINER	BRIAN BOOTHBY
DISTRICT SUPERVISOR	
C.O. EXAMINER	

APPROVED FOR DISTRICT OFFICE

DATE: 10/30/2023

(SIGNATURE)

E

GENERAL NOTES

- 1. ALL ELEVATIONS ARE REFERENCED TO CITY OF MILWAUKEE DATUM.
- 2. THERE MAY BE UTILITY FACILITIES WITHIN THE PROJECT AREA THAT ARE NOT SHOWN ON THE PLANS. THE CONTRACTOR SHALL COORDINATE CONSTRUCTION ACTIVITIES WITH A CALL TO DIGGERS HOTLINE AND/OR A DIRECT CALL TO THE UTILITIES THAT HAVE FACILITIES IN THE AREA. NOT ALL UTILITIES ARE MEMBERS OF DIGGERS HOTLINE.
- 3. STOCKPILE EXCESS MATERIAL OR SPOILS ON UPLAND AREAS AWAY FROM WETLANDS, FLOODPLAINS AND WATERWAYS. STOCKPILED SOIL SHALL BE PROTECTED AGAINST EROSION.
- 4. EROSION CONTROL BMP'S ARE SHOWN AT SUGGESTED LOCATIONS. THE ACTUAL LOCATIONS WILL BE DETERMINED BY THE CONTRACTOR'S ECIP AND BY THE ENGINEER. EROSION CONTROL BMP'S SHALL BE MAINTAINED UNTIL PERMANENT VEGETATION IS ESTABLISHED OR UNTIL THE ENGINEER DETERMINES THAT THE BMP IS NO LONGER NECESSARY.

STANDARD ABBREVIATIONS

ASPH.	- ASPHALT
B.M.	- BENCH MARK
CTR.	- CENTER
C/L	- CENTER LINE
COMB.	- COMBINED
CONC.	- CONCRETE
C.W.	- CONCRETE WALK
COR.	- CORNER
C	- CURB
ELEV.	- ELEVATION
ENT.	- ENTRANCE
EXIST.	- EXISTING
F	- FLANGE
G	- GUTTER, OR GAS
HYD.	- HYDRANT
LT	- LEFT
MMSD	- MILWAUKEE METROPOLITAN SEWERAGE DISTRICT
NB	- NORTHBOUND
P/L	- PROPERTY LINE
PGL	- PROFILE GRADE LINE
R OR RAD.	- RADIUS
RET.	- RETAINING
RT	- RIGHT
R/W	- RIGHT OF WAY
SB	- SOUTHBOUND
TEL	- AMERITECH
TES	- TRAFFIC ENGINEERING, AND ELECTRICAL SERVICES
T/L	- TRANSIT LINE
V.T. OR VT	- VARIABLE THICKNESS
WEP	- WISCONSIN ELECTRIC POWER

ORDER OF SECTION 2 SHEETS

General Notes
Utility Contacts
Project Overview
Erosion Control
Pavement Marking
Traffic Control and Construction Staging
Alignment

UTILITY CONTACTS

AT&T WISCONSIN
JAY BULANEK
435 S. 95TH STREET
MILWAUKEE, WI 53214
PHONE: 414-491-2855
EMAIL: JB5175@att.com

CHARTER / SPECTRUM
CHARLES BRASILE
1320 N. DR. MARTIN LUTHER KING JR. DR.
MILWAUKEE, WI 53212
PHONE: 414-908-4822
MOBILE: 414-430-5812
EMAIL: charles.brasile@charter.com

CITY OF MILWAUKEE, WATER WORKS
MWW CONTROL CENTER (24/7 CONTACT)
841 N. BROADWAY, ROOM 409
MILWAUKEE, WI 53202
PHONE: 414-286-3710

LUMEN TECHNOLOGIES
BRAHIM GADDOUR
3235 INTERTECH DRIVE, SUITE 600
BROOKFIELD, WI 53045
PHONE: 414-704-1026
EMAIL: brahim.gaddour@lumen.com

TELEPORT COMMUNICATIONS AMERICA, LLC
(AT&T LNS)
JASON STERENBERG
5101 THATCHER ROAD
DOWNERS GROVE, IL 60515
PHONE: 708-240-9085
EMAIL: jsterenberg@networkconnex.com

VERIZON BUSINESS (MCI)
RANDY CICATELLO
15725 W. RYERSON ROAD
NEW BERLIN, WI 53151
PHONE: 262-232-1323
EMAIL: randy.cicatello@verizon.com

WE ENERGIES - ELECTRIC
MITCHELL COMER
500 S. 116TH STREET
WEST ALLIS, WI 53214
PHONE: 920-205-0937
EMAIL: Mitchell.comer@we-energies.com
We Energies Electric Dispatch # 1-800-662-4797

WE ENERGIES - GAS
MITCHELL COMER
500 S. 116TH STREET
WEST ALLIS, WI 53214
PHONE: 920-205-0937
EMAIL: Mitchell.comer@we-energies.com
We Energies Gas Dispatch # 1-800-261-5325

OTHER CONTACTS

CITY OF MILWAUKEE, COMMUNICATIONS
DPW COMMUNICATIONS DISPATCH
BRYAN M. PAWLAK
1440 WEST CANAL STREET
MILWAUKEE, WI 53233
PHONE: 414-286-5970

CITY OF MILWAUKEE, STREET LIGHTING
NEAL KARWEIK
1540 WEST CANAL STREET
MILWAUKEE, WI 53233
PHONE: 414-286-5943
MOBILE: 414-708-4245
EMAIL: nkarwe@milwaukee.gov

MILWAUKEE COUNTY TRANSIT SYSTEM
1942 N. 17TH STREET
MILWAUKEE, WI 53205

ARMON SENSABAUGH
TRANSPORTATION COORDINATOR (DETOURS)
PHONE: 414-343-1728
EMAIL: asensabaugh@mcts.org

DAVID LOCHER
TRANSPORTATION MANAGER (BUS STOPS)
PHONE: 414-343-1727
EMAIL: dlocher@mcts.org


JESUS OCHOA
PLANNING MANAGER
PHONE: 414-344-4550 ext. 3591
EMAIL: jochoa@mcts.org


MILWAUKEE METROPOLITAN SEWERAGE DISTRICT
MICHAEL LEE
260 W. SEEBOTH STREET
MILWAUKEE, WI 53204
PHONE: 414-617-1429
EMAIL: mlee@mmsd.com


SOUTHEASTERN WISCONSIN REGIONAL PLANNING COMMISSION
ROB MERRY
W239 N1812 ROCKWOOD DRIVE
P.O. BOX 1607
WAUKESHA, WI 53187-1607
PHONE: 262-953-4289
CELL: 920-912-1036
EMAIL: rmerry@sewrpc.org

WISCONSIN DEPT. OF NATURAL RESOURCES
RYAN PAPPAS
1027 W. ST. PAUL AVENUE
MILWAUKEE, WI 53233
PHONE: 414-750-7495
EMAIL: ryan.pappas@wisconsin.gov










	1		5		9
	2		6		10
	3		7		11
	4		8		12

- WORK AREA
- FLEXIBLE TUBULAR MARKERS
25' SPACING
- DRUMS WITH ONE WARNING LIGHT TYPE C
25' SPACING
- TRAFFIC CONTROL BARRICADES TYPE II
WITH ONE WARNING LIGHT TYPE A AND
ATTACHED TRAFFIC CONTROL SIGNS
- TRAFFIC CONTROL BARRICADES TYPE III
WITH TWO WARNING LIGHTS TYPE A
- TRAFFIC CONTROL BARRICADES TYPE III
WITH TWO WARNING LIGHTS TYPE A AND
ATTACHED TRAFFIC CONTROL SIGNS
- TRAFFIC FLOW DIRECTION
- TEMPORARY PEDESTRIAN BARRICADE
- TEMPORARY CURB RAMP
- X ONE SIDE WALK CLOSED AT A TIME



Estimate Of Quantities

2984-12-74

Line	Item	Item Description	Unit	Total	Qty
0002	201.0210	Grubbing	SY	60.000	60.000
0004	203.0220	Removing Structure (structure) 001. P-40-875	EACH	1.000	1.000
0006	203.0330	Debris Containment (structure) 001. P-40-875	EACH	1.000	1.000
0008	204.0110	Removing Asphaltic Surface	SY	56.000	56.000
0010	204.0155	Removing Concrete Sidewalk	SY	195.000	195.000
0012	206.1001	Excavation for Structures Bridges (structure) 001. P-40-875	EACH	1.000	1.000
0014	210.1500	Backfill Structure Type A	TON	200.000	200.000
0016	213.0100	Finishing Roadway (project) 001. 2984-12-74	EACH	1.000	1.000
0018	305.0125	Base Aggregate Dense 1 1/4-Inch	CY	10.000	10.000
0020	320.0145	Concrete Base 8-Inch	SY	56.000	56.000
0022	465.0110	Asphaltic Surface Patching	TON	20.000	20.000
0024	502.0100	Concrete Masonry Bridges	CY	12.000	12.000
0026	502.0200	Concrete Masonry Bridges HES	CY	8.000	8.000
0028	502.3101	Expansion Device	LF	150.000	150.000
0030	502.3200	Protective Surface Treatment	SY	120.000	120.000
0032	502.3215	Protective Surface Treatment Reseal	SY	2,320.000	2,320.000
0034	502.4104	Adhesive Anchors 1/2-inch	EACH	6.000	6.000
0036	502.4204	Adhesive Anchors No. 4 Bar	EACH	16.000	16.000
0038	502.4205	Adhesive Anchors No. 5 Bar	EACH	263.000	263.000
0040	505.0600	Bar Steel Reinforcement HS Coated Structures	LB	7,600.000	7,600.000
0042	506.0105	Structural Steel Carbon	LB	84,000.000	84,000.000
0044	506.2610	Bearing Pads Elastomeric Laminated	EACH	7.000	7.000
0046	506.6000	Bearing Assemblies Expansion (structure) 001. P-40-875	EACH	1.000	1.000
0048	506.7050.S	Removing Bearings (structure) 001. P-40-875	EACH	8.000	8.000
0050	509.0301	Preparation Decks Type 1	SY	36.000	36.000
0052	509.0302	Preparation Decks Type 2	SY	12.000	12.000
0054	509.0310.S	Sawing Pavement Deck Preparation Areas	LF	410.000	410.000
0056	509.1000	Joint Repair	SY	60.000	60.000
0058	509.1500	Concrete Surface Repair	SF	206.000	206.000
0060	509.2000	Full-Depth Deck Repair	SY	2.000	2.000
0062	509.2100.S	Concrete Masonry Deck Repair	CY	31.000	31.000
0064	509.9020.S	Epoxy Crack Sealing	LF	95.000	95.000
0066	509.9025.S	Epoxy Injection Crack Repair	LF	48.000	48.000
0068	509.9026.S	Cored Holes 2-Inch Diameter	EACH	2.000	2.000
0070	511.1200	Temporary Shoring (structure) 001. P-40-875	SF	575.000	575.000
0072	516.0500	Rubberized Membrane Waterproofing	SY	30.000	30.000
0074	517.0601	Painting Epoxy System (structure) 001. P-40-875	EACH	1.000	1.000
0076	517.0901.S	Preparation and Coating of Top Flanges (structure) 001. P-40-875	EACH	1.000	1.000
0078	517.1801.S	Structure Repainting Recycled Abrasive (structure) 001. P-40-875	EACH	1.000	1.000
0080	517.4501.S	Negative Pressure Containment and Collection of Waste Materials (structure) 001. P-40-875	EACH	1.000	1.000
0082	517.6001.S	Portable Decontamination Facility	EACH	1.000	1.000
0084	602.0410	Concrete Sidewalk 5-Inch	SF	1,750.000	1,750.000
0086	604.0500	Slope Paving Crushed Aggregate	SY	170.000	170.000
0088	619.1000	Mobilization	EACH	1.000	1.000
0090	625.0100	Topsoil	SY	60.000	60.000
0092	628.1504	Silt Fence	LF	75.000	75.000
0094	628.1520	Silt Fence Maintenance	LF	75.000	75.000
0096	628.1905	Mobilizations Erosion Control	EACH	1.000	1.000
0098	628.1910	Mobilizations Emergency Erosion Control	EACH	5.000	5.000

Estimate Of Quantities

2984-12-74

Line	Item	Item Description	Unit	Total	Qty
0100	628.2023	Erosion Mat Class II Type B	SY	60.000	60.000
0102	628.7015	Inlet Protection Type C	EACH	24.000	24.000
0104	630.0120	Seeding Mixture No. 20	LB	2.000	2.000
0106	630.0500	Seed Water	MGAL	5.000	5.000
0108	642.5201	Field Office Type C	EACH	1.000	1.000
0110	643.0300	Traffic Control Drums	DAY	840.000	840.000
0112	643.0410	Traffic Control Barricades Type II	DAY	448.000	448.000
0114	643.0420	Traffic Control Barricades Type III	DAY	1,736.000	1,736.000
0116	643.0500	Traffic Control Flexible Tubular Marker Posts	EACH	12.000	12.000
0118	643.0600	Traffic Control Flexible Tubular Marker Bases	EACH	8.000	8.000
0120	643.0705	Traffic Control Warning Lights Type A	DAY	3,920.000	3,920.000
0122	643.0715	Traffic Control Warning Lights Type C	DAY	840.000	840.000
0124	643.0900	Traffic Control Signs	DAY	2,016.000	2,016.000
0126	643.0920	Traffic Control Covering Signs Type II	EACH	5.000	5.000
0128	643.5000	Traffic Control	EACH	1.000	1.000
0130	646.1020	Marking Line Epoxy 4-Inch	LF	25.000	25.000
0132	646.2020	Marking Line Epoxy 6-Inch	LF	20.000	20.000
0134	646.3020	Marking Line Epoxy 8-Inch	LF	5.000	5.000
0136	650.6501	Construction Staking Structure Layout (structure) 001. P-40-875	EACH	1.000	1.000
0138	650.9911	Construction Staking Supplemental Control (project) 001. 2984-12-74	EACH	1.000	1.000
0140	652.0125	Conduit Rigid Metallic 2-Inch	LF	3.000	3.000
0142	652.0135	Conduit Rigid Metallic 3-Inch	LF	24.000	24.000
0144	690.0250	Sawing Concrete	LF	150.000	150.000
0146	999.2000.S	Installing and Maintaining Bird Deterrent System (station) 001. P-40-875	EACH	1.000	1.000
0148	ASP.1T0A	On-the-Job Training Apprentice at \$5.00/HR	HRS	3,000.000	3,000.000
0150	ASP.1T0G	On-the-Job Training Graduate at \$5.00/HR	HRS	7,200.000	7,200.000
0152	SPV.0025	Special 501. Deep Concrete Surface Repair	CF	22.000	22.000
0154	SPV.0025	Special 505. Non-Shrink Grout	CF	24.000	24.000
0156	SPV.0035	Special 540. Stone Removal	CY	9.000	9.000
0158	SPV.0060	Special 010. Temporary No Parking Signs	EACH	12.000	12.000
0160	SPV.0060	Special 030. Pedestrian Protection Enclosure	EACH	1.000	1.000
0162	SPV.0060	Special 508. Temporary Shoring for Piers 9,10,11,12 and North Abutment Repair	EACH	1.000	1.000
0164	SPV.0060	Special 509. Temporary Supports P-40-875	EACH	2.000	2.000
0166	SPV.0060	Special 594. Junction Box 14" x 8" x 6"	EACH	1.000	1.000
0168	SPV.0060	Special 595. Junction Box 14" x 14" x 12"	EACH	2.000	2.000
0170	SPV.0060	Special 597. Protecting Utilities	EACH	1.000	1.000
0172	SPV.0085	Special 540. Stairway Structural Steel	LB	12,600.000	12,600.000
0174	SPV.0090	Special 501. Remove, Repair, Paint and Reinstall Existing Steel Railing	LF	180.000	180.000
0176	SPV.0090	Special 505. Stairway Railing and Protective Screening	LF	330.000	330.000
0178	SPV.0090	Special 530. Rehabilitation of Chain Link Fence	LF	16.000	16.000
0180	SPV.0180	Special 530. Abutment Seat Cleaning and Sealing	SY	10.000	10.000

GRUBBING		REMOVALS			FINISHING ROADWAY		MOBILIZATION	
CATEGORY 0010		CATEGORY 0010			CATEGORY 0010		CATEGORY 0010	
201.0210 GRUBBING SY		204.0110 REMOVING ASPHALTIC SURFACE SY			213.0100 FINISHING ROADWAY PROJECT 2984-12-74 EACH		619.1000 MOBILIZATION EACH	
LOCATION		LOCATION			LOCATION		LOCATION	
N. HOLTON STREET		N. HOLTON STREET			N. HOLTON STREET		PROJECT 2984-12-74	
60		56			1		1	
TOTAL		TOTALS			TOTAL		TOTAL	
60		56			1		1	

PAVING ITEMS					SAWING CONCRETE		LANDSCAPE ITEMS			
CATEGORY 0010					CATEGORY 0010		CATEGORY 0010			
305.0125 BASE AGGREGATE DENSE 1-1/4 INCH CY					690.0250 SAWING CONCRETE LF		625.0100 TOPSOIL SY			
320.0145 CONCRETE BASE 8-INCH SY							630.0120 SEEDING MIXTURE NO. 20 LB			
465.0110 ASPHALTIC SURFACE PATCHING TON							630.0500 SEED WATER MGAL			
602.0410 CONCRETE SIDEWALK 5-INCH SF										
LOCATION					LOCATION		LOCATION			
N. HOLTON STREET					UNDISTRIBUTED		N. HOLTON STREET			
10					150		60			
56					TOTAL		TOTALS			
20					150		60			
1,750							2			
							5			

EROSION CONTROL ITEMS

CATEGORY 0010

	628.1504 SILT FENCE	628.1520 SILT FENCE MAINTENANCE	628.2023 EROSION MAT CLASS II TYPE B SY	628.7015 INLET PROTECTION TYPE C EACH
LOCATION	LF	LF	SY	EACH
N. HOLTON STREET	75	75	60	24
TOTALS	75	75	60	24

MOBILIZATIONS EROSION CONTROL

CATEGORY 0010

	628.1905 MOBILIZATIONS EROSION CONTROL EACH	628.1910 MOBILIZATIONS EMERGENCY EROSION CONTROL EACH
LOCATION	EACH	EACH
PROJECT 2984-12-74	1	5
TOTALS	1	5

FIELD OFFICE

CATEGORY 0010

	642.5201 FIELD OFFICE TYPE C EACH
LOCATION	EACH
PROJECT 2984-12-74	1
TOTAL	1

TRAFFIC CONTROL ITEMS

CATEGORY 0010

		643.0300		643.0410		643.0420		643.0500		643.0600		643.0705		643.0715		643.0900		643.0920
		TRAFFIC CONTROL DRUMS		TRAFFIC CONTROL BARRICADES TYPE II		CONTROL BARRICADES TYPE III		TRAFFIC CONTROL FLEXIBLE TUBULAR MARKER POSTS		TRAFFIC CONTROL FLEXIBLE TUBULAR MARKER BASES		TRAFFIC CONTROL WARNING LIGHTS TYPE A		TRAFFIC CONTROL WARNING LIGHTS TYPE C		TRAFFIC CONTROL SIGNS		TRAFFIC CONTROL COVERING SIGNS TYPE II (UNDISTRIBUTED)
LOCATION	DAYS	EACH	DAY	EACH	DAY	EACH	DAY	EACH		EACH		EACH	DAY	EACH	DAY	EACH	DAY	EACH
PROJECT 2984-12-74	56	15	840	8	448	31	1736	12		8		70	3920	15	840	36	2016	5
TOTALS			840		448		1,736	12		8		3,920		840		2,016		5

(1) All Drums have one Type C Steady Burn Light.
(2) All Type II Barricades have one Type A Flashing Light.
(3) All Type III Barricades have two Type A Flashing Lights.

TRAFFIC CONTROL

CATEGORY 0010	
	643.5000
	TRAFFIC
	CONTROL
LOCATION	EACH
PROJECT 2984-12-74	1
TOTAL	
	1

PAVEMENT MARKING

CATEGORY 0010		646.1020	646.2020	646.3020
		MARKING	MARKING	MARKING
		LINE	LINE	LINE
		EPOXY	EPOXY	EPOXY
		4-INCH	6-INCH	8-INCH
		(WHITE)	(WHITE)	(YELLOW)
		LF	LF	LF
LOCATION				
UNDISTRIBUTED		15	20	5
TOTALS		25	20	5

PEDESTRIAN PROTECTION ENCLOSURE

CATEGORY 0020	
	SPV.0060.030
	PEDESTRIAN
	PROTECTION
	ENCLOSURE
LOCATION	EACH
N. HOLTON STREET	1
TOTAL	
	1

TEMPORARY NO PARKING SIGNS

CATEGORY 0010	
	SPV.0060.010
	TEMPORARY
	NO PARKING
	SIGNS
LOCATION	EACH
UNDISTRIBUTED	12
TOTAL	
	12

CONSTRUCTION STAKING


CATEGORY 0020		CATEGORY 0010
	650.6501	650.9911
	CONSTRUCTION STAKING	CONSTRUCTION STAKING
	STRUCTURE LAYOUT	SUPPLEMENTAL CONTROL
	P-40-0875	(2984-12-74)
	EACH	EACH
LOCATION		
N. HOLTON STREET	1	1
TOTALS		1

BIRD DETERRENT

CATEGORY 0020	
	999.2000.S
	INSTALLING AND
	MAINTAINING BIRD
	DETERRENT SYSTEM
	P-40-0875
LOCATION	EACH
N. HOLTON STREET	1
TOTAL	
	1

5

5



Standard Detail Drawing List



08E09-06	SILT FENCE
08E10-02	INLET PROTECTION TYPE A, B, C AND D
09B02-10	CONDUIT
13C15-08A	CONCRETE BASE
13C15-08B	CONCRETE BASE
15C02-09A	BARRICADES AND SIGNS FOR MAINLINE CLOSURES
15C02-09B	BARRICADES AND SIGNS FOR VARIOUS CLOSURES
15C05-05	TRAFFIC CONTROL, ADVANCE WARNING SIGNS 40 M.P.H. OR LESS
15C08-23A	PERMANENT LONGITUDINAL PAVEMENT MARKINGS
15C11-10A	CHANNELIZING DEVICES FLEXIBLE TUBULAR MARKER POST
15C11-10B	CHANNELIZING DEVICES DRUMS, CONES, BARRICADES AND VERTICAL PANELS
15D12-11A	TRAFFIC CONTROL, LANE CLOSURE



- ① HORIZONTAL BRACE REQUIRED WITH 2" X 4" WOODEN FRAME OR EQUIVALENT AT TOP OF POSTS.
- ② FOR MANUAL INSTALLATIONS THE TRENCH SHALL BE A MINIMUM OF 4" WIDE & 6" DEEP TO BURY AND ANCHOR THE GEOTEXTILE FABRIC. FOLD MATERIAL TO FIT TRENCH AND BACKFILL & COMPACT TRENCH WITH EXCAVATED SOIL.
- ③ WOOD POSTS SHALL BE A MINIMUM SIZE OF 1½" X 1½" OF OAK OR HICKORY.
- ④ SILT FENCE TO EXTEND ACROSS THE TOP OF THE PIPE.
- ⑤ CONSTRUCT SILT FENCE FROM A CONTINUOUS ROLL IF POSSIBLE BY CUTTING LENGTHS TO AVOID JOINTS. IF A JOINT IS NECESSARY USE ONE OF THE FOLLOWING TWO METHODS; A) OVERLAP THE END POSTS AND TWIST, OR ROTATE, AT LEAST 180 DEGREES, B) HOOK THE END OF EACH SILT FENCE LENGTH.



<p>SILT FENCE</p>	
<p>STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION</p>	
<p>APPROVED 4-29-05 DATE</p>	<p>/s/ Beth Cannestra CHIEF ROADWAY DEVELOPMENT ENGINEER</p>
<p>FHWA</p>	



INLET PROTECTION, TYPE A


GENERAL NOTES

INLET PROTECTION DEVICES SHALL BE MAINTAINED OR REPLACED AT THE DIRECTION OF THE ENGINEER.

MANUFACTURED ALTERNATIVES APPROVED AND LISTED ON THE DEPARTMENT'S EROSION CONTROL PRODUCT ACCEPTABILITY LIST MAY BE SUBSTITUTED.


WHEN REMOVING OR MAINTAINING INLET PROTECTION, CARE SHALL BE TAKEN SO THAT THE SEDIMENT TRAPPED ON THE GEOTEXTILE FABRIC DOES NOT FALL INTO THE INLET. ANY MATERIAL FALLING INTO THE INLET SHALL BE REMOVED IMMEDIATELY.

- ① FINISHED SIZE, INCLUDING FLAP POCKETS WHERE REQUIRED, SHALL EXTEND A MINIMUM OF 10" AROUND THE PERIMETER TO FACILITATE MAINTENANCE OR REMOVAL.
- ② FOR INLET PROTECTION, TYPE C (WITH CURB BOX), AN ADDITIONAL 18" OF FABRIC IS WRAPPED AROUND THE WOOD AND SECURED WITH STAPLES. THE WOOD SHALL NOT BLOCK THE ENTIRE HEIGHT OF THE CURB BOX OPENING.
- ③ FLAP POCKETS SHALL BE LARGE ENOUGH TO ACCEPT WOOD 2X4.



**INLET PROTECTION, TYPE B
(WITHOUT CURB BOX)**

(CAN BE INSTALLED IN ANY INLET WITHOUT A CURB BOX)



INLET PROTECTION, TYPE C (WITH CURB BOX)

INSTALLATION NOTES

TYPE B & C

TRIM EXCESS FABRIC IN THE FLOW LINE TO WITHIN 3" OF THE GRATE.


THE CONTRACTOR SHALL DEMONSTRATE A METHOD OF MAINTENANCE, USING A SEWN FLAP, HAND HOLDS OR OTHER METHOD TO PREVENT ACCUMULATED SEDIMENT FROM ENTERING THE INLET.

TYPE D

DO NOT INSTALL INLET PROTECTION TYPE D IN INLETS SHALLOWER THAN 30", MEASURED FROM THE BOTTOM OF THE INLET TO THE TOP OF THE GRATE.

TRIM EXCESS FABRIC IN THE FLOW LINE TO WITHIN 3" OF THE GRATE.


THE INSTALLED BAG SHALL HAVE A MINIMUM SIDE CLEARANCE, BETWEEN THE INLET WALLS AND THE BAG, MEASURED AT THE BOTTOM OF THE OVERFLOW HOLES, OF 3". WHERE NECESSARY THE CONTRACTOR SHALL CINCH THE BAG, USING PLASTIC ZIP TIES, TO ACHIEVE THE 3" CLEARANCE. THE TIES SHALL BE PLACED AT A MAXIMUM OF 4" FROM THE BOTTOM OF THE BAG.




INLET PROTECTION, TYPE D

(CAN BE INSTALLED IN ANY INLET TYPE WITH OR WITHOUT A CURB BOX AS PER NOTE ②)

INLET PROTECTION TYPE A, B, C, AND D	
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION	
APPROVED 10/16/02 DATE	/S/ Beth Cannestra CHIEF ROADWAY DEVELOPMENT ENGINEER
FHWA	



PLAN VIEW
ARROW MARK



SIDE ELEVATION
DETAIL FOR CONDUIT UNDER PAVED HIGHWAYS

*DEPTH OF CONDUIT AND LENGTH OF PULL BOX VARIES
WITH HEIGHT OF CURB USED. ALSO SEE PULL BOX S.D.D. 9B4

GENERAL NOTES

DETAILS OF CONSTRUCTION, MATERIALS AND WORKMANSHIP NOT SHOWN ON THIS DRAWING SHALL CONFORM TO THE PERTINENT REQUIREMENTS OF THE CONTRACT.

METALLIC (STANDARD SPECIFICATION 652.2.2) OR NONMETALLIC (STANDARD SPECIFICATION 652.2.3) CONDUIT SHALL BE FURNISHED AND PLACED AS SHOWN.

DEPTH OF CONDUIT INSTALLED BELOW THE TRAVELED WAY SHALL BE 24 INCHES MINIMUM AND 36 INCHES MAXIMUM.

DEPTH OF CONDUIT INSTALLED THAT IS NOT BELOW THE TRAVELED WAY SHALL BE 18 INCHES MINIMUM AND 36 INCHES MAXIMUM.

ANY EXCEPTION TO THE MAXIMUM DEPTH SHALL BE ONLY WITH THE WRITTEN APPROVAL OF THE ENGINEER.

THE TRENCH SHALL NOT BE BACKFILLED PRIOR TO INSPECTION OF THE CONDUIT.

ALL METALLIC CONDUIT RACEWAY ENDS SHALL BE REAMED AND THREADED.

ALL METALLIC CONDUIT IN WHICH WIRE OR CABLE IS TO BE INSTALLED SHALL BE BUSHED WITH APPROVED THREADED BUSHINGS BEFORE INSTALLATION OF THE WIRE OR CABLE.

ALL METALLIC CONDUITS IN WHICH WIRE OR CABLE IS NOT TO BE INSTALLED SHALL BE CAPPED WITH THREADED PROTECTIVE CAPS, AS APPROVED BY THE ENGINEER.

ALL NONMETALLIC CONDUIT SHALL BE CAPPED OR PLUGGED IMMEDIATELY AFTER INSTALLATION AND SHALL REMAIN CAPPED OR PLUGGED UNTIL WIRE/CABLES ARE INSTALLED.

NONMETALLIC CONDUITS IN WHICH WIRE OR CABLE IS NOT BEING INSTALLED SHALL REMAIN CAPPED OR PLUGGED.

BENDING OF PVC ELECTRICAL CONDUIT SHALL BE ACCOMPLISHED BY USING A BLANKET OR EMERSION TYPE TANK DESIGNED FOR THE PURPOSE OF BENDING PVC ELECTRICAL CONDUIT.

ALL CUT ENDS SHALL BE TRIMMED INSIDE AND OUTSIDE TO REMOVE ALL ROUGH EDGES ON NONMETALLIC CONDUIT. (SEE NEC 347.5)

WHEN REQUIRED TO CONNECT NONMETALLIC CONDUIT TO METALLIC CONDUIT, ONLY U.L. LISTED ADAPTER FITTINGS SHALL BE USED.

PRIOR TO CONDUIT ACCEPTANCE, CONDUIT CAPS OR PLUGS SHALL BE REMOVED, AND THE CAPS, PLUGS AND CONDUIT ENDS SHALL BE THOROUGHLY CLEANED AND THEN THE CAPS OR PLUGS REINSTALLED TO ENSURE THAT THE CAPS OR PLUGS CAN BE EASILY REMOVED IN THE FUTURE.

ALL CONDUIT BEING FURNISHED AND INSTALLED SHALL HAVE THE U.L. LABEL FIRMLY ATTACHED.

CONDUIT RUNS SHALL BE THE SAME SIZE OF CONDUIT FROM ONE END TO THE OTHER (FROM PULL BOX TO PULL BOX-OR-JUNCTION BOX TO JUNCTION BOX-OR-BASE TO BASE, ETC.).


TRACER WIRE SHALL BE INSTALLED AS STATED IN THE STANDARD SPECIFICATION, ITEM 652.3.1.1.

ALL CONDUIT RUNS SHALL BE STRAIGHT (WITHOUT BENDS) FROM PULL BOX TO PULL BOX, PULL BOX TO BASE AND BASE TO BASE AS SHOWN ON THE PLANS.


CONDUIT

STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION


APPROVED
March, 2017 /S/ Ahmet Demirbilek
DATE STATE ELECTRICAL ENGINEER
FHWA



TRANSVERSE JOINTS



**SECTION C - C
SAWED JOINT**




**SECTION F - F
CONTRACTION JOINT**

GENERAL NOTES


ANCHOR DOWEL BARS AND TIE BARS INTO DRILLED HOLES WITH AN EPOXY.

PROVIDE A MINIMUM DISTANCE OF 15 INCHES FROM AN EXISTING TRANSVERSE JOINT OR EDGE OF REPLACEMENT TO THE CENTER OF THE TIE BAR NEAREST THAT JOINT OR EDGE.


- ① INSTALL DOWEL BARS PARALLEL TO THE PAVEMENT CENTERLINE AND PAVEMENT SURFACE.
- ② APPLY A THIN UNIFORM COATING OF SURFACE TREATMENT TO THE FREE END OF DOWEL BARS TO PREVENT BONDING.




LONGITUDINAL JOINTS



SECTION D - D



**SECTION E - E
SPACING OF DOWEL BARS
ANCHORED INTO EXISTING PAVEMENT**



**PLAN VIEW
CONCRETE BASE
CONTRACTION JOINT LOCATIONS**

TIE BAR TABLE

PAVEMENT DEPTH (D)	TIE BAR SIZE	TIE BAR LENGTH (L)	MAX. TIE BAR SPACING
< 10 1/2"	NO. 4	30"	36"
≥ 10 1/2"	NO. 5	36"	36"
	NO. 4 *	30"	24" **

* SUBSTITUTE BENT BARS AT LONGITUDINAL JOINTS WHEN EQUIPMENT LIMITATIONS DURING CONSTRUCTION WARRANT (e.g. AUXILIARY LANES OR TURN LANES)


** CONFORM TO 15" MINIMUM SPACING FROM TRANSVERSE JOINTS; SPACING BETWEEN TIE BARS WILL BE 30" AT TRANSVERSE JOINTS.

**PAVEMENT DEPTH, DOWEL BAR SIZE
AND JOINT SPACING TABLE**


PAVEMENT DEPTH (D)	DOWEL BAR DIAMETER	CONTRACTION JOINT SPACING
6", 6 1/2"	NONE	12'
7", 7 1/2"	1"	14'
8" & ABOVE	1 1/4"	15'

CONCRETE BASE


STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION



SECTION G - G
TIE BARS ANCHORED INTO EXISTING PAVEMENT



SECTION H - H



PLAN VIEW
SINGLE LANE CONCRETE BASE REPAIR

GENERAL NOTES


- ① USE AN ENGINEER APPROVED BOND BREAKER (E.G. RELEASE AGENT, CURING COMPOUND) AT THE LONGITUDINAL JOINT IN LIEU OF TIE BARS FOR SINGLE LANE CONCRETE BASE REPAIRS UP TO 15 FEET IN LENGTH.
- ② ANCHOR TIE BARS INTO DRILLED HOLES WITH AN EPOXY.
- ③ PAVEMENT THAT WAS IN PLACE PRIOR TO THE CONTRACT.

CONCRETE BASE


STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION

APPROVED
November 2022 /S/ Peter Kemp P.E.
DATE PAVEMENT SUPERVISOR


FHWA



DETAIL A
MAINLINE CLOSURE WITH POSTED DETOUR
WORK ZONE GREATER THAN OR EQUAL TO ½ MILE FROM
DETOUR ROUTE (1000 FEET IF URBAN)



DETAIL B
MAINLINE CLOSURE WITH POSTED DETOUR
WORK ZONE LESS THAN ½ MILE FROM
DETOUR ROUTE (1000 FEET IF URBAN)



DETAIL C
MAINLINE CLOSURE, NO POSTED DETOUR

SPEED LIMIT (MPH)	"STOP AHEAD" ADVANCE WARNING DISTANCE (FT)
25	200
30	200
35	350
40	350
45	500
50	550
55	750

SEE SDD 15C2-SHEET "b"
FOR GENERAL NOTES
AND FOOTNOTES ① THROUGH ⑦


LEGEND

- SIGN ON PERMANENT SUPPORT
- TYPE III BARRICADE
- TYPE III BARRICADE WITH ATTACHED SIGN
- TYPE "A" WARNING LIGHT (FLASHING)
- WORK AREA
- FLAGS, 16" X 16" MIN. (ORANGE)
- DETOUR M4 - 8
- EAST M3 - X
- XX M1 - 4 OR XX M1 - 6 OR COUNTY M1 - 5A
- OR M05 - 1 OR M06 - 1


**BARRICADES AND SIGNS
FOR MAINLINE CLOSURES**

STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION

APPROVED
May 2023 /S/ Andrew Heidtke
DATE WORK ZONE ENGINEER
FHWA



**DETAIL D
ROAD CLOSURE BARRICADE DETAIL
APPROACH VIEW**



**DETAIL E
LANE CLOSURE BARRICADE DETAIL
APPROACH VIEW**

SEE SDD 15C2 - SHEET "a" FOR LEGEND

GENERAL NOTES

THE EXACT NUMBER, LOCATION, AND SPACING OF ALL SIGNS AND BARRICADES SHALL BE ADJUSTED TO FIT FIELD CONDITIONS AS APPROVED BY THE ENGINEER.

ANY SIGNS TEMPORARY OR EXISTING, WHICH CONFLICT WITH TRAFFIC CONTROL "IN USE", SHALL BE REMOVED OR COVERED AS NEEDED AND AS APPROVED BY THE ENGINEER.

THE SPACING BETWEEN TRAFFIC CONTROL SIGNS SHOULD BE ADJUSTED TO NOT CONFLICT WITH AND SHOULD PROVIDE A DESIRABLE MINIMUM OF 200 FEET CLEARANCE TO EXISTING SIGNS THAT WILL REMAIN IN PLACE.

BARRICADES THAT MUST BE MOVED FOR A WORK OPERATION SHALL BE IMMEDIATELY RE-ESTABLISHED UPON COMPLETION OF THE OPERATION, OR FOR CONTINUING OPERATIONS, AT THE END OF EACH WORKING DAY.

SIGNS THAT WILL BE IN PLACE LESS THAN 7 CONTINUOUS DAYS AND NIGHTS MAY BE MOUNTED ON PORTABLE SUPPORTS.

ALL TYPE III BARRICADES SHALL HAVE RAILS REFLECTORIZED ON BOTH FACES. STRIPES SHALL BE PROPERLY SLOPED DOWN TOWARD THE TRAFFIC SIDE OR AS SHOWN IN THE ROAD CLOSURE BARRICADE DETAIL "D" FOR FULL ROAD CLOSURES.

TYPE "A" LOW - INTENSITY FLASHING WARNING LIGHTS SHALL BE VISIBLE ON BOTH SIDES OF THE BARRICADE.

THE R11 - 2, R11 - 3, M4 - 9, R11 - 4, AND R10 - 61 SIGNS PLACED ON THE BARRICADES SHALL COVER NO MORE THAN THE TOP RAIL. THE SIGNS SHALL NOT COVER ANY PORTION OF THE MIDDLE RAIL OR BOTTOM RAILS.

"WO" AND "MO" SIGNS ARE THE SAME AS "W" AND "M" SIGNS EXCEPT THE BACKGROUND IS ORANGE.

ALL SIGNS SHALL BE 48" X 48" UNLESS OTHERWISE NOTED BELOW:

- R11 - 2 SHALL BE 48" X 30"
- R11 - 3 SHALL, R11 - 4 AND R10 - 61 SHALL BE 60 " X 30"
- M4 - 9 SHALL BE 30" X 24"
- M3 - X SHALL BE 24" X 12" (36" X 18" IF NEEDED TO MATCH EXISTING SIGNS)
- M4 - 8 SHALL BE 24" X 12" (36" X 18" IF NEEDED TO MATCH EXISTING SIGNS)
- M1 - 4, M1 - 5A AND M1 - 6 SHALL BE 24" X 24" (36" X 36" IF NEEDED TO MATCH EXISTING SIGNS)
- MO5 - 1 AND MO6 - 1 SHALL BE 21" X 21" (30" X 30" IF NEEDED TO MATCH EXISTING SIGNS)
- D1 - X SHALL BE AS SHOWN ON SPECIFIC PROJECT SIGNING DETAIL SHEETS.
- R1 - 1 SHALL BE 36" X 36"

- 1 TWO WARNING LIGHTS SHALL BE PROVIDED ON THE CENTER BARRICADE AND A MINIMUM OF ONE WARNING LIGHT SHALL BE PROVIDED ON EACH OF THE OTHER BARRICADES WITHIN THE ROADWAY LIMITS. SPACING OF THE WARNING LIGHTS SHALL BE UNIFORM TO THE EDGE OF ROADWAY AS SHOWN (APPROX. 8 FOOT LIGHT SPACING).
- 2 THESE SIGNS AND BARRICADES ARE NOT REQUIRED IF ROAD CLOSURE BEGINS AT AN INTERSECTION.
- 3 FOR ROAD CLOSURE WITHOUT LOCAL ACCESS TO PROJECT, SEE ROAD CLOSURE BARRICADE DETAIL "D".
- 4 FOR ROAD CLOSURE WITH LOCAL ACCESS TO PROJECT, SEE ROAD CLOSURE BARRICADE DETAIL "E".
- 5 FOR BRIDGE OR CULVERT REPLACEMENTS, SUBSTITUTE "BRIDGE OUT" INSTEAD OF "ROAD CLOSED" ON R11 - 2 AND R11 - 3 SIGNS.
- 6 INSTALL DETOUR AND COMMUNITY GUIDE SIGNS AND ARROWS ONLY IF SPECIFIED IN THE CONTRACT. IF THERE ARE EXISTING ROUTE MARKER ASSEMBLIES THAT WILL REMAIN IN PLACE, ADJUST THE LOCATION OF THE DETOUR ROUTE SIGNS TO CORRESPOND WITH THE EXISTING ASSEMBLIES. MODIFY EXISTING SIGNS WHERE POSSIBLE. SEE SPECIFIC PROJECT DETOUR SIGNING DETAIL SHEETS. IF DETOUR SIGNS ARE BEING INSTALLED BY OTHERS, PLACE THE CONTRACTED TRAFFIC CONTROL SIGNS TO ALLOW FOR PLACEMENT OF ALL WARNING, DETOUR AND GUIDE SIGNS AS SHOWN.
- 7 "EAST" CARDINAL DIRECTION MARKERS AND RIGHT TURN ARROWS ARE SHOWN. USE OTHER CARDINAL DIRECTIONS AND ARROWS AS APPROPRIATE.

BARRICADES AND SIGNS FOR VARIOUS CLOSURES

STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION

APPROVED
May 2023 /S/ Andrew Heidtke
DATE WORK ZONE ENGINEER

FHWA

GENERAL NOTES

THE EXACT NUMBER, LOCATION, AND SPACING OF ALL SIGNS AND DEVICES SHALL BE ADJUSTED TO FIT FIELD CONDITIONS.

THE SPACING BETWEEN TRAFFIC CONTROL SIGNS SHOULD BE ADJUSTED TO NOT CONFLICT WITH AND SHOULD PROVIDE A MINIMUM OF 200 FEET (500 FEET DESIRABLE) CLEARANCE TO EXISTING SIGNS THAT WILL REMAIN IN PLACE.




ALL SIGNS ARE 48" X 48" UNLESS OTHERWISE NOTED. IF NECESSARY DUE TO SPACE CONSTRAINTS, 36"X36" SIGNS MAY BE USED INSTEAD OF 48" X 48" SIGNS.


SIGNS THAT WILL BE IN PLACE LESS THAN SEVEN CONTINUOUS DAYS AND NIGHTS MAY BE MOUNTED ON PORTABLE SUPPORTS.

IF A "STOP" SIGN MUST BE REMOVED FOR A WORK OPERATION, A TEMPORARY "STOP" SIGN SHALL BE PLACED PRIOR TO THE SIGN REMOVAL, OR A FLAGGER SHALL BE PROVIDED UNTIL THE SIGN IS REESTABLISHED.


* THE THIRD W20-1 SIGN IS REQUIRED ONLY IF THERE IS AN INTERSECTION BETWEEN THE "ROAD WORK 500 FEET" SIGN AND THE WORK ZONE. ADJUST THE PLACEMENT OF THIS SIGN BASED ON INTERSECTION LOCATION AND OTHER FIELD CONDITIONS.

LEGEND

-  SIGN ON PERMANENT SUPPORT
-  DIRECTION OF TRAFFIC
-  WORK AREA



TYPICAL SIDE ROAD APPROACH
WARNING SIGN DETAIL




TRAFFIC CONTROL, ADVANCE WARNING SIGNS 40MPH OR LESS

TRAFFIC CONTROL, ADVANCE WARNING
SIGNS 40 MPH OR LESS TWO-WAY
UNDIVIDED ROAD OPEN TO TRAFFIC


STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION

APPROVED
July 2018
DATE
/S/ Andrew Heidtke
WORK ZONE ENGINEER

FHWA



TWO WAY TRAFFIC



ONE WAY TRAFFIC

PERMANENT PAVEMENT MARKING

* CONFIRM MARKING LINE WIDTH WITH THE MISCELLANEOUS QUANTITIES

GENERAL NOTES

DETAILS OF CONSTRUCTION NOT SHOWN ON THIS DRAWING SHALL CONFORM TO STANDARD SPECIFICATIONS AND SPECIAL PROVISIONS.

- ① LOCATE THE NO PASSING ZONE W14-3 SIGN WITHIN 50 FEET OF THE "T" MARKING
- ② MEASURE FROM EDGE OF MARKING TO JOINT LINE. THIS DOES NOT INCLUDE SPACE NEEDED FOR GROOVING OPERATIONS.

LEGEND


- "T" MARKING
- SIGN ON PERMANENT SUPPORT
- ➡ DIRECTION OF TRAFFIC

PERMANENT LONGITUDINAL PAVEMENT MARKINGS

STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION

APPROVED
May 2023
DATE
/S/ Jeannie Silver
STATEWIDE SIGNING AND MARKING
ENGINEER

FHWA



FLEXIBLE TUBULAR
MARKER POST
WORK ZONE

GENERAL NOTES

DETAILS OF CONSTRUCTION NOT SHOWN ON THIS DRAWING SHALL CONFORM TO THE PERTINENT REQUIREMENTS OF THE STANDARD SPECIFICATIONS AND THE APPLICABLE SPECIAL PROVISIONS.

SURFACE MOUNTED BASES SHALL BE FURNISHED IN ACCORDANCE WITH MANUFACTURERS RECOMMENDATIONS TO BE COMPATIBLE WITH FLEXIBLE TUBULAR MARKER POSTS TO A SIZE AND SHAPE THAT WILL PROVIDE A STABLE POST FOUNDATION WHEN SECURED TO THE PAVEMENT.

THE ASPHALTIC ADHESIVE OR BUTYL PAD FURNISHED SHALL BE IN ACCORDANCE WITH MANUFACTURERS RECOMMENDATIONS, UNLESS DIRECTED BY THE ENGINEER TO USE BOLTS.


① REFLECTIVE SHEETING SHALL FOLLOW THE REQUIREMENTS IN THE APPROVED PRODUCTS LISTING FOR SIGN SHEETING.

CHANNELIZING DEVICES
FLEXIBLE TUBULAR
MARKER POST

STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION


APPROVED
November 2022 /S/ Andrew Heidtke
DATE WORK ZONE ENGINEER

FHWA




DRUM

BALLAST WIDTHS
RANGE FROM 24"-36"




42" CONE

DO NOT USE IN TAPERS
½ SPACING OF DRUMS
BALLAST WIDTHS
RANGE FROM 14"-20"




VERTICAL PANEL

THE STRIPES SHALL SLOPE DOWNWARD TO
THE TRAFFIC SIDE FOR CHANNELIZATION.



TYPE II BARRICADE

FOR RAILS LESS THAN 36" LONG, 4" WIDE STRIPES
MAY BE USED. ALL STRIPES SHALL SLOPE DOWNWARD
TO THE TRAFFIC SIDE FOR CHANNELIZATION.



TYPE III BARRICADE

IF SIGN MOUNTED, DO NOT COVER MORE THAN 50% OF THE TOP
TWO RAILS OR 33% OF THE TOTAL AREA OF THE THREE RAILS.

* IF USED FOR A PERMANENT APPLICATION USE RED SHEETING.

GENERAL NOTES

- ① REFLECTIVE SHEETING SHALL FOLLOW THE REQUIREMENTS IN THE APPROVED PRODUCTS LISTING FOR SIGN SHEETING.
- ② LOCATION OF WARNING LIGHTS WHEN SHOWN ON THE PLAN.

**CHANNELIZING DEVICES
DRUMS, CONES, BARRICADES
AND VERTICAL PANELS**

STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION

APPROVED
November 2022 /S/ Andrew Heidtke
DATE WORK ZONE ENGINEER

FHWA

GENERAL NOTES

THE EXACT NUMBER, LOCATION, AND SPACING OF ALL SIGNS AND DEVICES SHALL BE ADJUSTED TO FIT FIELD CONDITIONS AS APPROVED BY THE ENGINEER.

THE SPACING BETWEEN SIGNS SHOULD BE ADJUSTED TO NOT CONFLICT WITH AND TO PROVIDE A MINIMUM OF 200 FEET (500 FEET DESIRABLE) CLEARANCE TO EXISTING SIGNS.

THIS LANE CLOSURE IS TYPICAL FOR CLOSING RIGHT LANE - REVERSE FOR CLOSING LEFT LANE.

ALL SIGNS ARE 48" x 48" UNLESS OTHERWISE NOTED.

"WO" IS THE SAME AS "W" EXCEPT THE BACKGROUND IS ORANGE.

ANY SIGNS TEMPORARY OR EXISTING, WHICH CONFLICT WITH TRAFFIC CONTROL "IN USE" SHALL BE REMOVED OR COVERED AS NEEDED OR AS APPROVED BY THE ENGINEER.

FOR A LANE CLOSURE THAT IS IN PLACE LESS THAN 7 CONTINUOUS DAYS AND NIGHTS, THE ADVANCED WARNING SIGNS MAY BE MOUNTED ON PORTABLE SUPPORTS.

REMOVE PAVEMENT MARKINGS AND PLACE TEMPORARY PAVEMENT MARKING LINE IF LANE CLOSURE IS TO BE IN PLACE 4 OR MORE CONTINUOUS DAYS AND NIGHTS.

IF THE HORIZONTAL ALIGNMENT IS SUCH THAT A CURVE MAY REQUIRE ADDITIONAL DELINEATION, THE DEVICE SPACING MAY BE DECREASED TO 50 FEET.

WARNING LIGHTS ARE NOT REQUIRED IF THE LANE CLOSURE IS A DAYTIME ONLY OPERATION.


ADJUSTMENTS IN BUFFER SPACE NEED TO BE INCORPORATED WHEN THE LANE CLOSURE OCCURS

NEAR AN INTERCHANGE EXIT OR ENTRANCE RAMP OR INTERSECTION. THE LANE CLOSURE MUST TAKE PLACE FAR ENOUGH IN ADVANCE OF AN EXIT OR ENTRANCE RAMP TO STILL ALLOW FOR ADEQUATE BUFFER SPACE. THE MINIMUM LENGTH OF THE BUFFER SPACE BEFORE AN EXIT RAMP SHOULD BE ONE HALF THE LENGTH OF THE TRANSITION AREA. THE ENTRANCE RAMP SHOULD BE FOLLOWED BY THE ORIGINAL BUFFER SPACE LENGTH OF 800 FEET DESIRABLE PRIOR TO ANOTHER TRAFFIC CONTROL CHANGE SUCH AS A CROSSOVER MANEUVER.

CONSIDER ROADWAY GEOMETRICS WHEN LOCATING SIGNS AND ARROW BOARD SO THE DRIVER HAS A CLEAR VIEW OF THE ARROW BOARD AND LANE CLOSURE DRUMS.


LEGEND

- SIGN ON PERMANENT SUPPORT
- TRAFFIC CONTROL DRUM
- TRAFFIC CONTROL DRUM WITH TYPE "C" STEADY BURN LIGHT
- TYPE III BARRICADE WITH ATTACHED SIGN
- TYPE "A" WARNING LIGHT (FLASHING)
- REMOVING PAVEMENT MARKINGS
- DIRECTION OF TRAFFIC
- WORK AREA
- FLASHING ARROW BOARD



TRAFFIC CONTROL LANE CLOSURE	
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION	
APPROVED May 2023 DATE	/S/ Andrew Heidtke WORK ZONE ENGINEER

STRUCTURE P-40-875
N. HOLTEN ST. VIADUCT
OVER MILWAUKEE RIVER




SITE PLAN AND ELEVATION (1 OF 3)	SHEET 1 OF 7




CITY OF MILWAUKEE CONTACT:
JONATHAN THOMAS 414-286-0463

REVISED: 12-05-2023 GJR

8



PLAN




WEST ELEVATION
(LOOKING NORTH EAST)

LEGEND:


- STRUCTURAL STEEL REPAIRS TO BENT AND/OR SUPERSTRUCTURE
- PAINT BENT
- CONCRETE SUBSTRUCTURE REPAIRS

STATE PROJECT NUMBER

2984-12-74




NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
STRUCTURE P-40-875			
DRAWN BY		GJR	PLANS CK'D. JPH
SITE PLAN AND ELEVATION (2 OF 3)		SHEET 2 OF 72	



NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
STRUCTURE P-40-875			
DRAWN BY		GJR	PLANS CK'D. JF
SITE PLAN AND ELEVATION (3 OF 3)		SHEET 3 OF 7	


LIST OF DRAWINGS

- 1. SITE PLAN AND ELEVATION (1 OF 3)
- 2. SITE PLAN AND ELEVATION (2 OF 3)
- 3. SITE PLAN AND ELEVATION (3 OF 3)
- 4. CROSS SECTIONS
- 5. ESTIMATE OF QUANTITIES
- 6. TOP OF DECK REPAIR PLAN SPANS 12-14
- 7. NORTH ABUTMENT EXPANSION JOINT PLAN EAST END
- 8. NORTH ABUTMENT EXP. JOINT PLAN WEST & MIDDLE
- 9. NORTH ABUTMENT EXPANSION JOINT SECTION
- 10. NORTH ABUTMENT EXPANSION JOINT BILL OF BARS
- 11. EXPANSION JOINT DETAILS
- 12. NORTH ABUTMENT CONCRETE REPAIRS
- 13. NORTH ABUTMENT WINGWALL AND DETAILS
- 14. REPLACEMENT DETAILS NORTH ABUTMENT
- 15. NORTH ABUTMENT STONE REPLACEMENT DETAILS 1
- 16. NORTH ABUTMENT STONE REPLACEMENT DETAILS 2
- 17. PIERS 9-14 CONCRETE REPAIRS
- 18. FENCING AND CONDUIT DETAILS
- 19. NORTH ABUTMENT BEARING AND GIRDER DETAILS
- 20. BRG. REPLACEMENT DETAILS NORTH ABUTMENT
- 21. STAIR TOWER REPLACEMENT
- 22. 40S1 AND 41S1 STAIRWAY DETAILS
- 23. 42S1, 43S1 AND 44S1 STAIRWAY DETAILS
- 24. 114 MEMBER DETAILS
- 25. 115 MEMBER DETAILS
- 26. 60F2 AND 115 MEMBER DETAILS
- 27. STAIRWAY FENCING AND RAILING DETAILS
- 28. NORTH AND SOUTH ELEVATIONS BENT 9
- 29. WEST AND EAST ELEVATIONS BENT 9
- 30. NORTH AND SOUTH ELEVATIONS BENT 10
- 31. NORTH AND SOUTH ELEVATIONS BENT 11
- 32. WEST AND EAST ELEVATIONS BENT 11
- 33. NORTH AND SOUTH ELEVATIONS BENT 12
- 34. WEST AND EAST ELEVATIONS BENT 12
- 35. 14 MEMBER DETAILS
- 36. 152R/L MEMBER DETAILS
- 37. 151R/L MEMBER DETAILS
- 38. 17 MEMBER DETAILS
- 39. 16 MEMBER DETAILS
- 40. 47 MEMBER DETAILS
- 41. 48 MEMBER DETAILS
- 42. 49 MEMBER DETAILS
- 43. 50 MEMBER DETAILS
- 44. 51 MEMBER DETAILS
- 45. 52 MEMBER DETAILS
- 46. 22G1 MEMBER DETAILS
- 47. 20G1 MEMBER DETAILS
- 48. SIDEWALK BRACKET MEMBER DETAILS
- 49. 46 MEMBER DETAILS
- 50. 71 MEMBER DETAILS
- 51. 72 MEMBER DETAILS
- 52. 112 MEMBER DETAILS
- 53. 109B5 MEMBER DETAILS
- 54. 19G1 MEMBER DETAILS
- 55. 65G1 MEMBER DETAILS
- 56. 127D1 MEMBER DETAILS
- 57. 101G1 MEMBER DETAILS
- 58. 126G1 MEMBER DETAILS
- 59. 152R/L, 47T1R E.&W. ELEVATION MEMBER DETAILS
- 60. 151R MEMBER DETAILS
- 61. 152L MEMBER DETAILS
- 62. 152R MEMBER DETAILS
- 63. 47T1R & 47T1LA FAR SIDE MEMBER DETAILS
- 64. 47T1LA NEAR SIDE MEMBER DETAILS
- 65. 47T1R NEAR SIDE MEMBER DETAILS
- 66. 49T1 FAR AND NEAR SIDES MEMBER DETAILS
- 67. 50T1 FAR SIDE MEMBER DETAILS
- 68. 50T1 NEAR SIDE MEMBER DETAILS
- 69. 51T1 FAR SIDE MEMBER DETAILS
- 70. 51T1 NEAR SIDE MEMBER DETAILS
- 71. 52T1 FAR SIDE MEMBER DETAILS
- 72. 52T1 NEAR SIDE MEMBER DETAILS



TYPICAL CROSS SECTION

(FIXED SPANS 8-10)
(LOOKING NORTH)



TYPICAL CROSS SECTION

(FIXED SPANS 11-14)
(LOOKING NORTH)

NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
STRUCTURE P-40-875			
DRAWN BY		GJR	PLANS CK'D. JPH
CROSS SECTIONS			SHEET 4 OF 72

ESTIMATE OF QUANTITIES

ITEM NO.	BID ITEM	UNIT	N. ABUT.	SUPER.	SUBST.	TOTAL
203.0220	REMOVING STRUCTURE P-40-875	EACH		1		1
203.0330	DEBRIS CONTAINMENT P-40-875	EACH		1		1
206.1001	EXCAVATION FOR STRUCTURES BRIDGES P-40-875	EACH	1			1
210.1500	BACKFILL STRUCTURE TYPE A	TON	200			200
502.0100	CONCRETE MASONRY BRIDGES	CY	8	1	3	12
502.0200	CONCRETE MASONRY BRIDGES HES	CY	8			8
502.3101	EXPANSION DEVICE	LF		150		150
502.3200	PROTECTIVE SURFACE TREATMENT	SY		100	20	120
502.3215	PROTECTIVE SURFACE TREATMENT RESEAL	SY		2,320		2,320
502.4104	ADHESIVE ANCHORS 1/2-INCH	EACH		6		6
502.4204	ADHESIVE ANCHORS NO. 4 BAR	EACH	16			16
502.4205	ADHESIVE ANCHORS NO. 5 BAR	EACH	263			263
505.0600	BAR STEEL REINFORCEMENT HS COATED STRUCTURES	LB	2,410	4,640	550	7,600
506.0105	STRUCTURAL STEEL CARBON	LB	2,150	5,380	76,470	84,000
506.2610	BEARING PADS ELASTOMERIC LAMINATED	EACH	7			7
506.6000	BEARING ASSEMBLIES EXPANSION P-40-875	EACH	1			1
506.7050.S	REMOVING BEARINGS P-40-875	EACH	8			8
509.0301	PREPARATION DECKS TYPE 1	SY		36		36
509.0302	PREPARATION DECKS TYPE 2	SY		12		12
509.0310.S	SAWING PAVEMENT DECK PREPARATION AREAS	LF		410		410
509.1000	JOINT REPAIR	SY		60		60
509.1500	CONCRETE SURFACE REPAIR	SF	105	7	94	206
509.2000	FULL DEPTH DECK REPAIR	SY		2		2
509.2100.S	CONCRETE MASONRY DECK REPAIR	CY		31		31
509.9020.S	EPOXY CRACK SEALING	LF	95			95
509.9025.S	EPOXY INJECTION CRACK REPAIR	LF			48	48
509.9026.S	CORED HOLES 2-INCH DIAMETER	EACH	1		1	2
511.1200	TEMPORARY SHORING P-40-875	SF	575			575
516.0500	RUBBERIZED MEMBRANE WATERPROOFING	SY	30			30
517.0601	PAINTING EPOXY SYSTEM P-40-875	EACH		1		1
517.0901.S	PREPARATION AND COATING OF TOP FLANGES P-40-875	EACH		1		1
517.1801.S	STRUCTURE REPAINTING RECYCLED ABRASIVE P-40-875	EACH		1		1
517.4501.S	NEGATIVE PRESSURE CONTAINMENT AND COLLECTION OF WASTE MATERIALS P-40-875	EACH		1		1
517.6001.S	PORTABLE DECONTAMINATION FACILITY	EACH		1		1
604.0500	SLOPE PAVING CRUSHED AGGREGATE	SY	170			170
652.0125	CONDUIT RIGID METALLIC 2-INCH	LF		3		3
652.0135	CONDUIT RIGID METALLIC 3-INCH	LF		24		24
SPV.0025.501	DEEP CONCRETE SURFACE REPAIR	CF			22	22
SPV.0025.505	NON-SHRINK GROUT	CF	24			24
SPV.0035.540	STONE REMOVAL	CY	9			9
SPV.0060.508	TEMPORARY SHORING FOR PIERS 9,10,11,12 AND NORTH ABUTMENT REPAIR	EACH			1	1
SPV.0060.509	TEMPORARY SUPPORTS P-40-875	EACH	2			2
SPV.0060.594	JUNCTION BOX 14"X8"X6"	EACH		1		1
SPV.0060.595	JUNCTION BOX 14"X14"X12"	EACH		2		2
SPV.0060.597	PROTECTING UTILITIES	EACH		1		1
SPV.0085.540	STAIRWAY STRUCTURAL STEEL	LB			12,600	12,600
SPV.0090.501	REMOVE, REPAIR, PAINT AND REINSTALL EXISTING STEEL RAILING	LF		180		180
SPV.0090.505	STAIRWAY RAILING AND PROTECTIVE SCREENING	LF			330	330
SPV.0090.530	REHABILITATION OF CHAIN LINK FENCE	LF		16		16
SPV.0180.530	ABUTMENT SEAT CLEANING AND SEALING	SY	10			10
	NON-BID ITEMS					
	PREFORMED JOINT FILLER					
	NON-BITUMINOUS JOINT FILLER					
	PLASTIC OR ZINC SHEETS 1/8-INCH					
	POLYETHYLENE SHEETS					
	TEFLON PADS					

GENERAL NOTES

ALL STATIONS AND ELEVATIONS ARE IN FEET.

DIMENSIONS SHOWN ARE BASED ON ORIGINAL STRUCTURE PLANS.

ELEVATIONS ARE REFERRED TO CITY OF MILWAUKEE DATUM: 580.6 NGVD.

DRAWINGS SHALL NOT BE SCALED.

ROADWAY ALIGNMENTS, STATIONING AND BASE MAPPING ARE BASED ON A FIELD SURVEY AND ARE TO BE USED FOR INFORMATIONAL PURPOSES ONLY. STATIONING SHOWN DOES NOT CORRELATE WITH PRIOR PLANS.

BAR STEEL REINFORCEMENT SHALL BE EMBEDDED 2" CLEAR UNLESS OTHERWISE SHOWN OR NOTED.

BEVEL EXPOSED CONCRETE EDGES ¾" UNLESS OTHERWISE NOTED.

THE FIRST OR FIRST TWO DIGITS OF THE BAR MARK SIGNIFIES THE BAR SIZE.

BENDING DIMENSIONS FOR REINFORCING BARS ARE OUT TO OUT.

SPACES EXCAVATED AND NOT OCCUPIED BY NEW CONSTRUCTION SHALL BE BACKFILLED WITH BID ITEM 210.1500 "BACKFILL STRUCTURE TYPE A".

JOINT FILLER SHALL CONFORM TO AASHTO DESIGNATION M 153 TYPE I, II, OR III, OR AASHTO DESIGNATION M213.

LOCATIONS OF EXISTING AND PROPOSED UTILITY INSTALLATIONS AS SHOWN ON PLANS ARE APPROXIMATE. THERE MAY BE OTHER UTILITY INSTALLATIONS WITHIN PROJECT AREA THAT ARE NOT SHOWN.

SEE ROADWAY PLANS FOR EXISTING AND PROPOSED UTILITY LOCATIONS.

PAINT FOR STEEL TO MATCH AMS STANDARD NO. 595A COLOR NO. 20318.

ALL EXISTING STEEL SHALL BE SANDBLASTED AND PAINTED UNDER BID ITEMS 517.0901.S "PREPARATION AND COATING OF TOP FLANGES P-40-875", 517.1801.S "STRUCTURE REPAINTING RECYCLED ABRASIVE P-40-875", AND 517.4501.S "NEGATIVE PRESSURE CONTAINMENT AND COLLECTION OF WASTE MATERIALS P-40-875."

EXISTING ABUTMENTS AND PIERS ARE TO REMAIN IN PLACE AS SHOWN AND INCORPORATED INTO NEW CONSTRUCTION.

UTILIZE EXISTING BAR STEEL REINFORCEMENT WHERE SHOWN AND EXTEND 24 BAR DIAMETERS INTO NEW WORK, UNLESS SPECIFIED OTHERWISE.

ALL CONCRETE REMOVALS SHALL BE DEFINED BY A 1-INCH DEEP SAW CUT.

PROTECTIVE SURFACE TREATMENT SHALL BE APPLIED TO THE TOP OF NEW CONCRETE AT JOINT REPAIR, INCLUDING THE TOP, INSIDE AND OUTSIDE FACES OF PARAPETS AND CRASH BARRIERS.

THE EXISTING STRUCTURE P-40-875 IS A 15 SPAN STEEL GIRDER BRIDGE WITH AN OVERALL LENGTH OF 969'-6¾" AND TYPICAL WIDTH OF 77'-7".

EXISTING CONDUIT IN PARAPET TO REMAIN IN PLACE EXCEPT AT EXPANSION JOINT REPLACEMENT. CONTRACTOR SHALL PROVIDE ADEQUATE PROTECTION DURING CONSTRUCTION AND REPAIR ANY DAMAGED WIRING OR CONDUIT AT NO EXPENSE TO THE DEPARTMENT.

INSTALLATION OF EXPANSION JOINT ASSEMBLY, INCLUDING ANCHOR STUDS, HARDWARE, AND ANY GROUTING AND WELDING SHALL BE PAID FOR AT THE LF PRICE AS BID ITEM 502.3101 "EXPANSION DEVICE".

REMOVAL OF EXISTING EXPANSION JOINT AND STEEL IS INCLUDED WITH THE BID ITEM 509.1000 "JOINT REPAIR".

WELDING NOT SHOWN ON THE PLANS WILL NOT BE PERMITTED, EXCEPT BY WRITTEN PERMISSION FROM THE ENGINEER AND WITH AN APPROVED WELD PROCEDURE BY THE CONTRACTOR.

USE GALVANIZED ⅞" DIAMETER ASTM A-325 BOLTS FOR ALL CONNECTIONS, UNLESS NOTED OTHERWISE ON THE PLANS.

EXERCISE CARE WHILE REMOVING EXISTING BOLTS OR RIVETS AND INSTALLING NEW BOLTS. DO NOT DAMAGE EXISTING STEEL OR BOLT HOLES. ANY DAMAGE WILL BE REPAIRED OR REPLACED AT NO ADDITIONAL COST.

PROVIDE A MINIMUM RADIUS OF 1" AT ALL INTERIOR AND RE-ENTERANT CUTS, UNLESS NOTED OTHERWISE ON THE PLANS.

ALL NEW OR EXISTING HOLES IN STEEL NOT BEING USED ARE TO BE FILLED WITH HIGH STRENGTH, GALVANIZED BOLTS PRIOR TO STRUCTURAL PAINTING.

DRAWINGS 21 THRU 72 INCLUDE STRUCTURAL STEEL ERECTION DRAWINGS, FROM 1926 AND 1987. DETAILED FABRICATION DRAWINGS ARE ON FILE WITH THE CITY OF MILWAUKEE.


REMOVALS WILL BE MADE AS INDICATED ON THE DRAWINGS. ALL REMOVALS WILL BE COMPLETE AND INCLUDE ALL FOREIGN OBJECTS SUCH AS BRACKETS, HANGER, ABANDONED CONDUIT, ETC. THAT IS NOT NEEDED STRUCTURALLY, WHETHER MENTIONED OR NOT AND REMOVED AS DIRECTED BY THE ENGINEER IN THE FIELD.

STRUCTURAL STEEL REPAIRS AND MODIFICATIONS WILL BE MADE AS INDICATED PER THE PLANS.

ALL NEW STEEL MEMBERS SHALL BE PAINTED UNDER BID ITEM 517.0601 "PAINTING EPOXY SYSTEM P-40-875".

ALL STRUCTURAL STEEL AREAS IN CONTACT WITH NEW CONCRETE ARE TO BE CLEANED AND PRIME PAINT COATED IN ACCORDANCE WITH THE BID ITEM 517.0901.S "PREPARATION AND COATING OF TOP FLANGES P-40-875". ALL RUSTED AND CORRODED AREAS WITHIN 4" OF THE STRUCTURAL STEEL WITHIN CONCRETE ARE TO BE CLEANED, PRIME PAINT COATED, AND RECEIVE ONE FINISH PAINT COAT.

PAINTING LIMITS SHALL BE FROM THE TOP OF THE CONCRETE SUBSTRUCTURE TO THE ELEVATION OF THE BOTTOM FLANGE OF THE MAIN STEEL GIRDERS.



MINIMUM CONSTRUCTION CLEARANCE ENVELOPE

NORMAL TO B-40-910

TEMPORARY MINIMUM CLEARANCE OF 9'-0" SHALL BE MAINTAINED ABOVE STRUCTURE B-40-910 AT ALL TIMES. LIMITED SHORT TERM CLOSURES MAY BE ALLOWED WITH APPROVAL OF ENGINEER.

STATE PROJECT NUMBER

2984-12-74

DESIGN DATA

DEAD LOAD

CONCRETE = 150 PCF
FWS = 20 PSF

LIVE LOAD

TAKEN FROM HSI, 06/06/2023
INVENTORY RATING: HS-19
OPERATING RATING: HS-26
WISCONSIN STANDARD PERMIT VEHICLE (WIS-SPV) = N/A

MATERIAL PROPERTIES:

CONCRETE SUPERSTRUCTURE f'c = 4,000 PSI
CONCRETE SUBSTRUCTURE f'c = 3,500 PSI

BAR STEEL REINFORCEMENT Fy = 60,000 PSI

NEW STEEL BEAMS/SHAPES (ASTM A709) Fy = 36,000 PSI

TRAFFIC DATA

A.D.T. (2018) = 9,300 VEHICLES/DAY
A.D.T. (2035) = 12,579 VEHICLES/DAY
R.D.S. = 30 MPH

BRIDGE CONSTRUCTION NOTES

EXISTING BRIDGE PLANS ARE ON FILE IN CITY OF MILWAUKEE INFRASTRUCTURE SERVICES DIVISION'S STRUCTURAL DESIGN UNIT, ROOM 907, FRANK P. ZEIDLER MUNICIPAL BUILDING, 841 N. BROADWAY, MILWAUKEE, WI 53202
PHONE (414)-286-0463.


PROPOSED IMPROVEMENTS

THE NORTH HOLTON STREET VIADUCT REHABILITATION PHASE II SPECIFIC REPAIRS ARE AS FOLLOWS:
STRUCTURAL STEEL REPAIRS TO BENTS 9 THRU 12 INCLUDING STEEL COLUMN, CROSS BRACING (LATERAL AND TRANSVERSE); STRUCTURAL STEEL AND GIRDER REPAIRS INCLUDE REPAIR AND/OR REPLACEMENT OF STRUCTURAL MEMBERS; CONCRETE SUBSTRUCTURE REPAIRS TO BENTS 9-14 AND NORTH ABUTMENT AND WINGWALLS; CONCRETE SUBSTRUCTURE REPAIRS INCLUDE CRACK, SPALL, AND DELAMINATION REPAIR; PAINTING OF BENTS 9-14; NEW EXPANSION JOINT AT NORTH ABUTMENT; REPLACEMENT OF STEEL STAIRCASE AT EAST SIDE OF BENT 12; DECK REPAIRS FROM SPAN 12 TO SPAN 14. REPLACEMENT OF NORTH ABUTMENT EXPANSION BEARINGS. SLOPE PAVING REPAIR.

UTILITIES

EXISTING CONDUITS MOUNTED TO THE UNDERSIDE OF THE SUPERSTRUCTURE SHALL REMAIN IN PLACE AND BE PROTECTED DURING CONSTRUCTION. SEE PROJECT SPECIFICATIONS.

NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
STRUCTURE P-40-875			
		DRAWN BY JC	PLANS CK'D. JPH
ESTIMATE OF QUANTITIES		SHEET 5 OF 72	



TOP OF DECK REPAIR PLAN

SPAN 12 - SPAN 14

NOTE

USE CAUTION FOR CONCRETE REMOVALS TO PREVENT DAMAGE TO REINFORCING STEEL. SEE STANDARD SPECIFICATION SECTIONS 203, 502 & 509 FOR PROPER CONSTRUCTION METHODS.

DECK REPAIR AND CONCRETE SURFACE REPAIR LOCATIONS AS DIRECTED BY THE ENGINEER.

FOR PREPARATION OF DECKS TYPE 1 & 2:
S.F. OF AREAS ARE GIVEN ON TOP OF DECK REPAIR PLAN FOR PREPARATION OF DECKS TYPE 1.
AREA FOR PREPARATION OF DECKS TYPE 2 IS ESTIMATED TO BE ONE-THIRD (1/3) OF PREPARATION OF DECKS TYPE 1 AREA.

TYPE 2 LOCATIONS TO BE DETERMINED AS DIRECTED BY THE ENGINEER AFTER TYPE 1 REMOVALS ARE UNDERWAY.

AREAS OF FULL-DEPTH DECK REPAIR TO BE DETERMINED AS DIRECTED BY THE ENGINEER AFTER TYPE 2 REMOVALS ARE UNDERWAY.

PROTECTIVE SURFACE TREATMENT RESEAL SHALL BE APPLIED TO THE EXISTING DECK, SIDEWALK, CRASH BARRIER, AND PARAPET. SURFACE PREPARATION IS INCLUDED IN THE BID ITEM "PROTECTIVE SURFACE TREATMENT RESEAL".

4-1" CONDUITS SHOWN IN DECK ARE TO REMAIN IN SERVICE.


SPAN LENGTH DIMENSIONS ARE ALONG T/L.

DECK REPAIR AND CONCRETE SURFACE REPAIR LOCATIONS AS DIRECTED BY THE ENGINEER.

LEGEND

- PREPARATION DECK AREA (TYPE 1 AND/OR TYPE 2) (SF)
- CRASH BARRIER CONCRETE SURFACE REPAIR (SF)
- EXP. JOINT REPAIR SEE SHEETS 7-11

NO.		DATE	REVISION		BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION					
STRUCTURE P-40-875					
			DRAWN BY	HMD	PLANS CK'D. JPH
TOP OF DECK REPAIR PLAN SPANS 12-14				SHEET 6 OF 72	



PLAN VIEW OF NORTH ABUTMENT
EXPANSION JOINT EAST END

EAST END

NOTE

AT EXP. JNT. #11 LOCATED AT THE NORTH ABUTMENT. 1 CONDUIT IN EAST CONCRETE PARAPET, 2 CONDUITS IN WEST CONCRETE PARAPET.

ELECTRICAL BOXES IN APPROACH WALKS AND WINGWALL PARAPETS AT BOTH EAST AND WEST SIDE (4 TOTAL). EAST AND WEST APPROACH WALK BOXES AND WEST PARAPET BOX TO BE REPLACED (3 TOTAL).

KEY:



- 3'-0" ABUTMENT REMOVE TO BACK WALL CUT LEVEL.
- EXISTING BARS ARE LIKELY TO BE CORRODED AND/OR DAMAGED DURING CONCRETE REMOVAL. PRESERVE AND INCORPORATE AS MUCH REBAR AS PRACTICAL.
- STRIKE OFF AND LEAVE ROUGH.

STATE PROJECT NUMBER

2984-12-74

NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
STRUCTURE P-40-875			
DRAWN BY GJR		PLANS CK'D. JPH	
NORTH ABUTMENT EXPANSION JOINT PLAN EAST END		SHEET 7 OF 72	


REVISED DATE: 12-05-2023 GJR










KEY:

- ◇ 3'-0" ABUTMENT
REMOVE TO BACK WALL
CUT LEVEL.
- ☆ EXISTING BARS ARE LIKELY TO BE CORRODED
AND/OR DAMAGED DURING CONCRETE REMOVAL.
PRESERVE AND INCORPORATE AS MUCH REBAR
AS PRACTICAL.

NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
STRUCTURE P-40-875			
		DRAWN BY	PLANS CK'D.
NORTH ABUTMENT EXP. JOINT PLAN WEST & MIDDLE		SHEET 8 OF 7	



-  MEMBER 1095B TO BE REPLACED.
-  EXISTING BARS ARE LIKELY TO BE CORRODED AND/OR DAMAGED DURING CONCRETE REMOVAL. PRESERVE AND INCORPORATE AS MUCH REBAR AS PRACTICAL.
-  LOCATIONS DETERMINED BY ENGINEER (SEE NOTE "A").
-  PLACE MULTIPLE LAYERS OF POLYETHYLENE SHEETS OVER ENTIRE ABUTMENT ADD-ON. TOTAL THICKNESS OF SHEETS SHALL BE AT LEAST 0.03".
-  SALVAGED RAILING WITH 6 1/2" POST AND 9 1/4"x10 1/2" BASE PLATE AND 4-3/4"x12" ANCHOR BOLTS. SEE SPV.0090.501. (SEE SHEETS 8 AND 18).
-  SET JOINT OPENING TO 1 3/4" NORMAL TO JOINT.
-  STRIKE OFF AND LEAVE ROUGH.

- A. DIAPHRAGM SUPPORT ANGLES SHALL BE ASTM A709 GRADE 36. BOLTS ARE $\frac{3}{4}$ " DIA. ALL BOLTS, NUTS AND WASHERS SHALL BE ASTM A325 TYPE 1.
- B. ALL SUPPORT ANGLES SHALL BE HOT-DIPPED GALVANIZED. ALL BOLTS, NUTS AND WASHERS SHALL BE HOT-DIPPED GALVANIZED. IN ACCORDANCE WITH ASTM A153 CLASS C. GALVANIZED NUTS SHALL BE TAPPED OVERSIZED IN ACCORDANCE WITH THE REQUIREMENTS OF ASTM A563 AND SHALL MEET THE REQUIREMENTS OF SUPPLEMENTARY REQUIREMENT S1 OF ASTM A563, LUBRICANT AND TEST FOR COATED NUTS.
- C. ALL DIAPHRAGM SUPPORT HARDWARE SHALL BE INCIDENTAL TO "CONCRETE MASONRY DECK REPAIR".

















WEST BAYS BETWEEN GIRDERS
104G1, 107G1, 107G2 AND 110G1

NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
STRUCTURE P-40-875			
DRAWN BY		HMD	PLANS CK'D. JF
NORTH ABUTMENT EXPANSION JOINT SECTION		SHEET 9 OF 7	

BILL OF BARS - NORTH ABUTMENT EXPANSION JOINT

BAR MARK	COAT	NO. REQ'D	LENGTH	BENT	BAR SERIES	LOCATION
N501	X	93	2'-5"	X		PAVING BLOCK VERT. ANCHORS - EAST END
N403	X	93	3'-10"	X		PAVING BLOCK VERT. - EAST END
N505	X	4	22'-0"			PAVING BLOCK HORIZ. - EAST END
N406	X	203	4'-4"	X		DECK JOINT VERT. STIRRUPS - EAST, MIDDLE & WEST ENDS
N507	X	5	22'-0"			DECK JOINT HORIZ. - EAST END
N508	X	5	41'-9"			DECK JOINT HORIZ. - MIDDLE
N509	X	5	11'-10"	X		DECK JOINT HORIZ. - EAST END
N510	X	4	11'-7"	X		PAVING BLOCK HORIZ. - EAST END
N611	X	145	4'-0"			DECK JOINT HORIZ. BTWN. GIRD./STRINGERS - EAST, MIDDLE & WEST ENDS
N512	X	4	42'-1"			PAVING BLOCK HORIZ. - MIDDLE
N513	X	9	6'-0"	X		DECK JOINT HORIZ. SPLICE - MIDDLE & WEST END
N515	X	10	6'-3"	X		DECK - TIE BAR
N516	X	3	3'-2"	X		VERT. TIE BAR DECK - EAST SIDE CRASH BARRIER
N517	X	6	7'-3"	X		PARAPET VERT. TIE BAR SDWK. - EAST, MIDDLE & WEST ENDS
N518	X	4	10'-0"			PAVING BLOCK HORIZ. - WEST END
N519	X	20	8'-5"			SDWK. HORIZ. TOP & BOTTOM - EAST, MIDDLE & WEST ENDS
N520	X	16	3'-2"	X		SDWK. VERT. TIE BAR - EAST, MIDDLE & WEST ENDS
N421	X	16	2'-7"	X		SDWK. VERT. TIE BAR - EAST, MIDDLE & WEST ENDS
N622	X	4	7'-2"			SDWK. PAVING BLOCK HORIZ. - EAST, MIDDLE & WEST ENDS
N424	X	6	4'-5"	X		BOTTOM HORIZ. SDWK. DECK OVERHANG - EAST, MIDDLE & WEST ENDS
N425	X	16	2'-8"	X		SDWK. VERT. PAVING BLOCK TIE BAR - EAST, MIDDLE & WEST ENDS
N426	X	6	7'-2"			SDWK. HORIZ. BACKWALL ADD-ON - EAST, MIDDLE & WEST ENDS
N527	X	10	31'-9"			DECK JOINT HORIZ. CURB - MIDDLE & WEST END
N529	X	5	12'-3"			DECK JOINT HORIZ. - WEST END
N430	X	84	5'-8"	X		DECK JOINT VERT. STIRRUPS CURB AREA - MIDDLE & WEST END
N431	X	54	5'-0"	X		PAVING BLOCK VERT. CURB - MIDDLE & WEST END
N532	X	54	3'-3"	X		PAVING BLOCK VERT. ANCHORS CURB - MIDDLE & WEST END
N533	X	10	28'-7"			PAVING BLOCK HORIZ. CURB - MIDDLE & WEST END
N534	X	2	2'-3"			HORIZ. DOWEL CRASH BARRIER - EAST END



NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
STRUCTURE P-40-875			
DRAWN BY		JC	PLANS CK'D. JPH
NORTH ABUTMENT EXPANSION JOINT BILL OF BARS		SHEET 10 OF 72	

LEGEND

- 1 NEOPRENE STRIP SEAL (4-INCH) AND STEEL EXTRUSIONS. SET JOINT OPENING AT 1 3/4".
- 2 STUDS 5/8" DIA. x 6 3/8" LONG AT 6" ALTERNATE CENTERS. WELD TO EXTRUSIONS AND BEND AS SHOWN AFTER WELDING.
- 2A 1/2" THICK ANCHOR PLATE WITH 5/8" DIA. ROD (OR ALTERNATE STRIP SEAL ANCHOR). WELD ROD TO ANCHOR PLATE. WELD ANCHOR PLATE TO NO. 1 AT 1'-6" CENTERS BETWEEN GIRDERS.
- 3 3/4" DIA. THREADED ROD WITH 2 NUTS AND PLATE WASHERS. FOR STEEL GIRDERS, WELD THREADED ROD TO TOP FLANGE OR ATTACH BY BOLTING THRU FLANGE. ON ABUTMENT SIDE, GROUT THREADED ROD INTO FIELD DRILLED HOLES IN ABUTMENT BACKWALL AS SHOWN.
- 4 3/4" DIA. THREADED ROD WITH NUT. TACK WELD NUT TO NO. 5.
- 5 FABRICATE SUPPORT FROM 3" x 1/2" BAR AS SHOWN OR EQUIVALENT. ONE PER GIRDER PER SIDE. SHOP OR FIELD WELD TO NO. 1. IF FIELD WELDED, COVER WELDED AREAS WITH EPOXY-COATING MATERIAL. PROVIDE 1 1/2" DIA. HOLE FOR NO. 3 AND 1" DIA. HOLE FOR NO. 4.
- 7 3/4" DIA. x 1 1/2" STAINLESS STEEL SOCKET FLAT HEAD SCREWS WITH ANTI-SIEZE LUBRICANT. PLACE IN COUNTERSUNK HOLE. RECESS 1/16" BELOW PLATE SURFACE.
- 8 3/4" DIA. x 4" GALVANIZED HEX HEAD BEND. BEND 45°.
- 9 3/4" DIA. x 2 1/4" GALVANIZED THREADED COUPLING.
- 10 SIDEWALK COVER PLATE 3/8" x 2'-0" WIDE x LIMITS SHOWN AT LOCATIONS #1-#3. 3/8" x 1'-0" WIDE x LIMITS SHOWN AT LOCATION #4. BEND DOWN FACE OF SIDEWALK WITH HOLES FOR NO. 7. GALVANIZE PLATE AFTER SLIP-RESISTANT SURFACE IS APPLIED.
- 11 1" x 5" SLOTTED COUNTERSUNK HOLE FOR NO. 7. PLACE SLOT PARALLEL TO DIRECTION OF MOVEMENT.
- ⊗ BLOCK OUT CONCRETE 2" EACH SIDE OF JOINT OPENING.
- ▣ JOINT OPENING DIM. ALONG SKEW PLUS 1/2".

NOTES

ONE FIELD SPLICE PERMITTED IN STEEL EXTRUSIONS, UNLESS MORE ARE REQUIRED FOR STAGED CONSTRUCTION, HANDLING OR GALVANIZING REQUIREMENTS. IF USED, ANCHOR PLATES SHALL BE PROVIDED 3" FROM EACH SIDE OF THE FIELD SPLICE. DETAILS SHALL BE SUBMITTED FOR APPROVAL. NO SPLICING IS PERMITTED IN NEOPRENE STRIP SEAL.

AFTER FABRICATION, BUT BEFORE SHIPMENT, STRAIGHTEN STEEL EXTRUSIONS SUCH THAT THEY SHALL BE FREE FROM WARP, TWIST AND SWEEP.


FABRICATOR SHALL PROVIDE MEANS FOR KEEPING GALVANIZED EXTRUSIONS CLEAN AND SMOOTH DURING SHIPMENT AND PRIOR TO APPLYING LUBRICANT ADHESIVE FOR NEOPRENE GLAND INSTALLATION.

SANDBLAST PLATES, SUPPORTS AND EXTRUSIONS AFTER FABRICATION IN ACCORDANCE WITH SSPC SP. #6 "COMMERCIAL BLAST CLEANING". AFTER BLAST CLEANING, THE PLATES, SUPPORTS AND EXTRUSIONS SHALL BE HOT DIPPED GALVANIZED. SLIP-RESISTANT SURFACE IS APPLIED TO SIDEWALK COVER PLATES BY THE MANUFACTURER AND THEN HOT DIPPED GALVANIZED TO THEIR RECOMMENDATIONS TO MAINTAIN THE INTEGRITY OF THIS SURFACE.

ANCHOR SYSTEM NO. 8 AND NO. 9 SHALL CONFORM TO ASTM A307 AND SHALL BE GALVANIZED IN ACCORDANCE WITH ASTM A153 CLASS C AND D.

ALL MATERIAL IN THE EXPANSION JOINT ASSEMBLY, INCLUDING ANCHOR STUDS AND HARDWARE, SHALL BE PAID AT THE UNIT PRICE BID FOR 502.3101 "EXPANSION DEVICE", LF.


SIDEWALK COVER PLATE TABLE			
LOCATION	LENGTH	CURB	PARAPET/ RAILING POST
#1, N.W. W.SIDE	7'-8 1/2"	NO	YES (NOTCH PLATE FOR 1'-4" PARAPET)
#2, N.E.	7'-9 1/2"	YES	YES (NOTCH PLATE FOR 1'-4" PARAPET)
#3, N.W. E.SIDE	12'-2" TO 12'-11"	YES (RADIAL SKEW)	NO
#4, N.W. CENTER	39'-4"	NO	YES (12" WIDE PLATE)



SECTION THRU JOINT


ROADWAY TRAFFIC AREA
BETWEEN GIRDERS

2
11




PLAN OF SIDEWALK COVER PLATE
WITH SLIP-RESISTANT SURFACE

PLACE SLIP-RESISTANT SURFACE ON TOP WALKING SURFACE IN SHADED AREA ONLY (NOT ON CURB FACE).




ALTERNATE STRIP
SEAL ANCHOR

SDWK. WITHOUT CURB
FACE - 2 LOCATIONS,
N.W. 88.50 LT. (#1)
N.W. 54.30 LT. (#4)




PARTIAL PLAN STRIP SEAL EXPANSION JOINT

APPROVED SLIP-RESISTANT APPLIED SURFACES FOR STEEL PLATES		
PRODUCT	MANUFACTURER	CONTACT AT
SLIPNOT GRADE 2, STEEL	W. S. MOLNAR COMPANY	1-800-SLIPNOT
ALGRIP, STEEL	ROSS TECHNOLOGY CORP.	1-800-345-8170




PLAN AT SIDEWALK




SECTION THRU JOINT

EXTERIOR GIRDER TO EDGE OF DECK AND
AT PARAPETS, MEDIANS AND SIDEWALKS

1
11



SECTION B-B



SECTION A-A

SDWK. WITHOUT
PARAPET & OVERHANG
2 LOCATIONS,
N.W. AT RDWY. CURB,
54.10 LT. (#3)
N.W. ALONG RAILING,
88.30 LT. (#4)

NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
STRUCTURE P-40-875			
DRAWN BY		HMD	PLANS CK'D. JPH
EXPANSION JOINT DETAILS		SHEET 11 OF 72	

KEY

- X' EPOXY INJECTION CRACK REPAIR (X LF)
- STONE REPLACEMENT AREA. SEE SHEETS 15 & 16
- CONCRETE SURFACE REPAIR AREA (X SF.)
- CONCRETE REPLACEMENT SEE SHEETS 13 & 14


NOTE

AREAS OF REPAIR TO BE DETERMINED IN THE FIELD BY ENGINEER.


BID ITEM 509.9025.S "EPOXY INJECTION CRACK REPAIR" TO BE USED ON CRACKS GREATER THAN 0.06 INCHES IN WIDTH.

TOP OF ABUTMENT BACK WALL TO BE REMOVED FOR EXPANSION JOINT REPLACEMENT. SEE SHEET 7-9 FOR REMOVAL LIMITS.


GRADE LINE TO BE RESTORED TO MATCH EXISTING GRADE LINE FOLLOWING ALL REPAIR WORK AT NORTH ABUTMENT AND WINGWALLS.




NORTHWEST WINGWALL ELEVATION
(LOOKING EAST)



NORTHEAST WINGWALL ELEVATION
(LOOKING WEST)




NORTH ABUTMENT ELEVATION EAST END FRONT FACE
(LOOKING NORTH)



NORTH ABUTMENT ELEVATION WEST END FRONT FACE
(LOOKING NORTH)

NO.	DATE	REVISION	BY
		STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION	
		STRUCTURE P-40-875	
		DRAWN BY GJR PLANS CK'D. JPH	
		NORTH ABUTMENT CONCRETE REPAIRS	SHEET 12 OF 72




NORTHWEST WINGWALL ELEVATION

(LOOKING EAST)

NORTH ABUTMENT ELEVATION - FRONT FACE


(WEST END LOOKING NORTH)



REPLACE 7"x6"x1/2" EXPANSION BRG. PL. ON FASCIA CHANNEL I-FILL 3 1/2"x1/2"x6" SMOOTH PL. & ROUND OFF CORNERS FOR SLIDING FIT. SEE BEARING #8 LOCATION ON SHT. 19


SIDEWALK CHANNEL BEARING DETAIL

LOOKING EAST



4' PARAPET SECTION

SEE SHEET 8 FOR LOCATION




3' PARAPET SECTION

SEE SHEETS 7 & 8 FOR LOCATION


KEY

- CONCRETE REMOVAL AREA
- EXISTING CONCRETE TO REMAIN



FASCIA SECTION A-A


3'-10" OVERALL LENGTH



ANCHOR BOLT
DETAIL

SIDEWALK FASCIA CHANNEL REPLACEMENT AT ABUTMENT

(N.W. SIDE)



CONCRETE PARAPET ELEVATION

EAST ELEVATION LOOKING WEST




LEGEND

- EXISTING BARS ARE LIKELY TO BE CORRODED AND/OR DAMAGED DURING CONCRETE REMOVAL. PRESERVE AND INCORPORATE AS MUCH REBAR AS PRACTICAL.





NOTE:

TEMPORARY SHORING IS REQUIRED FOR EXCAVATION. SEE LOCATION ON SHEET 1.

NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
STRUCTURE P-40-875			
DRAWN BY		HMD	PLANS CK'D. JPH
NORTH ABUTMENT WINGWALL AND DETAILS		SHEET 13 OF 72	



BILL OF BARS NORTH ABUTMENT						
BAR MARK	COAT	NO. REQ'D	LENGTH	BENT	BAR SERIES	LOCATION
W501	X	6	13'-11"			WINGWALL VERT. E.F.
W502	X	16	7'-3"			WINGWALL HORIZ. E.F. (UPPER)
W503	X	8	14'-5"	X		N. ABUT. REPAIR VERT. STIRRUP
W504	X	18	5'-4"			ABUT. HORIZ. E.F.
W505	X	4	5'-3"			WINGWALL HORIZ. E.F.
W506	X	6	12'-9"			WINGWALL VERT. E.F.
W507	X	57	3'-9"			DOWELS-HORIZ./VERT. WINGWALL/N.
W508	X	19	3'-6"	X		DOWELS-VERT. B.F. ABUT./WINGWALL
W509	X	16	3'-6"	X		DOWELS-N. ABUT. REPAIR W. SIDE
W510	X	40	1'-11"	X		DOWELS-N. ABUT./WINGWALL
W511	X	7	11'-5"	X		PARAPET VERT. DOWEL AT 4 FT PARAPET
W513	X	8	5'-3"			PARAPET HORIZ. E.F.
W514	X	8	5'-6"	X		WINGWALL TOP CAP STIRRUP
W515	X	22	3'-8"			WINGWALL HORIZ. E.F. (LOWER)
W516	X	8	6'-5"			WINGWALL VERT. E.F.





NORTH ABUTMENT ELEVATION- FRONT FACE
(WEST END LOOKING NORTH)

NOTE:

EXISTING BARS ARE LIKELY TO BE CORRODED
AND/OR DAMAGED DURING CONCRETE REMOVAL.
PRESERVE AND INCORPORATE AS MUCH REBAR
AS PRACTICAL.




#5 BAR ADHESIVE ANCHOR
MINIMUM EDGE DISTANCE = $3\frac{3}{4}$ "

KEY:


 = NEW CONCRETE
 = EXISTING CONCRETE
 E.F. = EACH FACE
 B.F. = BACK FACE
 F.F. = FRONT FACE

NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
STRUCTURE P-40-875			
DRAWN BY		GJR	PLANS CK'D. J
REPLACEMENT DETAILS NORTH ABUTMENT		SHEET 14 OF 7	

* SEE SHEET 16



ELEVATION AT GIRDER G3




ELEVATION AT GIRDER G2


CONSTRUCTION NOTES

1. THE ABUTMENT REPAIRS DETAILED IN THIS SHEET SHALL BE PERFORMED IN CONJUNCTION WITH THE PROPOSED BEARING REPLACEMENTS, DECK JOINT REPLACEMENT AND STEEL REPAIRS, DETAILED ELSEWHERE IN THE PLANS, AT OR IN THE VICINITY OF THE ABUTMENT REPAIRS.
2. THE ABUTMENT REPAIRS SHALL BE PERFORMED ONLY AFTER THE GIRDERS ARE SUPPORTED BY THE TEMPORARY SUPPORT SYSTEM FOR THE STRUCTURE'S DEAD LOAD (ESTIMATED SERVICE DEAD LOAD REACTION = 80 KIPS MAX.) AND ANY CONSTRUCTION LOADS PLANNED OR ANTICIPATED BY THE CONTRACTOR, REFER TO SPECIAL PROVISION FOR TEMPORARY SUPPORTS P-40-875.
3. TRAFFIC (LIVE LOAD) AND HEAVY CONSTRUCTION LOAD OR EQUIPMENT SHALL NOT BE PLACED WITHIN THE LIMITS SHOWN IN "TRAFFIC RESTRICTIONS" WHILE THE GIRDER IS SUPPORTED ON TEMPORARY SUPPORT AND UNTIL THE ABUTMENT REPAIR IS COMPLETED, THE GIRDER IS SEATED ON THE NEW REPLACEMENT BEARING AND THE TEMPORARY SUPPORT IS REMOVED.
4. THE ABUTMENT REPAIRS SHALL BE PERFORMED IN SEGMENTS, ONE SEGMENT AT A TIME, AND IN SEQUENCE AS INDICATED IN THIS SHEET. THE ABUTMENT REPAIRS INVOLVE REMOVAL OF EXISTING STONE AND THEN PLACEMENT OF REINFORCING STEEL, HIGH EARLY STRENGTH CONCRETE AND NON-SHRINK GROUT.
5. FOR STONE REMOVAL, REFER TO SPECIAL PROVISION FOR STONE REMOVAL.
6. REINFORCING STEEL AND CONCRETE SHALL BE PROVIDED ACCORDING TO STANDARD SPECS 505 AND 502.
7. NON-SHRINK GROUT SHALL BE PROVIDED ACCORDING TO SPECIAL PROVISION FOR NON-SHRINK GROUT.
8. WORK ON THE ADJACENT SEGMENT SHALL NOT BEGIN UNTIL THE CONCRETE AND GROUT ATTAIN A MINIMUM 2500 PSI STRENGTH OR 24 HOURS AFTER GROUT IS PLACED, WHICHEVER OCCURS LATER.
9. REPEAT ABOVE STEPS FOR ALL SEGMENTS AT A GIVEN GIRDER LOCATION.
10. INSTALL THE REPLACEMENT BEARING AND RESEAT THE GIRDER ON THE BRIDGE SEAT AFTER THE CONCRETE AND GROUT IN THE LAST POURED SEGMENT ATTAIN A MINIMUM 3500 PSI STRENGTH OR 4 DAYS AFTER LAST SEGMENT WAS POURED, WHICHEVER OCCURS LATER.
11. REMOVE TEMPORARY SUPPORT AFTER GIRDER IS SEATED ON THE NEW BEARING AND THE BRIDGE SEAT.
12. CLEAN AND SEAL TOP & FRONT SURFACES OF THE BRIDGE SEAT SILL AND THE EXPOSED TOP SURFACE OF THE NEWLY PLACED GROUT WITHIN THE REPAIR LIMITS. REFER TO SPECIAL PROVISION FOR ABUTMENT SEAT CLEANING AND SEALING.
13. RESTORE EXISTING STRUCTURE IN KIND IF ANY COMPONENTS WERE MODIFIED OR REMOVED TO INSTALL TEMPORARY SUPPORTS AND/OR PERFORM THE ABUTMENT REPAIRS. COST SHALL BE INCIDENTAL TO BID ITEMS RELATED TO STONE REPLACEMENT WORK.


NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
STRUCTURE P-40-875			
DRAWN BY		SH	PLANS CK'D. VP
NORTH ABUTMENT STONE REPLACEMENT DETAILS - 1		SHEET 15 OF 72	




TRAFFIC RESTRICTIONS
(ABUTMENT REPAIRS BELOW GIRDER G3)



TRAFFIC RESTRICTIONS
(ABUTMENT REPAIRS BELOW GIRDER G2)



SECTION A-A - REMOVAL




SECTION A-A - PROPOSED

(GIRDER AND TEMPORARY SUPPORT NOT SHOWN FOR CLARITY)

NOTES

1. ABUTMENT REPAIR IS PERMITTED ONLY AT ONE GIRDER LOCATION AT A TIME.
2. ABUTMENT REPAIRS TO BE PERFORMED ONLY AFTER SUPPORTING THE GIRDER ON TEMPORARY SUPPORT AND RELIEVING THE ABUTMENT BRIDGE SEAT OF ANY LOAD FROM THE SUPERSTRUCTURE.
3. TRAFFIC RESTRICTIONS
 - A. FOR ABUTMENT REPAIRS BELOW GIRDER G3, NO LIVE LOAD OR HEAVY EQUIPMENT SHALL BE PLACED IN AN AREA BOUNDED BY GIRDER G2, BENT#14, THE WEST CONCRETE BARRIER AND A MINIMUM 10 FEET BEHIND THE NORTH ABUTMENT.
 - B. FOR ABUTMENT REPAIRS BELOW GIRDER G2, NO LIVE LOAD OR HEAVY EQUIPMENT SHALL BE PLACED IN AN AREA BOUNDED BY GIRDER G3, BENT#14, THE EAST CONCRETE BARRIER AND A MINIMUM 10 FEET BEHIND THE NORTH ABUTMENT.
4. NOMINAL CONSTRUCTION LOADING UPTO 20 PSF MAY BE PERMITTED IN THIS AREA PROVIDED THE TEMPORARY SUPPORT OF THE GIRDER IS DESIGNED FOR SUCH ADDITIONAL LOADING.
5. THE DIMENSIONS FOR EXISTING ABUTMENT ARE TAKEN FROM THE 1926 ORIGINAL RECORD PLANS.
6. BARS FOR REPLACEMENT SECTION AT GIRDER G2 MAY REQUIRE FIELD BENDING, REPAIR COATING ON CUT AND/OR FIELD BENT BARS ACCORDING TO SECTION 505.2.4.3 OF THE STANDARD SPECIFICATIONS PRIOR TO PLACEMENT.




REBAR CAGE, SECTION

BILL OF BARS


NOTE: THE FIRST OR FIRST TWO DIGITS OF THE BAR MARK SIGNIFIES THE BAR SIZE.

BAR MARK	COAT	NO. REQ'D.	LENGTH	BENT	LOCATION
K501	X	82	6'-9"	X	STIRRUPS
K502	X	20	25'-0"		HORIZONTAL BARS


NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
STRUCTURE P-40-875			
DRAWN BY		SH	PLANS CK'D. VP
NORTH ABUTMENT STONE REPLACEMENT DETAILS - 2		SHEET 16 OF 72	




BENT 9
(PLAN VIEW)




BENT 10
(PLAN VIEW)



BENT 11
(PLAN VIEW)



BENT 12
(PLAN VIEW)



BENT 13
(PLAN VIEW)

KEY

X' EPOXY INJECTION CRACK REPAIR (X LF) AT BENTS 9-13

CONCRETE SURFACE REPAIR (X SF)

DEEP CONCRETE SURFACE REPAIR (X SF)
(SPV.0025.501)


NOTE

AREAS OF REPAIR TO BE DETERMINED BY
ENGINEER IN THE FIELD.


BID ITEM 509.9025.S "EPOXY INJECTION CRACK
REPAIR" TO BE USED ON CRACKS GREATER
THAN 0.06 INCHES IN WIDTH.

BID ITEM SPV.0025.501 "DEEP CONCRETE SURFACE
REPAIR" TO BE USED ON SPALLED AREAS WITH
DEPTH EQUAL OR GREATER THAN 6 INCHES.

NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
STRUCTURE P-40-875			
DRAWN BY		HMD	PLANS CK'D. JPH
PIERS 9-14 CONCRETE REPAIRS		SHEET 17 OF 72	



SECTION THRU FENCE
ON PARAPET



DETAIL 'A'

UNIT SHALL BE GALVANIZED AFTER FABRICATION
NOTE: IN LIEU OF USING THE POST SLEEVE, THE FENCE
POST MAY BE WELDED TO THE BASE PLATE.

NOTES


CONDUITS SHALL BE EMBEDDED 2" CLEAR.

CONDUIT FITTINGS, CONDUIT BENDS, ADAPTER FITTINGS
AND EXP. FTG. INCIDENTAL TO CONDUIT WORK, CONDUIT
PAID WITH BID ITEMS 652.0125 "CONDUIT RIGID METALLIC
2-INCH" AND 652.0135 CONDUIT RIGID METALLIC 3-INCH.


CONDUIT BENDS SHALL CONFORM TO THE NATIONAL
ELECTRIC CODE.

PROVIDE JUNCTION BOXES ACCORDING TO
SPECIFICATIONS. JUNCTION BOXES PAID WITH BID ITEM
SPV.0060.594 "JUNCTION BOX 14"X8"X6"."


SALVAGE POSTS AND FENCING PAID WITH BID ITEM
SPV.0090.530 "REHABILITATION OF CHAIN LINK FENCE".



FENCE PART ELEVATION
(INSIDE FACE AT N.W., LOOKING WEST)




BASE PLATE



ANCHOR PLATE

NOTE: ANCHOR PLATE NOT REQUIRED
WHEN ADHESIVE ANCHORS ARE USED.




PLAN OF RAILING POST BASE PLATE
AT NORTHWEST ISLAND CURB
(SEE SHEET 8 FOR LOCATION)

LEGEND


- CAULK AROUND PERIMETER OF BASE PLATE AND FILL
PORTION OF SLOTTED HOLE AROUND ANCHOR BOLT IN SHIM
WITH NON-STAINING GRAY NON-BITUMINOUS JOINT SEALER.
- ANCHOR BOLTS, NUTS AND WASHERS SHALL BE EITHER STAINLESS
STEEL OR ASTM 307. IF 307 IS USED, ANCHOR BOLTS, NUTS AND
WASHERS SHALL BE GALVANIZED.
- ALTERNATIVE ANCHORAGE: CONCRETE ADHESIVE ANCHORS
1/2-INCH. EMBED 7" IN CONCRETE. ADHESIVE ANCHORS SHALL
CONFORM TO SECTIONS 502.2.12 AND 502.3.14 OF THE
STANDARD SPECIFICATIONS.
- USE 3" DIA. RIGID METALLIC (RMC) CONDUIT AT FITTINGS.
PROVIDE RMC FOR ENTIRE LENGTH ON EACH SIDE OF JOINT
OPENINGS UNLESS NOTED OTHERWISE.

DEFLECTION/EXPANSION FITTING REQUIREMENTS:
- UP TO 1 3/4" CONDUIT CONTRACTION OR EXPANSION AND UP TO
30 DEGREES OF ANGULAR MISALIGNMENT IN ANY DIRECTION
WITH BONDING JUMPER.


SPONGE RUBBER WRAP TO BE AASHTO M153, TYPE I OR EQUIVALENT
1/4" MINIMUM THICKNESS. PROVIDE WRAP FOR THE ENTIRE LENGTH
OF THE FITTING OR AS SHOWN. SPONGE RUBBER WRAP INCIDENTAL
TO BID ITEM 652.0135 "CONDUIT RIGID METALLIC 3-INCH".



DEFLECTION/EXPANSION
FITTING DETAIL






LIGHT POLE ANCHORAGE DETAIL



FENCE PLAN

NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
STRUCTURE P-40-875			
DRAWN BY		SB	PLANS CK'D. JPH
FENCING AND CONDUIT DETAILS		SHEET 18 OF 72	



B0113_2024_19_NORTH ABUTMENT BEARING AND GIRDER DETAILS.dwg

REVISED: 08-10-2023 BY GJR


8

LEGEND


- * SEE BEARING DATA TABLE
- ▲ REMOVAL OF EXISTING GROUT PAD REQUIRED TO INSTALL BEARINGS TO ACCOMMODATE BEARING ASSEMBLIES. INSTALL NEW GROUT PAD BELOW BEARING ASSEMBLIES.
- ⊗ SEE PLAN OF LOCATION 3 FLANGE PLATE AND ELASTOMERIC BEARING ON SHEET 19

BEARING DATA TABLE




LOCATION	BOTTOM FLANGE WIDTH (inches)	TOTAL BEARING HEIGHT H (inches)	TOTAL ELASTOMER THICKNESS (INCHES)	NUMBER OF PLATES REQUIRED	LONGITUDINAL LENGTH OF BEARING L (MIN.) (INCHES)	HOTIZONTAL WIDTH OF BEARING W (INCHES)	LONGITUDINAL LENGTH OF TOP PLATE LP (MIN.) (INCHES)	HORIZONTAL WIDTH TOP OF PLATE WP (INCHES)	THICKNESS OF TOP PLATE			END OF GIRDER TO C/L BRG. D (INCHES)	LONGITUDINAL LENGTH OF MASONRY PLATE ML (INCHES)	HORIZONTAL WIDTH OF MASONRY PLATE MW (INCHES)	MASONRY PLATE THICKNESS (INCHES)	STEEL SHIM PLATE THICKNESS SP (INCHES)	ANCHOR BOLT LENGTH (INCHES)
									TPS (INCHES)	TP (INCHES)	TPN (INCHES)						
1	12 5/16	6 1/4	17/8	3	17	14	19	16	3/4	1 1/32	1 5/16	10	19	26	2	2 3/8	21
2	12 3/8	8 3/4	17/8	3	17	14	19	16	3/4	1 1/32	1 5/16	10	19	26	2	4	21
3	12 3/8	9 1/4	17/8	3	18	14	20	16	3/4	1 1/32	1 5/16	10	21 1/8	26	2	6	24
4	12 5/16	3 1/4	17/8	3	17	14	19	16	3/4	1 3/32	1 7/16	10	19	26	1/4	0	24
5	12 5/16	3 1/4	17/8	3	17	14	19	16	3/4	1 3/32	1 7/16	10	19	26	1/4	0	24
6	12 5/16	3 1/4	17/8	3	17	14	19	16	3/4	1 3/32	1 7/16	10	19	26	1/4	0	24
7	12 5/16	3 1/4	17/8	3	17	14	19	16	3/4	1 3/32	1 7/16	10	19	26	1/4	0	24



SECTION I-19 (ALL BAYS)



TAPERED PLATE DIAGRAM



BEARING NOTES


- BEARINGS SHALL NOT BE PLACED AT A TEMPERATURE GREATER THAN 85° F.
- ALL MATERIAL IN BEARINGS, INCLUDING SHIM PLATES, BUT EXCLUDING ANCHOR BOLTS, NUTS AND WASHERS SHALL CONFORM TO ASTM A709 GRADE 50W OR A588. (PAINTED)
- ALL MATERIAL IN BEARINGS, INCLUDING SHIM PLATES, EPOXY ANCHORS, ANCHOR BOLTS, STEEL PLATES, AND BEARING PADS, SHALL BE PAID FOR AT THE UNIT PRICE BID FOR "BEARING PADS ELASTOMERIC LAMINATED", EACH.
- ALL STRUCTURAL STEEL PLATES SHALL BE FLAT ROLLED WITH ALL SURFACES SMOOTH AND FREE FROM WARP AND ALL EDGES SMOOTH, STRAIGHT AND VERTICAL.
- ALL PLATE CUTS SHALL BE MACHINE OR MACHINE FLAME CUTS.
- ANCHOR BOLTS FOR BEARINGS SHALL BE THREADED 3", PROVIDE ONE STANDARD WROUGHT WASHER AND ONE HEX NUT PER BOLT. BOLT LENGTH TO BE AS SPECIFIED FOR 1/2" DIA. BOLTS. PROJECT ANCHOR BOLTS, MASONRY PLATE AND SHIM PLATE THICKNESS + 2 1/4", ABOVE TOP OF CONCRETE.
- PROVIDE 1/8" THICK BEARING PAD SAME SIZE AS MASONRY PLATE FOR BEARINGS.
- CHAMFER ANCHOR BOLTS PRIOR TO THREADING.
- DRILLED HOLES FOR ANCHOR BOLTS IN MASONRY & SHIM PLATES SHALL HAVE A DIAMETER 3/8" LARGER THAN ANCHOR BOLT.
- ALL ANCHOR BOLTS, NUTS AND WASHERS SHALL CONFORM TO ASTM A709 GRADE 36, OR MATERIAL OF EQUIVALENT YIELD STRENGTH AND ELONGATION.
- ANCHOR BOLTS, NUTS AND WASHERS SHALL BE GALVANIZED AS REQUIRED BY ASTM DESIGNATION A153, CLASS C.
- NEW ELASTOMERIC BEARINGS TO BE PLACED AT ALL GIRDER LOCATIONS AT NORTH ABUTMENT. SEE REPLACEMENT PLAN ON SHEET 19.
- BURN EXISTING ANCHOR BOLTS OFF FLUSH WITH BEAM SEAT.
- REMOVE RIVETS HOLDING EXISTING BEARING ASSEMBLY TO BOTTOM FLANGE OF GIRDER, GRIND AFFECTED AREAS SMOOTH.

WELDING PROCEDURES SHALL BE ESTABLISHED BY THE CONTRACTOR TO RESTRICT THE MAXIMUM TEMPERATURE REACHED BY SURFACES IN CONTACT WITH ELASTOMER TO 200°F (93°C). TEMPERATURES SHALL BE CONTROLLED BY TEMPERATURE INDICATING WAX PENCILS OR OTHER SUITABLE MEANS APPROVED BY THE ENGINEER.


SEE PLANS ON SHEET 19 FOR ADDITIONAL MASONRY PLATE AND FLANGE PLATE DETAILS.

NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
STRUCTURE P-40-875			
DRAWN BY		GJR	PLANS CK'D. JPH/JES
BRG. REPLACEMENT DETAILS NORTH ABUTMENT		SHEET 20 OF 72	


8




SOUTH ELEVATION
(LOOKING NORTH)



EAST ELEVATION
(LOOKING WEST)



PLAN VIEW
(ELEVATION 35.16 TO 79.66)




SECTION A-A

NOTE:
SEE SHEETS 22 - 27 FOR ADDITIONAL STAIRWAY DETAILS.
FOR PROTECTIVE SCREENING AND RAILING DETAILS, SEE SHEET 27.
FOR BENT 12 FRAMING, SEE SHEET 33.
ALL MATERIAL IN STAIRWAY INCLUDING SHIM PLATES, STEEL PLATES, STEEL MEMBERS, ANCHOR BOLTS, & STEEL BOLTS SHALL BE PAID FOR AT THE UNIT PRICE FOR "STAIRWAY STRUCTURAL STEEL", LB.

BILL OF BARS - STAIRWAY LANDINGS


BAR MARK	COAT	NO. REQ'D	LENGTH	BENT	BAR SERIES	LOCATION
L401	X	17	8'- 2"			TRANS. BARS AT LANDING 1
L402	X	8	3'- 5"			LONGIT. BARS AT LANDING 1
L403	X	16	7'- 6"			TRANS. BARS AT LANDING 2
L404	X	8	3'- 5"			LONGIT. BARS AT LANDING 2
L405	X	15	7'- 0"			TRANS. BARS AT LANDING 3
L406	X	8	3'- 5"			LONGIT. BARS AT LANDING 3
L407	X	18	8'- 6"			TRANS. BARS AT LANDING 4
L408	X	8	3'- 3"			LONGIT. BARS AT LANDING 4
L409	X	7	3'- 0"			TRANS. BARS AT LANDING 5
L410	X	10	4'- 3"			LONGIT. BARS AT LANDING 5
L411	X	7	3'- 0"			TRANS. BARS AT LANDING 6
L412	X	10	4'- 5"			LONGIT. BARS AT LANDING 6
L413	X	7	3'- 0"			TRANS. BARS AT LANDING 7
L414	X	10	4'- 3"			LONGIT. BARS AT LANDING 7



REMOVE AND REPLACE CONCRETE.
PLACE EPOXY COATED #4 BAR
@ 6" C/C BOTH DIRECTIONS.
(SEE BILL OF BARS THIS SHEET).

TYPICAL DETAIL AT LANDINGS

NO.	DATE	REVISION	BY
		STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION	
		STRUCTURE P-40-875	
		DRAWN BY HMD PLANS CK'D. JPH	
		STAIR TOWER REPLACEMENT	SHEET 21 OF 72



REVISED: 08-29-2023 BY GJR

NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
STRUCTURE P-40-875			
DRAWN BY		HMD	PLANS CK'D. JPH
40S1 AND 41S1 STAIRWAY DETAILS		SHEET 22 OF 72	

SECTION B-B

STAIRWAY - 43S1
(3 LOCATIONS)

SECTION A-A

STAIRWAY - 42S1


STAIRWAY - 44S1

DETAIL A

CHANNEL 42C2
LOCATED AT 42S1


NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
STRUCTURE P-40-875			
DRAWN BY		HMD	PLANS CK'D. JPH
42S1, 43S1 AND 44S1 STAIRWAY DETAILS			SHEET 23 OF 72

NOTE:
SHADED MEMBERS
TO REMAIN




114B1

NOTE:
SHADED MEMBERS
TO REMAIN



114B2

(LOCATED AT C/L FLOOR BEAM 57B6R)



114P1, 114P2, 114X1, 114X2

114X5

114X6

114X7

NOTE: NO REMAINING

SEC DD

SEC CC

114P3

114X3

114H1A

114H1R



114H1R

114H1R



114H1A

114P3, 114X3, 114H1R, 114H1A


NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
STRUCTURE P-40-875			
DRAWN BY		HMD	PLANS CK'D. JPH
114 MEMBER DETAILS		SHEET 24 OF 72	



NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
STRUCTURE P-40-875			
DRAWN BY		HMD	PLANS CK'D. JPH
115 MEMBER DETAILS		SHEET 25 OF 72	



PLAN VIEW FASCIA STRINGER 60F2



115P5, 115X2, 115B1


LEGEND

- * MEMBER 60F2 TO BE REPLACED AS FOLLOWS:
REMOVE 3/4" RIVETS HOLDING 60F2 MEMBER TO THE 2-BENT FLAT BARS 1 1/2" x 3/8" x 1'-4 1/4" @ 3'-0" C/C (TO REMAIN IN WALK) EMBEDDED IN THE EXISTING 7" REINFORCED CONCRETE WALK. MOUNT THE NEW MEMBER 60F2 TO THE BENT FLAT BARS USING SELF TAPPING 3/4" STRUCTURAL BOLTS.
 - ☆ ALTERNATIVE ANCHORAGE: CONCRETE ADHESIVE ANCHORS 1/2-INCH, EMBED 7" IN CONCRETE. ADHESIVE ANCHORS SHALL CONFORM TO SECTIONS 502.2J2 AND 502.3J4 OF THE STANDARD SPECIFICATIONS.
- USE A TOTAL OF 4 ANCHORS. LOCATION TO BE DETERMINED BY ENGINEER.

NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
STRUCTURE P-40-875			
DRAWN BY		HMD	PLANS CK'D. JPH
60F2 AND 115 MEMBER DETAILS		SHEET 26 OF 72	


NOTES

- POSTS ARE TO BE SET VERTICAL.
- ALL FENCE COMPONENTS SHALL BE GALVANIZED STEEL WITH A COLORED POLYMER COATING ON THE OUTSIDE.
- FABRIC SHALL CONFORM TO ASTM F668, CLASS 2B. STEEL RAILS, POSTS AND POST SLEEVES SHALL CONFORM TO ASTM F1083, STANDARD WEIGHT PIPE (SCHEDULE 40). FITTINGS SHALL CONFORM TO ASTM F626. SEE THE "BRIDGE SPECIAL PROVISIONS" FOR ADDITIONAL DETAILS.
- THE COLOR OF THE POLYMER-COATING FOR THIS STRUCTURE SHALL BE BLACK IN ACCORDANCE WITH ASTM F934.
- THE BID ITEM SHALL BE "STAIRWAY RAILING AND PROTECTIVE SCREENING SPV.0090.505, LF".
- COMPLETE ANY REQUIRED WELDING OF COMPONENTS BEFORE GALVANIZING.
- POSTS BASE PLATES SHALL BE FLAT WITH ALL SURFACES SMOOTH AND FREE FROM WARP AND ALL EDGES SMOOTH, STRAIGHT AND VERTICAL. ALL PLATE CUTS SHALL BE MACHINE OR MACHINE FLAME CUT.
- BASE PLATES, ANCHOR PLATES AND SHIMS SHALL BE ASTM A709, GRADE 36.
- ALL POST SPACINGS ARE MEASURED ALONG SUPPORTING MEMBER ALONG C/L OF THE POST.
- ANCHOR BOLTS, NUTS AND WASHERS SHALL BE EITHER STAINLESS STEEL OR ASTM 307. IF 307 IS USED, ANCHOR BOLTS, NUTS AND WASHERS SHALL BE GALVANIZED.
- ✱ ALTERNATE TO DOUBLE CLAMP: USE LINE RAIL CLAMP (BOULEVARD) OR 180 BRACE BAND, WHICH MAY BE USED WHEN THE POSTS ARE WELDED TO THE BASE PLATE




FENCE FABRIC


FENCE FABRIC WOVEN OF 9-GAGE WIRE IN 2" DIAMOND PATTERN MESH WITH BOTH THE TOP AND BOTTOM SELVAGES KNUCKLED.



SECTION THRU FENCE




FENCE PART ELEVATION




DETAIL 'A'

UNIT SHALL BE GALVANIZED AFTER FABRICATION




POST SHIM DETAILS


PROVIDE 4 SHIMS PER POST. USE WHERE REQUIRED FOR ALIGNMENT




HANDRAIL SPLICE DETAIL



HANDRAIL DETAILS




BASE PLATE



SECTION A-A


NOTE: PLACE ALL BOLT HEADS ON SIDE OF FENCE ADJACENT TO PEDESTRIANS

NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
STRUCTURE P-40-875			
DRAWN BY		HMD	PLANS CK'D. JPH
STAIRWAY FENCING AND RAILING DETAILS		SHEET 27 OF 72	



BENT 9 - NORTH ELEVATION (F.S.)

(LOOKING SOUTH)



BENT 9 - SOUTH ELEVATION (N.S.)

(LOOKING NORTH)

KEY:

XXXX 1926 SHOP DRAWING PART NUMBER - REMOVE AND REPLACE PART

XXXX 1926 SHOP DRAWING PART NUMBER

- ① REPLACE 3' MEMBER 17S3. SEE SHT. 38, DETAIL 3 (4 LOCATIONS).
- ② ADD FLANGE PLATES TO MEMBER 15T2L. ☒ 2-(INNER & OUTER) 5"x1/2"x33'-0" (OVERALL LENGTH EACH LOCATION) AT S.W. SEE SHTS. 36 AND 61.
- ③ ADD FLANGE PLATE TO MEMBER 15T2L. 2-(INNER) 5"x1/2"x6'-0" AT N.W. ADD WEB PLATE TO MEMBER 15T2L. 1-5/4"x1/2"x6'-0" W. FACE, SEE SHTS. 36 AND 61.
- ④ REPLACE BATTEN PLATE (16P1) AT MEMBER 16B5(1 EACH), 16B7(2 EACH), 16B8(2 EACH). 8/2"x7/6"x12", SEE SHT. 39.
- ⑤ ADD FLANGE PLATES TO MEMBER 17S10R. 2-(TOP & BOTTOM) 4"x1/2"x1'-6" AT W. SEE SHT. 38, DETAILS 1 AND 2.
- ⑥ ADD FLANGE PLATE TO MEMBER 15T2R. 2-(INNER) 5"x1/2"x6'-0" N.E. AND N.W. ADD WEB PLATE TO MEMBER 15T2R. 1-5/4"x1/2"x6'-0" E. FACE. SEE SHTS. 36 AND 62.

- ⑦ ADD FLANGE PLATE TO MEMBER 15T2R. 1-(OUTER) 1'-0"x1/2"x6'-0" AT N. SEE SHTS. 36 AND 62.
- ⑧ ADD FLANGE PLATES TO MEMBER 15T2R. ☒ 2-(INNER & OUTER) 5"x1/2"x50'-10" (OVERALL LENGTH EACH LOCATION) AT S.E. SEE SHTS. 36 AND 62, DETAILS 4 AND 5.
- ⑨ ADD FLANGE PLATE TO MEMBER 15T2R. 1-(INNER) 5"x1/2"x15'-0" AT S.W. SEE SHTS. 36 AND 62.
- ⑩ REPLACE ANCHOR NUTS 1 1/2" AT AB4, AB4A, (N./S. NUT LOCATION). SEE SHTS. 35 AND 36.
- ⑪ -XX REPLACE GUSSET PLATES (15P3, 15P4, 15P5, 15P6, 15P7, 15P8, AND 15P9), (INNER AND/OR OUTER) TO MEMBERS 15T2R/L AND 16&17 MEMBERS (F.S./N.S.) SEE SHT. 36.
- ⑫ REPLACE GUSSET PLATE (16P2) INNER AND OUTER TO MEMBER 16B5/B6. SEE SHT. 39.

NOTES:

SEE STRUCTURE B-40-910 PLANS FOR MODIFICATIONS TO ORIGINAL MEMBERS AND CONNECTIONS.

USE EXISTING BOLT SPACING AT ALL GUSSET PLATE REPLACEMENT LOCATIONS.


ALL PLATES 1/2" THICK (EXCEPT AS NOTED).

MATCH EXISTING BOLT SPACING WHERE APPLICABLE.

⊕: ADDITIONAL FILL PLATES REQUIRED AT FLANGE/WEB ADD-ON PLATE LOCATIONS AND CONNECTIONS.


☒: FABRICATE AND INSTALL IN MORE THAN ONE PEICE TO FACILITATE INSTALLATION.

NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
STRUCTURE P-40-875			
DRAWN BY JC		PLANS CK'D. JPH	
NORTH AND SOUTH ELEVATIONS BENT 9		SHEET 28 OF 72	



BENT 9 - WEST ELEVATION

(LOOKING EAST)



BENT 9 - EAST ELEVATION

(LOOKING WEST)

KEY:

- ① REPLACE INNER STIFFENER (22S1) TO MEMBER 22G1R/L 1-Z BAR 3 5/16"X5 1/16"X3 7/8"X7'-11 1/2". SEE SHT. 46.
- ② REPLACE LOWER 1'-2 1/2" OF EAST SIDE STIFFENERS TO MEMBER 22G1L (INNER) (22S2), 2 TOTAL. SEE SHT. 46.
- ③ ADD BOT. FLANGE PLATE (15P10) TO MEMBER 15T2R/L 2-1'-0 1/2"X1 1/2"X6'-0". SEE DETAIL 1 SHT. 36 AND 59.
- ④ REPLACE FULL HEIGHT STIFFENERS (20S1) (INNER) 2-L3 1/2"X5"X1 1/16"X7'-11 1/2" TO MEMBERS 20G1R/L SEE SHT. 47.
- ⑤ REPLACE LOWER 1'-2 1/2" OF STIFFENERS (INNER) 2-L3 1/2"X5"X1 1/16"X1'-2 1/2" TO MEMBERS 20G1R/L, SEE SHT. 47.
- ⑥ ADD WEB PLATES (2) TO 15T2L (INNER AND OUTER) (15P11) 2-8 1/2"X1 1/2"X2'-0" TO EAST SIDE TOWER 15T2L. SEE SHT. 36 AND 59.
- ⑦ REPLACE (1) - C6"Ø10.5"X4'-6 1/2" AT TOWER 15T2L SEE SHT. 36.
- ⑧ ADD PLATE (15P12) TO STIFFENER TO MEMBER 15T2L 1-5"X1 1/2"X4'-5 3/4". SEE SHT. 36 AND 59.
- ⑨ ADD FLANGE PLATES (15F14) TO MEMBERS 15T2R/L 2-6"X1 1/2"X3'-0". SEE SHT. 36 AND 59.
- ⑩ ADD PLATE (15P13) TO SOUTH SIDE OF L3X3 OF MEMBER 15T2R 1-3"X1 1/2"X1'-6". SEE SHT. 36 AND 59.
- ⑪ REPLACE (1) C8"Ø13.75"X7'-10" AND L3 1/2"X3 1/2"X3 7/8"X5'-10 1/2". SEE SHT. 36.

NOTES:

SEE STRUCTURE B-40-910 PLANS FOR MODIFICATIONS TO ORIGINAL MEMBERS AND CONNECTIONS.


USE EXISTING BOLT SPACING AT ALL GUSSET PLATE REPLACEMENT LOCATIONS.

ALL PLATES 1/2" THICK (EXCEPT AS NOTED).

MATCH EXISTING BOLT SPACING WHERE APPLICABLE.

ADDITIONAL FILL PLATES REQUIRED AT FLANGE/WEB ADD-ON PLATE LOCATIONS AND CONNECTIONS.

NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
STRUCTURE P-40-875			
DRAWN BY JC		PLANS CK'D. JPH	
WEST AND EAST ELEVATIONS BENT 9		SHEET 29 OF 72	




BENT 10 - NORTH ELEVATION (F.S.)
(LOOKING SOUTH)

KEY:

XXXX 1926 SHOP DRAWING PART NUMBER - REMOVE AND REPLACE PART

XXXX 1926 SHOP DRAWING PART NUMBER

- ① ADD (2) FLANGE PLATES TO MEMBER 15T1R (INSIDE, OUTSIDE) S.E. 5"x1/2"x1'-8". SEE SHT. 37 AND 60.
- ② REPLACE ANCHOR NUTS 1 1/2" AT AB4, AB4A, (N./S. NUT LOCATION), SEE SHTS. 35 AND 37 FOR DETAILS.
- ③ ADD N. SIDE BASE PLATE, (14P3), SEE SHT. 35 FOR DETAILS.
- ④ REPLACE GUSSET PLATE (14P4) (INNER) TO MEMBER 14T1A. SEE SHT. 35 FOR DETAILS.
- ⑤ REPLACE GUSSET PLATE (15P5) (OUTER) TO MEMBER 15T1R, 17S3, 16B5/B6. SEE SHT. 37 FOR DETAILS.



BENT 10 - SOUTH ELEVATION (N.S.)
(LOOKING NORTH)

NOTES:

SEE STRUCTURE B-40-910 PLANS FOR MODIFICATIONS TO ORIGINAL MEMBERS AND CONNECTIONS.

USE EXISTING BOLT SPACING AT ALL GUSSET PLATE REPLACEMENT LOCATIONS.

ALL PLATES 1/2" THICK (EXCEPT AS NOTED).

MATCH EXISTING BOLT SPACING WHERE APPLICABLE.

ADDITIONAL FILL PLATES REQUIRED AT FLANGE/WEB ADD-ON PLATE LOCATIONS AND CONNECTIONS.

NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
STRUCTURE P-40-875			
DRAWN BY		JC	PLANS CK'D. JPH
NORTH AND SOUTH ELEVATIONS BENT 10		SHEET 30 OF 72	



NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
STRUCTURE P-40-875			
		DRAWN BY	JC PLANS CK'D. JP
NORTH AND SOUTH ELEVATIONS		SHEET 31 OF 72	
BENT 11			




- ① REPLACE (OUTER) W./E. SIDE STIFFENERS (65S1, FULL HEIGHT), (127D1, LOWER 1'-2 1/2") TO MEMBERS 65G1 AND 127D1. SEE SHTS. 55 AND 56.
- ② ADD FLANGE PLATE TO MEMBER 47T1R (47P12), N.W. FLANGE, 1-6"x1/2"x2'-0". SEE SHT. 40.
- ③ REPLACE INNER (2) AND OUTER (2) EXPANSION JOINT BOLTS (94E4). BOLTS MOUNT TO MEMBERS 47T1 LA, 123B-1, AND 19G1 L. SEE SHT. 54.
- ④ REPLACE LOWER 1'-2 1/2" OF STIFFENERS TO MEMBERS 19G1 R/L (OUTER) (19S1), SEE SHT. 54.
- ⑤ REPLACE INNER STIFFENERS TO MEMBERS 19G1 R/L (19S2). SEE SHT. 54.
- ⑥ REPLACE LOWER STIFFENERS (OUTER) AT MEMBER 123B1 ATTACHED TO MEMBER 47T1R (WEST SIDE).
(1) L3 1/2"x6"x3'-4 3/4"x3 5/8"
(1) L3 1/2"x6"x2'-4"x3 5/8"
SEE DETAIL SHT. 54.

SEE STRUCTURE B-40-910 PLANS FOR
MODIFICATIONS TO ORIGINAL MEMBERS AND
CONNECTIONS.

ADDITIONAL FILL PLATES REQUIRED AT
FLANGE/WEB ADD-ON PLATE LOCATIONS AND
CONNECTIONS.

NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
STRUCTURE P-40-875			
DRAWN BY		JC	PLANS CK'D. JF
WEST AND EAST ELEVATIONS BENT 11		SHEET 32 OF 7	



KEY:

XXXX 1926 SHOP DRAWING PART NUMBER
REMOVE AND REPLACE PART

XXXX 1926 SHOP DRAWING PART NUMBER

- ① ADD FLANGE PLATE TO MEMBER 50T1
1-(INNER) 5"x1/2"x9'-0" AT S.W. SEE SHTS 43 AND 68.
- ② ADD FLANGE PLATE TO MEMBER 49T1
1-(OUTER) 1'-0/2"x1/2"x6'-0" AT S. SEE SHTS 42 AND 66.
- ③ ADD FLANGE PLATES TO MEMBER 50T1
2-(OUTER) 1'-0/2"x1/2"x6'-0" AT S./N. SEE SHTS 43 AND 68.
- ④ ADD FLANGE PLATES TO MEMBER 51T1
2-(INNER) 5"x1/2"x10'-0" AT N.E./S.E. SEE SHTS 44 AND 70.
- ⑤ ADD FLANGE PLATES TO MEMBER 51T1
1-(INNER) 5"x1/2"x16'-0" AT N.E.
1-(OUTER) 5"x1/2"x16'-0" AT N.E.
SEE SHTS 44 AND 70.
- ⑥ ADD FLANGE PLATES TO MEMBER 51T1
2-(INNER) 5"x1/2"x3'-0" AT S.E.
SEE SHTS 44 AND 70.

- ⑦ ADD FLANGE PLATES TO MEMBER 52T1
2-(INNER) 5"x1/2"x16'-0" AT S.E. S.W.
1-(OUTER) 1'-0/2"x1/2"x16'-0" AT SOUTH FACE.
SEE SHTS 45 AND 72.
- ⑧ ADD FLANGE PLATES TO MEMBER 52T1
2-(INNER) 5"x1/2"x6'-0" AT N.E., N.W.
1-(OUTER) 1'-0/2"x1/2"x6'-0" AT N. SEE SHTS 45 AND 72.
- ⑨ ADD FLANGE PLATES TO MEMBER 52T1
2-(INNER) 5"x1/2"x12'-0" AT N.W., S.W.
2-(OUTER) 5"x1/2"x12'-0" AT N.W., S.W. SEE SHTS 45 AND 72.
- ⑩ ADD FLANGE PLATES TO MEMBER 52T1
1-(INNER) 5"x1/2"x16'-0" (S.W.),
1-(OUTER) 5"x1/2"x16'-0" (S.W.),
2-(INNER) 5"x1/2"x8'-0" (N.W. & N.E.). SEE SHTS 45 AND 71.
- ⑪ ADD FLANGE PLATE TO MEMBER 49T1
1-(INNER) 5"x1/2"x16'-0" AT N.E.
1-(OUTER) 1'-0/2"x1/2"x16'-0" AT N. FACE, SEE SHTS 42 AND 66.
- ⑫ ADD FLANGE PLATES TO MEMBER 51T1
1-(INNER) 5"x1/2"x12'-6" (S.W.)
1-(OUTER) 5"x1/2"x12'-6" (S.W.)
1-(INNER) 5"x1/2"x21'-6" (S.W.)
1-(OUTER) 5"x1/2"x21'-6" (S.W.). SEE SHTS 44 AND 69.

- ⑬ ADD N./S. BASE SIDE PLATES (50P10, 51P7)
SEE SHTS 43 AND 44.
- ⑭ REPLACE ANCHOR NUTS 1 1/2" AT AB4, AB4A,
(N/S NUT LOCATION) SEE SHTS 42-45.
- ⑮ ADD FLANGE PLATES TO MEMBER 50T1
2-(OUTER) 1'-0/2"x1/2"x12'-6" AT S./N.
4-(INNER) 5"x1/2"x12'-6" AT N.E., N.W., S.E. & S.W.
2-(OUTER) 1'-0/2"x1/2"x20'-0" AT S./N.
4-(INNER) 5"x1/2"x20'-0" AT N.E., N.W., S.E. & S.W.
SEE SHTS 43 AND 67.
- ⑯ ADD WEB PLATES TO MEMBER 50T1
1-5"x1/2"x2'-6" AT WEST (INSIDE FACE)
1-5"x1/2"x3'-6" AT WEST (INSIDE FACE)
1-5"x1/2"x6'-0" AT WEST (INSIDE FACE)
3 LOCATIONS, SEE SHTS 43 AND 67.
- ⑰ ADD FLANGE PLATE TO MEMBER 49T1
1-(INNER) 5"x1/2"x6'-0" AT (NW) SEE SHTS 42 AND 66.
- ⑱ -XX REPLACE GUSSET PLATES (46P3, 71P1, 71P2, 72P1, 72P2),
(INNER AND/OR OUTER) TO MEMBERS 46B7/B8, 71B1/B2/B7/
B7A/B9 AND 72B4/B6. SEE SHTS 49-51.


- ⑲ -XX REPLACE AND/OR REINSTALL EXISTING GUSSET PLATES
(49P1, 49P2, 49P3, 49P4, 49P5, 49P6, 49P7, 49P8, 49P9, 49P10, 49P11, 49P12),
(INNER AND/OR OUTER) TO MEMBERS 49T1 (N.S./F.S.).
SEE SHT 42.
- ⑳ -XX REPLACE AND/OR REINSTALL EXISTING GUSSET PLATES
(50P2-P9), (INNER AND/OR OUTER) TO MEMBERS 50T1 (N.S./F.S.).
SEE SHT 43.
- ㉑ -XX REPLACE AND/OR REINSTALL EXISTING GUSSET PLATES
(51P1-P6) (INNER AND/OR OUTER) TO MEMBERS 51T1 (N.S./F.S.).
SEE SHT 44.
- ㉒ -XX REPLACE AND/OR REINSTALL EXISTING GUSSET PLATES
(52P1-14) (INNER AND/OR OUTER) TO MEMBERS 52T1 (N.S./F.S.).
SEE SHT 45.
- ㉓ ADD FLANGE PLATES TO MEMBER 51T1
6-(INNER) 5"x1/2"x3'-0" (N.E., N.W. & S.E.)
SEE SHTS 44 AND 69.

NOTES:

SEE STRUCTURE B-40-910 PLANS FOR MODIFICATIONS
TO ORIGINAL MEMBERS AND CONNECTIONS.USE EXISTING BOLT SPACING AT ALL GUSSET
PLATE REPLACEMENT LOCATIONS.REMOVE AND REINSTALL GUSSET PLATES AT NOTES
20-24 LOCATIONS.ALL GUSSET PLATES TO BE REINSTALLED ARE
PAINTED WITH GREY PRIMER AND USE NEW A325 BOLTS.⊙: ADDITIONAL FILL PLATES REQUIRED AT FLANGE/WEB
ADD-ON PLATE LOCATIONS AND CONNECTIONS.

UTILITIES NOT SHOWN FOR CLARITY.

NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
STRUCTURE P-40-875			
DRAWN BY JC		PLANS CK'D. JPH	
NORTH AND SOUTH ELEVATIONS BENT 12		SHEET 33 OF 72	



BENT 12 - WEST ELEVATION
(LOOKING EAST)

BENT 12 - EAST ELEVATION
(LOOKING WEST)

KEY:

- ① REPLACE AND/OR REINSTALL LONGITUDINAL CROSS BRACING (DIAGONALS, GUSSET PLATES AND HORIZONTALS) BETWEEN COLUMNS OF TOWERS 51T1 AND 50T1. REINSTALLED STEEL IS PAINTED WITH GREY PRIMER AND USE A325 BOLTS. SEE SHT. 43 AND 44. STEEL TO BE REPLACED IS SHOWN IN BOLD ABOVE.
- ② REPLACE INNER AND OUTER BRG. SEAT AT MEMBER 126D1 (2) L3 1/2"X5"X1/2"X1'-10 3/8". SEE SHT. 58.
- ③ ADD PLATE TO WEB TO MEMBER 101G1 6"X6"X1/2". SEE DETAILS SHT. 57.
- ④ REPLACE 1'-2 1/2" OF VERTICAL STIFFENER AND Z BAR (OUTER) (1) L3 1/2"X5 1/2"X1'-2 1/2"X3 3/8" STIFFENER TO MEMBER 101G1. SEE SHT. 57. (1) Z BAR 3 3/8"X5 1/8"X1'-2 1/2"X3 3/8" TO MEMBER 126D1. SEE SHT. 58.
- ⑤ REPLACE 3 OUTER EXPANSION BOLT ASSEMBLES, 3-94E12 CONNECTING MEMBERS 101G1, 126D1 AND 123B8. SEE SHT. 57.

NOTES:

SEE STRUCTURE B-40-910 PLANS FOR MODIFICATIONS TO ORIGINAL MEMBERS AND CONNECTIONS.

USE EXISTING BOLT SPACING AT ALL GUSSET PLATE REPLACEMENT LOCATIONS.


ALL PLATES 1/2" THICK (EXCEPT AS NOTED).

MATCH EXISTING BOLT SPACING WHERE APPLICABLE.

ADDITIONAL FILL PLATES REQUIRED AT FLANGE/WEB ADD-ON PLATE LOCATIONS AND CONNECTIONS.


UTILITIES AT BENT 12 ARE NOT SHOWN FOR CLARITY.

NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
STRUCTURE P-40-875			
DRAWN BY JC		PLANS CK'D. JPH	
WEST AND EAST ELEVATIONS BENT 12		SHEET 34 OF 72	






NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
STRUCTURE P-40-875			
DRAWN BY		GJR	PLANS CK'D. JPL
15T1 R/L MEMBER DETAILS		SHEET 37 OF 72	




17S1 & 17S3




17S3 DETAIL 3


ELEVATION VIEW
(LOOKING SOUTH)




SECTION 1
38



FLANGE PLATE DETAIL 1
NORTH ELEVATION OF NEW FLANGE PLATE
(LOOKING SOUTH)




17S3



17S3 DETAIL 3

PLAN VIEW
(LOOKING DOWN)




SECTION A-A

NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
STRUCTURE P-40-875			
DRAWN BY		JC	PLANS CK'D.
17 MEMBER DETAILS		SHEET 38 OF 7	


NOTE:


SEE NOTE ① SHEET 28
FOR LOCATION OF DETAILS.




REVISED: 12-08-2023 BY GJR


NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
STRUCTURE P-40-875			
DRAWN BY		HMD	PLANS CK'D. JPH
16 MEMBER DETAILS		SHEET 39 OF 72	








NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
STRUCTURE P-40-875			
DRAWN BY		JC	PLANS CK'D. JPH
49 MEMBER DETAILS		SHEET 42 OF 72	











NOTE ① SHEET 29
REPLACE INNER STIFFENER 22S1
TO MEMBERS 22G1R/L

NOTE ② SHEET 29
REPLACE EAST SIDE LOWER 1'-2 1/2"
OF MEMBER 22G1L STIFFENERS 22S2 (INNER) (2 TOTAL)
SEE DETAILS THIS SHEET.



NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
STRUCTURE P-40-875			
DRAWN BY		JC	PLANS CK'D. JPH
22G1 MEMBER DETAILS		SHEET 46 OF 72	







SHEET 29: NOTE ④
REPLACE 1-FULL HEIGHT
STIFFENER (INNER), 20S1,
1-L3/2"x5"x1/6"X7'-11 1/2"
TO MEMBERS 20G1R/L


20G1 R/L

SHEET 29: NOTE ⑤
REPLACE LOWER 1'-2 1/2" OF STIFFENERS 20S2
TO MEMBERS 20G1R/L (INNER)
2-L3/2"x5"x1/6"X7'-11 1/2"
SEE DETAILS FOR LOWER SECTION OF
STIFFENER REPLACEMENT ON SHEET 46

NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
STRUCTURE P-40-875			
DRAWN BY		JC	PLANS CK'D. JPH
20G1 MEMBER DETAILS		SHEET 47 OF 72	



NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
STRUCTURE P-40-875			
DRAWN BY		HMD	PLANS CK'D. JPH
SIDEWALK BRACKET MEMBER DETAILS		SHEET 48 OF 72	




46B1 & 46B2

46P2 (INNER AND OUTER)


DETAIL 17
SHT. 31

SEC. A-A
FOR 46S3 ONLY



46S1, 46S1A, 46S2 & 46S2A


46S3, 46S3A, 46S4 & 46S4A



46B3 & 46B4

46P1 (INNER AND OUTER)

DETAIL 16
SHT. 31




46B7 & 46B8


46P3 (INNER AND OUTER)

DETAIL 18
SHT. 33

NO.	DATE	REVISION	BY
		STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION	
		STRUCTURE P-40-875	
		DRAWN BY HMD	PLANS CK'D. JPH
		46 MEMBER DETAILS	SHEET 49 OF 72




71P1
DETAIL 18
SHT. 33




71P2
DETAIL 18
SHT. 33

71B1 & 71B2

71B7, 71B7A & 71B9







71S3 & 71S3A






71S1, 71S2 & 71S2A

NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
STRUCTURE P-40-875			
DRAWN BY		HMD	PLANS CK'D. JPH
71 MEMBER DETAILS		SHEET 50 OF 72	




NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
STRUCTURE P-40-875			
DRAWN BY		HMD	PLANS CK'D. JPH
72 MEMBER DETAILS		SHEET 51 OF 72	




STEEL REPAIRS TO GIRDER STIFFENERS AT NORTH ABUTMENT		
GIRDER NUMBER	GIRDER NAME	REPAIR WORK
1	103G1	ADD 3/8" X 4 1/2" X 1'-0" PLATES TO BOTTOM OF N.W. STIFFENER
2	100G1	ADD 3/8" X 4 1/2" X 1'-0" PLATES TO BOTTOM OF S.W. AND S.E. STIFFENERS
3	99G1	ADD 3/8" X 4 1/2" X 1'-0" PLATES TO BOTTOM OF N.W. STIFFENER
4	110G1	ADD 3/8" X 4 1/2" X 1'-0" PLATES TO BOTTOM OF N.W. AND N.E. STIFFENERS
5	107G2	ADD 3/8" X 4 1/2" X 1'-0" PLATES TO BOTTOM OF S.W., N.W. AND S.E. STIFFENERS
6	107G1	ADD 3/8" X 4 1/2" X 1'-0" PLATES TO BOTTOM OF S.W., S.E. AND N.E. STIFFENERS

109B5



EAST ELEVATION
(WEST ELEVATION OPPOSITE HAND)



SECTION A-A

NOTES:

SEE SHEET 19 FOR LOCATION.
ALL STIFFENER REPAIRS ARE BOLTED CONNECTIONS USING 3/4" DIA. GRADE A325 BOLTS WITH 1 3/8" DIA. HOLES. SEE TYPICAL DETAILS THIS SHEET.

NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
STRUCTURE P-40-875			
DRAWN BY JC		PLANS CK'D. JPH	
109B5 MEMBER DETAILS		SHEET 53 OF 72	

SYMM. ABOUT C
EXCEPT AS SHOWN

TO 123B1 TO 47TIR/L

NOTE ③ SHEET 32
1-BOLT 1/8"ØX0'-4" (24) 94E4
1-PC. GALV. PIPE
1"ØX0'-1/4" (28) 94E4
1-WASHER 3"ØX3/8" THICK (52)

94E4
(24)


NOTE ⑥ SHEET 32
REPLACE LOWER STIFFENERS
(OUTER) AT
MEMBER 123-B1
ATTACHED TO
MEMBER 47TIR
(WEST SIDE)

123-B1

NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
STRUCTURE P-40-875			
DRAWN BY		JC	PLANS CK'D. JPH
19G1 MEMBER DETAILS		SHEET 54 OF 72	


19G1 R/L

SAVE TEMPLATES






NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
STRUCTURE P-40-875			
DRAWN BY		HMD	PLANS CK'D. JPM
65G1 MEMBER DETAILS		SHEET 55 OF 72	



NOTE ① SHEET 32
REPLACE 1'-2 1/2" OF STIFFENER
(OUTER) 127D1 AT EAST
ELEVATION
SEE DETAILS FOR LOWER
SECTION OF STIFFENER
REPLACEMENT ON SHEET 46

NOTE ① SHT. 32
REPLACE 1'-2 1/2" OF
OUTER STIFFENER
SEE DETAILS FOR LOWER
SECTION OF STIFFENER
REPLACEMENT ON SHEET 46


NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
STRUCTURE P-40-875			
DRAWN BY		HMD	PLANS CK'D. JPH
127D1 MEMBER DETAILS		SHEET 56 OF 72	



INSIDE FACE, LOOKING EAST



(NEW WEB PLATE TO 101G1)




NOTE ④ SHEET 34
REPLACE 1'-2 1/2" OF
VERTICAL STIFFENER
L3 1/2"x5"x3 3/8"x1'-2 1/2"
SEE DETAILS FOR LOWER SECTION OF
STIFFENER REPLACEMENT ON SHEET 46


NOTE: BRACKET 123B8 BELOW

— NOTE ⑤ SHEET 34 AND SHEET 58
REPLACE 3 OUTER
EXPANSION BOLT ASSEMBLIES.

NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
STRUCTURE P-40-875			
		DRAWN BY	HMD PLANS CK'D. JF
101G1 MEMBER DETAILS		SHEET 57 OF 7	




NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
STRUCTURE P-40-875			
DRAWN BY		HMD	PLANS CK'D. JPH
126G1 MEMBER DETAILS		SHEET 58 OF 72	




BOTTOM FLANGE PLATE DETAIL 1


(2) FLANGE PLATES 15P10 AT BOTTOM FLANGES OF 15T2 R/L (BENT 9)
NOTE ③ SHEET 29



SECTION 1
(BENT 9) 36/59



SECTION 5
(BENT 9) 36/59



OUTER FLANGE PLATE DETAIL 3

OUTER FLANGE PLATE AT SOUTH FLANGE OF 15T2R (BENT 9)
NOTE ⑨ SHEET 29






PLATE DETAIL 2


PLATE STIFFENER OF 15T2L (BENT 9)
NOTE ⑧ SHEET 29



SECTION 4
(BENT 9) 59




SECTION 2
(BENT 9) 36/59




FLANGE PLATE DETAIL 4

NEW FLANGE PALTE TO SW FLANGE OF 15T2R (BENT 9)
NOTE ⑩ SHEET 29




SECTION 6
(BENT 11) 40/59



FLANGE PLATE DETAIL 5

OUTER FLANGE PLATE TO NW FLANGE OF MEMBER 47T1R (BENT 11)
NOTE ② SHEET 32




SECTION 6
(BENT 11) 59

FLANGE PLATE DETAIL 6

WEST ELEVATION (LOOKING EAST) MEMBER 47T1R (BENT 11)

(2) NEW OUTER WEB PLATES TO EAST AND WEST FACES OF 15T2L OF BENT 9 (8 1/2" X 1/2" X 2'-0")


SECTION 3
(BENT 9) 36/59



SECTION 3
(BENT 9) 36/59

WEB PLATES DETAIL 7

EAST ELEVATION (LOOKING WEST) MEMBER 15T2L (BENT 9)
NOTE ⑥ SHEET 29



WEB PLATES DETAIL 8


WEST ELEVATION (LOOKING EAST) MEMBER 15T2L (BENT 9)
NOTE ⑥ SHEET 29

NOTE:

USE EXISTING BOLT SPACING AT ALL GUSSET PLATE REPLACEMENT LOCATIONS.


MATCH EXISTING BOLT SPACE WHERE APPLICABLE.

NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
STRUCTURE P-40-875			
DRAWN BY		HMD	PLANS CK'D. JPH
15T2R/L, 47T1R E.&W. ELEVATION MEMBER DETAILS		SHEET 59 OF 72	




FLANGE PLATES DETAIL 1

WEST ELEVATION (LOOKING EAST)
MEMBER 15T1R
(BENT 10)




FLANGE PLATES DETAIL 3

EAST ELEVATION (LOOKING WEST)
MEMBER 15T1R
(BENT 10)




SECTION 1
37/60



OUTER FLANGE PLATE DETAIL 2

(1) OUTER FLANGE PLATE
AT SOUTHEAST FLANGE OF 15T1R
NOTE ① SHEET 30




INNER FLANGE PLATE DETAIL 4

(1) INNER FLANGE PLATE
AT SOUTHEAST FLANGE OF 15T1R
NOTE ① SHEET 30

NOTE:
USE EXISTING BOLT SPACING AT ALL GUSSET PLATE
REPLACEMENT LOCATION.

MATCH EXISTING BOLT SPACING WHERE APPLICABLE.

NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
STRUCTURE P-40-875			
DRAWN BY		HMD	PLANS CK'D. JPH
15T1R MEMBER DETAILS		SHEET 60 OF 72	



WEB & FLANGE PLATES DETAILS 5

WEST ELEVATION (LOOKING EAST)
MEMBER 15T2L
(BENT 9)

WEB & FLANGE PLATES DETAILS 4

EAST ELEVATION (LOOKING WEST)
MEMBER 15T2L
(BENT 9)

NEW INNER FLANGE PLATE
TO NW FLANGE OF 15T2L
(5"x $\frac{1}{2}$ "x6'-0")

NEW INNER FLANGE PLATE
TO NW FLANGE OF 15T2L
(5"x $\frac{1}{2}$ "x6'-0")

INNER FLANGE PLATE DETAIL 1

(1) INNER FLANGE PLATE
AT NW FLANGE OF 15T2L
(NOTE ④) SHEET 28)

INNER FLANGE PLATE DETAIL 3

(1) INNER FLANGE PLATE
AT NW FLANGE OF 15T2L
(NOTE ④) SHEET 28)

NOTE:

MATCH EXISTING BOLT SPACING
WHERE APPLICABLE.


*-ELEVATION OF PLATE BUTT
JOINTS TO BE DETERMINED BY
ENGINEER IN THE FIELD.

☒: FABRICATE AND INSTALL IN
MORE THAN ONE PIECE TO
FACILITATE INSTALLATION.


NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
STRUCTURE P-40-875			
DRAWN BY		HMD	PLANS CK'D. JPH
15T2L MEMBER DETAILS		SHEET 61 OF 72	

STATE PROJECT NUMBER

2984-12-74





SECTION 1
36/61




SECTION 2
36/61

INNER & OUTER FLANGE PLATE DETAIL 2

(1) INNER & (1) OUTER FLANGE PLATES
AT SW FLANGE OF 15T2L





WEB & FLANGE PLATES DETAIL 4

NOTES:

USE EXISTING BOLT SPACING AT ALL GUSSET PLATE REPLACEMENT LOCATIONS.

MATCH EXISTING BOLT SPACES WHERE APPLICABLE.

*-ELEVATION OF PLATE BUTT JOINT TO BE DETERMINED BY ENGINEER IN THE FIELD.

☒: FABRICATE AND INSTALL IN MORE THAN ONE PIECE TO FACILITATE INSTALLATION.

WEST ELEVATION (LOOKING EAST)
MEMBER 15T2R
(BENT 9)

7/8" DIA. GRADE A 325 BOLTS
WITH 15/16" DIA. HOLES

NEW OUTER FLANGE PLATE
TO NORTH FACE OF 15T2R
(1'-0"X1/2"X6'-0")


NORTH FACE

☒ *NEW INNER & OUTER
FLANGE PLATES TO SE
FLANGE OF 15T2R
2-(5"X1/2"X50'-10"
TOTAL LENGTH,
EACH LOCATION)

SOUTH FACE

LONGITUDINAL WEB
PLATE EXTENSION
NOT SHOWN
FOR CLARITY

SECTION 1
36/62



WEB & FLANGE PLATES DETAILS 5

EAST ELEVATION (LOOKING WEST)
MEMBER 15T2R
(BENT 9)

NEW WEB PLATE TO
EAST FACE OF 15T2R
(5 1/4"X1/2"X6'-0")

NORTH FACE

NEW INNER FLANGE
PLATES AT NW, NE
FLANGE OF 15T2R
(5"X1/2"X6'-0")


☒ *NEW INNER & OUTER FLANGE
PLATES TO SE FLANGE OF 15T2R
2-(5"X1/2"X50'-10", TOTAL LENGTH
EACH LOCATION)

7/8" DIA. GRADE A 325 BOLTS
WITH 15/16" DIA. HOLES

SOUTH FACE


LONGITUDINAL WEB PLATE
EXTENSION NOT SHOWN
FOR CLARITY

SECTION 2
36/62




INNER FLANGE PLATE DETAIL 1

(2) INNER FLANGE PLATE
AT NW, NE FLANGE OF 15T2R
NOTE ⑥ SHEET 28




INNER FLANGE PLATE DETAIL 3

(2) INNER FLANGE PLATE
AT NW, NE FLANGE OF 15T2R
NOTE ⑥ SHEET 28




OUTER FLANGE PLATE DETAIL 2

(1) OUTER FLANGE PLATE
AT NORTH FLANGE OF 15T2R
NOTE ⑦ SHEET 28




SECTION 3
36/62


NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
STRUCTURE P-40-875			
DRAWN BY		HMD	PLANS CK'D. JPH
15T2R MEMBER DETAILS		SHEET 62 OF 72	



SECTION 1
40/63




SECTION 2
40/63




INNER FLANGE PLATE DETAIL 4

(1) INNER FLANGE PLATE
AT SW FLANGE OF 47T1R
AT FAR SIDE OF BENT 11
NOTE ① SHEET 31




FLANGE PLATE DETAIL 3

WEST ELEVATION (LOOKING EAST)
MEMBER 47T1R
(BENT 11)



FLANGE PLATE DETAIL 2

WEST ELEVATION (LOOKING EAST)
MEMBER 47T1LA
(BENT 11)





INNER FLANGE PLATE DETAIL 1

(1) INNER FLANGE PLATE
AT SW FLANGE OF 47T1LA
AT FAR SIDE OF BENT 11
NOTE ① SHEET 31

NOTE


MATCH EXISTING BOLT SPACING
WHERE APPLICABLE.

NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
STRUCTURE P-40-875			
DRAWN BY		HMD	PLANS CK'D. JPH
47T1R & 47T1LA FAR SIDE MEMBER DETAILS		SHEET 63 OF 72	




WEB AND FLANGE PLATE DETAIL 1

WEST ELEVATION (LOOKING EAST)
MEMBER 47T1LA
(BENT 11)




SECTION 1
40/64




WEB AND FLANGE PLATE DETAIL 2

EAST ELEVATION (LOOKING WEST)
MEMBER 47T1LA
(BENT 11)



INNER FLANGE PLATE DETAIL 3

(1) INNER FLANGE PLATE
AT NE FLANGE OF 47T1LA
NOTE ⑥ SHEET 31



INNER AND OUTER FLANGE PLATE DETAIL 4

(4) INNER & OUTER FLANGE PLATES
AT NW AND SW FLANGES OF 47T1LA
NOTE ⑤ SHEET 31

NOTES:

USE EXISTING BOLT SPACING
AT ALL GUSSET PLATE
REPLACEMENT LOCATIONS.

MATCH EXISTING BOLT
SPACES WHERE APPLICABLE.



*- ELEVATION OF PLATE BUTT
JOINTS TO BE DETERMINED BY
ENGINEER IN THE FIELD.

NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
STRUCTURE P-40-875			
DRAWN BY		HMD	PLANS CK'D. JPH
47T1LA NEAR SIDE MEMBER DETAILS		SHEET 64 OF 72	

PLOT NAME : B0113 2024 65 47T1R NEAR SIDE MEMBER DETAILS.dgn

REVISED: 12-04-2023 GJR

8



KEY:

Δ = MATCH EXISTING BOLT SPACING WHERE APPLICABLE.


□ = ALIGN BOLT HOLES WITH OUTSIDE FLANGE/GUSSET PLATE BOLT SPACING WHERE APPLICABLE.

MIN. BOLT SPACING ≥ 2.625"
MAX BOLT SPACING ≤ 6"



NOTES:

USE EXISTING BOLT SPACING AT ALL GUSSET PLATE REPLACEMENT LOCATIONS.

MATCH EXISTING BOLT SPACES WHERE APPLICABLE.





INNER FLANGE PLATE AT NW FLANGE OF 49T1 (BENT 12)
NOTE (19) SHEET 33





FLANGE PLATE DETAIL 2

WEST ELEVATION (LOOKING EAST)
MEMBER 49T1 (BENT 12)





FLANGE PLATE DETAIL 4

EAST ELEVATION (LOOKING WEST)
MEMBER 49T1 (BENT 12)



INNER FLANGE PLATE DETAIL 6


INNER FLANGE PLATE AT NE FLANGE OF 49T1 (BENT 12)
NOTE (11) SHEET 33



OUTER FLANGE PLATE DETAIL 8

OUTER FLANGE PLATE AT NORTH FLANGE OF 49T1 (BENT 12)
NOTE (1) SHEET 33

NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
STRUCTURE P-40-875			
DRAWN BY		HMD	PLANS CK'D. JPH
49T1 FAR AND NEAR SIDES MEMBER DETAILS		SHEET 66 OF 72	



KEY:

Δ = MATCH EXISTING BOLT SPACING WHERE APPLICABLE.

□ = ALIGN BOLT HOLES WITH OUTSIDE FLANGE/GUSSET PLATE BOLT SPACING WHERE APPLICABLE.

* MIN BOLT SPACING ≥ 2.625"
MAX BOLT SPACING ≤ 6"

NOTES:

USE EXISTING BOLT SPACING
AT ALL GUSSET PLATE
REPLACEMENT LOCATIONS.

MATCH EXISTING BOLT
SPACES WHERE APPLICABLE.

Δ □

(2) NEW OUTER FLANGE
PLATES TO NORTH & SOUTH
FLANGES OF 50T1 NEAR SIDE
OF BENT 12 (1'-0 1/2"X1 1/2"X6'-0")

NORTH FACE

7/8" DIA. GRADE A 325 BOLTS
WITH 15/16" DIA. HOLES

SOUTH FACE

Δ □

NEW INNER FLANGE
PLATE TO SW OF 50T1
NEAR SIDE OF BENT 12
(5"X1 1/2"X9'-0")

SECTION 1


43/68

Δ □

(2) NEW OUTER FLANGE PLATES
TO NORTH & SOUTH FLANGES
OF 50T1 (1'-0 1/2"X1 1/2"X6'-0")

Δ □

NEW INNER FLANGE
PLATE TO SW
FLANGE OF 50T1
(5"X1 1/2"X9'-0")




FLANGE PLATES DETAIL 4

WEST ELEVATION (LOOKING EAST)
MEMBER 50T1
(BENT 12)

Δ □

NEW INNER FLANGE PLATE
AT SW FLANGE OF 50T1
(5"X1 1/2"X9'-0")




INNER FLANGE PLATE DETAIL 2

INNER FLANGE PLATE
AT SW FLANGE OF 50T1
(BENT 12)
NOTE ① SHEET 33

Δ □

(2) NEW OUTER FLANGE
PLATES TO NORTH &
SOUTH FLANGES OF 50T1
(1'-0 1/2"X1 1/2"X6'-0")




OUTER FLANGE PLATE DETAIL 3

(2) OUTER FLANGE PLATES
AT NORTH & SOUTH FLANGES OF 50T1
(BENT 12)
NOTE ③ SHEET 33

Δ □







NEW INNER FLANGE
PLATE TO SW FLANGE
OF 50T1 (5"X1 1/2"X9'-0")



FLANGE PLATES DETAIL 1










EAST ELEVATION (LOOKING WEST)
MEMBER 50T1
(BENT 12)

NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
STRUCTURE P-40-875			
DRAWN BY		HMD	PLANS CK'D. JPH
50T1 NEAR SIDE MEMBER DETAILS		SHEET 68 OF 72	



▲ = MATCH EXISTING BOLT SPACING WHERE APPLICABLE.
 □ = ALIGN BOLT HOLES WITH OUTSIDE FLANGE/GUSSET
 PLATE BOLT SPACING WHERE APPLICABLE.
 * =MIN. BOLT SPACING $\geq 2.625"$
 MAX BOLT SPACING $\leq 6"$
 ☒ =ELEVATION OF PLATE BUTT JOINTS TO BE
 DETERMINED BY ENGINEER IN THE FIELD.







NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
STRUCTURE P-40-875			
DRAWN BY		HMD	PLANS CK'D. JF
51T1 FAR SIDE MEMBER DETAILS		SHEET 69 OF 7	



KEY:

- △ = MATCH EXISTING BOLT SPACING WHERE APPLICABLE.
- = ALIGN BOLT HOLES WITH OUTSIDE FLANGE/GUSSET PLATE BOLT SPACING WHERE APPLICABLE.
- * = MIN. BOLT SPACING ≥ 2.625"
MAX BOLT SPACING ≤ 6"
- ⊠ = ELEVATION OF PLATE BUTT JOINTS TO BE DETERMINED BY ENGINEER IN THE FIELD.

NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
STRUCTURE P-40-875			
DRAWN BY		HMD	PLANS CK'D. JPH
51T1 NEAR SIDE MEMBER DETAILS		SHEET 70 OF 72	



KEY:

Δ = MATCH EXISTING BOLT SPACING WHERE APPLICABLE.

□ = ALIGN BOLT HOLES WITH OUTSIDE FLANGE/GUSSET PLATE BOLT SPACING WHERE APPLICABLE.

MIN BOLT SPACING ≥ 2.625"

MAX BOLT SPACING ≤ 6"

NOTES:

USE EXISTING BOLT SPACING AT ALL GUSSET PLATE REPLACEMENT LOCATIONS.

MATCH EXISTING BOLT SPACES WHERE APPLICABLE.

NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
STRUCTURE P-40-875			
DRAWN BY		HMD	PLANS CK'D. JPH
52T1 FAR SIDE MEMBER DETAILS		SHEET 71 OF 72	

Δ (2) NEW INNER FLANGE PLATES TO NW & NE FLANGES OF 52T1 NEAR SIDE OF BENT 12 (5"x1/2"x6'-0")

Δ (2) NEW INNER FLANGE PLATES TO SW & SE FLANGES OF 52T1 NEAR SIDE OF BENT 12 (5"x1/2"x16'-0")

Δ NEW OUTER FLANGE PLATE TO NORTH FALNGE OF 52T1 NEAR SIDE OF BENT 12 (1'-0/2"x1/2"x6'-0")


Δ NEW OUTER FLANGE PLATE AT SOUTH FACE OF 52T1 (1'-0/2"x1/2"x16'-0")

Δ (2) NEW INNER FLANGE PLATES TO NW & SW FLANGES OF 52T1 NEAR SIDE OF BENT 12 (5"x1/2"x12'-0")

Δ (2) NEW OUTER FLANGE PLATES AT NW & SW FLANGES OF 52T1 (5"x1/2"x12'-0")


SECTION 1
45/72

SECTION 2
45/72




INNER FLANGE PLATE DETAIL 2

(2) INNER FLANGE PLATES
AT NW & NE FLANGES OF 51T1
(BENT 12)
NOTE ⑧ SHEET 33




INNER FLANGE PLATE DETAIL 3

(2) INNER FLANGE PLATES
AT SW & SE FLANGES OF 51T1
(BENT 12)
NOTE ⑦ SHEET 33




INNER FLANGE PLATES DETAIL 5

(2) INNER FLANGE PLATES
AT NW & SW FLANGES OF 52T1
(BENT 12)
NOTE ⑨ SHEET 33



OUTER FLANGE PLATE DETAIL 7

(2) OUTER FLANGE PLATES
AT SW & SE FLANGES OF 52T1
NOTE ⑨ SHEET 33



FLANGE PLATES DETAIL 1

WEST ELEVATION (LOOKING EAST)
MEMBER 51T1
(BENT 12)


Δ (2) NEW INNER FLANGE PLATES TO NW & SW FLANGES OF 52T1 (5"x1/2"x12'-0")

Δ (2) NEW OUTER FLANGE PLATES TO NW & NE FLANGES OF 52T1 (5" X 1/2" X 12'-0")

Δ (2) NEW INNER FLANGE PLATES TO SW & SE FLANGES OF 52T1 (5" X 1/2" X 16'-0")

Δ NEW OUTER FLANGE PLATE TO SOUTH FACE OF 52T1 (1'-0/2" X 1/2" X 16'-0")


Δ (2) NEW INNER FLANGE PLATES TO NW & NE FLANGES OF 52T1 (5"x1/2"x6'-0")



FLANGE PLATES DETAIL 4

EAST ELEVATION (LOOKING WEST)
MEMBER 52T1
(BENT 12)


Δ NEW OUTER FLANGE PLATE TO NORTH FLANGE OF 52T1 (1'-0/2"x1/2"x6'-0")



OUTER FLANGE PLATE DETAIL 6

OUTER FLANGE PLATE
AT NORTH FLANGE OF 52T1
(BENT 12)
NOTE ⑧ SHEET 33

Δ NEW OUTER FLANGE PLATE TO SOUTH FLANGE OF 52T1 (1'-0/2"x1/2"x16'-0")



OUTER FLANGE PLATE DETAIL 8

OUTER FLANGE PLATE
AT SOUTH FLANGE OF 52T1
(BENT 12)
NOTE ⑦ SHEET 33

KEY:

- Δ = MATCH EXISTING BOLT SPACING WHERE APPLICABLE.
- = ALIGN BOLT HOLES WITH OUTSIDE FLANGE/GUSSET PLATE BOLT SPACING WHERE APPLICABLE.
- * =MIN. BOLT SPACING ≥ 2.625"
MAX BOLT SPACING ≤ 6"

NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
STRUCTURE P-40-875			
DRAWN BY		HMD	PLANS CK'D. JPH
52T1 NEAR SIDE MEMBER DETAILS		SHEET 72 OF 72	



Wisconsin Department of Transportation

Dedicated people creating transportation solutions
through innovation and exceptional service.

<http://www.dot.wisconsin.gov>