

MAD

PROJECT ID:

WITH:

3050-01-63

COUNTY:


DANE

SEPTEMBER 2024

ORDER OF SHEETS

|                        |              |                                    |
|------------------------|--------------|------------------------------------|
| Section No.            | 1            | Title                              |
| Section No.            | 2            | Typical Sections and Details       |
| Section No.            | 3            | Estimate of Quantities             |
| Section No.            | 3            | Miscellaneous Quantities           |
| <del>Section No.</del> | <del>4</del> | <del>Right of Way Plat</del>       |
| <del>Section No.</del> | <del>5</del> | <del>Plan and Profile</del>        |
| Section No.            | 6            | Standard Detail Drawings           |
| <del>Section No.</del> | <del>7</del> | <del>Sign Plates</del>             |
| Section No.            | 8            | Structure Plans                    |
| <del>Section No.</del> | <del>9</del> | <del>Computer Earthwork Data</del> |
| <del>Section No.</del> | <del>9</del> | <del>Cross Sections</del>          |

TOTAL SHEETS = 38



|                    |            |   |      |
|--------------------|------------|---|------|
| DESIGN DESIGNATION | 3050-01-33 |   |      |
| A.A.D.T.           | 2024       | = | 5200 |
| A.A.D.T.           |            | = |      |
| D.H.V.             |            | = |      |
| D.D.               |            | = |      |
| T.                 |            | = | 10.2 |
| DESIGN SPEED       |            | = | 60   |
| ESALS              |            | = |      |

CONVENTIONAL SYMBOLS

|                                |  |
|--------------------------------|--|
| PLAN                           |  |
| CORPORATE LIMITS               |  |
| PROPERTY LINE                  |  |
| LOT LINE                       |  |
| LIMITED HIGHWAY EASEMENT       |  |
| EXISTING RIGHT OF WAY          |  |
| PROPOSED OR NEW R/W LINE       |  |
| SLOPE INTERCEPT                |  |
| REFERENCE LINE                 |  |
| EXISTING CULVERT               |  |
| PROPOSED CULVERT (Box or Pipe) |  |
| COMBUSTIBLE FLUIDS             |  |
| MARSH AREA                     |  |
| WOODED OR SHRUB AREA           |  |

|   |  |
|---|--|
| PROFILE                                     |  |
| GRADE LINE                                  |  |
| ORIGINAL GROUND                             |  |
| MARSH OR ROCK PROFILE (To be noted as such) |  |
| SPECIAL DITCH                               |  |
| GRADE ELEVATION                             |  |
| CULVERT (Profile View)                      |  |
| UTILITIES                                   |  |
| ELECTRIC                                    |  |
| FIBER OPTIC                                 |  |
| GAS   |  |
| SANITARY SEWER                              |  |
| STORM SEWER                                 |  |
| TELEPHONE                                   |  |
| WATER                                       |  |
| UTILITY PEDESTAL                            |  |
| POWER POLE                                  |  |
| TELEPHONE POLE                              |  |

STATE OF WISCONSIN  
DEPARTMENT OF TRANSPORTATION

PLAN OF PROPOSED IMPROVEMENT


SUN PRAIRIE - WATERTOWN

MAUNESHA RIVER STRUCTURE B-13-190


STH 19

DANE

|                      |
|----------------------|
| STATE PROJECT NUMBER |
| 3050-01-63           |



| STATE PROJECT | FEDERAL PROJECT |          |
|---------------|-----------------|----------|
|               | PROJECT         | CONTRACT |
| 3050-01-63    |                 |          |
|               |                 |          |
|               |                 |          |
|               |                 |          |

| STATE OF WISCONSIN<br>DEPARTMENT OF TRANSPORTATION |   |
|--|---|
| PREPARED BY  |   |
| Surveyor   |   |
| Designer   | MADISON MARCHESE  |
| Project Manager                                    | DAVID SCHMIDT P.E.  |
| Regional Examiner                                  |   |
| Regional Supervisor                                | JENNIFER KOBRYN, P.E.   |
| APPROVED FOR THE DEPARTMENT                        |   |
| DATE:  | David B Schmidt   |
|  |  |
|  | (Signature)   |

GENERAL NOTES

THERE ARE UTILITY FACILITIES WITHIN THE PROJECT AREA THAT ARE NOT SHOWN ON THE PLANS. THE CONTRACTOR SHALL COORDINATE HIS CONSTRUCTION ACTIVITIES WITH A CALL TO DIGGERS HOTLINE AND/OR A DIRECT CALL TO THE UTILITIES THAT HAVE FACILITIES IN THE AREA. NOT ALL UTILITIES ARE MEMBERS OF DIGGERS HOTLINE.

UTILITIES CONTACTS

WE ENERGIES  
ELECTRICITY  
WE ENERGIES UTILITY COORDINATOR  
500 S 116TH STREET  
WEST AKKUS, WI 53214  
PHONE: (414) 944-5738  
EMAIL: We-Utility-relocations@we-energies.com


WISCONSIN DNR LIAISON


ERIC HEGGELUND  
SOUTH CENTRAL REGION HEADQUARTERS  
3911 FISH HATCHERY ROAD  
FITCHBURG, WI 53711-5397  
PHONE: 608-275-3301  
EMAIL: ERIC.HEGGELUND@WISCONSIN.GOV

DESIGN PROJECT LEADER

DAVID SCHMIDT, P.E.  
WISDOT SW REGIOIN  
2012 WRIGHT STREET  
MADISON, WI 53704  
PHONE: 608-246-3867  
EMAIL: DAVID2.SCHMIDT@DOT.WI.GOV



Dial  or (800)242-8511  
[www.DiggersHotline.com](http://www.DiggersHotline.com)



|                        |             |              |                  |       |   |
|------------------------|-------------|--------------|------------------|-------|---|
| PROJECT NO: 3050-01-63 | HWY: STH 19 | COUNTY: DANE | PROJECT OVERVIEW | SHEET | E |
|------------------------|-------------|--------------|------------------|-------|---|

Estimate Of Quantities

3050-01-63

| Line | Item     | Item Description   | Unit | Total     | Qty       |
|------|----------|--|------|-----------|-----------|
| 0002 | 203.0220 | Removing Structure (structure) 01. B-13-190                    | EACH | 1.000     | 1.000     |
| 0004 | 213.0100 | Finishing Roadway (project) 01. 3050-01-63                     | EACH | 1.000     | 1.000     |
| 0006 | 502.0100 | Concrete Masonry Bridges                                       | CY   | 5.300     | 5.300     |
| 0008 | 502.3200 | Protective Surface Treatment                                   | SY   | 28.000    | 28.000    |
| 0010 | 505.0600 | Bar Steel Reinforcement HS Coated Structures                   | LB   | 1,400.000 | 1,400.000 |
| 0012 | 513.4051 | Railing Tubular Type F   | LF   | 65.000    | 65.000    |
| 0014 | 603.8000 | Concrete Barrier Temporary Precast Delivered                   | LF   | 550.000   | 550.000   |
| 0016 | 603.8125 | Concrete Barrier Temporary Precast Installed                   | LF   | 550.000   | 550.000   |
| 0018 | 614.0905 | Crash Cushions Temporary                                       | EACH | 2.000     | 2.000     |
| 0020 | 618.0100 | Maintenance and Repair of Haul Roads (project) 01. 3050-01-63  | EACH | 1.000     | 1.000     |
| 0022 | 619.1000 | Mobilization   | EACH | 1.000     | 1.000     |
| 0024 | 643.0300 | Traffic Control Drums  | DAY  | 288.000   | 288.000   |
| 0026 | 643.0420 | Traffic Control Barricades Type III                            | DAY  | 16.000    | 16.000    |
| 0028 | 643.0715 | Traffic Control Warning Lights Type C                          | DAY  | 160.000   | 160.000   |
| 0030 | 643.0900 | Traffic Control Signs  | DAY  | 320.000   | 320.000   |
| 0032 | 643.1050 | Traffic Control Signs PCMS                                     | DAY  | 32.000    | 32.000    |
| 0034 | 643.3180 | Temporary Marking Line Removable Tape 6-Inch                   | LF   | 4,100.000 | 4,100.000 |
| 0036 | 643.3850 | Temporary Marking Stop Line Removable Tape 18-Inch             | LF   | 24.000    | 24.000    |
| 0038 | 643.5000 | Traffic Control  | EACH | 1.000     | 1.000     |
| 0040 | 646.2020 | Marking Line Epoxy 6-Inch                                      | LF   | 612.000   | 612.000   |
| 0042 | 646.9000 | Marking Removal Line 4-Inch                                    | LF   | 572.000   | 572.000   |
| 0044 | 661.0101 | Temporary Traffic Signals for Bridges (structure) 01. B-13-190 | EACH | 1.000     | 1.000     |
| 0046 | 715.0502 | Incentive Strength Concrete Structures                         | DOL  | 500.000   | 500.000   |

| GENERAL  |            |                                  |                                     |         |
|----------|------------|----------------------------------|-------------------------------------|---------|
| CATEGORY | LOCATION   | 619.1000<br>MOBILIZATION<br>EACH | 643.5000<br>TRAFFIC CONTROL<br>EACH | REMARKS |
| 0010     | PROJECT    | 1                                | 1                                   |         |
|          | TOTAL 0010 | 1                                | 1                                   |         |

| REMOVING PAVEMENT MARKING |            |  |                         |
|---------------------------|------------|--|-------------------------|
| CATEGORY                  | LOCATION   | 646.9000<br>MARKING<br>REMOVAL LINE 4-<br>INCH<br>LF | REMARKS                 |
| 0010                      | STH 19     | 572  | CENTERLINE YELLOW SKIPS |
|                           | TOTAL 0010 | 572  |                         |

| TEMPORARY PAVEMENT MARKING |            |  |   |   |                       |
|----------------------------|------------|--|---|---|-----------------------|
| CATEGORY                   | LOCATION   | 643.3180<br>TEMPORARY<br>MARKING LINE<br>REMOVABLE TAPE<br>6-INCH (YELLOW)<br>LF | TEMPORARY<br>MARKING LINE<br>REMOVABLE TAPE<br>6-INCH (WHITE) | 643.3850<br>TEMPORARY<br>MARKING STOP<br>LINE REMOVABLE<br>TAPE 18-INCH<br>LF | REMARKS               |
| 0010                       | STH 19     | 1,400  | -   | 12  | WEST END OF STRUCTURE |
| 0010                       | B-13-190   | -  | 1,300   | -   | ON STRUCTURE          |
| 0010                       | STH 19     | 1,400  | -   | 12  | EAST END OF STRUCTURE |
|                            | TOTAL 0010 | 4,100  |   | 24  |                       |


| TRAFFIC CONTROL |            |  |  |   |  |  |   |  |   |                             |
|-----------------|------------|--|--|---|--|--|---|--|---|-----------------------------|
| CATEGORY        | LOCATION   | 603.8000<br>CONCRETE<br>BARRIER<br>TEMPORARY<br>PRECAST<br>DELIVERED<br>LF | 603.8125<br>CONCRETE<br>BARRIER<br>TEMPORARY<br>PRECAST<br>INSTALLED<br>LF | 643.0300<br><br>TRAFFIC CONTROL<br>DRUMS<br>DAY | 643.0420<br><br>TRAFFIC CONTROL<br>BARRICADES TYPE<br>III<br>DAY | 643.0715<br><br>TRAFFIC CONTROL<br>WARNING LIGHTS<br>TYPE C<br>DAY | 643.0900<br><br>TRAFFIC CONTROL<br>SIGNS<br>DAY | 643.1050<br><br>TRAFFIC CONTROL<br>SIGNS PCMS<br>DAY | 661.0101.01<br>TEMPORARY<br>TRAFFIC SIGNALS<br>FOR BRIDGES<br>(STRUCTURE) (01.<br>B-13-190)<br>EACH | REMARKS                     |
| 0010            | PROJECT    | 550  | 550  | 288   | 16   | 160  | 320   | 32   | 1   | PROJECT DURATION IS 16 DAYS |
|                 | TOTAL 0010 | 550  | 550  | 288   | 16   | 160  | 320   | 32   | 1   |                             |

| TEMPORARY CRASH CUSHIONS |            |   |            |                           |                  |                      |                  |   |         |
|--------------------------|------------|---|------------|---------------------------|------------------|----------------------|------------------|---|---------|
| CATEGORY                 | LOCATION   | 614.0905<br>CRASH CUSHIONS<br>TEMPORARY<br>EACH | BACK WIDTH | OBJECT MARKING<br>PATTERN | CRASH TEST LEVEL | TRAFFIC<br>DIRECTION | TRAFFIC LOCATION | CRASH CUSHION SHIELDS                   | REMARKS |
| 0010                     | STH 19     | 2   | 4          | OM-3R (W05-59R)           | TL-3             | BIDIRECTIONAL        | L and R          | Temporary crash cushion in<br>work zone |         |
|                          | TOTAL 0010 | 2   |            |                           |                  |                      |                  |   |         |

| PAVEMENT MARKING |            |  |   |  |                         |
|------------------|------------|--|---|--|-------------------------|
| CATEGORY         | LOCATION   | 213.0100.01<br>FINISHING<br>ROADWAY<br>(PROJECT) (01.<br>3050-01-63)<br>EACH | 646.2020<br><br>MARKING LINE<br>EPOXY 6-INCH<br>(WHITE)<br>LF | MARKING LINE<br>EPOXY 6-INCH<br>(YELLOW) | REMARKS                 |
| 0010             | STH 19     |  | -   | 572                                      | CENTERLINE YELLOW SKIPS |
| 0010             | B-13-190   | 1  | 40  | -  | REPAIR ON STRCUTURE     |
|                  | TOTAL 0010 | 1  | 612   |  |                         |

Standard Detail Drawing List

|           |  |
|-----------|--|
| 09G02-05A | BRIDGE TEMPORARY TRAFFIC SIGNAL INSTALLATION                               |
| 09G02-05B | BRIDGE TEMPORARY TRAFFIC SIGNAL INSTALLATION                               |
| 09G02-05C | BRIDGE TEMPORARY TRAFFIC SIGNAL INSTALLATION                               |
| 14B07-16A | CONCRETE BARRIER TEMPORARY PRECAST, 12'-6"                                 |
| 14B07-16B | CONCRETE BARRIER TEMPORARY PRECAST, 12'-6"                                 |
| 14B07-16C | CONCRETE BARRIER TEMPORARY PRECAST, 12'-6"                                 |
| 14B07-16D | CONCRETE BARRIER TEMPORARY PRECAST, 12'-6"                                 |
| 14B07-16E | CONCRETE BARRIER TEMPORARY PRECAST, 12'-6"                                 |
| 14B07-16F | CONCRETE BARRIER TEMPORARY PRECAST, 12'-6"                                 |
| 14B07-16G | CONCRETE BARRIER TEMPORARY PRECAST, 12'-6"                                 |
| 14B07-16H | CONCRETE BARRIER TEMPORARY PRECAST, 12'-6"                                 |
| 14B07-16I | CONCRETE BARRIER TEMPORARY PRECAST, 12'-6"                                 |
| 14B07-16J | CONCRETE BARRIER TEMPORARY PRECAST, 12'-6"                                 |
| 14B07-16K | CONCRETE BARRIER TEMPORARY PRECAST, 12'-6"                                 |
| 14B07-16L | CONCRETE BARRIER TEMPORARY PRECAST, 12'-6"                                 |
| 14B07-16M | CONCRETE BARRIER TEMPORARY PRECAST, 12'-6"                                 |
| 14B07-16N | CONCRETE BARRIER TEMPORARY PRECAST, 12'-6"                                 |
| 14B08-02A | CRASH CUSHION/SAND BARREL ARRAY AND OTHER TEMPORARY BARRIER LAYOUT DETAILS |
| 14B08-02B | CRASH CUSHION/SAND BARREL ARRAY AND OTHER TEMPORARY BARRIER LAYOUT DETAILS |
| 14B08-02C | CRASH CUSHION/SAND BARREL ARRAY AND OTHER TEMPORARY BARRIER LAYOUT DETAILS |
| 14B08-02D | CRASH CUSHION/SAND BARREL ARRAY AND OTHER TEMPORARY BARRIER LAYOUT DETAILS |
| 14B08-02E | CRASH CUSHION/SAND BARREL ARRAY AND OTHER TEMPORARY BARRIER LAYOUT DETAILS |
| 15C08-23A | PERMANENT LONGITUDINAL PAVEMENT MARKINGS                                   |
| 15C08-23B | TEMPORARY LONGITUDINAL PAVEMENT MARKING                                    |
| 15C08-23C | PAVEMENT MARKING (TURN LANES)  |
| 15C08-23D | PAVEMENT MARKING (TURN LANES)  |
| 15C11-10B | CHANNELIZING DEVICES DRUMS, CONES, BARRICADES AND VERTICAL PANELS          |
| 15D33-09  | TRAFFIC CONTROL, ONE LANE ROAD WITH TEMPORARY SIGNALS                      |



TYPICAL BRIDGE TEMPORARY TRAFFIC SIGNAL LOCATION

LEGEND

- WOOD POLE (NON-BREAKAWAY)
- WOOD POST (BREAKAWAY)
- SIGNAL CABLE
- SIGNAL CABLE W/MESSENGER
- DIRECTION OF TRAFFIC
- LED TRAFFIC SIGNAL WITH BACKPLATE

GENERAL NOTES

DETAILS OF CONSTRUCTION, MATERIALS AND WORKMANSHIP NOT SHOWN ON THIS DRAWING SHALL CONFORM TO THE PERTINENT REQUIREMENTS OF THE CONTRACT.

POLE MOUNTED TRAFFIC SIGNAL CONTROL CABINET MAY BE MOUNTED ON THE SERVICE POLE IF THE ELECTRICAL UTILITY ALLOWS THE INSTALLATION.

WHEN UTILITY POLES ARE USED TO SPAN THE TEMPORARY OVERHEAD CABLE, WRITTEN PERMISSION MUST BE OBTAINED FROM THE OWNER OF THE POLES AND GIVEN TO THE PROJECT MANAGER. ALL PERTINENT UTILITY AND CODE CLEARANCES SHALL BE MAINTAINED.

WOOD POLES (NON-BREAKAWAY) SHALL BE NO CLOSER TO EDGE OF PAVEMENT THAN OFFSET DISTANCE CHART ALLOWS OR 4 FEET BEHIND PROTECTIVE BARRIER (BEAM GUARD, ETC.).


WOOD POSTS (BREAKAWAY) SHALL BE NO CLOSER THAN 2 FEET OUTSIDE OF SHOULDER.

VERTICAL CLEARANCE ETC. PER NEC.


TRAFFIC SIGNAL FACES SHALL BE TYPICALLY PLACED 12 FEET FROM EDGE OF PAVEMENT.

EACH TRAFFIC SIGNAL SHALL HAVE A BACKPLATE.


SIGNING, PAVEMENT MARKING AND LANE CONTROL REQUIREMENTS SHALL CONFORM TO STANDARD DETAIL DRAWING 15D33.



TYPICAL DROP TO TRAFFIC SIGNAL FACE



POLE MOUNT CABINET INSTALLATION



GROUND MOUNT CABINET INSTALLATION

| MINIMUM POLE LENGTHS | CLASS | POLE BURIAL DEPTHS |
|----------------------|-------|--------------------|
| 25'                  | V     | 5'                 |
| 30'                  | V     | 6'                 |
| 35'                  | IV    | 7'                 |
| 40'                  | IV    | 8'                 |
| 45'                  | IV    | 9'                 |

| OFFSET DISTANCES FOR TEMPORARY NON-BREAKAWAY POLES |                  |
|--|------------------|
| SPEED LIMIT  | OFFSET DISTANCE* |
| GREATER THAN 45 MPH                                | 18 FT            |
| 45 MPH OR LESS                                     | 12 FT            |
| 45 MPH OR LESS W/CURBS                             | 2 FT             |


\* NOTE: OFFSET MEASURED FROM OUTER EDGE OF OUTSIDE THRU LANE.

BRIDGE TEMPORARY TRAFFIC SIGNAL INSTALLATION

STATE OF WISCONSIN  
DEPARTMENT OF TRANSPORTATION

APPROVED  
March 2018 /S/ Ahmet Demirbilek  
DATE ROADWAY STANDARDS DEVELOPMENT  
FHWA ENGINEER





**GENERAL NOTES**

USE 3/4\"/>


**TYPICAL DEAD-ENDINGS OR GUYING**

**BRIDGE TEMPORARY TRAFFIC  
SIGNAL INSTALLATION**

STATE OF WISCONSIN  
DEPARTMENT OF TRANSPORTATION

APPROVED  
June 2015 /S/ Ahmet Demerbilek  
DATE ROADWAY STANDARDS DEVELOPMENT  
ENGINEER

FHWA




TRAILER MOUNTED TRAFFIC SIGNAL

GENERAL NOTES

DETAIL OF CONSTRUCTION, MATERIALS AND WORKMANSHIP NOT SHOWN ON THIS DRAWING SHALL CONFORM TO THE PERTINENT REQUIREMENTS OF THE CONTRACT.

SIGNING, PAVEMENT MARKING AND LANE CONTROL REQUIREMENTS SHALL CONFORM TO STANDARD DETAIL DRAWING 15D33.



TYPICAL TRAILER MOUNTED TRAFFIC SIGNAL LOCATION


LEGEND

- POST MOUNTED SIGN
- TEMPORARY PRECAST CONCRETE BARRIER
- TRAILER MOUNTED TRAFFIC SIGNAL
- REMOVE PAVEMENT MARKINGS
- DIRECTION OF TRAFFIC


BRIDGE TEMPORARY TRAFFIC SIGNAL INSTALLATION

STATE OF WISCONSIN  
DEPARTMENT OF TRANSPORTATION



APPROVED  
June 2015  
DATE /S/ Ahmet Demerbilek  
ROADWAY STANDARDS DEVELOPMENT  
ENGINEER  
FHWA




CROSS SECTION




ANCHOR BLOCK  
DETAIL




PROFILE VIEW



PLAN VIEW  
TEMPORARY BARRIER



LIFTING SLOT DETAIL  
(TYP.)




PROFILE VIEW  
TEMPORARY BARRIER REINFORCEMENT

GENERAL NOTES

PLACE BARRIER ON PAVED SURFACE. BEFORE PLACEMENT OF TEMPORARY BARRIER, REMOVE ALL LOOSE MATERIAL FROM PAVED SURFACE.


LOOP BARS C1, C2 AND C3 ARE NOT FOR PLACEMENT OR MOVEMENT OF BARRIER.

- 100 PERMANENTLY FORM INTO ONE END OF BARRIER THE FOLLOWING INFORMATION:
  - A. TYPE OF BARRIER: WI-CBTP
  - B. MANUFACTURER
  - C. DATE OF MANUFACTURE (MONTH AND YEAR)
- 101 1" OPTIONAL CHAMFER
- 102 SEE LIFTING SLOT DETAIL
- 103 SEE ANCHOR BLOCK DETAIL
- 104 1 3/4" MIN. CLEAR COVER
- 105 2" MIN. CLEAR COVER
- 106 1" MIN. CLEAR COVER
- 107 ± 1/8" MEASURED FROM FACE OF CONCRETE BARRIER TO OUTSIDE OF LOOP BAR (TYP.)
- 108 USE DELINEATORS CONFORMING TO SECTION 633 OF THE STANDARD SPECIFICATIONS. CONTRACTOR MY USE ALTERNATE SHAPES AND HOUSING. INSTALL DELINEATORS ACCORDING TO MANUFACTURERS INSTRUCTION. INSTALL YELLOW REFLECTORS WHEN BARRIER IS LOCATED LEFT OF TRAFFIC AND WHITE WHEN BARRIER IS LOCATED RIGHT OF TRAFFIC. SPACE DELINEATORS A MAXIMUM OF 25 FEET APART, PROVIDE TOP MOUNTED DELINEATORS IN ADDITION TO SIDE MOUNTED DELINEATORS ON BARRIER INSTALLATIONS LOCATED ON A CURVED ALIGNMENT LONGER THAT 200 FEET AND ON BARRIERS USED TO SEPARATE OPPOSING TRAFFIC.




CONCRETE BARRIER  
TEMPORARY PRECAST,  
12' - 6"


STATE OF WISCONSIN  
DEPARTMENT OF TRANSPORTATION






B4 BAR DETAIL





B5 BAR DETAIL





PROFILE VIEW  
LOOP BAR ASSEMBLY



C BAR DETAILS




**CONNECTING TEMPORARY BARRIER SECTIONS**




**SIDE VIEW**

**ASPHALT ANCHOR INSTALLATION THROUGH ASPHALT PAVEMENT**




**SIDE VIEW**

**ASPHALT ANCHOR INSTALLATION THROUGH ASPHALT OVERLAY ON TOP OF CONCRETE PAVEMENT**



**SIDE VIEW**

**THROUGH BOLT ANCHOR INSTALLATION**



**SIDE VIEW**


**ADHESIVE ANCHOR INSTALLATION**

**GENERAL NOTES**


- (300) SET WITH 3 5/8" WOOD BLOCK.
- (301) HOLE IS OPTIONAL.
- (302) CONNECTOR PIN ASSEMBLY.
- (303) CONCRETE PAVEMENT, APPROACH SLAB, OR DECK.
- (304) CONCRETE DECK.
- (305) DO NOT USE ON CONCRETE BRIDGE DECK WITH ASPHALT OVERLAY OR CONCRETE PAVEMENT WITH ASPHALT OVERLAY.
- (306) MINIMUM OF 2" OF ASPHALT.
- (307) ASPHALT ANCHOR PIN ASSEMBLY
- (308) IF DRILLING A PILOT HOLE, THE MAX. DIA. OF THE HOLE IS 3/4"
- (309) WHEN THERE IS ASPHALT OVERLAYING CONCRETE PAVEMENT, A 1 5/8" DIA. PILOT HOLE CAN BE DRILLED INTO THE OVERLAY AND CONCRETE. IF NEEDED DRILL A 3/4" PILOT HOLE IN BASE COURSE.

**CONCRETE BARRIER  
TEMPORARY PRECAST,  
12' - 6"**


STATE OF WISCONSIN  
DEPARTMENT OF TRANSPORTATION




**PLAN VIEW**  
**TRANSITION FROM FREE STANDING TO ANCHORED BARRIER**




**PROFILE VIEW**  
**ANCHORED BARRIER NEAR EXPANSION JOINT**




**CROSS SECTION**  
**FREE STANDING BARRIER**



**CROSS SECTION**  
**ANCHORED BARRIER FOR OBJECTS ABOVE  
THE GRADE LINE AND NEAR THE BARRIER**



**CROSS SECTION**  
**ANCHORED BARRIER NEAR VERTICAL DROP OFF**



**CROSS SECTION**  
**ANCHORED BARRIER NEAR A SLOPE**

### GENERAL NOTES

- (400) NO SINGLE CONCRETE BARRIER SECTION SHALL BE ANCHORED TO BOTH THE BRIDGE DECK AND THE APPROACH SLAB. ALL ANCHOR BOLT LOCATIONS SHALL BE ANCHORED TO THE DECK IN ACCORDANCE WITH THE DETAIL. NO MORE THAN ONE ANCHOR BOLT SHALL BE ELIMINATED FROM A BARRIER SECTION WHEN SPANNING AN EXPANSION JOINT.
- (401) CONCRETE DECK
- (402) CONCRETE DECK OR APPROACH SLAB.
- (403) EXPANSION JOINT
- (404) ADHESIVE ANCHOR SHOWN. SEE ANCHOR DETAILS.
- (405) ANCHORED TEMPORARY BARRIER
- (406) TRANSITION FROM ANCHORED TEMPORARY BARRIER TO FREE STANDING
- (407) FREE STANDING BARRIER
- (408) REMOVE ALL ANCHORS WHEN NO LONGER NEEDED. FILL CONCRETE PAVEMENTS, DECKS AND APPROACH SLABS WITH NON-SHRINK COMMERCIAL GROUT FROM THE APPROVED PRODUCT LIST. FILL ASPHALT PAVEMENTS WITH ASTM D6690 TYPE II RUBBERIZED CRACK FILLER.
- (409) TRAFFIC SIDE
- (410) NON-TRAFFIC SIDE
- (411) ANCHOR LOCATION. SEE ANCHORING DETAILS.
- (412) WORK AREA
- (413) AREA FREE OF OBJECTS AND WORKERS
- (414) GRADE LINE
- (415) EXTENDED GRADE LINE
- (416) ANCHORED TEMPORARY BARRIER. SEE BOLT THROUGH DECK, REMOVABLE ADHESIVE ANCHOR, OR AN ASPHALT ANCHOR ROD DETAILS FOR MORE INFORMATION. ASPHALT ANCHOR ROD SHOWN.
- (417) WHEN OBJECTS EXTEND ABOVE THE GRADE. A MINIMUM OF 1 FOOT IS REQUIRED FROM BACK OF BARRIER TO OBJECT.
- (418) OBJECTS ARE NOT TO BE PLACED ON, MOUNTED TO, OR ALLOWED TO LEAN AGAINST THE BARRIER WITHOUT WRITTEN PERMISSION OF THE PROJECT ENGINEER.
- (419) DEPTHS OF 3 FEET OR MORE.
- (420)  $Y = 6.5'$
- (421) OFFSET FROM BACK OF BARRIER EDGE:
- |                   |      |
|-------------------|------|
| CONCRETE PAVEMENT | 0.5' |
| ASPHALT           | 0.5' |
- (422) POSTED SPEED (MPH):
- |               |      |
|---------------|------|
| 45 OR GREATER | 4.0' |
| 40 OR LOWER   | 2.0' |

**CONCRETE BARRIER**  
**TEMPORARY PRECAST,**  
**12' - 6"**

STATE OF WISCONSIN  
DEPARTMENT OF TRANSPORTATION

GENERAL NOTES

- 500 EXISTING RIGID BARRIERS (VARIES)

501 TEMPORARY BARRIER

502 SEE OTHER DETAIL ON HOW TO ANCHOR TEMPORARY BARRIER (BARRIER ASPHALT ANCHOR SHOWN).

503 ANCHORS ARE REQUIRED ON BOTH SIDE OF THE TEMPORARY BARRIER.

504 NESTED RAILS ARE REQUIRED ON BOTH SIDES OF THE TEMPORARY BARRIER FOR ALL INSTALLATIONS.

505 TRAFFIC TRAVELS FROM PERMANENT BARRIER TO TEMPORARY BARRIER.
- 506 TRAFFIC TRAVELS FROM TEMPORARY BARRIER TO PERMANENT BARRIER.

507 VERTICAL BARRIER

508 SAFETY SHAPE BARRIER

509 SINGLE SLOPE BARRIER

510 CAP END PLATE PLACED FLUSH WITH UPSTREAM END OF RIGID BARRIER.

511 BENT THRIE BEAM TO FIT.

512 THRIE BEAM PIECES ARE OFFSET 15 1/4" TO PREVENT INTERFERENCE FROM THE ANCHORS ON OPPOSING SIDES.
- 513 TWO (2) P1, P2 AND P3 ARE REQUIRED

514 FIVE (5) N1, N2 AND N3 ARE REQUIRED


515 TWO (2) R1, R2 AND R3 ARE REQUIRED

516 CUT WOOD BLOCK TO FIT.


517 SEE THRIE BEAM RAIL TERMINAL CONNECTOR DETAIL ASSEMBLY.

518 CAP ASSEMBLY


519 4" MAX. GAP BETWEEN TEMPORARY BARRIER AND RIGID BARRIER.
- 520 ALL TWELVE SPLICE HOLES REQUIRE M1 AND M2




PROFILE VIEW




PLAN VIEW  
TRANSITION TO RIGID BARRIER




PLAN DETAIL VIEW  
TRANSITION TO RIGID BARRIER




FRONT DETAIL VIEW  
TRANSITION TO RIGID BARRIER




CROSS SECTION  
TEMPORARY BARRIER  
PLACEMENT SINGLE SLOPE




CROSS SECTION  
TEMPORARY BARRIER  
PLACEMENT SAFETY SHAPE



CROSS SECTION  
TEMPORARY BARRIER  
PLACEMENT VERTICAL





BACK DETAIL VIEW  
TRANSITION TO RIGID BARRIER



517 DETAIL PLAN VIEW  
THRIE BEAM RAIL TERMINAL CONNECTOR ASSEMBLY

CONCRETE BARRIER  
TEMPORARY PRECAST,  
12' - 6"

STATE OF WISCONSIN  
DEPARTMENT OF TRANSPORTATION



**GENERAL NOTES**

STITCH WELD GUSSET PLATES AND END PLATES ON THREE SIDES


STITCH WELD TWO SIDE PLATES TO TOP PLATE, END PLATE AND GUSSETS.

600 SIDE PLATES (S3) NOT SHOWN FOR CLARITY.


**CONCRETE BARRIER  
TEMPORARY PRECAST,  
12' - 6"**

STATE OF WISCONSIN  
DEPARTMENT OF TRANSPORTATION







SIDE VIEW  
T4



SIDE VIEW  
T3



SIDE VIEW  
TOP PLATE T1



PLAN VIEW  
TOP PLATE T1

END  
VIEW

END  
VIEW


GENERAL NOTES

STITCH WELD GUSSET PLATES AND END PLATES ON THRIE SIDES


STITCH WELD TWO SIDE PLATES TO TOP PLATE, END PLATE AND GUSSETS.

SIDE PLATES, TOP PLATE, END PLATE AND GUSSETS ARE 12 GAUGE ASTM A36 GALVANIZED STEEL.


(700) SIDE PLATES (T3 AND T4) NOT SHOWN FOR CLARITY.




END VIEW  
56 INCH TOP CAP




ISOMETRIC  
56 INCH TOP CAP




SIDE VIEW  
56 INCH TOP CAP (700)




DETAIL "A"



DETAIL "B"



END PLATE T2





GUSSET PLATES  
T5 - T16



| GUSSET DIMENSIONS |           |          |          |         |
|-------------------|-----------|----------|----------|---------|
| GUSSET NO.        | A         | B        | C        | D       |
| T5                | 22 13/16" | 5 1/16"  | 2 5/16"  | 8 1/16" |
| T6                | 21"       | 5 7/8"   | 2 3/16"  | 8 1/16" |
| T7                | 19 3/16"  | 6 1/16"  | 1 15/16" | 8 1/16" |
| T8                | 17 3/8"   | 6 1/4"   | 1 13/16" | 8 1/16" |
| T9                | 15 9/16"  | 6 5/16"  | 1 9/16"  | 8 1/16" |
| T10               | 13 3/4"   | 6 5/8"   | 1 7/16"  | 8 1/16" |
| T11               | 11 15/16" | 6 13/16" | 1 1/4"   | 8 1/16" |
| T12               | 10 1/8"   | 7"       | 1 1/16"  | 8 1/16" |
| T13               | 8 5/16"   | 7 3/16"  | 7/8"     | 8 1/16" |
| T14               | 6 1/2"    | 7 3/8"   | 1 1/16"  | 8 1/16" |
| T15               | 4 1/16"   | 7 9/16"  | 1/2"     | 8"      |
| T16               | 2 7/8"    | 7 3/4"   | 1/4"     | 8"      |

CONCRETE BARRIER  
TEMPORARY PRECAST,  
12' - 6"

STATE OF WISCONSIN  
DEPARTMENT OF TRANSPORTATION




- GENERAL NOTES**
- 800 FREE STANDING TEMPORARY BARRIER
  - 801 GAP STIFFENER ASSEMBLY
  - 802 THRIE BEAMS ARE NESTED ON BOTH SIDES OF THE TEMPORARY BARRIER.
  - 803 SEE THRIE BEAM RAIL TERMINAL CONNECTOR DETAIL




**PORTABLE CONCRETE BARRIER GAP THRIE BEAM COVER**


|   |
|---|
| <b>CONCRETE BARRIER<br/>TEMPORARY PRECAST,<br/>12' - 6"</b> |
| STATE OF WISCONSIN<br>DEPARTMENT OF TRANSPORTATION          |




**PLAN VIEW  
GAP WITHIN SPACING**




**PLAN VIEW  
TEMPORARY BARRIER GAP OVER 4" TO 1' MAX.**



**PLAN VIEW  
TEMPORARY BARRIER GAP OVER 1' TO 4' MAX.**



**PLAN VIEW  
TEMPORARY BARRIER GAP OVER 4' TO 7' MAX.**




**PLAN VIEW  
TEMPORARY BARRIER GAP OVER 7' TO 12.5' MAX.**

**GENERAL NOTES**


- (900) SEE OTHER DETAILS FOR TEMPORARY GAP HARDWARE (TYP.)
- (901) TEMPORARY BARRIER GAP
- (902) GAP STIFFENER ASSEMBLY CENTERED IN THE GAP.
- (903) GAP STIFFENER ASSEMBLY IS OFFSET 18 3/4" FROM CENTER
- (904) MINIMUM NUMBER OF GAP STIFFENERS SHOWN FOR THE GAP RANGE SHOWN.
- (905) MINIMUM OF 8 CONTINUOUS FREE STANDING TEMPORARY BARRIERS

**CONCRETE BARRIER  
TEMPORARY PRECAST,  
12' - 6"**


STATE OF WISCONSIN  
DEPARTMENT OF TRANSPORTATION




**PROFILE VIEW**  
**STIFFENER ASSEMBLY**  
**CENTER PANEL U1**




**FLAT PATTERN**  
**STIFFENER ASSEMBLY**  
**SIDE PANEL U2**




**PROFILE VIEW**  
**STIFFENER ASSEMBLY**  
**BOTTOM PANEL U3**




**SECTION A - A**




**SECTION B - B**




**PLAN VIEW**



**PROFILE VIEW**



**SIDE VIEW**




**ISOMETRIC**

**GAP STIFFENER ASSEMBLY**




**PLAN VIEW**




**SIDE VIEW**

**ELEVATION VIEW**  
**W1 TOE PLATE**




**CONCRETE BARRIER**  
**TEMPORARY PRECAST,**  
**12' - 6"**

STATE OF WISCONSIN  
DEPARTMENT OF TRANSPORTATION




ELEVATION VIEW

**THRIE BEAM  
TERMINAL CONNECTOR**



ELEVATION VIEW


**ADDITIONAL THRIE BEAM  
TERMINAL CONNECTOR HOLE DETAIL**




**PLATE WASHER DETAIL  
G2, H3**

**GENERAL NOTES**

- (1100) 1" DIA. HOLE
- (1101)  $\frac{3}{4}"$  DIA. HOLE
- (1102) PROVIDE HOLES IN THRIE BEAM TERMINAL CONNECTOR TO LIMIT STEEL REINFORCEMENT OR LOOP BAR CONFLICT. CONTRACTOR MAY FIELD DRILL ADDITIONAL HOLE OR PROVIDE THRIE BEAM TERMINAL CONNECTOR WITH ADDITIONAL HOLES FROM SUPPLIER.




**SLOTTED THRIE BEAM RAIL K1**




**SECTION THROUGH  
BEAM K1**

**CONCRETE BARRIER  
TEMPORARY PRECAST,  
12' - 6"**

STATE OF WISCONSIN  
DEPARTMENT OF TRANSPORTATION




**SIDE ELEVATION**  
(FOR CONNECTION TO LEFT END OF BARRIER)




**SIDE ELEVATION**  
LOOP BAR ASSEMBLY INVERTED FOR OPPOSITE END  
(FOR CONNECTION TO RIGHT END OF BARRIER)

**GENERAL NOTES**  
(1200) SEE LIFTING SLOT DETAIL. LOCATION OF LIFTING SLOTS DETERMINED BY CONTRACTOR.




**FLARE AT BARRIER END**


| POSTED SPEED, (MPH) | FLARE RATE |
|---------------------|------------|
| 40 OR LESS          | 6:1        |
| 45 OR GREATER       | 8:1        |



**PLAN VIEW**




**FRONT ELEVATION**




**END SECTION**


**DETAILS OF BARRIER TAPER SECTION**



**BENT BAR DETAIL**



**BENT BAR DETAIL**



| BAR | A          | B      |
|-----|------------|--------|
| B6  | 10"        | 1"     |
| B7  | 1'- 1"     | 1 1/4" |
| B8  | 1'- 5"     | 1 5/8" |
| B9  | 1'- 8"     | 1 7/8" |
| B10 | 2'- 0 1/2" | 2 3/8" |
| B11 | 2'- 3"     | 2 3/4" |

**B BARS**  
2 OF EACH SIZE REQUIRED  
FOR STIRRUP ASSEMBLY

**CONCRETE BARRIER  
TEMPORARY PRECAST,  
12' - 6"**

STATE OF WISCONSIN  
DEPARTMENT OF TRANSPORTATION

6

SDD 14B07-16m

BILL OF MATERIALS - CONCRETE BARRIER PRECAST

| PART | DESCRIPTION                          | MATERIALS SPECIFICATIONS  | NOTES                   |
|------|--------------------------------------|---|-------------------------|
| A1   | PRECAST TEMPORARY BARRIER - CONCRETE | MIN. = f'c 5000 PSI   |                         |
| B1   | REBAR                                | STANDARD SPEC. 505.2 GRADE 60 UNCOATED REBAR  | #5 REBAR, LENGTH 12'-2" |
| B2   | REBAR                                | STANDARD SPEC. 505.2 GRADE 60 UNCOATED REBAR  | #4 REBAR, LENGTH 12'-2" |
| B3   | REBAR                                | STANDARD SPEC. 505.2 GRADE 60 UNCOATED REBAR  | #5 REBAR, LENGTH 12'-2" |
| B4   | REBAR                                | STANDARD SPEC. 505.2 GRADE 60 UNCOATED REBAR  | #4 REBAR, LENGTH 6'-0"  |
| B5   | REBAR                                | STANDARD SPEC. 505.2 GRADE 60 UNCOATED REBAR  | #6 REBAR, LENGTH 2'-11" |
| B6   | REBAR                                | STANDARD SPEC. 505.2 GRADE 60 UNCOATED REBAR  | #4 REBAR, LENGTH 1'-11" |
| B7   | REBAR                                | STANDARD SPEC. 505.2 GRADE 60 UNCOATED REBAR  | #4 REBAR, LENGTH 2'-2"  |
| B8   | REBAR                                | STANDARD SPEC. 505.2 GRADE 60 UNCOATED REBAR  | #4 REBAR, LENGTH 2'-6"  |
| B9   | REBAR                                | STANDARD SPEC. 505.2 GRADE 60 UNCOATED REBAR  | #4 REBAR, LENGTH 2'-9"  |
| B10  | REBAR                                | STANDARD SPEC. 505.2 GRADE 60 UNCOATED REBAR  | #4 REBAR, LENGTH 3'-2"  |
| B11  | REBAR                                | STANDARD SPEC. 505.2 GRADE 60 UNCOATED REBAR  | #4 REBAR, LENGTH 3'-4"  |
| B12  | REBAR                                | STANDARD SPEC. 505.2 GRADE 60 UNCOATED REBAR  | #4 REBAR, LENGTH 12'-0" |
| B13  | REBAR                                | STANDARD SPEC. 505.2 GRADE 60 UNCOATED REBAR  | #4 REBAR, LENGTH 7'-9"  |
| B14  | REBAR                                | STANDARD SPEC. 505.2 GRADE 60 UNCOATED REBAR  | #5 REBAR, LENGTH 11'-9" |
| C1   | LOOP BAR                             | ASTM A709 GRADE 70 SMOOTH BAR OR ASTM A706 GRADE 60 REBAR UNCOATED  | ¾" DIA.                 |
| C2   | LOOP BAR                             | ASTM A709 GRADE 70 SMOOTH BAR OR ASTM A706 GRADE 60 REBAR UNCOATED  | ¾" DIA.                 |
| C3   | LOOP BAR                             | ASTM A709 GRADE 70 SMOOTH BAR OR ASTM A706 GRADE 60 REBAR UNCOATED  | ¾" DIA.                 |
| D1   | CONNECTION PIN - ROD                 | ASTM A36 MIN. STRENGTH 36 KSI / ASTM A529 MAX. STRENGTH 50 KSI / ASTM A572 MAX STRENGTH 50 KSI / ASTM A709 MAX STRENGTH 50 KSI / ASTM A992 MAX STRENGTH 50 KSI  | 1 ¼" DIA.               |
| D2   | CONNECTION PIN - TOP PLATE           | ASTM A36 MIN. STRENGTH 36 KSI / ASTM A529 MAX. STRENGTH 50 KSI / ASTM A572 MAX STRENGTH 50 KSI / ASTM A709 MAX STRENGTH 50 KSI / ASTM A992 MAX STRENGTH 50 KSI  |                         |
| G1   | BOLT THROUGH ANCHOR - THREADED ROD   | HOT DIP AASHTO M232 CLASS / ASTM A153 CLASS C / ASTM F2329 C OR MECHANICAL GALVANIZE TO AASHTO M298 CLASS 55 TYPE 2 / ASTM B695 CLASS 55 TYPE 2 A307 GRADE A OR SAE J429 GRADE 2 UNC  | 1 ⅝" DIA.               |
| G2   | BOLT THROUGH ANCHOR - WASHER, SQUARE | ASTM A36 MIN. STRENGTH 36 KSI / ASTM A529 MAX. STRENGTH 50 KSI / ASTM A572 MAX STRENGTH 50 KSI / ASTM A709 MAX STRENGTH 50 KSI / ASTM A992 MAX STRENGTH 50 KSI  |                         |
| G3   | BOLT THROUGH ANCHOR - NUT            | HOT DIP AASHTO M232 CLASS / ASTM A153 CLASS C / ASTM F2329 C OR MECHANICAL GALVANIZE TO AASHTO M298 CLASS 55 TYPE 2 / ASTM B695 CLASS 55 UNC OVER TAP NUTS AS SPECIFIED IN AASHTO 291 / ASTM A 563 HEAVY HEX HEAD ASTM A563DH OR SAE J995 GRADE 5 |                         |
| H1   | ADHESIVE ANCHOR - ADHESIVE           | ICC-ES-AC308 5 ¼" EMBEDMENT WITH A MIN. BOND STRENGTH OF 1,650 PSI. SEE 603.2 AND 603.3.1.2 OF THE WISCONSIN STANDARD SPECIFICATIONS FOR MORE INFORMATION ON ADHESIVE ANCHORS.  |                         |
| H2   | ADHESIVE ANCHOR - THREADED ROD       | HOT DIP AASHTO M232 CLASS / ASTM A153 CLASS C / ASTM F2329 C OR MECHANICAL GALVANIZE TO AASHTO M298 CLASS 55 TYPE 2 / ASTM B695 CLASS 55 TYPE 2 A307 GRADE A / SAE J429 GRADE 2 UNC   | 1 ⅝" DIA.               |
| H3   | ADHESIVE ANCHOR - WASHER, SQUARE     | ASTM A36 MIN. STRENGTH 36 KSI / ASTM A529 MAX. STRENGTH 50 KSI / ASTM A572 MAX STRENGTH 50 KSI / ASTM A709 MAX STRENGTH 50 KSI / ASTM A992 MAX STRENGTH 50 KSI  |                         |
| H4   | ADHESIVE ANCHOR - NUT                | HOT DIP AASHTO M232 CLASS / ASTM A153 CLASS C / ASTM F2329 C OR MECHANICAL GALVANIZE TO AASHTO M298 CLASS 55 TYPE 2 / ASTM B695 CLASS 55 UNC OVER TAP NUTS AS SPECIFIED IN AASHTO 291 / ASTM A 563 HEAVY HEX HEAD ASTM A563DH OR SAE J995 GRADE 5 |                         |
| J1   | ASPHALT ANCHOR PIN - ROD             | ASTM A36 MIN. STRENGTH 36 KSI / ASTM A529 MAX. STRENGTH 50 KSI / ASTM A572 MAX STRENGTH 50 KSI / ASTM A709 MAX STRENGTH 50 KSI / ASTM A992 MAX STRENGTH 50 KSI  | 1 ½" DIA.               |
| J2   | ASPHALT ANCHOR PIN - STOP PLATE      | ASTM A36 MIN. STRENGTH 36 KSI / ASTM A529 MAX. STRENGTH 50 KSI / ASTM A572 MAX STRENGTH 50 KSI / ASTM A709 MAX STRENGTH 50 KSI / ASTM A992 MAX STRENGTH 50 KSI  |                         |
| K1   | THRIE BEAM RAIL                      | AASHTO M180 CLASS A TYPE 2 APPROVED PRODUCER  | 12 GAUGE                |
| L1   | THRIE BEAM RAIL - TERMINAL           | AASHTO M180 CLASS A TYPE 2 APPROVED PRODUCER  | 12 GAUGE                |

| PART | DESCRIPTION  | MATERIALS SPECIFICATIONS   | NOTES             |
|------|--|--|-------------------|
| M1   | SPLICE BOLT  | HOT DIP AASHTO M232 CLASS / ASTM A153 CLASS C / ASTM F2329 C OR MECHANICAL GAL. TO AASHTO M298 CLASS 55 TYPE 2 / ASTM B695 CLASS 55 TYPE 2 UNC AASHTO M180 HEAD ASTM A307 GRADE B OR SAE J429 GRADE 2 OR ASTM F1554 GRADE 36   | ⅝" DIA.           |
| M2   | SPLICE BOLT - NUT  | HOT DIP AASHTO M232 CLASS / ASTM A153 CLASS C / ASTM F2329 C OR MECHANICAL GALVANIZE TO AASHTO M298 CLASS 55 TYPE 2 / ASTM B695 CLASS 55 UNC OVER TAP NUTS AS SPECIFIED IN AASHTO 291 / ASTM A 563 AASHTO M180 RECESSED HEAVY HEX HEAD ASTM A563DH OR SAE J995 GRADE 5 |                   |
| N1   | THRIE BEAM RAIL TERMINAL - MECHANICAL ANCHOR               | HOT DIP AASHTO M232 CLASS / ASTM A153 CLASS C / ASTM F2329 C OR MECHANICAL GALVANIZE TO AASHTO M298 CLASS 55 TYPE 2 / ASTM B695 CLASS 55 UNC OVER TAP NUTS AS SPECIFIED IN AASHTO 291 / ASTM A 563 AASHTO M180 RECESSED HEAVY HEX HEAD ASTM A563DH OR SAE J995 GRADE 5 | ¾" DIA. LENGTH 6" |
| N2   | THRIE BEAM RAIL TERMINAL - WASHER                          | HOT DIP AASHTO M232 CLASS / ASTM A153 CLASS C / ASTM F2329 C OR MECHANICAL GALVANIZE TO AASHTO M298 CLASS 55 TYPE 2 / ASTM B695 CLASS 55 TYPE 2 F436 TYPE 1  |                   |
| N3   | THRIE BEAM RAIL TERMINAL MECHANICAL OR ADHESIVE ANCHOR     | MINIMUM MECHANICAL OR ADHESIVE ANCHOR STRENGTH REQUIREMENTS: ULTIMATE TENSILE LOAD 17.9 KIPS AND ULTIMATE SHEAR LOAD 21.96 KIPS. SEE 603.2 AND 603.3.1.2 OF THE WISCONSIN STANDARD SPECIFICATIONS FOR MORE INFORMATION ON ADHESIVE ANCHORS.                            |                   |
| P1   | THRIE BEAM RAIL CONNECTION 1-BOLT                          | HOT DIP AASHTO M232 CLASS / ASTM A153 CLASS C / ASTM F2329 C OR MECHANICAL GALVANIZE TO AASHTO M298 CLASS 55 TYPE 2 / ASTM B695 CLASS 55 UNC OVER TAP NUTS AS SPECIFIED IN AASHTO 291 / ASTM A 563 AASHTO M180 RECESSED HEAVY HEX HEAD ASTM A563DH OR SAE J995 GRADE 5 | ¾" DIA.           |
| P2   | THRIE BEAM RAIL CONNECTION 1-WASHER                        | HOT DIP AASHTO M232 CLASS / ASTM A153 CLASS C / ASTM F2329 C OR MECHANICAL GAL. TO AASHTO M298 CLASS 55 TYPE 2 / ASTM B695 CLASS 55 TYPE 2 F436 TYPE 1   |                   |
| P3   | THRIE BEAM RAIL CONNETION 1- MECHANICAL OR ADHESIVE ANCHOR | MINIMUM MECHANICAL OR ADHESIVE ANCHOR STRENGTH REQUIREMENTS: ULTIMATE TENSILE LOAD 9.48 KIPS AND ULTIMATE SHEAR LOAD 10.48 KIPS. SEE 603.2 AND 603.3.1.2 OF THE WISCONSIN STANDARD SPECIFICATIONS FOR MORE INFORMATION ON ADHESIVE ANCHORS.                            |                   |
| Q1   | BLOCK WOOD   | SEE STANDARD SPEC. 614   |                   |
| R1   | CAP - BOLT   | HOT DIP AASHTO M232 CLASS / ASTM A153 CLASS C / ASTM F2329 C OR MECHANICAL GALVANIZE TO AASHTO M298 CLASS 55 TYPE 2 / ASTM B695 CLASS 55 UNC OVER TAP NUTS AS SPECIFIED IN AASHTO 291 / ASTM A 563 AASHTO M180 RECESSED HEAVY HEX HEAD ASTM A563DH OR SAE J995 GRADE 5 | ⅝" DIA.           |
| R2   | CAP- BOLT - WASHER   | HOT DIP AASHTO M232 CLASS / ASTM A153 CLASS C / ASTM F2329 C OR MECHANICAL GAL. TO AASHTO M298 CLASS 55 TYPE 2 / ASTM B695 CLASS 55 TYPE 2 F436 TYPE 1   |                   |
| R3   | CAP - BOLT - MECHANICAL ANCHOR                             | MINIMUM MECHANICAL OR ADHESIVE ANCHOR STRENGTH REQUIREMENTS ULTIMATE TENSILE LOAD 12.14 KIPS AND ULTIMATE SHEAR LOAD 17.5 KIPS.SEE 603.2 AND 603.3.1.2 OF THE WISCONSIN STANDARD SPECIFICATIONS FOR MORE INFORMATION ON ADHESIVE ANCHORS.                              | 12 GAUGE          |
| S1   | CAP 42-INCH TOP PLATE                                      | AASHTO M111 / ASTM A123 ASTM A36 MIN. STRENGTH 36 KSI, OR ASTM A529 MAX. STRENGTH 50 KSI, OR ASTM A572 MAX. STRENGTH 50 KSI, OR ASTM A709 MAX. STRENGTH 50 KSI, OR ASTM A992 MAX. STRENGTH 50 KSI  | 12 GAUGE          |
| S2   | CAP 42-INCH END PLATE                                      | AASHTO M111 / ASTM A123 ASTM A36 MIN. STRENGTH 36 KSI, OR ASTM A529 MAX. STRENGTH 50 KSI, OR ASTM A572 MAX. STRENGTH 50 KSI, OR ASTM A709 MAX. STRENGTH 50 KSI, OR ASTM A992 MAX. STRENGTH 50 KSI  | 12 GAUGE          |
| S3   | CAP 42-INCH SIDE PLATE                                     | AASHTO M111 / ASTM A123 ASTM A36 MIN. STRENGTH 36 KSI, OR ASTM A529 MAX. STRENGTH 50 KSI, OR ASTM A572 MAX. STRENGTH 50 KSI, OR ASTM A709 MAX. STRENGTH 50 KSI, OR ASTM A992 MAX. STRENGTH 50 KSI  | 12 GAUGE          |
| S4   | CAP 42-INCH GUSSET 1                                       | AASHTO M111 / ASTM A123 ASTM A36 MIN. STRENGTH 36 KSI, OR ASTM A529 MAX. STRENGTH 50 KSI, OR ASTM A572 MAX. STRENGTH 50 KSI, OR ASTM A709 MAX. STRENGTH 50 KSI, OR ASTM A992 MAX. STRENGTH 50 KSI  | 12 GAUGE          |
| S5   | CAP 42-INCH GUSSET 2                                       | AASHTO M111 / ASTM A123 ASTM A36 MIN. STRENGTH 36 KSI, OR ASTM A529 MAX. STRENGTH 50 KSI, OR ASTM A572 MAX. STRENGTH 50 KSI, OR ASTM A709 MAX. STRENGTH 50 KSI, OR ASTM A992 MAX. STRENGTH 50 KSI  | 12 GAUGE          |
| S6   | CAP 42-INCH GUSSET 3                                       | AASHTO M111 / ASTM A123 ASTM A36 MIN. STRENGTH 36 KSI, OR ASTM A529 MAX. STRENGTH 50 KSI, OR ASTM A572 MAX. STRENGTH 50 KSI, OR ASTM A709 MAX. STRENGTH 50 KSI, OR ASTM A992 MAX. STRENGTH 50 KSI  | 12 GAUGE          |
| S7   | CAP 42-INCH GUSSET 4                                       | AASHTO M111 / ASTM A123 ASTM A36 MIN. STRENGTH 36 KSI, OR ASTM A529 MAX. STRENGTH 50 KSI, OR ASTM A572 MAX. STRENGTH 50 KSI, OR ASTM A709 MAX. STRENGTH 50 KSI, OR ASTM A992 MAX. STRENGTH 50 KSI  | 12 GAUGE          |

6

SDD 14B07-16m

CONCRETE BARRIER  
TEMPORARY PRECAST,  
12' - 6"

STATE OF WISCONSIN  
DEPARTMENT OF TRANSPORTATION

BILL OF MATERIALS - CONCRETE BARRIER PRECAST

| PART | DESCRIPTION                          | MATERIALS SPECIFICATIONS  | NOTES    |
|------|--------------------------------------|---|----------|
| T1   | CAP 56-INCH TOP PLATE                | AASHTO M111 / ASTM A123 ASTM A36 MIN. STRENGTH 36 KSI, OR ASTM A529 MAX. STRENGTH 50 KSI, OR ASTM A572 MAX. STRENGTH 50 KSI, OR ASTM A709 MAX. STRENGTH 50 KSI, OR ASTM A992 MAX. STRENGTH 50 KSI | 12 GAUGE |
| T2   | CAP 56-INCH END PLATE                | AASHTO M111 / ASTM A123 ASTM A36 MIN. STRENGTH 36 KSI, OR ASTM A529 MAX. STRENGTH 50 KSI, OR ASTM A572 MAX. STRENGTH 50 KSI, OR ASTM A709 MAX. STRENGTH 50 KSI, OR ASTM A992 MAX. STRENGTH 50 KSI | 12 GAUGE |
| T3   | CAP 56-INCH SIDE PLATE 1             | AASHTO M111 / ASTM A123 ASTM A36 MIN. STRENGTH 36 KSI, OR ASTM A529 MAX. STRENGTH 50 KSI, OR ASTM A572 MAX. STRENGTH 50 KSI, OR ASTM A709 MAX. STRENGTH 50 KSI, OR ASTM A992 MAX. STRENGTH 50 KSI | 12 GAUGE |
| T4   | CAP 56-INCH SIDE PLATE 2             | AASHTO M111 / ASTM A123 ASTM A36 MIN. STRENGTH 36 KSI, OR ASTM A529 MAX. STRENGTH 50 KSI, OR ASTM A572 MAX. STRENGTH 50 KSI, OR ASTM A709 MAX. STRENGTH 50 KSI, OR ASTM A992 MAX. STRENGTH 50 KSI | 12 GAUGE |
| T5   | CAP 56-INCH GUSSET 1                 | AASHTO M111 / ASTM A123 ASTM A36 MIN. STRENGTH 36 KSI, OR ASTM A529 MAX. STRENGTH 50 KSI, OR ASTM A572 MAX. STRENGTH 50 KSI, OR ASTM A709 MAX. STRENGTH 50 KSI, OR ASTM A992 MAX. STRENGTH 50 KSI | 12 GAUGE |
| T6   | CAP 56-INCH GUSSET 2                 | AASHTO M111 / ASTM A123 ASTM A36 MIN. STRENGTH 36 KSI, OR ASTM A529 MAX. STRENGTH 50 KSI, OR ASTM A572 MAX. STRENGTH 50 KSI, OR ASTM A709 MAX. STRENGTH 50 KSI, OR ASTM A992 MAX. STRENGTH 50 KSI | 12 GAUGE |
| T7   | CAP 56-INCH GUSSET 3                 | AASHTO M111 / ASTM A123 ASTM A36 MIN. STRENGTH 36 KSI, OR ASTM A529 MAX. STRENGTH 50 KSI, OR ASTM A572 MAX. STRENGTH 50 KSI, OR ASTM A709 MAX. STRENGTH 50 KSI, OR ASTM A992 MAX. STRENGTH 50 KSI | 12 GAUGE |
| T8   | CAP 42-INCH GUSSET 4                 | AASHTO M111 / ASTM A123 ASTM A36 MIN. STRENGTH 36 KSI, OR ASTM A529 MAX. STRENGTH 50 KSI, OR ASTM A572 MAX. STRENGTH 50 KSI, OR ASTM A709 MAX. STRENGTH 50 KSI, OR ASTM A992 MAX. STRENGTH 50 KSI | 12 GAUGE |
| T9   | CAP 42-INCH GUSSET 5                 | AASHTO M111 / ASTM A123 ASTM A36 MIN. STRENGTH 36 KSI, OR ASTM A529 MAX. STRENGTH 50 KSI, OR ASTM A572 MAX. STRENGTH 50 KSI, OR ASTM A709 MAX. STRENGTH 50 KSI, OR ASTM A992 MAX. STRENGTH 50 KSI | 12 GAUGE |
| T10  | CAP 42-INCH GUSSET 6                 | AASHTO M111 / ASTM A123 ASTM A36 MIN. STRENGTH 36 KSI, OR ASTM A529 MAX. STRENGTH 50 KSI, OR ASTM A572 MAX. STRENGTH 50 KSI, OR ASTM A709 MAX. STRENGTH 50 KSI, OR ASTM A992 MAX. STRENGTH 50 KSI | 12 GAUGE |
| T11  | CAP 42-INCH GUSSET 7                 | AASHTO M111 / ASTM A123 ASTM A36 MIN. STRENGTH 36 KSI, OR ASTM A529 MAX. STRENGTH 50 KSI, OR ASTM A572 MAX. STRENGTH 50 KSI, OR ASTM A709 MAX. STRENGTH 50 KSI, OR ASTM A992 MAX. STRENGTH 50 KSI | 12 GAUGE |
| T12  | CAP 42-INCH GUSSET 8                 | AASHTO M111 / ASTM A123 ASTM A36 MIN. STRENGTH 36 KSI, OR ASTM A529 MAX. STRENGTH 50 KSI, OR ASTM A572 MAX. STRENGTH 50 KSI, OR ASTM A709 MAX. STRENGTH 50 KSI, OR ASTM A992 MAX. STRENGTH 50 KSI | 12 GAUGE |
| T13  | CAP 42-INCH GUSSET 9                 | AASHTO M111 / ASTM A123 ASTM A36 MIN. STRENGTH 36 KSI, OR ASTM A529 MAX. STRENGTH 50 KSI, OR ASTM A572 MAX. STRENGTH 50 KSI, OR ASTM A709 MAX. STRENGTH 50 KSI, OR ASTM A992 MAX. STRENGTH 50 KSI | 12 GAUGE |
| T14  | CAP 42-INCH GUSSET 10                | AASHTO M111 / ASTM A123 ASTM A36 MIN. STRENGTH 36 KSI, OR ASTM A529 MAX. STRENGTH 50 KSI, OR ASTM A572 MAX. STRENGTH 50 KSI, OR ASTM A709 MAX. STRENGTH 50 KSI, OR ASTM A992 MAX. STRENGTH 50 KSI | 12 GAUGE |
| T15  | CAP 42-INCH GUSSET 11                | AASHTO M111 / ASTM A123 ASTM A36 MIN. STRENGTH 36 KSI, OR ASTM A529 MAX. STRENGTH 50 KSI, OR ASTM A572 MAX. STRENGTH 50 KSI, OR ASTM A709 MAX. STRENGTH 50 KSI, OR ASTM A992 MAX. STRENGTH 50 KSI | 12 GAUGE |
| T16  | CAP 42-INCH GUSSET 12                | AASHTO M111 / ASTM A123 ASTM A36 MIN. STRENGTH 36 KSI, OR ASTM A529 MAX. STRENGTH 50 KSI, OR ASTM A572 MAX. STRENGTH 50 KSI, OR ASTM A709 MAX. STRENGTH 50 KSI, OR ASTM A992 MAX. STRENGTH 50 KSI | 12 GAUGE |
| U1   | GAP STIFFENER                        | AASHTO M111 / ASTM A123 ASTM A36 MIN. STRENGTH 36 KSI, OR ASTM A529 MAX. STRENGTH 50 KSI, OR ASTM A572 MAX. STRENGTH 50 KSI, OR ASTM A709 MAX. STRENGTH 50 KSI, OR ASTM A992 MAX. STRENGTH 50 KSI |          |
| U2   | GAP STIFFENER<br>- CONNECTOR PLATE 1 | AASHTO M111 / ASTM A123 ASTM A36 MIN. STRENGTH 36 KSI, OR ASTM A529 MAX. STRENGTH 50 KSI, OR ASTM A572 MAX. STRENGTH 50 KSI, OR ASTM A709 MAX. STRENGTH 50 KSI, OR ASTM A992 MAX. STRENGTH 50 KSI |          |
| U3   | GAP STIFFENER<br>- CONNECTOR PLATE 2 | AASHTO M111 / ASTM A123 ASTM A36 MIN. STRENGTH 36 KSI, OR ASTM A529 MAX. STRENGTH 50 KSI, OR ASTM A572 MAX. STRENGTH 50 KSI, OR ASTM A709 MAX. STRENGTH 50 KSI, OR ASTM A992 MAX. STRENGTH 50 KSI |          |


| PART | DESCRIPTION  | MATERIALS SPECIFICATIONS   | NOTES   |
|------|--|--|---------|
| V1   | THRIE BEAM RAIL TERMINAL<br>MECHANICAL OR ADHESIVE<br>ANCHOR | MINIMUM MECHANICAL OR ADHESIVE ANCHOR STRENGTH REQUIREMENTS ULTIMATE TENSILE LOAD 24.0 KIPS AND ULTIMATE SHEAR LOAD 21.5 KIPS. SEE 603.2 AND 603.3.1.2 OF THE WISCONSIN STANDARD SPECIFICATIONS FOR MORE INFORMATION ON ADHESIVE ANCHORS.  | ¾" DIA. |
| V2   | GAP STIFFENER - BOLT - NUT                                   | HOT DIP AASHTO M232 CLASS / ASTM A153 CLASS C / ASTM F2329 C O R MECHANICAL GALVANIZE TO AASHTO M298 CLASS 50 TYPE 1 / ASTM B695 CLASS 50 TYPE 1 UNC OVER TAP NUTS AS SPECIFIED IN AASHTO 291/ASTM A 563 HEAVY HEX HEAD ASTM A563DH OR SAE J995 GRADE 5  |         |
| W1   | TOE PLATE  | AASHTO M111/ASTM A123 ASTM A36 MIN STRENGTH 36 KSI, OR ASTM A529 MAX. STRENGTH 50 KSI, OR ASTM A572 MAX. STRENGTH 50 KSI, OR ASTM A709 MAX. STRENGTH 50 KSI, OR ASTM A992 MAX. STRENGTH 50 KSI   |         |
| X1   | TOE PLATE<br>- CONNECTION BOLT                               | HOT DIP AASHTO M232 CLASS / ASTM A153 CLASS C / ASTM F2329 C OR MECHANICAL GALVANIZE TO AASHTO M298 CLASS 55 TYPE 2 / ASTM B695 CLASS 55 TYPE 2 UNC HEAVY HEX HEAD OR AASTHO M180 HEAD, ASTM F3125 GRADE A325 TYPE 1 HEAVY HEX HEAD OR SAE J429 GRADE 5 HEAVY HEX HEAD / ASTM A449 TYPE 1 HEAVY HEX HEAD. BOLTS MAY BE FULLY THREADED. PROVIDE ENOUGH THREADING FOR PROPER TIGHTENING OF BOLT. | ¾" DIA. |
| X2   | TOE PLATE<br>- CONNECTION BOLT - WASHER                      | HOT DIP AASHTO M232 CLASS / ASTM A153 CLASS C / ASTM F2329 C OR MECHANICAL GALVANIZE TO AASHTO M298 CLASS 55 TYPE 2 / ASTM B695 CLASS 55 TYPE 2 F436 TYPE 1 (HARDEN WASHER ONLY)   |         |
| X3   | TOE PLATE -<br>CONNECTION BOLT - NUT                         | HOT DIP AASHTO M232 CLASS / ASTM A153 CLASS C / ASTM F2329 C OR MECHANICAL GALVANIZE TO AASHTO M298 CLASS 55 TYPE 2 / ASTM B695 CLASS 55 UNC OVER TAP NUTS AS SPECIFIED IN AASHTO 291 / ASTM A 563 HEAVY HEX HEAD ASTM A563DH OR SAE J995 GRADE 5  |         |

CONCRETE BARRIER  
TEMPORARY PRECAST,  
12' - 6"

STATE OF WISCONSIN  
DEPARTMENT OF TRANSPORTATION

APPROVED  
February 2023  
DATE /S/ Rodney Taylor  
ROADWAY STANDARDS DEVELOPMENT  
ENGINEER  
FHWA






**DIMENSION A TABLE** <sup>(2)</sup>

| FACILITY               | POSTED SPEED<br>MPH            | DIMENSION A |            |
|------------------------|--------------------------------|-------------|------------|
|                        |                                | MIN.<br>FT  | MAX.<br>FT |
| FREEWAY/EXPRESSWAY     | ALL                            | 15          | 20         |
| NON-FREEWAY/EXPRESSWAY | GREATER THAN<br>OR EQUAL TO 45 | 10          | 15         |
| NON-FREEWAY/EXPRESSWAY | LESS THAN 45                   | 8           | 10         |
| AADT LESS THAN 1,500   | ALL                            | 8           | 10         |

**DIMENSION B TABLE**<sup>(2)</sup>

| POSTED SPEEDS MPH | DIMENSION B FT |
|-------------------|----------------|
| 20                | 115            |
| 25                | 155            |
| 30                | 200            |
| 35                | 250            |
| 40                | 305            |
| 45                | 360            |
| 50                | 425            |
| 55                | 495            |
| 60                | 570            |
| 65                | 645            |

## CRASH CUSHION/SAND BARREL ARRAY AND TEMPORARY BARRIER INSTALLATION FOR TRAFFIC ON ONE SIDE OF BARRIER



**CRASH CUSHION/SAND BARREL ARRAY AND TEMPORARY BARRIER  
INSTALLATION FOR TRAFFIC ON BOTH SIDES OF BARRIER**

## GENERAL NOTES

SEE STANDARD DETAIL DRAWING 14B7 FOR MORE INFORMATION.

DETAILS PROVIDE A GENERAL LAYOUT OF TEMPORARY CONCRETE BARRIER, CRASH CUSHIONS, SAND BARREL ARRAYS AND TIE DOWN TRANSITIONS. DETAILS PROVIDED MAY NOT FIT ALL POSSIBLE SITUATIONS OR SITE CONDITIONS. SEE OTHER SECTIONS OF THE CONTRACT OR PROJECT ENGINEER FOR MORE DETAILS.

ADDITIONAL TEMPORARY BARRIER MAY BE REQUIRED TO PROTECT TRAVELING PUBLIC FROM HAZARDS, CONTRACTOR'S OPERATIONS OR TO CONTROL TRAFFIC.








TEMPORARY BARRIER MAY BE REQUIRED TO BE ANCHORED TO PAVEMENT OR BRIDGE DECK.

FOR DETAILS ON CRASH CUSHION OR SAND BARREL ARRAYS SEE OTHER SECTIONS OF THE PLAN AND MANUFACTURE'S DETAILS.

SLOPES LEADING TO TEMPORARY BARRIER, CRASH CUSHION OR SAND BARREL ARRAY ARE 10:1 OR LESS.


- ① FOR DEFLECTION INFORMATION SEE STANDARD DETAIL DRAWING 14B7.
- ② VALUES PROVIDED MAY NOT FIT ALL POSSIBLE SITUATIONS OR SITE CONDITIONS. SEE OTHER SECTIONS OF THE CONTRACT OR PROJECT ENGINEER FOR MORE DETAILS.
- ③ ANCHOR TEMPORARY BARRIER ACCORDING TO CRASH CUSHION OR SAND BARREL MANUFACTURER'S RECOMMENDATIONS. IF MANUFACTURER'S RECOMMENDATIONS ARE NOT PROVIDED, ANCHOR 3 PINS ON TRAFFIC SIDE.

### LEGEND


- |   |   |
|---|---|
| DIRECTION OF TRAVEL                                       |  |
| CRASH CUSHION OR SAND BARREL ARRAY                        |  |
| SEE FREE STANDING TRANSITION TO TIED-DOWN SYSTEM DETAILS  |  |
| SEE BI-DIRECTIONAL TRANSITION TO TIED-DOWN SYSTEM DETAILS |  |
| 3 PINS PLACED ON TRAFFIC SIDE OF BARRIER                  |  |
| PERMANENT CONCRETE BARRIER OR CONCRETE PARAPET            |  |
| FREE STANDING TEMPORARY BARRIER                           |  |

### CRASH CUSHION/SAND BARREL ARRAY AND OTHER TEMPORARY BARRIER LAYOUT DETAILS

STATE OF WISCONSIN  
DEPARTMENT OF TRANSPORTATION



**CRASH CUSHION/SAND BARREL ARRAY AND TEMPORARY BARRIER  
INSTALLATION FOR TRAFFIC ON ONE SIDE - FLARED INSTALLATION**




**TRANSITION FROM FREE STANDING TEMPORARY BARRIER  
TO ANCHORED BARRIER**

**LEGEND**


|   |  |
|---|--|
| DIRECTION OF TRAVEL                                       |  |
| CRASH CUSHION OR SAND BARREL ARRAY                        |  |
| SEE FREE STANDING TRANSITION TO TIED-DOWN SYSTEM DETAILS  |  |
| SEE BI-DIRECTIONAL TRANSITION TO TIED-DOWN SYSTEM DETAILS |  |
| 3 PINS PLACED ON TRAFFIC SIDE OF BARRIER                  |  |
| PERMANENT CONCRETE BARRIER OR CONCRETE PARAPET            |  |
| FREE STANDING TEMPORARY BARRIER                           |  |

**CRASH CUSHION/SAND BARREL  
ARRAY AND OTHER TEMPORARY  
BARRIER LAYOUT DETAILS**


STATE OF WISCONSIN  
DEPARTMENT OF TRANSPORTATION




**TEMPORARY BARRIER OVERLAP - ONE-WAY TRAFFIC**



**TEMPORARY BARRIER OVERLAP - TWO-WAY TRAFFIC**



**ENDING TEMPORARY BARRIER  
DOWNSTREAM - UNANCHORED**




**ENDING TEMPORARY BARRIER  
DOWNSTREAM - ANCHORED**

**LEGEND**


|  |  |
|--|--|
| DIRECTION OF TRAVEL  |  |
| CRASH CUSHION OR<br>SAND BARREL ARRAY                        |  |
| SEE FREE STANDING TRANSITION<br>TO TIED-DOWN SYSTEM DETAILS  |  |
| SEE BI-DIRECTIONAL TRANSITION<br>TO TIED-DOWN SYSTEM DETAILS |  |
| 3 PINS PLACED ON<br>TRAFFIC SIDE OF BARRIER                  |  |
| PERMANENT CONCRETE BARRIER<br>OR CONCRETE PARAPET            |  |
| FREE STANDING TEMPORARY<br>BARRIER                           |  |

**CRASH CUSHION/SAND BARREL  
ARRAY AND OTHER TEMPORARY  
BARRIER LAYOUT DETAILS**

STATE OF WISCONSIN  
DEPARTMENT OF TRANSPORTATION




CONNECTING TEMPORARY BARRIER TO PERMANENT  
CONCRETE BARRIER-TRAFFIC ON ONE SIDE




CONNECTING TEMPORARY BARRIER TO PERMANENT  
CONCRETE BARRIER-TRAFFIC ON BOTH SIDES

LEGEND

- DIRECTION OF TRAVEL
- CRASH CUSHION OR SAND BARREL ARRAY
- SEE FREE STANDING TRANSITION TO TIED-DOWN SYSTEM DETAILS
- SEE BI-DIRECTIONAL TRANSITION TO TIED-DOWN SYSTEM DETAILS
- 3 PINS PLACED ON TRAFFIC SIDE OF BARRIER
- PERMANENT CONCRETE BARRIER OR CONCRETE PARAPET
- FREE STANDING TEMPORARY BARRIER



OVERLAPPING TEMPORARY BARRIER AND PERMANENT BARRIER -  
ONE WAY TRAFFIC




OVERLAPPING TEMPORARY BARRIER AND PERMANENT BARRIER -  
TWO WAY TRAFFIC


CRASH CUSHION/SAND BARREL  
ARRAY AND OTHER TEMPORARY  
BARRIER LAYOUT DETAILS


STATE OF WISCONSIN  
DEPARTMENT OF TRANSPORTATION


LEGEND


- DIRECTION OF TRAVEL



- CRASH CUSHION OR SAND BARREL ARRAY



- SEE FREE STANDING TRANSITION TO TIED-DOWN SYSTEM DETAILS


- SEE BI-DIRECTIONAL TRANSITION TO TIED-DOWN SYSTEM DETAILS


- 3 PINS PLACED ON TRAFFIC SIDE OF BARRIER


- PERMANENT CONCRETE BARRIER OR CONCRETE PARAPET


- FREE STANDING TEMPORARY BARRIER



DIMENSION C TABLE

2

| AVAILABLE DEFLECTION DISTANCE                | MINIMUM LENGTH OF BARRIER BEYOND HAZARD FT |
|--|--|
| GREATER THAN 8'                              | 12.5                                       |
| LESS THAN OR EQUAL TO 8' BUT GREATER THAN 4' | 50   |
| LESS THAN OR EQUAL TO 4'                     | 100  |

6

6

CRASH CUSHION/SAND BARREL  
ARRAY AND OTHER TEMPORARY  
BARRIER LAYOUT DETAILS

STATE OF WISCONSIN  
DEPARTMENT OF TRANSPORTATION

APPROVED

June, 2015

DATE

FHWA

/S/ Jerry H. Zogg


ROADWAY STANDARDS DEVELOPMENT  
ENGINEER



## PERMANENT PAVEMENT MARKING

APPROVED  
May 2023  
DATE

/S/ Jeannie Silver  
Statewide Pavement Marking Engineer



TEMPORARY BARRIER OFFSET FROM EDGE LINE


GENERAL NOTES

DETAILS OF CONSTRUCTION NOT SHOWN ON THIS DRAWING SHALL CONFORM TO STANDARD SPECIFICATIONS AND SPECIAL PROVISIONS.


LEGEND

DIRECTION OF TRAFFIC


\* CONFIRM MARKING LINE WIDTH WITH THE MISCELLANEOUS QUANTITIES



TWO WAY TRAFFIC




ONE WAY TRAFFIC



FREEWAYS AND EXPRESSWAYS

TEMPORARY PAVEMENT MARKING

| TEMPORARY LONGITUDINAL PAVEMENT MARKING            |   |
|--|---|
| STATE OF WISCONSIN<br>DEPARTMENT OF TRANSPORTATION |   |
| APPROVED<br>May 2023<br>DATE                       | /S/ Jeannie Silver<br>Statewide Pavement Marking Engineer |



**GENERAL NOTES**

- ① A SET OF ARROWS IS REQUIRED EVERY 400 FEET OR NEAR INTERSECTIONS OR DRIVEWAYS WITH TURNING TRAFFIC.
- ② 10" WHITE
- ③ TURN BAY LENGTH OF LESS THAN 48' DOES NOT REQUIRE PAVEMENT ARROWS OR TEXT.


➡ DIRECTION OF TRAFFIC

\* CONFIRM MARKING LINE WIDTH WITH THE MISCELLANEOUS QUANTITIES

**PAVEMENT MARKING  
(TURN LANES)**

STATE OF WISCONSIN  
DEPARTMENT OF TRANSPORTATION








\*\* (SEE TURN LANE OPTIONS FOR PLACEMENT OF PAVEMENT MARKING ARROWS AND WORDS)

TURN LANE OPTIONS

LENGTH OF TURN BAY ( L ) OF 0 - 47' DOES NOT REQUIRE PAVEMENT MARKING ARROWS OR WORDS



GENERAL NOTES

① QUANTITY AND LOCATION OF TYPE 3 ARROWS ARE THE SAME AS THE TYPE II ARROWS IN THE ADJACENT TURN LANE. FOR TURN LANES WITH A PHYSICAL SEPARATION IN THE SAME DIRECTION OF TRAVEL, THE ARROWS AND "ONLY" MARKING MAY BE ELIMINATED.


➡ DIRECTION OF TRAFFIC

L = LENGTH OF TURN BAY

\* CONFIRM MARKING LINE WIDTH WITH THE MISCELLANEOUS QUANTITIES


PAVEMENT MARKING (TURN LANES)

STATE OF WISCONSIN  
DEPARTMENT OF TRANSPORTATION




**DRUM**

BALLAST WIDTHS  
RANGE FROM 24"-36"




**42" CONE**

DO NOT USE IN TAPERS  
½ SPACING OF DRUMS  
BALLAST WIDTHS  
RANGE FROM 14"-20"




**VERTICAL PANEL**

THE STRIPES SHALL SLOPE DOWNWARD TO  
THE TRAFFIC SIDE FOR CHANNELIZATION.



**TYPE II BARRICADE**

FOR RAILS LESS THAN 36" LONG, 4" WIDE STRIPES  
MAY BE USED. ALL STRIPES SHALL SLOPE DOWNWARD  
TO THE TRAFFIC SIDE FOR CHANNELIZATION.



**TYPE III BARRICADE**

IF SIGN MOUNTED, DO NOT COVER MORE THAN 50% OF THE TOP  
TWO RAILS OR 33% OF THE TOTAL AREA OF THE THREE RAILS.

\* IF USED FOR A PERMANENT APPLICATION USE RED SHEETING.

**GENERAL NOTES**

- ① REFLECTIVE SHEETING SHALL FOLLOW THE REQUIREMENTS IN THE APPROVED PRODUCTS LISTING FOR SIGN SHEETING.
- ② LOCATION OF WARNING LIGHTS WHEN SHOWN ON THE PLAN.











**CHANNELIZING DEVICES  
DRUMS, CONES, BARRICADES  
AND VERTICAL PANELS**

STATE OF WISCONSIN  
DEPARTMENT OF TRANSPORTATION


APPROVED  
November 2022 /S/ Andrew Heidtke  
DATE WORK ZONE ENGINEER

FHWA

## LEGEND

- |   |  |
|---|--|
|  | TYPE III BARRICADE WITH ATTACHED SIGN                |
|  | SIGN ON PERMANENT SUPPORT                            |
|  | TRAFFIC CONTROL DRUM WITH TYPE "C" STEADY BURN LIGHT |
|  | TRAFFIC CONTROL DRUM                                 |
|  | FLAGS, 16" X 16" MIN. (ORANGE)                       |
|  | REMOVING PAVEMENT MARKING                            |
|  | DIRECTION OF TRAFFIC                                 |
|  | ASPHALTIC PAVEMENT WIDENING                          |
|  | CONCRETE BARRIER TEMPORARY PRECAST                   |
|  | TEMPORARY SIGNAL. SEE SDD 09G02 FOR EXACT PLACEMENT  |

WIDTH ON SIGN TO BE APPROX. 1-FOOT  
LESS THAN AVAILABLE WIDTH. (OMIT IF  
AVAILABLE WIDTH IS MORE THAN 16 FEET)



## GENERAL NOTES

THE EXACT NUMBER, LOCATION, AND SPACING OF ALL SIGNS AND DEVICES SHALL BE ADJUSTED TO FIT FIELD CONDITIONS AS APPROVED BY THE ENGINEER.

THE SPACING BETWEEN TRAFFIC CONTROL SIGNS SHOULD BE ADJUSTED TO NOT CONFLICT WITH AND TO PROVIDE A MINIMUM OF 200 FEET (500 FEET DESIRABLE) CLEARANCE TO EXISTING SIGNS THAT WILL REMAIN IN PLACE..

THIS LANE CLOSURE IS TYPICAL FOR CLOSING RIGHT LANE - REVERSE FOR CLOSING LEFT LANE.

ALL SIGNS ARE 48" x 48" UNLESS OTHERWISE NOTED.

"WO" IS THE SAME AS "W" EXCEPT THE BACKGROUND IS ORANGE.

ANY SIGNS TEMPORARY OR EXISTING, WHICH CONFLICT WITH TRAFFIC CONTROL "IN USE" SHALL BE REMOVED OR COVERED AS NEEDED OR AS APPROVED BY THE ENGINEER.

REMOVE PAVEMENT MARKING AND PLACE TEMPORARY PAVEMENT MARKING LINES IF THE CLOSURE IS TO BE IN PLACE FOR 4 OR MORE CONTINUOUS DAYS AND NIGHTS.

INSTALL OVERHEAD TEMPORARY SIGNAL HEADS ABOVE THE MIDDLE OF THE TRAVEL LANE THEY ARE CONTROLLING.

- ① 500 FOOT SPACING SHOWN IS FOR ROADWAYS WITH A PRE-CONSTRUCTION REGULATORY SPEED LIMIT OF 45 MPH OR MORE. FOR 35 - 40 MPH, USE 350 FOOT TYPICAL SPACING. FOR 25 - 30 MPH, USE 200 FOOT TYPICAL SPACING.
- ② USE 300 FOOT SPACING IF THE PRE - CONSTRUCTION REGULATORY SPEED IS 35 MPH OR LESS.
- ③ DIMENSION DETERMINED BY CBTP TAPER FROM EDGE LINE TO TANGENT SECTION OF THE ROAD.
- ④ TEMPORARY PAVEMENT MARKING LINE, 18 INCH WHITE STOP LINE.
- ⑤ 700 FOOT TEMPORARY PAVEMENT MARKING LINE, 6 INCH DOUBLE YELLOW . WHEN THE DISTANCE FOR THE PRECEDING NO - PASSING ZONE IS LESS THAN THE MINIMUM DISTANCE BETWEEN ZONES AS INDICATED IN THE SPECIFICATIONS, THE TWO ZONES SHALL BE CONNECTED.
- ⑥ SEE SDD 15C02 - SHEET "F" FOR ADVANCED WIDTH RESTRICTION SIGNING.

## TRAFFIC CONTROL, ONE LANE ROAD WITH TEMPORARY SIGNALS

STATE OF WISCONSIN  
DEPARTMENT OF TRANSPORTATION

APPROVED  
May 2023  
DATE

/S/ Andrew Heidtke  
WORK ZONE ENGINEER

## GENERAL NOTES

DRAWINGS SHALL NOT BE SCALED.

DIMENSIONS BASED ON ORIGINAL STRUCTURE PLANS.

BAR STEEL REINFORCEMENT SHALL BE EMBEDDED 2" CLEAR UNLESS OTHERWISE SHOWN OR NOTED.

THE FIRST OR FIRST TWO DIGITS OF THE BAR MARK SIGNIFIES THE BAR SIZE.

BEVEL EXPOSED EDGES OF CONCRETE  $\frac{3}{4}$ " UNLESS OTHERWISE NOTED.

REMOVE EXISTING POSTS 14 TO 17 AND REPLACE WITH NEW POSTS.

MATCH NEW CONCRETE TO EXISTING DECK ELEVATIONS.

PROTECTIVE SURFACE TREATMENT TO BE APPLIED TO THE TOP, EDGE AND 1'-0" TO THE UNDERSIDE OF THE NEW PORTIONS OF DECK.

## DESIGN DATA

## MATERIAL PROPERTIES:

CONCRETE MASONRY: DECK  $F'_c = 4,000$  PSIBAR STEEL REINFORCEMENT: GRADE 60  $F_y = 60,000$  PSI

## PARTIAL SECTION THRU DECK

(LOOKING EAST)

## AREA OF DECK REPLACEMENT

(FULL DEPTH)

## RAILING JOINT PLAN

## SCOPE OF WORK

1. FULL DEPTH REMOVAL AND REPLACEMENT OF DECK AS INDICATED BY DESIGN ENGINEER
2. REMOVAL AND REPLACEMENT OF POSTS AND STRUCTURAL TUBING RAILS AS INDICATED BY DESIGN ENGINEER

## LIST OF DRAWINGS

1. RAILING & DECK REPAIR
2. TUBULAR RAILING TYPE 'F'





## LEGEND

- ▲ SALVAGE AND INCORPORATE EXISTING SLAB REINFORCEMENT INTO NEW WORK AS DETAILED.
- \* ALL LINES OF DECK REMOVAL SHALL BE DEFINED BY A 1" DEEP SAW CUT TOP AND BOTTOM. EDGE TROWEL NEW DECK & APPLY LOW VISCOSITY CRACK SEALER.
- AFTER REMOVAL OF PINNED TEMPORARY ROADWAY BARRIER, PATCH THE HOLES IN THE DECK WITH A DEPARTMENT APPROVED RAPID SETTING CONCRETE PATCH MATERIAL OR NON-SHRINK GROUT. WORK SHALL BE INCIDENTAL TO OTHER BID ITEMS.
- SALVAGE EXISTING GIRDER STIRRUPS AND INCORPORATE INTO NEW WORK.
- INDICATES RAIL POST NUMBER.
- INDICATES GIRDER NUMBER

## STRUCTURE DESIGN CONTACTS:

ISATOU CEESAY 608-266-9557  
DOMINIQUE BECHLE 608-261-8205


|                                 |                                  |             |               |
|---------------------------------|----------------------------------|-------------|---------------|
| NO.                             | DATE                             | REVISION    | BY            |
| <b>BUREAU OF STRUCTURES</b>     |                                  |             |               |
| ACCEPTED                        | CHIEF STRUCTURES DESIGN ENGINEER |             | DATE 08/06/24 |
| <b>STRUCTURE B-13-190</b>       |                                  |             |               |
| STH 19 OVER MAUNESHA RIVER      |                                  |             |               |
| COUNTY                          | DANE                             | TOWN        | MEDINA        |
| DESIGN SPEC. REHABILITATION N/A |                                  |             |               |
| DESIGNED BY                     | IFC                              | DESIGN CK'D | ACT           |
| DRAWN BY                        |                                  |             | IFC           |
| PLANS CK'D                      |                                  |             | ACT           |
| <b>RAIL &amp; DECK REPAIR</b>   |                                  |             | SHEET 1 OF 2  |



## BILL OF BARS

NOTE: THE FIRST OR FIRST TWO DIGITS OF THE BAR MARK SIGNIFIES THE BAR SIZE.

| BAR MARK | COA | NO. REQ'D. | LENGTH | BENT | BAR SERIES | LOCATION                               |
|----------|-----|------------|--------|------|------------|--|
| S401     | X   | 130        | 5'-11" |      |            | SLAB - TRANS. - TOP & BOT.             |
| S402     | X   | 9          | 31'-8" |      |            | SLAB - LONGIT. - BOT.                  |
| S403     | X   | 32         | 3'-6"  |      |            | SLAB - TRANS. - TOP - EDGE             |
| S604     | X   | 9          | 31'-8" |      |            | SLAB - LONGIT. - TOP                   |
| S605     | X   | 8          | 4'-0"  |      |            | SLAB - LONGIT. @ RAIL POSTS #14 TO #17 |
| S606     | X   | 8          | 12'-0" | X    |            | SLAB - TRANS. @ RAIL POSTS #14 TO #17  |



## TOTAL ESTIMATED QUANTITIES

| BID ITEM NUMBER | BID ITEMS                                    | UNIT | TOTALS |
|-----------------|--|------|--------|
| 203.0220        | REMOVING STRUCTURE B-13-190                  | EACH | 1      |
| 502.0100        | CONCRETE MASONRY BRIDGES                     | CY   | 5.3    |
| 502.3200        | PROTECTIVE SURFACE TREATMENT                 | SY   | 28     |
| 505.0600        | BAR STEEL REINFORCEMENT HS COATED STRUCTURES | LB   | 1,400  |
| 513.4051        | RAILING TUBULAR TYPE F                       | LF   | 65     |

LEGEND

- ① W6X25 WITH 1 1/4" DIA. HOLES ON EACH SIDE OF POST FOR STUD NO. 6. CUT BOTTOM OF POST TO MATCH CROSS SLOPE OF ROADWAY. PLACE POSTS NORMAL TO GRADE LINE.
- ② PLATE 1" X 9 1/2" X 10", WITH 1 1/16" X 1 1/2" SLOTTED HOLES FOR ANCHOR BOLTS NO. 3. WELD TO NO. 1 AS SHOWN.
- ③ A325 - 7/8" DIA. X 8" LONG HEX BOLTS (GALVANIZED) WITH A325 NUT & WASHER. 4 REQ'D. PER POST. THREAD 3" AND PLACE NORMAL TO PLATE NO. 2. CHAMFER TOP OF BOLTS BEFORE THREADING.
- ④ 1/4" X 8" X 8" FLAT BAR, WITH 1 1/16" DIA. HOLES FOR ANCHOR BOLTS NO.3.
- ⑤ TS 4 X 4 X 0.25 STRUCTURAL TUBING, CONFORMING TO ASTM DESIGNATION A501 OR A500 GRADE B. ATTACH TO NO. 1 WITH TWO NO. 6 STUDS.
- ⑥ 5/8" DIA. X 1 1/2" LG. SHOP WELDED STUDS WITH HEX NUT AND 2" WASHERS. (2 REQ'D AT EACH RAIL TO POST LOCATION.) STUDS MAY BE FIELD WELDED TO MATCH LOCATION OF HOLES IN EXISTING POSTS.
- ⑨ SQUARE SLEEVE FABRICATED FROM 1/4" PLATE. PROVIDE "SLIDING FIT" WITH A MINIMUM OUT TO OUT DIMENSION OF 3 13/32".
- ⑩ TS 3 X 3 X 0.25 X (1'-10" AT FIELD JOINTS) LONG. PROVIDE 1/2" DIA. SURFACE WELDS ON ALL SIDES AS SHOWN. GRIND WELDS TO FIT FREE INTO I.D. OF NO. 5. PROVIDE 3/8" DIA. X 1/2" WELDING STUDS ON TOP AND BOTTOM SURFACES AT CENTERLINE.

GENERAL NOTES

BID ITEM SHALL BE "RAILING TUBULAR TYPE B-13-190", WHICH INCLUDES ALL ITEMS SHOWN.

RAILING SHALL BE FABRICATED IN LENGTHS THAT INCLUDE 3 OR 4 POSTS

POST BASE PLATES, NO. 2, SHALL BE FLAT WITH ALL SURFACES SMOOTH, STRAIGHT AND FREE FROM WARP AND ALL EDGES SMOOTH, STRAIGHT AND VERTICAL. ALL PLATE CUTS SHALL BE MACHINE OR MACHINE FLAME CUT.

ALL MATERIAL, EXCEPT ANCHORAGE DETAIL NO. 4 SHALL BE GALVANIZED AFTER FABRICATION. PRIOR TO GALVANIZING, ALL STEEL RAILING POSTS & STEEL TUBING SHALL BE GIVEN A NO. 6 BLAST CLEANING BY SSPC SPECIFICATIONS.


FILL BOLT SLOT OPENINGS IN POST SHIMS AND PLATE NO. 2 WITH NON-STAINING GRAY NON-BITUMINOUS JOINT SEALER.

ALL MATERIALS USED IN FABRICATION SHALL BE MADE FROM MATERIALS CONFORMING TO ASTM DESIGNATION A709 GRADE 36 UNLESS NOTED OTHERWISE.


STEEL POST SHIMS MAY BE USED UNDER POSTS WHERE REQ'D. FOR ALIGNMENT.

PLACE FIRST BOTTOM LONGITUDINAL BAR CLEAR OF DRIP GROOVE.


▲ TIE TO TOP MAT OF STEEL.



SECTION THRU RAILING ON DECK  
(SHOWN AT NEW POSTS #14, #15, #16 AND #17)




SECTION A-A




SHOP RAIL  
SPLICE DETAIL

(LOCATION MUST BE SHOWN  
ON SHOP DRAWINGS)




POST SHIM  
DETAIL

4 PER POST



FIELD ERECTION  
JOINT DETAIL

☆ MIN. 3/8" FLAT SURFACE DIA.  
PUNCHINGS OR STUDS MAY  
BE USED AS AN ALTERNATE.



ANCHORAGE DETAIL

| NO.   | DATE | REVISION | BY             |
|---|------|----------|----------------|
| STATE OF WISCONSIN<br>DEPARTMENT OF TRANSPORTATION<br>STRUCTURES DESIGN SECTION |      |          |                |
| STRUCTURE B-13-190  |      |          |                |
| DRAWN BY  |      | IFC      | PLANS CK'D ACT |
| TUBULAR RAILING<br>TYPE 'F'   |      | SHEET 2  |                |



## ***Wisconsin Department of Transportation***

Dedicated people creating transportation solutions  
through innovation and exceptional service.

<http://www.dot.wisconsin.gov>