

## **Wisconsin Department of Transportation**

November 4, 2024

# **Division of Transportation Systems Development**

Bureau of Project Development 4822 Madison Yards Way, 4<sup>th</sup> Floor South Madison, WI 53705

Telephone: (608) 266-1631 Facsimile (FAX): (608) 266-8459

### **NOTICE TO ALL CONTRACTORS:**

Proposal #29: 4679-02-71, WISC 2025040

Buchanan – East County Line CTH ZZ to Outagamie Road

CTH Z

**Outagamie County** 

### Letting of November 12, 2024

This is Addendum No. 01, which provides for the following:

### **Special Provisions:**

Revised Special Provisions					
Article No.	Description				
19	Select Borrow, Item 208.1100.				

### Plan Sheets:

Revised Plan Sheets					
Plan Sheet	eet Plan Sheet Title (brief description of changes to sheet)				
7	Construction Details—modified Settlement Gauge Detail and Marsh Excavation Detail to				
	indicate backfill methods required if alternative materials are used for Select Borrow				

The responsibility for notifying potential subcontractors and suppliers of these changes remains with the prime contractor.

Sincerely,

Mike Coleman

Proposal Development Specialist Proposal Management Section

### ADDENDUM NO. 01 4679-02-71 November 4, 2024

#### **Special Provisions**

### 19. Select Borrow, Item 208.1100.

Replace the entire article language with the following:

Conform to standard spec 208 as modified in this special provision.

#### Material

Furnish and use material that consists of granular material meeting the following requirements:

Backfill Granular Grade 1 or 2 conforming to standard spec 209

Base Aggregate Dense 3-Inch conforming to standard spec 305

Breaker Run conforming to standard spec 311

Select Crushed Material conforming to standard spec 312, or

Pit Run conforming to standard spec 313.

stp-208-005 (20031103)

If Breaker Run, Select Crushed Material, or Pit Run are used as Select Borrow, place a layer of Geotextile Type SAS (conforming to standard spec 645) or 12 inches of Base Aggregate Dense 3-Inch between the Select Borrow material and the Base Aggregate Dense 1 ¼-Inch used beneath the HMA pavement. Geotextile Type SAS shall be incidental to Select Borrow if used as a separation layer. Base Aggregate Dense-3 Inch used as a separation layer shall be paid for measured quantities at the contract unit price for Select Borrow.

QMP Base Aggregate provisions do not apply to Base Aggregate Dense material that is used as Select Borrow.

### Plan Sheets

The following  $8\frac{1}{2}$  x 11-inch sheets are attached and made part of the plans for this proposal: Revised: 7.

**END OF ADDENDUM** 

