

WIS

PROJECT ID:  
WITH: N/A

6987-02-70


COUNTY:

WAUSHARA

FEBRUARY 2025  
ORDER OF SHEETS

Section No.	1	Title
Section No.	2	Typical Sections and Details
Section No.	3	Estimate of Quantities
Section No.	3	Miscellaneous Quantities
Section No.	4	Right of Way Plat
Section No.	5	Plan and Profile
Section No.	6	Standard Detail Drawings
Section No.	7	Sign Plates
Section No.	8	Structure Plans
Section No.	9	Computer Earthwork Data
Section No.	9	Cross Sections

TOTAL SHEETS = 76



DESIGN DESIGNATION 6987-02-00

A.A.D.T.	2025	=	800
A.A.D.T.	2045	=	1,190
D.H.V.		=	107
D.D.		=	60/40
T.		=	10% ASSUMED
DESIGN SPEED		=	50 M.P.H.
ESALS		=	847,300


CONVENTIONAL SYMBOLS

PLAN	
CORPORATE LIMITS	
PROPERTY LINE	
LOT LINE	
LIMITED HIGHWAY EASEMENT	
EXISTING RIGHT OF WAY	
PROPOSED OR NEW R/W LINE	
SLOPE INTERCEPT	
REFERENCE LINE	
EXISTING CULVERT	
PROPOSED CULVERT (Box or Pipe)	
COMBUSTIBLE FLUIDS	
MARSH AREA	
WOODED OR SHRUB AREA	

PROFILE	
GRADE LINE	
ORIGINAL GROUND	
MARSH OR ROCK PROFILE (To be noted as such)	
SPECIAL DITCH	
GRADE ELEVATION	
CULVERT (Profile View)	
UTILITIES	
ELECTRIC	
FIBER OPTIC	
GAS	
SANITARY SEWER	
STORM SEWER	
TELEPHONE	
WATER	
UTILITY PEDESTAL	
POWER POLE	
TELEPHONE POLE	

BEGIN PROJECT  
STA. 8+80

Y=157,553.02  
X=439,501.41



SCALE 0 2 MI

TOTAL NET LENGTH OF CENTERLINE = 0.066 MI

HORIZONTAL POSITIONS SHOWN ON THIS PLAN ARE WISCONSIN COORDINATE REFERENCE SYSTEM (WISCRS), WAUSHARA COUNTY, NAD83 (2011), IN U.S. SURVEY FEET. POSITIONS SHOWN ARE GRID COORDINATES, GRID BEARINGS, AND GRID DISTANCES. GRID DISTANCES ARE THE SAME AS GROUND DISTANCES.

ELEVATIONS ARE REFERENCED TO NAVD 88 (2012). GPS DERIVED ELEVATIONS ARE BASED ON GEOID (18).

STATE OF WISCONSIN  
DEPARTMENT OF TRANSPORTATION

PLAN OF PROPOSED IMPROVEMENT

REDGRANITE - CTH H

LITTLE SILVER LAKE CREEK BRIDGE, B-69-0054

CTH E

WAUSHARA COUNTY

STATE PROJECT NUMBER  
6987-02-70

END PROJECT  
STA. 12+30

STATE PROJECT	FEDERAL PROJECT	
	PROJECT	CONTRACT
6987-02-70		

ACCEPTED FOR

COUNTY WAUSHARA

10/10/24 Robert B. Hanold  
(Date) (Highway Commissioner)

ORIGINAL PLANS PREPARED BY

**JEWELL**  
associates engineers, inc  
Engineers - Architects - Surveyors

WISCONSIN  
ROBERT B. HANOLD  
E-45655  
PRAIRIE DU SAC  
WI  
PROFESSIONAL ENGINEER 10/10/2024  
Robert B. Hanold

STATE OF WISCONSIN  
DEPARTMENT OF TRANSPORTATION

PREPARED BY	
Surveyor	JEWELL ASSOCIATES ENGINEERS, INC.
Designer	JEWELL ASSOCIATES ENGINEERS, INC.
Project Manager	JASON SCHAEFFER
Regional Examiner	NC REGION
Regional Supervisor	DAN ERVA, P.E.

APPROVED FOR THE DEPARTMENT  
DATE: 10/29/2024 (Signature)

E

GENERAL NOTES

THE LOCATIONS OF EXISTING AND PROPOSED UTILITY INSTALLATIONS AS SHOWN ON THE PLAN ARE APPROXIMATE. THERE MAY BE OTHER UTILITY INSTALLATIONS WITHIN THE PROJECT AREA THAT ARE NOT SHOWN.

NO TREES OR SHRUBS ARE TO BE REMOVED UNLESS SUCH TREES OR SHRUBS HAVE FIRST BEEN INDICATED FOR REMOVAL BY THE ENGINEER IN THE FIELD.

EXCAVATION BELOW SUBGRADE (EBS) IS NOT USED TO BALANCE YARDAGE, AND IS NOT SHOWN ON THE CROSS SECTIONS BUT IS MEASURED AND PAID FOR AS COMMON EXCAVATION. EXACT LOCATIONS OF EBS WILL BE DETERMINED BY THE ENGINEER IN THE FIELD.

UNLESS SHOWN OTHERWISE, DISTURBED AREAS SHOWN WITHIN THE RIGHT-OF-WAY, EXCEPT THE AREAS WITHIN THE FINISHED SHOULDER POINTS ARE TO BE FERTILIZED (TYPE B), SEEDED (USE SEED MIX NO. 20), AND MULCHED AS DIRECTED BY THE ENGINEER. ALL POST CONSTRUCTION WET AREAS SHALL BE SEEDED WITH SEEDING MIXTURE NO. 60. DO NOT FERTILIZE WETLAND AREAS.

WHEN THE QUANTITY OF THE ITEM OF BASE AGGREGATE DENSE OR ASPHALTIC SURFACE IS MEASURED FOR PAYMENT BY THE TON, THE DEPTH OR THICKNESS OF THE COURSE SHOWN ON THE PLANS IS APPROXIMATE, AND THE ACTUAL THICKNESS WILL DEPEND ON THE DISTURBUTION OF MATERIAL AS DIRECTED BY THE ENGINEER IN THE FIELD.

SILT FENCE, TURBIDITY BARRIER, AND TEMPORARY DITCH CHECKS SHALL BE PLACED AS SHOWN ON THE PLAN OR AS DIRECTED BY THE ENGINEER IN THE FIELD. SILT FENCE AND TURBIDITY BARRIER SHALL BE PLACED PRIOR TO CONSTRUCTION AND SHALL BE IN PLACE PRIOR TO STRUCTURE REMOVAL.

REMOVAL OF ASPHALTIC SURFACES WHERE AN ABUTTING ASPHALTIC SURFACE IS TO REMAIN IN PLACE SHALL REQUIRE A SAWCUT MEETING THE APPROVAL OF THE ENGINEER IN THE FIELD.

THE LOCATION OF ALL PERMANENT SIGNING SHALL BE VERIFIED BY THE ENGINEER IN THE FIELD PRIOR TO PLACEMENT.

WETLANDS ARE PRESENT IN THE PROJECT LIMITS. THE CONTRACTOR SHALL NOT OPERATE EQUIPMENT OR STOCKPILE MATERIALS BEYOND THE EXISTING SLOPE INTERCEPT FROM STA. 9+40 - STA. 10+54 RT, STA. 9+82 - STA. 10+52 LT, STA. 10+85 - STA. 11+54 RT, STA. 10+86 - STA. 12+20 LT.

ASPHALTIC SURFACE QUANTITIES WERE CALCULATED USING 115 LB/SY/IN.

ADD TACK COAT AT A RATE OF 0.05 GAL/SY.

5-INCHES OF ASPHALTIC SURFACE SHALL BE CONSTRUCTED WITH A 1 ¾-INCH UPPER LAYER LAYER AND A 3 ¼-INCH LOWER LAYER.

ADJUST DITCH GRADING AS NECESSARY TO FIT FIELD CONDITIONS AND AS DIRECTED BY THE ENGINEER IN THE FIELD.

CONTACTS

**WAUSHARA COUNTY HIGHWAY DEPARTMENT:**  
BRIAN FREIMARK, COMMISSIONER  
1001 EAST MAIN STREET  
WAUTOMA, WI 54982  
PHONE: (920) 787-3327  
EMAIL: brian.freimark@co.waushara.wi.us

**WISCONSIN DEPT. OF TRANSPORTATION**  
WISDOT PROJECT MANAGER  
1681 SECOND AVENUE SOUTH  
WISCONSIN RAPIDS, WI 54495  
ATTN: JASON SCHAEFFER  
PHONE: (715) 421-7309  
EMAIL: jason.schaeffer@dot.wi.gov

**DESIGN CONSULTANT:**  
JEWELL ASSOCIATES ENGINEERS, INC.  
560 SUNRISE DRIVE  
SPRING GREEN, WI 53588  
ATTN: ROBERT HANOLD, P.E.  
PHONE: (608) 588-7484  
CELL: (608) 606-3568  
EMAIL: robert.hanold@jewellassoc.com

**DNR LIAISON:**  
DNR NORTH CENTRAL REGION HEADQUARTERS  
625 EAST COUNTY ROAD Y, SUITE 700  
OSHKOSH, WI 54901  
ATTN: MARTY DILLENBURG  
PHONE: (920) 410-7428  
EMAIL: marty.dillenburg@wisconsin.gov

UTILITIES

**ELECTRIC**  
ALLIANT ENERGY  
ATTN: CORY CLINCH  
880 N. WISCONSIN STREET  
BERLIN, WI 54923  
PHONE: (920) 361-5668  
EMAIL: coreyclinch@alliantenergy.com

**GAS**  
WE ENERGIES  
ATTN: LARRY KOCH  
1921 8TH STREET SOUTH  
WISCONSIN RAPIDS, WI 54494  
PHONE: (715) 421-7249  
EMAIL: larry.koch@we-energies.com

**COMMUNICATION LINE**  
AT&T  
ATTN: CHUCK BARTELT  
70 EAST DIVISION STREET  
FOND DU LAC, WI 54935  
PHONE: (920) 410-5104  
EMAIL: cb1461@att.com

BRIGHTSPEED  
ATTN: SCOTT HEINZELMAN  
144 N. PEARL STREET  
BERLIN, WI 54923  
PHONE: (920) 757-4802  
EMAIL: scott.heinzelman@brightspeed.com

DIGGERSHOTLINE




Dial 811 or (800) 242-8511


www.DiggersHotline.com

\*UTILITY NOT PART OF DIGGERS HOTLINE

LIST OF STANDARD ABBREVIATIONS

ABUT	Abutment	INV	Invert	RDWY	Roadway
AC	Acre	IP	Iron Pipe or Pin	SALV	Salvaged
AGG	Aggregate	IRS	Iron Rod Set	SAN S	Sanitary Sewer
AH	Ahead	JT	Joint	SEC	Section
<	Angle	JCT	Junction	SHLDR	Shoulder
ASPH	Asphaltic	LHF	Left-Hand Forward	SHR	Shrinkage
AVG	Average	L	Length of Curve	SW	Sidewalk
ADT	Average Daily Traffic	LIN FT or LF	Linear Foot	S	South
BAD	Base Aggregate Dense	LC	Long Chord of Curve	SQ	Square
BK	Back	MH	Manhole	SF or SQ FT	Square Feet
BF	Back Face	MB	Mailbox	SY or SQ YD	Square Yard
BM	Bench Mark	ML or M/L	Match Line	STD	Standard
BR	Bridge	N	North	SDD	Standard Detail Drawings
C or C/L	Center Line	Y	North Grid Coordinate	STH	State Trunk Highways
CC	Center to Center	O.A.L.	Overall Length	STA	Station
CTH	County Trunk Highway	OD	Outside Diameter	SS	Storm Sewer
CR	Creek	PLE	Permanent Limited Easement	SG	Subgrade
CR	Crushed	PT	Point	SE	Superelevation
CY or CU YD	Cubic Yard	PC	Point of Curvature	SL or S/L	Survey Line
CP	Culvert Pipe	PI	Point of Intersection	SV	Septic Vent
C & G	Curb and Gutter	PRC	Point of Reverse Curvature	T	Tangent
D	Degree of Curve	PT	Point of Tangency	TEL	Telephone
DHV	Design Hour Volume	POC	Point On Curve	TEMP	Temporary
DIA	Diameter	POT	Point on Tangent	TI	Temporary Interest
E	East	PVC	Polyvinyl Chloride	TLE	Temporary Limited Easement
X	East Grid Coordinate	PCC	Portland Cement Concrete	t	Ton
ELEC	Electric (al)	LB	Pound	T or TN	Town
EL or ELEV	Elevation	PSI	Pounds Per Square Inch	TRANS	Transition
ESALS	Equivalent Single Axle Loads	PE	Private Entrance	TL or T/L	Transit Line
EBS	Excavation Below Subgrade	R	Radius	T	Trucks (percent of)
ESTR	Existing Sign to Remain	RR	Railroad	TYP	Typical
FF	Face to Face	R	Range	UNCL	Unclassified
FE	Field Entrance	RL or R/L	Reference Line	UG	Underground Cable
F	Fill	RP	Reference Point	USH	United States Highway
FG	Finished Grade	RCCP	Reinforced Concrete Culvert	VAR	Variable
FL or F/L	Flow Line		Pipe	V	Velocity or Design Speed
FT	Foot	REQ'D	Required	VERT	Vertical
FTG	Footing	RES	Residence or Residential	VC	Vertical Curve
GN	Grid North	RW	Retaining Wall	VOL	Volume
HT	Height	RT	Right	WM	Water Main
CWT	Hundredweight	RHF	Right-Hand Forward	WV	Water Valve
HYD	Hydrant	R/W	Right-of-Way	W	West
INL	Inlet	R	River	WB	Westbound
ID	Inside Diameter	RD	Road	YD	Yard







BEAMGUARD LAYOUT TABLE

QUADRANT	LOCATION	STATION				
		①	②	③	④	⑤
SOUTHEAST	MAINLINE, RT.	8+36	8+81	9+55	10+08	10+46
SOUTHWEST	MAINLINE, LT.	8+80	8+90	9+65	10+18	10+56
NORTHWEST	MAINLINE, LT.	12+12	12+09	11+89	11+36	10+98
NORTHEAST	MAINLINE, RT.	12+35	12+26	11+79	11+26	10+88


GUARDRAIL LAYOUT DETAIL




SECTION A-A



PLAN VIEW



PROFILE VIEW




CROSS SECTION VIEW

1. EXACT LOCATION OF E.B.S. (EXCAVATION BELOW SUBGRADE) SHALL BE DETERMINED BY THE ENGINEER IN THE FIELD.
2. E.B.S. AREA TO BE BACKFILLED WITH MATERIAL ACCEPTABLE TO THE ENGINEER. BACKFILL MUST BE HOMOGENEOUS WITH ADJOINING FILL MATERIAL.
3. THE FILL SECTION WITHIN 100' OF THE MOUTH OF THE CUT MUST BE KEPT 2' BELOW SUBGRADE UNTIL E.B.S. IS COMPLETED. LATERAL LIMITS OF EXCAVATION SHALL BE THE SUBGRADE SHOULDER POINTS.

EXCAVATION BELOW SUBGRADE (E.B.S.) DETAIL



NO.	STA.	DESCRIPTION	Y	X
1	8+53	¾" IRON REBAR SET, 22.5' LT.	157,525.82	439,478.78
2	12+54	¾" IRON REBAR SET, 34.8' RT.	157,926.54	439,538.10
3	10+32	¾" IRON REBAR SET, 18.5' RT.	157,704.43	439,520.65



Estimate Of Quantities

6987-02-70

Line	Item	Item Description	Unit	Total	Qty
0002	201.0205	Grubbing	STA	4.000	4.000
0004	203.0270	Removing Structure Over Waterway Debris Capture (structure) 01. B-69-0202	EACH	1.000	1.000
0006	204.0110	Removing Asphaltic Surface	SY	550.000	550.000
0008	205.0100	Excavation Common	CY	610.000	610.000
0010	205.0508.S	Excavation, Hauling, and Disposal of Potential Creosote Contaminated Soil	TON	540.000	540.000
0012	206.1001	Excavation for Structures Bridges (structure) 01. B-69-0054	EACH	1.000	1.000
0014	210.1500	Backfill Structure Type A	TON	330.000	330.000
0016	211.0101	Prepare Foundation for Asphaltic Paving (project) 01. 6987-02-70	EACH	1.000	1.000
0018	213.0100	Finishing Roadway (project) 01. 6987-02-70	EACH	1.000	1.000
0020	305.0110	Base Aggregate Dense 3/4-Inch	TON	160.000	160.000
0022	305.0120	Base Aggregate Dense 1 1/4-Inch	TON	830.000	830.000
0024	455.0605	Tack Coat	GAL	49.000	49.000
0026	465.0105	Asphaltic Surface	TON	310.000	310.000
0028	502.0100	Concrete Masonry Bridges	CY	141.000	141.000
0030	502.3200	Protective Surface Treatment	SY	197.000	197.000
0032	505.0400	Bar Steel Reinforcement HS Structures	LB	4,660.000	4,660.000
0034	505.0600	Bar Steel Reinforcement HS Coated Structures	LB	23,190.000	23,190.000
0036	513.4061	Railing Tubular Type M	LF	90.000	90.000
0038	516.0500	Rubberized Membrane Waterproofing	SY	12.000	12.000
0040	550.2104	Piling CIP Concrete 10 3/4 X 0.25-Inch	LF	1,400.000	1,400.000
0042	606.0300	Riprap Heavy	CY	110.000	110.000
0044	612.0406	Pipe Underdrain Wrapped 6-Inch	LF	150.000	150.000
0046	614.2500	MGS Thrie Beam Transition	LF	160.000	160.000
0048	614.2610	MGS Guardrail Terminal EAT	EACH	4.000	4.000
0050	619.1000	Mobilization	EACH	1.000	1.000
0052	624.0100	Water	MGAL	15.000	15.000
0054	625.0500	Salvaged Topsoil	SY	1,330.000	1,330.000
0056	627.0200	Mulching	SY	1,330.000	1,330.000
0058	628.1504	Silt Fence	LF	660.000	660.000
0060	628.1520	Silt Fence Maintenance	LF	1,320.000	1,320.000
0062	628.1905	Mobilizations Erosion Control	EACH	3.000	3.000
0064	628.1910	Mobilizations Emergency Erosion Control	EACH	2.000	2.000
0066	628.6005	Turbidity Barriers	SY	200.000	200.000
0068	628.7504	Temporary Ditch Checks	LF	88.000	88.000
0070	629.0210	Fertilizer Type B	CWT	1.000	1.000
0072	630.0120	Seeding Mixture No. 20	LB	32.000	32.000
0074	630.0160	Seeding Mixture No. 60	LB	17.000	17.000
0076	630.0200	Seeding Temporary	LB	20.000	20.000
0078	630.0500	Seed Water	MGAL	40.000	40.000
0080	633.5100	Markers ROW	EACH	11.000	11.000
0082	634.0612	Posts Wood 4x6-Inch X 12-FT	EACH	6.000	6.000
0084	637.2230	Signs Type II Reflective F	SF	32.250	32.250
0086	638.2602	Removing Signs Type II	EACH	9.000	9.000
0088	638.3000	Removing Small Sign Supports	EACH	7.000	7.000
0090	642.5001	Field Office Type B	EACH	1.000	1.000
0092	643.0420	Traffic Control Barricades Type III	DAY	1,190.000	1,190.000
0094	643.0705	Traffic Control Warning Lights Type A	DAY	1,850.000	1,850.000
0096	643.0900	Traffic Control Signs	DAY	925.000	925.000
0098	643.1050	Traffic Control Signs PCMS	DAY	14.000	14.000

Estimate Of Quantities

6987-02-70

Line	Item	Item Description	Unit	Total	Qty
0100	643.5000	Traffic Control	EACH	1.000	1.000
0102	645.0111	Geotextile Type DF Schedule A	SY	96.000	96.000
0104	645.0120	Geotextile Type HR	SY	185.000	185.000
0106	646.1020	Marking Line Epoxy 4-Inch	LF	1,400.000	1,400.000
0108	650.4500	Construction Staking Subgrade	LF	310.000	310.000
0110	650.5000	Construction Staking Base	LF	310.000	310.000
0112	650.6501	Construction Staking Structure Layout (structure) 01. B-69-0054	EACH	1.000	1.000
0114	650.9911	Construction Staking Supplemental Control (project) 01. 6987-02-70	EACH	1.000	1.000
0116	650.9920	Construction Staking Slope Stakes	LF	310.000	310.000
0118	690.0150	Sawing Asphalt	LF	59.000	59.000
0120	715.0502	Incentive Strength Concrete Structures	DOL	846.000	846.000
0122	999.2005.S	Maintaining Bird Deterrent System (station) 01. STA. 10+72	EACH	1.000	1.000
0124	SPV.0090	Special 01. Flashing Stainless Steel	LF	75.000	75.000
0126	SPV.0195	Special 01. Select Crushed Material for Travel Corridor	TON	52.000	52.000

3

3

ALL ITEMS 010 UNLESS OTHERWISE NOTED											
GRUBBING				REMOVING ASPHALTIC SURFACE				EARTHWORK SUMMARY			
STATION-STATION		LOCATION		201.0205 GRUBBING (STA)		STATION-STATION		LOCATION		204.0110 (SY)	
8+80 - 12+30		MAINLINE		4		8+80 - 10+00		MAINLINE		295	
						11+40 - 12+30		MAINLINE		255	
TOTALS =				4		TOTALS =				550	
										NOTES: 1.) AVAILABLE MATERIAL=CUT 2.) EXPANDED FILL FACTOR 1.25: EXPANDED FILL = (UNEXPANDED FILL)*1.25 3.) THE MASS ORDINATE + OR - QTY CALCULATED FOR THE DIVISION. PLUS QUANTITY INDICATES AN EXCESS OF MATERIAL WITHIN THE CATEGORY. MINUS INDICATES A SHORTAGE OF MATERIAL WITHIN THE CATEGORY.	
BASE AGGREGATE DENSE				ASPHALTIC SURFACE				GUARDRAIL			
STATION - STATION		LOCATION		305.0110 BASE AGGREGATE DENSE 3/4-INCH (TON)		305.0120 BASE AGGREGATE DENSE 1 1/4-INCH (TON)		STATION - STATION		LOCATION	
8+80 - 12+30		MAINLINE		160		830		10+08 - 10+46		MAINLINE, RT.	
								10+18 - 10+56		MAINLINE, LT.	
								10+98 - 11+36		MAINLINE, LT.	
								10+88 - 11+26		MAINLINE, RT.	
TOTALS =				160		830		TOTALS =		160	
										TOTALS =	
										4	
FINISHING ITEMS										EXCAVATION, HAULING, AND DISPOSAL OF POTENTIAL CREOSOTE CONTAMINATED SOIL	
STATION - STATION		LOCATION		625.0500 SALVAGED TOPSOIL (SY)		627.0200 MULCHING (SY)		629.0210 FERTILIZER TYPE B (CWT)		630.0120 SEEDING MIXTURE NO. 20 (LB)	
8+80 - 12+30		MAINLINE		1,064		1,064		0.6		26	
-		UNDISTRIBUTED		266		266		0.4		6	
TOTALS =				1,330		1,330		1.0		32	
										STATION-STATION	
										LOCATION	
										205.0508.S (TON)	
										10+42 - 10+60	
										10+83 - 11+00	
										TOTALS =	
										540	
										SILT FENCE	
STATION - STATION		LOCATION		628.1504 SILT FENCE (LF)		628.1520 SILT FENCE MAINTENANCE (LF)					
9+35 - 10+48		MAINLINE, RT.		115		230					
9+76 - 10+77		MAINLINE, LT.		105		210					
10+63 - 12+35		MAINLINE, RT.		175		350					
11+01 - 12+30		MAINLINE, LT.		130		260					
-		UNDISTRIBUTED		135		270					
TOTALS =				660		1,320					
MOBILIZATION EROSION CONTROL				TURBIDITY BARRIER				WATER			
PROJECT		628.1905 MOBILIZATION EROSION CONTROL (EACH)		628.1910 MOBILIZATION EMERGENCY EROSION CONTROL (EACH)		LOCATION		628.6005 (SY)		STATION - STATION	
6987-02-70		3		2		SOUTH BANK		77		8+80 - 12+30	
						NORTH BANK		83		LOCATION	
						UNDISTRIBUTED		40		MAINLINE	
TOTALS =		3		2		TOTALS =		200		TOTAL =	
										15	
										TEMPORARY DITCH CHECKS	
STATION		LOCATION		628.7504 (LF)							
8+60		MAINLINE, RT.		8							
8+80		MAINLINE, RT.		8							
9+00		MAINLINE, RT.		8							
9+00		MAINLINE, LT.		8							
9+20		MAINLINE, RT.		8							
9+30		MAINLINE, LT.		8							
9+40		MAINLINE, RT.		8							
9+60		MAINLINE, LT.		8							
9+80		MAINLINE, LT.		8							
		UNDISTRIBUTED		16							
TOTALS =				88							
PROJECT NO: 6987-02-70				HWY: CTH E				COUNTY: WAUSHARA			
								MISCELLANEOUS QUANTITIES			
								SHEET			
								E			

ALL ITEMS 010 UNLESS OTHERWISE NOTED

MARKERS ROW

			633.5100	
			OFFSET FROM FINISHED C/L	MARKERS ROW
PT #	STATION	LOCATION	FT	(EACH)
100	12+30	RIGHT	33.00	1
101	9+50	RIGHT	33.00	1
102	9+50	RIGHT	45.00	1
103	8+45	RIGHT	45.00	1
104	8+45	RIGHT	33.00	1
105	8+45	LEFT	33.00	1
106	8+80	LEFT	33.00	1
107	8+80	LEFT	55.00	1
108	10+00	LEFT	55.00	1
109	10+00	LEFT	33.00	1
110	12+30	LEFT	33.00	1
TOTAL=				11

PERMANENT SIGNING

								634.0612	637.2230	638.2602	638.3000
								POSTS	SIGNS	REMOVING	REMOVING SMALL
								WOOD 4X6-	TYPE II	SIGNS	SMALL SIGN
APPROX. STATION	POSITION	LOCATION	SIGN CODE	SIGN DESCRIPTION	ORDER LINES	SIGN SIZE		INCH X 12-FT (EACH)	REFLECTIVE F (SF)	TYPE II (EACH)	SUPPORTS (EACH)
10+44	RT.	MAINLINE	W5-52R	BRIDGE HASH MARKS	-	12X36		1	3.00	-	-
10+55	LT.	MAINLINE	W5-52L	BRIDGE HASH MARKS	-	12X36		1	3.00	-	-
10+56	RT.	MAINLINE	W5-52R	BRIDGE HASH MARKS	-	12X36		-	--	1	1
10+56	LT.	MAINLINE	W5-52L	BRIDGE HASH MARKS	-	12X36		-	--	1	1
10+86	RT.	MAINLINE	W5-52L	BRIDGE HASH MARKS	-	12X36		-	--	1	1
10+86	LT.	MAINLINE	W5-52R	BRIDGE HASH MARKS	-	12X36		-	--	1	1
10+89	RT.	MAINLINE	W5-52L	BRIDGE HASH MARKS	-	12X36		1	3.00	-	-
10+99	LT.	MAINLINE	W5-52R	BRIDGE HASH MARKS	-	12X36		1	3.00	-	-
11+28	LT.	MAINLINE	--	--	-	-		-	--	-	1
12+23	RT.	MAINLINE	R1-1	STOP SIGN	-	30X30		1	6.25	1	1
12+23	RT.	MAINLINE	M1-5A	COUNTY	E	24X24		1	4.00	1	1
12+23	RT.	MAINLINE	M1-5A	COUNTY	H	24X24		-	4.00	1	-
12+23	RT.	MAINLINE	M6-1	LEFT ARROW	-	21X21		-	3.00	1	-
12+23	RT.	MAINLINE	M6-1	RIGHT ARROW	-	21X21		-	3.00	1	-
TOTALS =								6	32.25	9	7

TRAFFIC CONTROL

		643.0420	643.0705	643.0900	643.1050	643.5000
		BARRICADES	WARNING LIGHTS		SIGNS	TRAFFIC
		TYPE III	TYPE A	SIGNS	PCMS	CONTROL
LOCATION	(DAY)	(DAY)	(DAY)	(DAY)	(DAYS)	(EACH)
PROJECT	1,190	1,850	925	14	1	
TOTALS =	1,190	1,850	925	14	1	

MARKING LINE EPOXY 4-INCH

STATION - STATION	LOCATION	DESCRIPTION	646.1020 (LF)
8+80 - 12+30	MAINLINE	C/L YELLOW, DOUBLE SOLID	700
8+80 - 12+30	MAINLINE	C/L WHITE, SOLID EDGE LINE	700
TOTAL =			1,400

SAWING ASPHALT

STATION	LOCATION	690.0150 (LF)
8+80	MAINLINE	22
12+30	MAINLINE	37
TOTAL =		59

CONSTRUCTION STAKING

		650.4500	650.5000	*650.6501	650.9911	650.9920
		SUBGRADE	BASE	STRUCTURE	SUPPLEMENTAL	SLOPES
		(L.F.)	(L.F.)	LAYOUT (B-69-0054)	CONTROL	STAKES
STATION - STATION	LOCATION	(EACH)	(EACH)	(EACH)	(6987-02-70)	(L.F.)
8+80 - 10+50	MAINLINE	170	170	-	-	170
10+90 - 12+30	MAINLINE	140	140	-	-	140
6987-02-70	PROJECT	-	-	1	1	-
TOTAL =		310	310	1	1	310

\*CATEGORY 020



CONVENTIONAL SYMBOLS			
SECTION LINE	---	SECTION CORNER SYMBOL	
QUARTER LINE	---	R/W MONUMENT (TO BE SET)	●
SIXTEENTH LINE	---	NON-MONUMENTED R/W POINT	○
NEW REFERENCE LINE	---	FOUND IRON PIN (1-INCH UNLESS NOTED)	IP
NEW R/W LINE	---	GEODETIC SURVEY MONUMENT	
EXISTING R/W OR HE LINE	---	SIXTEENTH CORNER MONUMENT	
PROPERTY LINE	---	SIGN	
LOT, TIE & OTHER MINOR LINES	---	OFF-PREMISE SIGN	
SLOPE INTERCEPT	---	COMPENSABLE	
CORPORATE LIMITS	---	NON-COMPENSABLE	
UNDERGROUND FACILITY (COMMUNICATIONS, ELECTRIC, ETC.)	---	ELECTRIC POLE	
NEW R/W (FEE OR HE) (HATCHING VARIES BY OWNER)	---	TELEPHONE POLE	
TEMPORARY LIMITED EASEMENT AREA	---	PEDESTAL (LABEL TYPE) (TV, TEL, ELEC, ETC.)	
EASEMENT AREA (PERMANENT LIMITED OR RESTRICTED DEVELOPMENT)	---	ACCESS RESTRICTED BY ACQUISITION	
TRANSMISSION STRUCTURES	---	NO ACCESS (BY STATUTORY AUTHORITY)	
BUILDING		ACCESS RESTRICTED (BY PREVIOUS PROJECT OR CONTROL)	
TO BE REMOVED		NO ACCESS (NEW HIGHWAY)	
BRIDGE		PARCEL NUMBER (25)	
CULVERT		UTILITY NUMBER (40)	
PARALLEL OFFSETS			

CONVENTIONAL ABBREVIATIONS			
ACCESS RIGHTS	AR	POINT OF COMPOUND CURVE	PCC
ACRES	AC	POINT OF INTERSECTION	PI
AHEAD	AH	PROPERTY LINE	PL
ALUMINUM	ALUM	RECORDED AS	(100')
AND OTHERS	ET AL	REEL / IMAGE	R/I
BACK	BK	REFERENCE LINE	R/L
BLOCK	BLK	REMAINING	REM
CENTERLINE	C/L	RESTRICTIVE DEVELOPMENT	RDE
CERTIFIED SURVEY MAP	CSM	EASEMENT	
CONCRETE	CONC	RIGHT	RT
COUNTY	CO	RIGHT OF WAY	R/W
COUNTY TRUNK HIGHWAY	CTH	SECTION	SEC
DISTANCE	DIST	SEPTIC VENT	SEP
CORNER	COR	SQUARE FEET	SF
DOCUMENT NUMBER	DOC	STATE TRUNK HIGHWAY	STH
EASEMENT	EASE	STATION	STA
EXISTING	EX	TELEPHONE PEDESTAL	TP
GAS VALVE	GV	TEMPORARY LIMITED	TLE
GRID NORTH	GN	EASEMENT	
HIGHWAY EASEMENT	HE	TRANSPORTATION PROJECT PLAT	TPP
IDENTIFICATION	ID	UNITED STATES HIGHWAY	USH
LAND CONTRACT	LC	VOLUME	V
LEFT	LT	PAGE	P
MONUMENT	MON	POINT OF TANGENCY	PT
NATIONAL GEODETIC SURVEY	NGS	PERMANENT LIMITED	PLE
NUMBER	NO	EASEMENT	
OUTLOT	OL	POINT OF BEGINNING	POB
		POINT OF CURVATURE	PC

**NOTES**

POSITIONS SHOWN ON THIS PLAT ARE WISCONSIN COUNTY COORDINATES, WAUSHARA COUNTY, NAD 83 (2011) IN US SURVEY FEET. VALUES SHOWN ARE GRID COORDINATES, GRID BEARINGS, AND GRID DISTANCES. GRID DISTANCES MAY BE USED AS GROUND DISTANCES.

ALL NEW RIGHT-OF-WAY MONUMENTS WILL BE TYPE 2 MONUMENTS (TYPICALLY 3/4 X 24" IRON REBARS), UNLESS OTHERWISE NOTED, AND WILL BE PLACED PRIOR TO THE COMPLETION OF THE PROJECT.

RIGHT-OF-WAY BOUNDARIES ARE DEFINED WITH COURSES OF THE PERIMETER OF THE HIGHWAY LANDS REFERENCED TO THE U.S. PUBLIC LAND SURVEY SYSTEM OR OTHER "SURVEYS OF PUBLIC RECORD."

FOR CURRENT ACCESS/DRIVEWAY INFORMATION, CONTACT THE WAUSHARA COUNTY HIGHWAY DEPARTMENT.

ALL RIGHT-OF-WAY LINES DEPICTED IN THE NON-ACQUISITION AREAS ARE INTENDED TO RE-ESTABLISH EXISTING RIGHT-OF-WAY LINES AS DETERMINED FROM PREVIOUS PROJECTS, OTHER RECORDED DOCUMENTS, OR FROM CENTERLINE OF EXISTING PAVEMENTS.

DIMENSIONING FOR THE NEW RIGHT-OF-WAY IS MEASURED ALONG AND PERPENDICULAR TO THE NEW REFERENCE LINES.


A TEMPORARY LIMITED EASEMENT (TLE) IS A RIGHT FOR CONSTRUCTION PURPOSES, AS DEFINED HEREIN, INCLUDING THE RIGHT TO OPERATE NECESSARY EQUIPMENT THEREON, THE RIGHT OF INGRESS AND EGRESS, AS LONG AS REQUIRED FOR SUCH PUBLIC PURPOSE, INCLUDING THE RIGHT TO PRESERVE, PROTECT, REMOVE, OR PLANT THEREON ANY VEGETATION THAT THE HIGHWAY AUTHORITIES MAY DEEM DESIRABLE. ALL (TLEs) ON THIS PLAT EXPIRE AT THE COMPLETION OF THE CONSTRUCTION PROJECT FOR WHICH THIS INSTRUMENT IS GIVEN.

AN EASEMENT FOR HIGHWAY PURPOSES (HE), AS LONG AS SO USED, INCLUDING THE RIGHT-OF-WAY TO PRESERVE, PROTECT, REMOVE, OR PLANT THEREON ANY VEGETATION THAT THE HIGHWAY AUTHORITIES MAY DEEM DESIRABLE.

THIS PLAT IS A GRAPHIC REPRESENTATION AND IS FOR REFERENCE PURPOSE ONLY. DEEDS MUST BE CHECKED TO DETERMINE PROPERTY BOUNDARIES AND ACCESS RIGHTS.

CURVE DATA ABBREVIATIONS	
LONG CHORD	LCH
LONG CHORD BEARING	LCB
RADIUS	R
DEGREE OF CURVE	D
CENTRAL ANGLE	Δ/DELTA
LENGTH OF CURVE	L
TANGENT	T
DIRECTION AHEAD	DA
DIRECTION BACK	DB

CONVENTIONAL UTILITY SYMBOLS	
WATER	---
GAS	---
TELEPHONE	---
OVERHEAD TRANSMISSION LINES	---
ELECTRIC	---
CABLE TELEVISION	---
FIBER OPTIC	---
SANITARY SEWER	---
STORM SEWER	---
ELECTRIC TOWER	---



END RELOCATION ORDER

STA. 12+30.00  
32.82' SOUTH AND 324.11' WEST OF THE NE  
CORNER OF SECTION 9, T.19N., R.12E., TOWN  
OF LEON, WAUSHARA COUNTY, WI  
Y=157,903.019  
X=439,503.182



**JEWELL**  
associates engineers, inc.  
Engineers - Architects - Surveyors

560 SUNRISE DRIVE  
SPRING GREEN, WI 53588  
PHONE : 608.588.7484  
FAX : 608.588.9322

I HEREBY CERTIFY THAT THIS PLAT WAS  
MADE FOR WAUSHARA COUNTY, WISCONSIN  
AND IS CORRECT TO THE BEST OF MY  
KNOWLEDGE AND BELIEF.



DATE: 5-15-24

APPROVED FOR WAUSHARA COUNTY

DATE: 7/29/24  
(NAME/TITLE)  
Highway Commissioner

BEGIN RELOCATION ORDER

STA 8+45.00  
417.82' SOUTH AND 326.06' WEST OF THE NE  
CORNER OF SECTION 9, T.19N., R.12E., TOWN  
OF LEON, WAUSHARA COUNTY, WI  
Y=157,518.026  
X=439,501.234


EASEMENT TABLE				
EASEMENT NUMBER	OWNER	RECORDING INFORMATION	LOCATED IN R/W PARCEL #	REMARKS
1	WISCONSIN POWER AND LIGHT COMPANY	DOC. 106925, V.58, P.318	2	BLANKET EASEMENT E. 10 ACRES OF THE NE1/4 SEC. 9
2	WISCONSIN POWER AND LIGHT COMPANY	DOC. 106947, V.58, P.325	1	BLANKET EASEMENT W. 140 ACRES OF THE NE1/4 SEC. 9
3	MICHIGAN WISCONSIN PIPE LINE COMPANY	DOC. 189053, V.138, P.357	1	BLANKET EASEMENT W. 140 ACRES OF THE NE1/4 SEC. 9

UTILITY INTERESTS REQUIRED		
UTILITY NUMBER	OWNER	INTEREST REQUIRED
200	ALLIANT ENERGY (ELECTRIC)	RELEASE OF RIGHTS
201	WE ENERGIES (GAS)	RELEASE OF RIGHTS

N1/4 CORNER SEC. 9  
FOUND BROKEN HARRISON  
MONUMENT  
Y = 157,916.727  
X = 437,187.784

END RELOCATION ORDER

12+30.00  
32.82' SOUTH AND 324.11' WEST OF THE NE  
CORNER OF SECTION 9, T.19N., R.12E., TOWN  
OF LEON, WAUSHARA COUNTY, WI  
Y=157,903.019  
X=439,503.182



R/W COURSE TABLE		
POINT TO POINT	COURSE BEARING	DISTANCE
100 TO 101	S00° 17' 24"W	280.00'
101 TO 102	S89° 42' 36"E	12.00'
102 TO 103	S00° 17' 24"W	105.00'
103 TO 104	N89° 42' 29"W	12.00'
104 TO 105	N89° 42' 29"W	66.00'
105 TO 106	N00° 17' 24"E	35.00'
106 TO 107	N89° 42' 36"W	22.00'
107 TO 108	N00° 17' 24"E	120.00'
108 TO 109	S89° 42' 36"E	22.00'
109 TO 110	N00° 17' 24"E	230.00'
110 TO 100	S89° 42' 36"E	66.00'

R/W MONUMENT TABLE				
POINT NUMBER	STATION	OFFSET	Y	X
100	12+30.00	33.00'RT	157902.852	439536.181
101	9+50.00	33.00'RT	157622.856	439534.765
102	9+50.00	45.00'RT	157622.795	439546.765
103	8+45.00	45.00'RT	157517.797	439546.234
104	8+45.00	33.00'RT	157517.858	439534.234
105	8+45.00	33.00'LT	157518.194	439468.235
106	8+80.00	33.00'LT	157553.191	439468.412
107	8+80.00	55.00'LT	157553.302	439446.412
108	10+00.00	55.00'LT	157673.301	439447.019
109	10+00.00	33.00'LT	157673.189	439469.019
110	12+30.00	33.00'LT	157903.186	439470.182

TLE POINT TABLE				
POINT NUMBER	STATION	OFFSET	Y	X
500	12+00.00	33.00'RT	157872.853	439536.030
501	12+00.00	38.00'RT	157872.828	439541.030
502	10+85.00	38.00'RT	157757.829	439540.448
503	10+00.00	45.00'RT	157672.795	439547.018
504	10+00.00	40.00'LT	157673.225	439462.019
505	12+30.00	40.00'LT	157903.222	439463.182

SCHEDULE OF LANDS & INTERESTS REQUIRED						
PARCEL NUMBER	OWNER (S)	INTERESTS REQUIRED	FEE ACRES REQUIRED			TLE ACRES
			NEW	EXISTING	TOTAL	
1	JEFFERY L. JURGENSEN, A MARRIED MAN	FEE, TLE	0.06	0.10	0.16	0.04
2	ROBERT L. WATERMAN AND BARBARA A. WATERMAN, TRUSTEES, OR THEIR SUCCESSORS IN TRUST, UNDER THE ROBERT L. AND BARBARA A. WATERMAN REVOCABLE TRUST DATED NOVEMBER 17, 2016	FEE, TLE	0.03	0.48	0.51	0.04



NOTE: AREAS SHOWN IN THE TOTAL ACRES COLUMN MAY BE APPROXIMATE AND ARE DERIVED FROM TAX ROLLS OR OTHER AVAILABLE SOURCES AND MAY NOT INCLUDE LANDS OF THE OWNER WHICH ARE NOT CONTIGUOUS TO THE AREA TO BE ACQUIRED. OWNER'S NAMES ARE SHOWN FOR REFERENCE PURPOSES ONLY AND ARE SUBJECT TO CHANGE PRIOR TO THE TRANSFER OF LAND INTERESTS TO WAUSHARA COUNTY.

NOTE: EXISTING C/L OF CTH E, BASED ON CENTERLINE OF EXISTING PAVEMENT.

EXISTING RIGHT-OF-WAY FOR CTH E, BASED ON THE CENTERLINE OF EXISTING PAVEMENT AND WIS. STATUTE 82.31(2).

REVISION DATE <div><div></div><div></div><div></div><div></div></div>	DATE 5/16/2024	SCALE, FEET <div><div>01020</div></div>	HWY: CTH E	STATE R/W PROJECT NUMBER 6987-02-00	PLAT SHEET 4.02	
	GRID FACTOR <div></div>		COUNTY: WAUSHARA	CONSTRUCTION PROJECT NUMBER 6987-02-70	PS&E SHEET <div></div>	








Standard Detail Drawing List



08E08-03	TYPICAL INSTALLATIONS OF EROSION BALES / TEMPORARY DITCH CHECKS
08E09-06	SILT FENCE
08E11-02	TURBIDITY BARRIER
12A03-10	NAME PLATE (STRUCTURES)
13C19-03	HMA LONGITUDINAL JOINTS
14B42-07A	MIDWEST GUARDRAIL SYSTEM (MGS) GUARDRAIL
14B42-07B	MIDWEST GUARDRAIL SYSTEM (MGS) GUARDRAIL
14B42-07C	MIDWEST GUARDRAIL SYSTEM (MGS) GUARDRAIL
14B42-07D	MIDWEST GUARDRAIL SYSTEM (MGS) GUARDRAIL
14B44-04A	MIDWEST GUARDRAIL SYSTEM ENERGY ABSORBING TERMINAL (MGS)
14B44-04B	MIDWEST GUARDRAIL SYSTEM ENERGY ABSORBING TERMINAL (MGS)
14B44-04C	MIDWEST GUARDRAIL SYSTEM ENERGY ABSORBING TERMINAL (MGS)
14B45-05A	MIDWEST GUARDRAIL SYSTEM THRIE BEAM TRANSITION (MGS)
14B45-05B	MIDWEST GUARDRAIL SYSTEM THRIE BEAM TRANSITION (MGS)
14B45-05C	MIDWEST GUARDRAIL SYSTEM THRIE BEAM TRANSITION (MGS)
14B45-05D	MIDWEST GUARDRAIL SYSTEM THRIE BEAM TRANSITION (MGS)
14B45-05E	MIDWEST GUARDRAIL SYSTEM THRIE BEAM TRANSITION (MGS)
14B45-05F	MIDWEST GUARDRAIL SYSTEM THRIE BEAM TRANSITION (MGS)
14B45-05G	MIDWEST GUARDRAIL SYSTEM THRIE BEAM TRANSITION (MGS)
14B45-05H	MIDWEST GUARDRAIL SYSTEM THRIE BEAM TRANSITION (MGS)
14B45-05I	MIDWEST GUARDRAIL SYSTEM THRIE BEAM TRANSITION (MGS)
14B45-05J	MIDWEST GUARDRAIL SYSTEM THRIE BEAM TRANSITION (MGS)
14B45-05K	MIDWEST GUARDRAIL SYSTEM THRIE BEAM TRANSITION (MGS)
14B45-05L	MIDWEST GUARDRAIL SYSTEM THRIE BEAM TRANSITION (MGS)
15A01-13A	MARKER POST FOR RIGHT-OF-WAY
15C02-09A	BARRICADES AND SIGNS FOR MAINLINE CLOSURES
15C02-09B	BARRICADES AND SIGNS FOR VARIOUS CLOSURES
15C06-12	SIGNING & MARKING FOR TWO LANE BRIDGES
15C08-23A	PERMANENT LONGITUDINAL PAVEMENT MARKINGS
15C11-10B	CHANNELIZING DEVICES DRUMS, CONES, BARRICADES AND VERTICAL PANELS



## GENERAL NOTES

DETAILS OF CONSTRUCTION, MATERIALS AND WORKMANSHIP NOT SHOWN ON THIS DRAWING SHALL CONFORM TO THE PERTINENT REQUIREMENTS OF THE STANDARD SPECIFICATIONS AND THE APPLICABLE SPECIAL PROVISIONS.

- ① TEMPORARY DITCH CHECKS EITHER EROSION BALES OR MANUFACTURED SHALL BE PAID FOR UNDER THE BID ITEM OF TEMPORARY DITCH CHECK. THE DEPARTMENT WILL NOT PAY FOR TEMPORARY DITCH CHECKS CONSTRUCTED OF A SINGLE ROW OF EROSION BALES.

TYPICAL INSTALLATIONS OF  
EROSION BALES / TEMPORARY  
DITCH CHECKS

STATE OF WISCONSIN  
DEPARTMENT OF TRANSPORTATION

APPROVED


6/04/02  
DATE

/S/ Beth Canestra  
CHIEF ROADWAY DEVELOPMENT ENGINEER


FHWA



- ① HORIZONTAL BRACE REQUIRED WITH 2" X 4" WOODEN FRAME OR EQUIVALENT AT TOP OF POSTS.
- ② FOR MANUAL INSTALLATIONS THE TRENCH SHALL BE A MINIMUM OF 4" WIDE & 6" DEEP TO BURY AND ANCHOR THE GEOTEXTILE FABRIC. FOLD MATERIAL TO FIT TRENCH AND BACKFILL & COMPACT TRENCH WITH EXCAVATED SOIL.
- ③ WOOD POSTS SHALL BE A MINIMUM SIZE OF 1 1/8" X 1 1/8" OF OAK OR HICKORY.
- ④ SILT FENCE TO EXTEND ACROSS THE TOP OF THE PIPE.
- ⑤ CONSTRUCT SILT FENCE FROM A CONTINUOUS ROLL IF POSSIBLE BY CUTTING LENGTHS TO AVOID JOINTS. IF A JOINT IS NECESSARY USE ONE OF THE FOLLOWING TWO METHODS; A) OVERLAP THE END POSTS AND TWIST, OR ROTATE, AT LEAST 180 DEGREES, B) HOOK THE END OF EACH SILT FENCE LENGTH.




<div>SILT FENCE</div>	
<div>STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION</div>	
<div>APPROVED</div> <div>4-29-05</div> <div>DATE</div>	<div>/S/ Beth Cannestra</div> <div>CHIEF ROADWAY DEVELOPMENT ENGINEER</div>



SECTION B - B


**TURBIDITY BARRIER - FLOAT ALTERNATIVE**  
**CAUTION - SEE NOTE 6**




SECTION A - A

**TURBIDITY BARRIER - STANDARD POST INSTALLATION**

**TURBIDITY BARRIER PLACEMENT DETAILS**



PLAN VIEW




PLAN VIEW

**GENERAL NOTES**


DETAILS OF CONSTRUCTION, MATERIALS AND WORKMANSHIP NOT SHOWN ON THIS DRAWING SHALL CONFORM TO THE PERTINENT REQUIREMENTS OF THE STANDARD SPECIFICATIONS AND THE APPLICABLE SPECIAL PROVISIONS.

TURBIDITY BARRIER MAY BE REMOVED AT THE ENGINEERS DISCRETION, WHEN PERMANENT EROSION CONTROL MEASURES HAVE BEEN ESTABLISHED.

- 1 DRIVEN STEEL POSTS, PIPES, OR CHANNELS. LENGTH SHALL BE SUFFICIENT TO SECURELY SUPPORT BARRIER AT HIGH WATER ELEVATIONS.
- 2 SAND BAGS TO BE USED AS ADDITIONAL BALLAST WHEN ORDERED BY THE ENGINEER TO MEET ADVERSE FIELD CONDITIONS. SPACE AS APPROPRIATE FOR SITE CONDITIONS.
- 3 WHEN BARRIER HEIGHT "H" EXCEEDS 8 FEET, POST SPACING MAY NEED TO BE DECREASED.
- 4 IN WATERWAYS SUBJECT TO FLUCTUATING WATER ELEVATIONS, PROVISIONS SHOULD BE MADE TO ALLOW THE WATER TO EQUALIZE ON EACH SIDE OF THE BARRIER. THIS MAY BE ACCOMPLISHED BY LEAVING A PORTION OF THE BARRIER OPEN ON THE UPSTREAM END.
- 5 ESTIMATED HIGH WATER ELEVATION DURING CONSTRUCTION PERIOD. MINIMUM BARRIER HEIGHT SHALL BE 2' GREATER THAN EITHER THE Q2 ELEVATION OR THE ESTIMATED HIGH WATER ELEVATION DURING CONSTRUCTION, WHICHEVER IS GREATER.
- 6 FLOAT ALTERNATIVE WILL ONLY BE ALLOWED WITH WRITTEN APPROVAL OF THE ENGINEER, AND IS MEANT FOR LOCATIONS WHERE BEDROCK PREVENTS THE INSTALLATION OF POSTS.
- 7 ALLOW SUFFICIENT SLACK VERTICALLY AND HORIZONTALLY SO THAT SEDIMENT BUILD UP WILL NOT SEPARATE OR LOWER THE TURBIDITY BARRIER.
- 8 USE AS DIRECTED BY COAST GUARD OR DNR PERMIT WHEN WORKING IN NAVIGABLE WATERWAYS.



PLAN VIEW




SECTION C - C

**TURBIDITY BARRIER DETAIL SHOWING**  
**TYPICAL PLACEMENT AT STRUCTURES**


**TURBIDITY BARRIER**

STATE OF WISCONSIN  
DEPARTMENT OF TRANSPORTATION

APPROVED  
6/4/02  
DATE  
/S/ Beth Canestra  
CHIEF ROADWAY DEVELOPMENT  
ENGINEER  
FHWA



**TYPICAL NAME PLATE**  
(BRIDGES, CULVERTS, AND RETAINING WALLS)




**NUMBERING DESIGNATION  
MULTI-UNIT STRUCTURES**

## GENERAL NOTES


NAME PLATES TO BE INSTALLED ON BRIDGES, CULVERTS, AND RETAINING WALLS SHALL CONFORM TO THE REQUIREMENTS OF SECTION 502.3.11 OF THE STANDARD SPECIFICATIONS.

THE BRIDGE NUMBER AND YEAR BUILT SHOWN ON THIS DRAWING ARE EXAMPLES ONLY. SEE CONSTRUCTION PLANS FOR INDIVIDUAL NUMBERING AND YEAR BUILT.

- ① EPOXY RESIN SHALL BE FROM AN APPROVED MANUFACTURER AND USED IN ACCORDANCE WITH MANUFACTURER'S RECOMMENDATIONS.
- ② REHABILITATION OF AN EXISTING STRUCTURE SHOULD USE THE DATE OF ORIGINAL STRUCTURE CONSTRUCTION.




**SECTION A-A**



**ALTERNATE LUG**

- ① ADHERE ANCHOR LUG TO PRECAST RETAINING WALL WITH EPOXY RESIN.



**ALTERNATE LUG**  
(FOR ATTACHMENT TO PRECAST STRUCTURES)

**NAME PLATE  
(STRUCTURES)**


STATE OF WISCONSIN  
DEPARTMENT OF TRANSPORTATION

APPROVED


3/26/10  
DATE

FHWA


/S/ Scot Becker  
CHIEF STRUCTURAL DEVELOPMENT ENGINEER



**TYPICAL PAVEMENT CROSS SECTION  
NOTCHED WEDGE JOINT**



**TYPICAL PAVEMENT CROSS SECTION  
VERTICAL JOINT**



**TYPICAL PAVEMENT CROSS SECTION  
VERTICAL JOINT (MILLED)**

**GENERAL NOTES**


IN ADDITION TO THE DETAILS PROVIDED IN THIS DRAWING, CONFORM TO STANDARD SPECIFICATION 450.3.2.8 FOR WHEN A NOTCHED WEDGE JOINT IS REQUIRED AND FOR GENERAL JOINT CONSTRUCTION REQUIREMENTS.

FOR ALL LONGITUDINAL JOINTS, ENSURE THE PAVER SCREED OVERLAPS THE PREVIOUSLY PLACED PAVEMENT BY  $1" \pm 0.5"$  AND THE HOT SIDE OF THE JOINT REMAINS HIGHER THAN THE COLD SIDE BY APPROXIMATELY  $0.1"$  AFTER FINAL COMPACTION. (IT WILL BE FLUSH WHEN PAVING IN ECHELON.)

ONLY REMOVE THE LONGITUDINAL NOTCHED WEDGE JOINT FOR SMA PAVEMENT OR AS DIRECTED BY THE ENGINEER TO ADDRESS SPECIFIC LENGTHS OF JOINT DAMAGED BY TRAFFIC.

WHEN MILLING BACK OR REMOVING ANY LONGITUDINAL JOINT, LIMIT THE MATERIAL REMOVED TO  $2"$  FROM THE TOP NOTCH OR FROM THE VERTICAL JOINT EDGE ON THE COLD SIDE OF THE JOINT.

USE LONGITUDINAL MILLED JOINT AS PLANS SHOW OR THE AS THE ENGINEER DIRECTS.












**OVERLAP DETAIL (TYPICAL)**

**HMA LONGITUDINAL JOINTS**

STATE OF WISCONSIN  
DEPARTMENT OF TRANSPORTATION


APPROVED  
November 2020 /S/ Steven Hefel  
DATE HMA PAVEMENT ENGINEER  
FHWA

- ① WOOD OR STEEL POSTS (w6X9 OR w6X8.5) MAY BE USED. DO NOT INTERMIX WOOD AND STEEL POSTS. INSTALL STEEL POSTS WITH HOLES ON APPROACHING TRAFFIC SIDE.
- ② USE WOOD OR APPROVED PLASTIC BLOCKOUTS. WOOD BLOCKOUTS MAY BE CONSTRUCTED OUT OF TWO OR MORE WOOD BLOCKOUTS. SEE ALTERNATE WOOD BLOCKOUT DETAIL. DIMENSIONS OF APPROVED PLASTIC BLOCKOUTS MAY VARY.
- ③ IF ROCK IS ENCOUNTERED DURING EXCAVATION, PROVIDE A HOLE 12 INCHES IN DIAMETER EXTENDING 20 INCHES DEEP INTO THE ROCK. PLACE APPROXIMATELY 2 1/2" INCHES OF GRANULAR MATERIAL IN THE BOTTOM OF THE HOLE. CUT THE POSTS THE TO LENGTH AND INSTALL. BACKFILL WITH EXCAVATED MATERIAL AND COMPACT. BACKFILL IS TO BE FREE OF LARGE ROCKS.
- ④ WHEN THE DISTANCE FROM BACK OF POST TO SHOULDER HINGE POINT IS LESS THAN 2 FEET INSTALL LONGER POST AT HALF POST SPACING (K).
- ⑤ FOR NEW MGS INSTALLATION TOP OF W-BEAM RAIL TOLERANCE IS  $\pm 1"$ . FOR EXISTING MGS INSTALLATION TOP OF W-BEAM IS BETWEEN 27 3/4" TO 32".
- ⑥ WHEN USING STEEL POST AND WOOD BLOCKOUTS INSTALL FOUR 16D GALVANIZED NAILS. INSTALL NAILS AT THE BACK CORNERS OF THE BLOCK AND BEND THE NAILS OVER THE FLANGE OF THE STEEL POST.
- ⑦ TOTAL POST LENGTH FOR TYPE K IS 7' - 0".  
TOTAL POST LENGTH FOR OTHER MGS TYPES IS 6' - 0".




**MIDWEST GUARDRAIL SYSTEM  
(MGS) GUARDRAIL**


STATE OF WISCONSIN  
DEPARTMENT OF TRANSPORTATION




**FRONT VIEW  
POST SPACING STANDARD INSTALLATION**




**FRONT VIEW  
HALF POST SPACING (HS) AND  
HALF POST SPACING WITH LONGER POSTS (K)**




**FRONT VIEW  
QUARTER POST SPACING (QS)**




**FRONT VIEW  
MID-SPAN BEAM SPLICE**



**FRONT VIEW AT STEEL POST**




**FRONT VIEW AT WOOD POST**



**ONE SIDED REFLECTOR DETAIL  
AND TYPICAL INSTALLATION**

**GENERAL NOTES**

- ⑧ DO NOT INSTALL REFLECTORS ON THE FIRST 50 FEET OF THE APPROACH END OF THE ENERGY ABSORBING TERMINAL.
  - ⑨ 25 FEET OF HALF POST SPACING IS REQUIRED ON APPROACH AND DEPARTURE ENDS OF QUARTER POST SPACING.
- POST BOLTS ARE A 3/8" DIAMETER ASTM A307 GUARDRAIL BOLT. A POST BOLT REQUIRES 3/8" DIAMETER A563A DOUBLE RECESSED (DR) HEAVY HEX NUT AND 3/8" DIAMETER F844 FLAT WASHER. POST BOLTS MAY BE LONGER IF MULTIPLE BLOCKOUTS ARE BEING USED.
- GUARD RAIL SPLICE BOLTS ARE A 3/8" DIAMETER ASTM A307 GUARDRAIL HEAD BOLT. A GUARDRAIL SPLICE BOLT REQUIRES 3/8" DIAMETER A563A DOUBLE RECESSED (DR) HEAVY HEX NUT.




**SECTION THRU W-BEAM RAIL**

**MIDWEST GUARDRAIL SYSTEM  
(MGS) GUARDRAIL**


STATE OF WISCONSIN  
DEPARTMENT OF TRANSPORTATION






DETAIL FOR 16" BLOCKOUT DEPTH

IT IS ACCEPTABLE TO USE BLOCKOUTS UP TO 16" DEEP TO INCREASE THE POST OFFSET TO AVOID UNDERGROUND OBSTACLES. THERE IS NO LIMIT TO THE NUMBER OF POSTS THAT CAN HAVE ADDITIONAL BLOCKOUTS UP TO 16" DEEP.




POST BOLT TABLE


L	T (MIN.)
1 1/4"	1 1/8"
2"	1 3/4"
10"	4"
14"	4 1/16"
18"	4"
21"	4 1/16"
25"	4"




ALTERNATE BOLT HEAD




POST BOLT, SPLICE BOLT AND RECESS NUT




PLAN VIEW  
BEAM LAPPING DETAIL



POST DRIVING FOR CONTINUOUS  
UNDERGROUND OBSTRUCTION



SIDE VIEW



PLAN VIEW


ALTERNATE WOOD  
BLOCKOUT DETAIL

NOTES: UNDER SPECIAL CIRCUMSTANCES, SUCH AS AVOIDING OBSTACLES THAT ARE NOT RELOCATED, IT IS ACCEPTABLE TO INSTALL ADDITIONAL BLOCKOUTS TO OBTAIN UP TO 36" DEPTH FOR ONE OR TWO POSTS IN A SECTION OF GUARDRAIL.  
DO NOT USE 16" OR 36" BLOCKOUTS IF IT CAUSES THE POST TO BE DRIVEN BEYOND SHOULDER HINGE POINT OR CAUSES A FIXED OBJECT TO BE WITHIN THE DEFLECTION DISTANCE OF THE BARRIER.


6 WHEN USING STEEL POST AD WOOD BLOCKOUTS, INSTALL FOUR 16D GALVANIZED NAILS. INSTALL NAILS AT THE BACK CORNERS OF THE BLOCK AND BEND THE NAILS OVER THE FLANGE OF THE STEEL POST.

MIDWEST GUARDRAIL SYSTEM  
(MGS) GUARDRAIL


STATE OF WISCONSIN  
DEPARTMENT OF TRANSPORTATION




**MISSING POST IN MGS GUARDRAIL**




**MISSING POST IN MGS GUARDRAIL NEAR EAT**




**MISSING POST IN MGS GUARDRAIL NEAR AN APPROACH TRANSITION**



**MISSING POST IN MGS GUARDRAIL NEAR FLARED BEAM GUARD**




**MISSING POST IN MGS GUARDRAIL NEAR A TYPE 2 END TERMINAL**




**MISSING POST IN SHORT SPAN MGS GUARDRAIL NEAR CURB (SL)**

- (400) MAX SPAN 12' - 6"
- (401) 2' MIN.
- (402) MGS GUARDRAIL 3
- (403) NESTING BEAM GUARD
- (404) ASYMMETRIC TRANSITION
- (405) SOIL WELL DRAINED AND COMPACTED
- (406) SEE OTHER DRAWINGS IN THIS SDD
- (407) SEE OTHER DRAWINGS FOR MIN. SPACING BETWEEN SPANS
- (408) SEE SDD 14B44
- (409) SEE SDD 14B45
- (410) SEE SDD 14B47
- (411) MINIMUM DISTANCE BETWEEN MISSING POST SPANS.



**SECTION A - A**



**SECTION B - B**

**MIDWEST GUARDRAIL SYSTEM  
(MGS) GUARDRAIL**

STATE OF WISCONSIN  
DEPARTMENT OF TRANSPORTATION

APPROVED  
May 2021  
DATE  
/S/ Rodney Taylor  
ROADWAY STANDARDS DEVELOPMENT  
UNIT SUPERVISOR

FHWA


- (A) THE SLOPE IN THE AREA BOUNDED BY THE GRADELINE, THE HINGE POINT LINE (HPL) AND THE CLEAR ZONE LIMITS (CZL) SHALL BE 4:1 OR FLATTER.
- (B) AFTER FINAL ASSEMBLY, RECHECK CABLE TO BE SURE IT IS TAUT AND HAS NOT RELAXED
- (C) DIFFERENT MANUFACTURERS REQUIRE DIFFERENT PERFORATED W - BEAM RAIL END PANELS. SEE MANUFACTURER'S INFORMATION.
- (D) ATTACH ALUMINUM SHEET TO E.A.T. HEAD USING 4 STAINLESS STEEL SELF - TAPPING SCREWS. ONE SCREW PER CORNER.
- (E) HARDWARE MAY VARY BETWEEN MANUFACTURER. SEE MANUFACTURER'S DRAWING FOR INFORMATION.

DIMENSIONS MAY VARY, MANUFACTURER'S INFORMATION.

THE CENTER OF THE UPPER 3½" DIAMETER HOLE ON POST NUMBER 3 THROUGH POST 9 IS TO BE FLUSH WITH THE GROUND LINE UP TO A MAXIMUM OF 2" ABOVE GROUND LINE. WOOD BLOCKS ON POSTS NUMBERED 3 THROUGH 9 MAY BE ADJUSTED UP TO 3" ABOVE THE TOP OF POST.




STATE OF WISCONSIN  
DEPARTMENT OF TRANSPORTATION




GENERIC GROUND STRUT<sup>⑨</sup> <sup>Ⓔ</sup>

BILL OF MATERIALS	
PART NO.	DESCRIPTION MATERIALS PROVIDED BY MGS EAT MANUFACTURER. SEE MANUFACTURER'S DETAILS FOR MORE INFORMATION.
①	UPPER POST NO. 1 6" X 6" TUBE
②	LOWER POST NO. 1
③	WOOD CRT
④	WOOD BLOCKOUT
⑤	PIPE SLEEVE
⑥	BEARING PLATE
⑦	BCT CABLE ASSEMBLY
⑧	ANCHOR CABLE BOX
⑨	GROUND STRUT
⑩	PERFORATED W-BEAM RAIL END PANEL, 12'-6" LONG.
⑪	STANDARD W-BEAM RAIL. MULTIPLE SECTIONS REQUIRED. SECTIONS VARY IN LENGTH.
⑫	IMPACT HEAD
⑬	EAT MARKER POST - YELLOW (SEE APPROVED PRODUCTS LIST)
⑭	SOIL PLATE
⑮	UPPER POST NO. 2
⑯	LOWER POST NO. 2




GENERIC ANCHOR CABLE BOX<sup>⑨</sup> <sup>Ⓔ</sup>




BEARING PLATE<sup>⑥</sup> <sup>Ⓔ</sup>

MIDWEST GUARDRAIL SYSTEM  
ENERGY ABSORBING TERMINAL  
(MGS)


STATE OF WISCONSIN  
DEPARTMENT OF TRANSPORTATION




UPPER POST NO. 1<sup>(1) (E)</sup>




LOWER POST NO. 1<sup>(2) (E)</sup>




WOOD CRT POST<sup>(3) (E)</sup>  
POSTS NUMBER 3-9




UPPER POST NO. 2<sup>(15) (E)</sup>




LOWER POST NO. 2<sup>(16) (E)</sup>



WOOD BLOCKOUT<sup>(4)</sup>  
REQ'D. AT ALL POSTS EXCEPT POST NO'S 1 & 2




REFLECTIVE SHEETING DETAIL<sup>(E)</sup>




FRONT VIEW

SIDE VIEW

E.A.T. MARKER POST<sup>(13)</sup>



SIDE VIEW




TOP VIEW

ALTERNATE WOOD  
BLOCKOUT DETAIL


**MIDWEST GUARDRAIL SYSTEM  
ENERGY ABSORBING TERMINAL  
(MGS)**

STATE OF WISCONSIN  
DEPARTMENT OF TRANSPORTATION

APPROVED  
7/2018  
DATE  
/S/ Rodney Taylor  
ROADWAY STANDARDS DEVELOPMENT  
UNIT SUPERVISOR  
FHWA



TWO WAY TRAFFIC



ONE WAY TRAFFIC

(T) THRIE BEAM CONNECTION

(W) W-BEAM CONNECTION WHEN REQUIRED

## TYPICAL LOCATIONS OF THRIE BEAM AND W-BEAM CONNECTIONS TO BRIDGE

### GENERAL NOTES

IF ROCK IS ENCOUNTERED, REMOVE ROCK TO FULL DEPTH OF POST PLUS 2 1/2", AND 12" DIAMETER AROUND POST. SEE 14B42 FOR MORE DETAILS.

TRANSITION USES STEEL POSTS ONLY.


SEE STANDARD DETAIL DRAWING 14 B 42 FOR MORE INFORMATION.

POST 2 THROUGH 17 USES STEEL POST ONLY


① BRIDGE RAILING TYPE "W" DOES NOT REQUIRE A TERMINAL CONNECTOR.

② OPTIONAL CURB AND GUTTER OR DRAINAGE FEATURE SEE PLAN FOR INFORMATION.

⑬ STEEL OR WOOD POST IS ACCEPTABLE AT POST 1. SEE SDD14B42



PLAN VIEW



ELEVATION VIEW


## MIDWEST GUARDRAIL SYSTEM THRIE BEAM TRANSITION

MIDWEST GUARDRAIL SYSTEM  
THRIE BEAM TRANSITION (MGS)


STATE OF WISCONSIN  
DEPARTMENT OF TRANSPORTATION

GENERAL NOTES


- 2 OPTIONAL CURB AND GUTTER OR DRAINAGE FEATURE SEE PLAN FOR INFORMATION.
- 3 WHEN USING STEEL POSTS AND WOOD BLOCKOUTS INSTALL FOUR 10D GALVANIZED NAILS. INSTALL NAILS AT THE BACK CORNERS OF THE BLOCK AND BEND THE NAILS OVER THE FLANGE OF THE STEEL POST.
- 4 TOLERANCE FOR TOP OF W-BEAM RAIL IS  $\pm 1"$ .
- 13 STEEL OR WOOD POST IS ACCEPTABLE AT POST 1. SEE SDD 14B42




SECTION A-A  
POSTS 1-5



SECTION D-D  
POSTS 12-17



SECTION B-B  
POST 6



SECTION C-C  
POSTS 7-11







PLATE WASHER DETAIL



SPLICE DETAIL




THRIE BEAM  
TERMINAL CONNECTOR




SECTION THRU THRIE  
BEAM RAIL ELEMENT

MIDWEST GUARDRAIL SYSTEM  
THRIE BEAM TRANSITION (MGS)


STATE OF WISCONSIN  
DEPARTMENT OF TRANSPORTATION




W-BEAM TO THRIE BEAM TRANSITION SECTION




6'-3" THRIE BEAM SECTION



12'-6" THRIE BEAM SECTION




SIDE VIEW



TOP VIEW


ALTERNATE WOOD BLOCKOUT DETAIL




FRONT VIEW

SIDE VIEW

STEEL POSTS 1-5




TOP VIEW



FRONT VIEW


BLOCKOUT POSTS 1-5




FRONT VIEW

SIDE VIEW

STEEL POSTS 6-17



TOP VIEW



FRONT VIEW

BLOCKOUT POSTS 6-17

### GENERAL NOTES

STEEL POSTS ARE W6X9 OR W6X8.5.

BOLT HOLES FOR POST ARE ON FRONT AND OF SIDE OF POST.

③ WHEN USING STEEL POSTS AND WOOD BLOCKOUTS INSTALL FOUR 16D GALVANIZED NAILS. INSTALL NAILS AT THE BACK CORNERS OF THE BLOCK AND BEND THE NAILS OVER THE FLANGE OF THE STEEL POST.


⑤ WOOD BLOCKS MAY BE CONSTRUCTED OUT OF 2 WOOD BLOCKS. SEE ALTERNATE WOOD BLOCK DETAIL.

⑬ STEEL OR WOOD POST IS ACCEPTABLE AT POST 1. SEE SDD 14B42.

MIDWEST GUARDRAIL SYSTEM  
THRIE BEAM TRANSITION (MGS)



STATE OF WISCONSIN  
DEPARTMENT OF TRANSPORTATION






**GENERAL NOTES**

- THESE ARE TYPICAL CONNECTION DETAILS. ADJUST THE POSTION OF CONNECTIONS TO EXISTING BRIDGES TO FIT THE ACTUAL BRIDGE AND SITE DIMENSIONS.
- ② OPTIONAL CURB AND GUTTER OR DRAINAGE FEATURE SEE PLAN FOR INFORMATION.
- ④ TOLERANCE FOR TOP OF BEAM IS  $\pm 1"$ .
- ⑥ DRILLING BOLT HOLES THROUGH THE PARAPET, BOLTS, NUTS, WASHERS AND REPAIRING DAMAGED CONCRETE ARE INCIDENTAL TO THE CONTRACT.
- ⑦ BOLTS MAY BE A325 BOLTS OR A449 BOLTS. BOLT LENGTH AND THREADING LENGTH ARE TO ALLOW FOR A TIGHT CONNECTION BETWEEN RIGID BARRIER AND THRIE BEAM CONNECTION PLATE. CONTRACTOR IS TO FIELD VERIFY BOLT LENGTH AND THREAD LENGTH. ONE ROUND WASHER REQUIRED BETWEEN BOLT HEAD AND THRIE BEAM CONNECTOR PLATE. BOLTS THAT EXTEND THROUGH THE PARAPET AND OUT THE BACK FACE REQUIRE A HARDENED ROUND STEEL WASHER THAT IS 2" O.D. X 5/32" THICK AND ONE PLATE WASHER. REPAIR ANY DAMAGED CONCRETE FROM BOLT INSTALLATION.
- ⑧ THE RECESS FOR A W-BEAM CONNECTION, WHICH EXISTS ON SOME PARAPETS OF THIS TYPE, SHALL BE FILLED WITH A TREATED TIMBER BLOCKOUT. BLOCKOUT SIZE IS 1'-6" X 2'-0" X 3 1/2".



**SECTION F-F**




MIDWEST GUARDRAIL SYSTEM THRIE BEAM TRANSITION (MGS)	
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION	
APPROVED 07/2018 DATE	/S/ Rodney Taylor ROADWAY STANDARDS DEVELOPMENT UNIT SUPERVISOR
FHWA	


GENERAL NOTES

THESE ARE TYPICAL CONNECTION DETAILS. ADJUST THE POSTION OF CONNECTIONS TO EXISTING BRIDGES TO FIT THE ACTUAL BRIDGE AND SITE DIMENSIONS.


- ②
- OPTIONAL CURB AND GUTTER OR DRAINAGE FEATURE SEE PLAN FOR INFORMATION.
- ④
- TOLERANCE FOR TOP OF BEAM IS ± 1".
- ⑥
- DRILLING BOLT HOLES THROUGH THE PARAPET, BOLTS, NUTS, WASHERS AND REPAIRING DAMAGED CONCRETE ARE INCIDENTAL TO THE CONTRACT.
- ⑦
- BOLTS MAY BE A325 BOLTS OR A449 BOLTS. BOLT LENGTH AND THREADING LENGTH ARE TO ALLOW FOR A TIGHT CONNECTION BETWEEN RIGID BARRIER AND THRIE BEAM CONNECTION PLATE. CONTRACTOR IS TO FIELD VERIFY BOLT LENGTH AND THREAD LENGTH. ONE ROUND WASHER REQUIRED BETWEEN BOLT HEAD AND THRIE BEAM CONNECTOR PLATE. BOLTS THAT EXTEND THROUGH THE PARAPET AND OUT THE BACK FACE REQUIRE A HARDENED ROUND STEEL WASHER THAT IS 2" O.D. X 5/32" THICK AND ONE PLATE WASHER. REPAIR ANY DAMAGED CONCRETE FROM BOLT INSTALLATION.
- ⑧
- THE RECESS FOR A W-BEAM CONNECTION, WHICH EXISTS ON SOME PARAPETS OF THIS TYPE, SHALL BE FILLED WITH A TREATED TIMBER BLOCKOUT. BLOCKOUT SIZE IS 1'-6" X 2'-0" X 3 1/2".
- ⑨
- BOLT, NUT AND WASHERS NOT REQUIRED FOR THIS LOCATION WHEN RETROFITTING AN EXISTING PAPAPET AND THE HOLE IS EITHER ABOVE PARAPET OR WITHIN 4 INCHES OF THE EDGE OF PARAPET.



FRONT VIEW  
W BEAM CONNECTION TO VERTICAL FACE PARAPET  
(USE ONLY ON THE TRAFFIC EXIT END OF ONE WAY BRIDGES)




SECTION G-G




FRONT VIEW

THRIE BEAM CONNECTION TO VERTICAL FACED PARAPETS



SECTION H-H


MIDWEST GUARDRAIL SYSTEM THRIE BEAM TRANSITION (MGS)	
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION	
APPROVED 07/2018	/S/ Rodney Taylor
DATE	ROADWAY STANDARDS DEVELOPMENT UNIT SUPERVISOR
FHWA	




**W BEAM CONNECTION TO  
PARAPETS WITH SLOPED ENDS**  
(USE ONLY AT TRAFFIC EXIT END OF ONE WAY BRIDGE)

## GENERAL NOTES


- ② OPTIONAL CURB AND GUTTER OR DRAINAGE FEATURE SEE PLAN FOR INFORMATION.
- ④ TOLERANCE FOR TOP OF BEAM IS  $\pm 1"$ .
- ⑥ DRILLING BOLT HOLES THROUGH THE PARAPET, BOLTS, NUTS, WASHERS AND REPAIRING DAMAGED CONCRETE ARE INCIDENTAL TO THE CONTRACT.
- ⑦ BOLTS MAY BE A325 BOLTS OR A449 BOLTS. BOLT LENGTH AND THREADING LENGTH ARE TO ALLOW FOR A TIGHT CONNECTION BETWEEN RIGID BARRIER AND THRIE BEAM CONNECTION PLATE. CONTRACTOR IS TO FIELD VERIFY BOLT LENGTH AND THREAD LENGTH. ONE ROUND WASHER REQUIRED BETWEEN BOLT HEAD AND THRIE BEAM CONNECTOR PLATE. BOLTS THAT EXTEND THROUGH THE PARAPET AND OUT THE BACK FACE REQUIRE A HARDENED ROUND STEEL WASHER THAT IS 2" O.D. X 5/32" THICK AND ONE PLATE WASHER. REPAIR ANY DAMAGED CONCRETE FROM BOLT INSTALLATION.



**DRILL HOLE LOCATION AND PATTERN  
FOR THRIE BEAM CONNECTION**




**THRIE BEAM CONNECTION TO BRIDGE  
PARAPETS WITH SLOPED ENDS**




**MIDWEST GUARDRAIL SYSTEM  
THRIE BEAM TRANSITION (MGS)**

STATE OF WISCONSIN  
DEPARTMENT OF TRANSPORTATION


APPROVED  
07/2018  
DATE /S/ Rodney Taylor  
ROADWAY STANDARDS DEVELOPMENT  
UNIT SUPERVISOR  
FHWA




BACK-UP PLATE DETAIL



SECTION J-J




BACK-UP PLATE MOUNTING ONTO BRIDGE RAILING



FRONT VIEW


THRIE BEAM CONNECTION TO TUBULAR RAILING TYPE "F"



SECTION K-K

GENERAL NOTES

- ④ TOLERANCE FOR TOP OF BEAM IS  $\pm 1"$ .
- ⑥ DRILLING HOLES THROUGH THE PAPER, BOLTS, NUTS, WASHERS AND REPAIRING DAMAGED CONCRETE ARE INCIDENTAL TO THE CONTRACT.




FRONT VIEW

THRIE BEAM CONNECTION TO STEEL RAILING TYPE "W"


MIDWEST GUARDRAIL SYSTEM THRIE BEAM TRANSITION (MGS)	
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION	
APPROVED 07/2018 DATE	/S/ Rodney Taylor ROADWAY STANDARDS DEVELOPMENT UNIT SUPERVISOR
FHWA	

GENERAL NOTES


④ TOLERANCE FOR TOP OF W-BEAM RAIL IS ± 1".



FRONT VIEW




PLAN VIEW  
BACK-UP PLATE DETAIL, TYPE "M"




FRONT VIEW

ANCHOR  
PLATE DETAIL,  
TYPE "M"




SECTION M-M



SECTION L-L


FRONT VIEW

ANCHOR AND BACK-UP PLATE MOUNTING TO BRIDGE RAILING, TYPE "M"



FRONT VIEW

M




PLAN VIEW

THRIE BEAM CONNECTION TO TUBULAR RAILING, TYPE "M"

MIDWEST GUARDRAIL SYSTEM  
THRIE BEAM TRANSITION (MGS)

STATE OF WISCONSIN  
DEPARTMENT OF TRANSPORTATION

APPROVED  
07/2018 /S/ Rodney Taylor  
DATE ROADWAY STANDARDS DEVELOPMENT  
FHWA UNIT SUPERVISOR



WELDING INSTRUCTION  
(VIEWED FROM BACK SIDE OF PLATE)

CONNECTOR PLATE DIMENSION (PER ASSEMBLY)				
PLATE	QUANTITY	SHAPE	SIZE (A x B x C x D)	THICKNESS
P1	1		20" x 20"	3/16"
P2	1		20" x 20" x 28 3/16"	3/16"
P3	1		39" x 3 5/8" x 20" x 19 5/16"	3/16"
S1	4		18 7/16" x 3 5/8" x 18 3/4"	1/4"
S2	1		10 1/4" x 2 1/16" x 10 3/8" x 1/2"	1/4"
S3	1		3" x 1 1/16" x 3 3/8" x 1/2"	1/4"
S4	1		6 1/8" x 2 7/16"	1/4"
S5	1		6 1/8" x 1 1/16"	1/4"
S6	1		7 3/4" x 1 3/4"	1/4"
S7	1		2 3/16" x 6" x 3 5/8" x 5 7/8"	1/4"
S8	1		1 5/32" x 7 1/2" x 2 1/2" x 7 3/8"	1/4"
S9	1		6 1/16" x 6 3/16" x 1 3/32"	1/4"
S10	1		1 7/8" x 9 7/8" x 3 5/8" x 9 11/16"	1/4"
S11	1		8 1/2" x 8 3/4" x 1 3/16"	1/4"

SINGLE SLOPE CONNECTION PLATE

GENERAL NOTES

- COVER PLATE PANELS ARE 3/16" THICK.
- ALL STIFFENERS ARE 1/4" THICK.
- CONNECTOR PLATE SHALL BE FABRICATED FROM ASTM GRADE A36 STEEL AND GALVANIZED.
- FOR GALVANIZED REQUIREMENTS, SEE SECTION 614 OF THE STANDARD SPECIFICATIONS.
- ALL HOLE DIAMETERS SHALL BE 1".
- FOR OPPOSITE SIDE INSTALLATION MIRROR DRAWINGS.

- STIFFENERS LOCATED AT THE OUTSIDE EDGES OF THE COVER PLATES SHALL BE WELDED AS FOLLOWS:  
SINGLE BEVEL GROOVE WELD ON EXTERNAL SIDES AND 3/16" FILLET WELD BY 1" LONG SPACED AT 2" ON INTERNAL SIDES.
- STIFFENERS LOCATED ON THE INSIDE OF THE COVER PLATE SHALL BE WELDED AS FOLLOWS:  
3/16" FILLET WELD BY 1" LONG SPACED AT 2".





PLATE AND STIFFENER IDENTIFICATION  
(VIEWED FROM BACK SIDE OF PLATE)


MIDWEST GUARDRAIL SYSTEM  
THRIE BEAM TRANSITION (MGS)

STATE OF WISCONSIN  
DEPARTMENT OF TRANSPORTATION

APPROVED  
7/2018  
DATE  
/S/ Rodney Taylor  
ROADWAY STANDARDS DEVELOPMENT  
UNIT SUPERVISOR  
FHWA




THRIE BEAM CONNECTION TO SINGLE SLOPE BARRIER




SINGLE SLOPE CONNECTION PLATE PLACEMENT

GENERAL NOTES

- CONNECTOR PLATE, DRILLING BOLT HOLES THROUGH THE PARAPET, BOLTS, NUTS, WASHERS AND REPAIRING DAMAGED CONCRETE ARE INCIDENTAL TO THE CONTRACT.
- (2) OPTIONAL CURB AND GUTTER OR DRAINAGE FEATURE SEE PLAN FOR INFORMATION.
- (7) BOLTS MAY BE A325 BOLTS OR A449 BOLTS. BOLT LENGTH AND THREADING LENGTH ARE TO ALLOW FOR A TIGHT CONNECTION BETWEEN RIGID BARRIER AND THRIE BEAM CONNECTION PLATE. CONTRACTOR IS TO FIELD VERIFY BOLT LENGTH AND THREAD LENGTH. ONE ROUND WASHER REQUIRED BETWEEN BOLT HEAD AND THRIE BEAM CONNECTION PLATE. BOLTS THAT EXTEND THROUGH THE PARAPET AND OUT THE BACK FACE REQUIRE A HARDENED ROUND STEEL WASHER THAT IS 2" O.D. X 5/32" THICK AND ONE PLATE WASHER. REPAIR ANY DAMAGED CONCRETE FROM BOLT INSTALLATION.




SECTION N-N




MIDWEST GUARDRAIL SYSTEM THRIE BEAM TRANSITION (MGS)	
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION	
APPROVED 7/2018 DATE	/S/ Rodney Taylor ROADWAY STANDARDS DEVELOPMENT UNIT SUPERVISOR
FHWA	

GENERAL NOTES

- ④ TOLERANCE FOR TOP OF BEAM IS  $\pm 1"$ .
- ⑫ BOLTS MAY BE A325 BOLTS OR A449 BOLTS. BOLT LENGTH AND THREADING LENGTH ARE TO ALLOW FOR A TIGHT CONNECTION BETWEEN RIGID BARRIER AND THRIE BEAM CONNECTION PLATE. CONTRACTOR IS TO FIELD VERIFY BOLT LENGTH AND THREAD LENGTH. ONE ROUND WASHER REQUIRED BETWEEN BOLT HEAD AND THRIE BEAM CONNECTOR PLATE. ON BACKSIDE OF PARAPET ONE ROUND WASHER, AND NUT REQUIRED. BOLT THREAD IS TO EXTEND  $\frac{1}{2}$ -INCH BEYOND NUT.



ELEVATION OF DETAIL AT NY3 END POST  
THRIE BEAM RAIL ATTACHMENT




ELEVATION OF DETAIL AT NY4 END POST  
THRIE BEAM RAIL ATTACHMENT

MIDWEST GUARDRAIL SYSTEM  
THRIE BEAM TRANSITION (MGS)

STATE OF WISCONSIN  
DEPARTMENT OF TRANSPORTATION

APPROVED	/S/ Rodney Taylor
7/2018	ROADWAY STANDARDS DEVELOPMENT
DATE	UNIT SUPERVISOR
FHWA	






## GENERAL NOTES

④ TOLERANCE FOR TOP OF BEAM IS  $\pm 1"$ .

⑫ BOLTS MAY BE A325 BOLTS OR A449 BOLTS. BOLT LENGTH AND THREADING LENGTH ARE TO ALLOW FOR A TIGHT CONNECTION BETWEEN RIGID BARRIER AND THRIE BEAM CONNECTION PLATE. CONTRACTOR IS TO FIELD VERIFY BOLT LENGTH AND THREAD LENGTH. ONE ROUND WASHER REQUIRED BETWEEN BOLT HEAD AND THRIE BEAM CONNECTOR PLATE. ON BACKSIDE OF PARAPET ONE ROUND WASHER, AND NUT REQUIRED. BOLT THREAD IS TO EXTEND  $\frac{1}{2}$ -INCH BEYOND NUT.

FRONT VIEW

### W BEAM TRANSITION AND CONNECTION TO BRIDGE RAILING TYPE "NY3" (USE ONLY ON THE TRAFFIC EXIT END OF ONE WAY BRIDGES)



FRONT VIEW

### W BEAM TRANSITION AND CONNECTION TO BRIDGE RAILING TYPE "NY4" (USE ONLY ON THE TRAFFIC EXIT END OF ONE WAY BRIDGES)

MIDWEST GUARDRAIL SYSTEM  
THRIE BEAM TRANSITION (MGS)

STATE OF WISCONSIN  
DEPARTMENT OF TRANSPORTATION

APPROVED

7/2018


DATE

FHWA


/S/ Rodney Taylor

ROADWAY STANDARDS DEVELOPMENT

UNIT SUPERVISOR




**PLAN VIEW  
STEEL MARKER POST**



**R / W PLAQUE**

THE RIGHT-OF-WAY PLAQUE AND INFORMATIVE PLAQUE WILL BE FURNISHED BY THE WISCONSIN DEPARTMENT OF TRANSPORTATION.



**INFORMATIVE PLAQUE**

## GENERAL NOTES


DETAILS OF CONSTRUCTION NOT SHOWN ON THIS DRAWING SHALL CONFORM TO THE PERTINENT REQUIREMENTS OF THE STANDARD SPECIFICATIONS AND THE APPLICABLE SPECIAL PROVISIONS.

A STEEL MARKER POST FOR RIGHT -OF-WAY SHALL BE PLACED IN THE RIGHT-OF-WAY WITH THE BACK OF THE POST ON THE LONGER RIGHT-OF-WAY TANGENT, 6 INCHES TO 24 INCHES FROM EACH TYPE 2 MONUMENT TO SERVE AS A GUARD POST, AND AT OTHER LOCATIONS AS SHOWN ON THE PLANS OR AS DIRECTED BY THE ENGINEER.


THE "R/W" PLAQUE SHALL FACE THE ROADWAY AND THE INFORMATIVE PLAQUE SHALL FACE AWAY FROM THE ROADWAY. "R/W" AND INFORMATIVE PLAQUES WILL BE FURNISHED BY THE WISCONSIN DEPARTMENT OF TRANSPORTATION.

STEEL MARKER POSTS SHALL MEET THE MINIMUM MATERIAL REQUIREMENTS FOR STEEL DELINEATOR POSTS; EXCEPT POSTS PAINTED WITH FEDERAL YELLOW ENAMEL NEED NOT BE ZINC COATED.


- ① IN AREAS OF SOLID ROCK, DRILL A BORE HOLE 2" GREATER THAN THE WIDEST DIMENSION OF THE POST CROSS SECTION INTO THE ROCK A MINIMUM DEPTH OF 12 INCHES. CUT OR SPLICE THE POST SO THAT A MINIMUM LENGTH OF 3' - 10" PROTRUDES ABOVE THE GROUND. BLOW OUT THE BORE HOLE IN THE ROCK USING COMPRESSED AIR. FILL THE BORE HOLE WITH CEMENT GROUT OR EQUIVALENT, DEPENDING ON THE STABILITY OF THE ROCK.




**FRONT VIEW  
STEEL MARKER POST**




**FRONT VIEW  
ROCK INSTALLATION** ①



**FRONT VIEW  
SPLICE DETAIL**



**SECTION A - A**



**SECTION B - B**


## MARKER POST FOR RIGHT - OF - WAY

STATE OF WISCONSIN  
DEPARTMENT OF TRANSPORTATION


APPROVED  
2/18/2016  
DATE

/S/ Ray Kumapayi  
CHIEF SURVEYING AND MAPPING  
ENGINEER

FHWA



**DETAIL A**  
**MAINLINE CLOSURE WITH POSTED DETOUR**  
WORK ZONE GREATER THAN OR EQUAL TO ½ MILE FROM  
DETOUR ROUTE ( 1000 FEET IF URBAN )




**DETAIL B**  
**MAINLINE CLOSURE WITH POSTED DETOUR**  
WORK ZONE LESS THAN ½ MILE FROM  
DETOUR ROUTE ( 1000 FEET IF URBAN )

- LEGEND**
- SIGN ON PERMANENT SUPPORT
  - TYPE III BARRICADE
  - TYPE III BARRICADE WITH ATTACHED SIGN
  - TYPE "A" WARNING LIGHT (FLASHING)
  - WORK AREA
  - FLAGS, 16" X 16" MIN. (ORANGE)

- DETOUR M4 - 8
- EAST M3 - X
- XX M1 - 4 OR XX M1 - 6 OR COUNTY X M1 - 5A
- OR M05 - 1 OR M06 - 1

SPEED LIMIT (MPH)	"STOP AHEAD" ADVANCE WARNING DISTANCE (FT)
25	200
30	200
35	350
40	350
45	500
50	550
55	750

SEE SDD 15C2-SHEET "b"  
FOR GENERAL NOTES  
AND FOOTNOTES ① THROUGH ⑦




**DETAIL C**  
**MAINLINE CLOSURE, NO POSTED DETOUR**

**BARRICADES AND SIGNS  
FOR MAINLINE CLOSURES**


STATE OF WISCONSIN  
DEPARTMENT OF TRANSPORTATION

APPROVED  
May 2023 /S/ Andrew Heidtke  
DATE WORK ZONE ENGINEER

FHWA



**DETAIL D**  
**ROAD CLOSURE BARRICADE DETAIL**  
**APPROACH VIEW**



**DETAIL E**  
**LANE CLOSURE BARRICADE DETAIL**  
**APPROACH VIEW**

SEE SDD 15C2 - SHEET "a" FOR LEGEND

**GENERAL NOTES**

THE EXACT NUMBER, LOCATION, AND SPACING OF ALL SIGNS AND BARRICADES SHALL BE ADJUSTED TO FIT FIELD CONDITIONS AS APPROVED BY THE ENGINEER.

ANY SIGNS TEMPORARY OR EXISTING, WHICH CONFLICT WITH TRAFFIC CONTROL "IN USE", SHALL BE REMOVED OR COVERED AS NEEDED AND AS APPROVED BY THE ENGINEER.

THE SPACING BETWEEN TRAFFIC CONTROL SIGNS SHOULD BE ADJUSTED TO NOT CONFLICT WITH AND SHOULD PROVIDE A DESIRABLE MINIMUM OF 200 FEET CLEARANCE TO EXISTING SIGNS THAT WILL REMAIN IN PLACE.

BARRICADES THAT MUST BE MOVED FOR A WORK OPERATION SHALL BE IMMEDIATELY RE-ESTABLISHED UPON COMPLETION OF THE OPERATION, OR FOR CONTINUING OPERATIONS, AT THE END OF EACH WORKING DAY.

SIGNS THAT WILL BE IN PLACE LESS THAN 7 CONTINUOUS DAYS AND NIGHTS MAY BE MOUNTED ON PORTABLE SUPPORTS.

ALL TYPE III BARRICADES SHALL HAVE RAILS REFLECTORIZED ON BOTH FACES. STRIPES SHALL BE PROPERLY SLOPED DOWN TOWARD THE TRAFFIC SIDE OR AS SHOWN IN THE ROAD CLOSURE BARRICADE DETAIL "D" FOR FULL ROAD CLOSURES.

TYPE "A" LOW - INTENSITY FLASHING WARNING LIGHTS SHALL BE VISIBLE ON BOTH SIDES OF THE BARRICADE.

THE R11 - 2, R11 - 3, M4 - 9, R11 - 4, AND R10 - 61 SIGNS PLACED ON THE BARRICADES SHALL COVER NO MORE THAN THE TOP RAIL. THE SIGNS SHALL NOT COVER ANY PORTION OF THE MIDDLE RAIL OR BOTTOM RAILS.

"WO" AND "MO" SIGNS ARE THE SAME AS "W" AND "M" SIGNS EXCEPT THE BACKGROUND IS ORANGE.

ALL SIGNS SHALL BE 48" X 48" UNLESS OTHERWISE NOTED BELOW:

- R11 - 2 SHALL BE 48" X 30"
- R11 - 3 SHALL, R11 - 4 AND R10 - 61 SHALL BE 60 " X 30"
- M4 - 9 SHALL BE 30" X 24"
- M3 - X SHALL BE 24" X 12" (36" X 18" IF NEEDED TO MATCH EXISTING SIGNS)
- M4 - 8 SHALL BE 24" X 12" (36" X 18" IF NEEDED TO MATCH EXISTING SIGNS)
- M1 - 4, M1 - 5A AND M1 - 6 SHALL BE 24" X 24" (36" X 36" IF NEEDED TO MATCH EXISTING SIGNS)
- MO5 - 1 AND MO6 - 1 SHALL BE 21" X 21" (30" X 30" IF NEEDED TO MATCH EXISTING SIGNS)
- D1 - X SHALL BE AS SHOWN ON SPECIFIC PROJECT SIGNING DETAIL SHEETS.
- R1 - 1 SHALL BE 36" X 36"


- 1 TWO WARNING LIGHTS SHALL BE PROVIDED ON THE CENTER BARRICADE AND A MINIMUM OF ONE WARNING LIGHT SHALL BE PROVIDED ON EACH OF THE OTHER BARRICADES WITHIN THE ROADWAY LIMITS. SPACING OF THE WARNING LIGHTS SHALL BE UNIFORM TO THE EDGE OF ROADWAY AS SHOWN (APPROX. 8 FOOT LIGHT SPACING).
- 2 THESE SIGNS AND BARRICADES ARE NOT REQUIRED IF ROAD CLOSURE BEGINS AT AN INTERSECTION.
- 3 FOR ROAD CLOSURE WITHOUT LOCAL ACCESS TO PROJECT, SEE ROAD CLOSURE BARRICADE DETAIL "D".
- 4 FOR ROAD CLOSURE WITH LOCAL ACCESS TO PROJECT, SEE ROAD CLOSURE BARRICADE DETAIL "E".
- 5 FOR BRIDGE OR CULVERT REPLACEMENTS, SUBSTITUTE "BRIDGE OUT" INSTEAD OF "ROAD CLOSED" ON R11 - 2 AND R11 - 3 SIGNS.
- 6 INSTALL DETOUR AND COMMUNITY GUIDE SIGNS AND ARROWS ONLY IF SPECIFIED IN THE CONTRACT. IF THERE ARE EXISTING ROUTE MARKER ASSEMBLIES THAT WILL REMAIN IN PLACE, ADJUST THE LOCATION OF THE DETOUR ROUTE SIGNS TO CORRESPOND WITH THE EXISTING ASSEMBLIES. MODIFY EXISTING SIGNS WHERE POSSIBLE. SEE SPECIFIC PROJECT DETOUR SIGNING DETAIL SHEETS. IF DETOUR SIGNS ARE BEING INSTALLED BY OTHERS, PLACE THE CONTRACTED TRAFFIC CONTROL SIGNS TO ALLOW FOR PLACEMENT OF ALL WARNING, DETOUR AND GUIDE SIGNS AS SHOWN.
- 7 "EAST" CARDINAL DIRECTION MARKERS AND RIGHT TURN ARROWS ARE SHOWN. USE OTHER CARDINAL DIRECTIONS AND ARROWS AS APPROPRIATE.

**BARRICADES AND SIGNS**  
**FOR**  
**VARIOUS CLOSURES**


STATE OF WISCONSIN  
DEPARTMENT OF TRANSPORTATION

APPROVED  
May 2023 /S/ Andrew Heidtke  
DATE WORK ZONE ENGINEER

FHWA



**SITUATION 1**  
WARRANTING CRITERIA:  
BRIDGE WIDTH IS AT LEAST 16 FEET BUT LESS THAN 24 FEET.



**SITUATION 2**  
WARRANTING CRITERIA:  
1. BRIDGE WIDTH IS AT LEAST 24 FEET AND  
2. BRIDGE SHOULDER WIDTH IS LESS THAN 6 FEET

**GENERAL NOTES**

DETAILS OF TRAFFIC CONTROL DEVICES AND INSTALLATION NOT SHOWN ON THE DRAWING SHALL CONFORM TO THE PERTINENT REQUIREMENTS OF THE STANDARD SPECIFICATIONS, THE SPECIAL PROVISIONS, AND THE MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES.

LOCATE W5-52 SIGN POST(S) BEHIND GUARDRAIL WHEN PRESENT.

PLACE THE EDGE OF THE W5-52 SIGN IN LINE WITH FACE OF CURB OR PARAPET.

ON BRIDGE ONLY PROJECTS, PLACE 300 FEET OF EDGELINE.

OMIT EDGELINES ON ROADWAYS WITHOUT EXISTING EDGELINES.

① OMIT ON ONE-WAY TRAVELED WAYS.

**LEGEND**

⊙ SIGN ON PERMANENT SUPPORT

➡ DIRECTION OF TRAFFIC


**DISTANCE TABLE**

POSTED OR 85TH PERCENTILE SPEED	DISTANCE "A"
25	150'
30	200'
35	250'
40	300'
45	400'
50	550'
55	700'


**SIGNING AND MARKING  
FOR TWO LANE BRIDGES**

STATE OF WISCONSIN  
DEPARTMENT OF TRANSPORTATION

APPROVED  
May 2023 /S/ Jeannie Silver  
DATE Statewide Pavement Marking Engineer  
FHWA



TWO WAY TRAFFIC



ONE WAY TRAFFIC

PERMANENT PAVEMENT MARKING

\*CONFIRM MARKING LINE WIDTH WITH THE MISCELLANEOUS QUANTITIES

GENERAL NOTES


DETAILS OF CONSTRUCTION NOT SHOWN ON THIS DRAWING SHALL CONFORM TO STANDARD SPECIFICATIONS AND SPECIAL PROVISIONS.

- ① LOCATE THE NO PASSING ZONE W14-3 SIGN WITHIN 50 FEET OF THE "T" MARKING
- ② MEASURE FROM EDGE OF MARKING TO JOINT LINE. THIS DOES NOT INCLUDE SPACE NEEDED FOR GROOVING OPERATIONS.

LEGEND


- "T" MARKING
- SIGN ON PERMANENT SUPPORT
- DIRECTION OF TRAFFIC

PERMANENT LONGITUDINAL PAVEMENT MARKINGS	
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION	
APPROVED May 2023 DATE	/S/ Jeannie Silver Statewide Pavement Marking Engineer
FHWA	




**DRUM**

BALLAST WIDTHS  
RANGE FROM 24"-36"




**42" CONE**

DO NOT USE IN TAPERS  
½ SPACING OF DRUMS  
BALLAST WIDTHS  
RANGE FROM 14"-20"




**VERTICAL PANEL**

THE STRIPES SHALL SLOPE DOWNWARD TO  
THE TRAFFIC SIDE FOR CHANNELIZATION.



**TYPE II BARRICADE**

FOR RAILS LESS THAN 36" LONG, 4" WIDE STRIPES  
MAY BE USED. ALL STRIPES SHALL SLOPE DOWNWARD  
TO THE TRAFFIC SIDE FOR CHANNELIZATION.



**TYPE III BARRICADE**

IF SIGN MOUNTED, DO NOT COVER MORE THAN 50% OF THE TOP  
TWO RAILS OR 33% OF THE TOTAL AREA OF THE THREE RAILS.

\* IF USED FOR A PERMANENT APPLICATION USE RED SHEETING.

**GENERAL NOTES**

- ① REFLECTIVE SHEETING SHALL FOLLOW THE REQUIREMENTS IN THE APPROVED PRODUCTS LISTING FOR SIGN SHEETING.
- ② LOCATION OF WARNING LIGHTS WHEN SHOWN ON THE PLAN.


**CHANNELIZING DEVICES  
DRUMS, CONES, BARRICADES  
AND VERTICAL PANELS**

STATE OF WISCONSIN  
DEPARTMENT OF TRANSPORTATION


APPROVED  
November 2022 /S/ Andrew Heidtke  
DATE WORK ZONE ENGINEER

FHWA


TYPICAL ASSEMBLIES



J1-1




J1-2




J1-3




JR1-1




J2-1




J2-2




J2-3



J3-1




J3-2




J3-3




J4-1




J4-2




J4-2




J12-1




J13-1




J32-1



J33-1



J22-1



J23-1




JR13-1



JR23-1



JR99-1




JH-1

Blue Background

Black

blue background with interstate





JV

( Typical Vertical J-Assembly  
See Note 10 and 11)

NOTES

1. Signs are Type II - Type H Reflective
2. Color:  
Background - Black Non-reflective  
Message - see Note 4
3. Message Series - See Note 4
4. The colors and message spacing on each marker shall be according to the applicable route marker panel specifications.
5. Certain marker heads require the component pieces to be the same color. As an example, all the components used with an M1-1 Interstate marker shall be blue.
6. Single panel j-assemblies shall only be used with route marker shields that are same size. If the route marker shields are different size use multiple piece component.
7. Route assemblies that have 24 inch route shields and have dimensions greater than 48 inches (both vertical and horizontal) shall have one horizontal splice between the arrows and route shields. Vertical splices shall not be used on route assemblies with a horizontal dimension of 144 inches or less. The contractor shall not use more than one vertical joint per sign and the joint shall be between route shields.
8. Route assemblies that have 36 inch shields and have dimensions greater than 48 inches (both vertical and horizontal) shall have two horizontal splices. One horizontal splice shall be between the cardinal direction and route shields and the other horizontal splice shall be between the arrows and route shields. Vertical splices shall not be used on route assemblies with a horizontal dimension of 144 or less. The contractor shall not use more than one vertical joint per sign and the joint shall be between route shields.
9. All Vertical J Assemblies are given a Sign Code of JV
10. For JV Assemblies that have a mixture of Interstate and Non-Interstate shields, arrows and cardinals shall be white on blue.
11. For JV Assemblies that have a mixture of Non-Interstate and Auto-Tour shields, arrows and cardinals shall be black on white.



black background

ROUTE MARKERS & COMPONENTS  
IN TYPICAL ASSEMBLIES

WISCONSIN DEPT OF TRANSPORTATION

APPROVED *Matthew R. Rauch*  
for State Traffic Engineer

DATE 6/7/23 PLATE NO. A2-1S.10



PROJECT NO:

SHEET NO:

E





## URBAN AREA



\* \* The existence of curb and gutter does not in itself mandate the vertical clearance illustrated. That height is typically measured where there is sidewalk adjacent to the roadway or parking is permitted. In the absence of sidewalk vertical clearance is measured from the top of the curb. Offset of signs is measured from the flow line.

## RURAL AREA (See Note 2)



\* 6 feet from edge of a paved shoulder or 12 feet from the edge of pavement (edge line location) or 2 feet from outside edge of gravel, whichever is greater unless directed by project engineer.

## GENERAL NOTES

1. Signs wider than 4 feet or 20 sq.ft or larger, shall be mounted on multiple posts. Refer to plate A4-4.
2. If signs are mounted on or behind barrier wall, see A4-10 sign plate.  
The Double Arrow sign (W12-1D) shall be mounted at a height of 2'-3" (±) 3". The Chevron sign (W1-8), Roundabout Chevron panel (R6-4B), Enhanced Reference Markers, Clearance Markers (W5-52), Mile Markers (D10 series), In Road Object Markers (W5-54) & End of Road Markers (W5-56) shall be mounted at a height of 4'-3" (±) 3".
3. For expressways and freeways, mounting height is 7'- 3" (±) 3" or 6'-3" (±) 3" depending upon existence of a sub-sign.
4. Minimum mounting height for signs mounted on traffic signal poles is 5'- 3" (±) 3".
5. Offset distance shall be consistent with existing signs or consistent throughout length of project.
6. Folding signs shall be mounted at a height of 5'-3" (±) 3" or as directed by the Engineer.

## POST EMBEDMENT DEPTH

Area of Sign Installation ( Sq. Ft. )	D ( Min )
20 or Less	4'
Greater than 20	5'

TYPICAL INSTALLATION  
OF PERMANENT TYPE II  
SIGNS ON SINGLE POSTS

WISCONSIN DEPT OF TRANSPORTATION

APPROVED

*Matthew R. Rauch*  
for State Traffic Engineer

DATE 12/6/23

PLATE NO. A4-3.23


PROJECT NO:

HWY:

COUNTY:

SHEET NO:


E



### ELEVATION VIEW


DETAIL OF WOOD 4 X 6 SIGN POST IN BOX-OUT

- NOTES: 1. ALL MATERIAL TO BE APPROVED BY ENGINEER PRIOR TO INSTALLATION
2. SEE SIGN PLATE A4-8 FOR SIGN HARDWARE REQUIREMENTS
3. 18 INCH X 18 INCH SQUARE BOX-OUTS MAY BE USED FOR INSTALLATIONS IN EXISTING CONCRETE OR ASPHALT LOCATIONS.



### ELEVATION VIEW

DETAIL OF STEEL 2 X 2 SIGN POST IN BOX-OUT



### PLAN VIEW

FOR NEW CONCRETE/ASPHALT INSTALLATIONS

SIGN POST  
BOX-OUTS  
A4-3B

WISCONSIN DEPT OF TRANSPORTATION

APPROVED *Matthew R. Rauch*  
for State Traffic Engineer

DATE 1/27/14 PLATE NO. A4-3B.1

PROJECT NO:


HWY:

COUNTY:



SHEET NO:

E


URBAN AREA




RURAL AREA (See Note 3)



2' Min - 4' Max (See Note 6)



48" DIAMOND WARNING SIGN



48" DIAMOND WARNING SIGN

\*\*\*

SIGN SHAPE OTHER THAN DIAMOND (TWO POSTS REQUIRED)	
L	E
Greater than 48" Less than 60"	12"
60" to 108"	L/5

SIGN SHAPE OTHER THAN DIAMOND (THREE POSTS REQUIRED)	
L	E
Greater than 108" to 144"	12"

POST EMBEDMENT DEPTH

Area of Sign Installation ( Sq.Ft. )	D ( Min )
20 or Less	4'
Greater than 20	5'

TYPICAL INSTALLATION  
OF TYPE II SIGNS  
ON MULTIPLE POSTS

WISCONSIN DEPT OF TRANSPORTATION	
APPROVED	<i>Matthew R. Rauch</i> for State Traffic Engineer
DATE 12/6/23	PLATE NO. A4-4.16


GENERAL NOTES

- For 3 or 4 post installations, individual post spacing shall be greater than 3'-6".
- See tables below for required number of posts.
- For expressways and freeways, mounting height is 7'-3" (±) 3" or 6'-3" (±) 3" depending upon existence of sub-sign.
- The (±) tolerance for mounting height is 3 inches.
- J-Assemblies are considered to be one sign for mounting height.
- Offset distance shall be consistent with existing signs or consistent throughout length of project.
- Folding signs shall be mounted at a height of 5'-3" (±) 3" or as directed by the engineer.
- The Double Arrow sign (W12-1) shall be mounted at a height of 2'-3" (±) 3". The Chevron sign (W1-8), Roundabout Chevron panel (R6-4B), Clearance Markers (W5-52), Mile Markers (D10 series), In Road Object Markers (W5-54) & End of Road Markers (W5-56) shall be mounted at a height of 4'-3" (±) 3".


\* 6 feet from edge of a paved shoulder or 12 feet from the edge of pavement (edge line location) or 2 feet from outside edge of gravel, whichever is greater unless directed by project engineer.

\*\* The existence of curb and gutter does not in itself mandate the vertical clearance illustrated. That height is typically measured where there is sidewalk adjacent to the roadway or parking is permitted. In the absence of sidewalk vertical clearance is measured from the top of the curb. Offset of signs is measured from the flow line.

\*\*\* See A4-3 sign plate for signs 4' or less in width and less than 20 S.F. in area.



SIGN SHALL BE MOUNTED TO PROJECT  
ABOVE THE TOP OF THE POST



Nuts, bolts and lags used for mounting signs shall have hexagonal heads and shall be either :

- a. Hot dip galvanized in accordance with ASTM Designation: A 153, Class D, or SC 3
- b. Electro-galvanized in accordance with ASTM Designation : B 633, TYPE III, SC 3.

Threads on bolts and nuts shall be manufactured with sufficient allowance for the cadmium plate or galvanized coating to permit the nuts to run freely on the bolts.

STRINGER BOLTING TO ALUMINUM SIGNS (SEE SIGN PLATE A4-18)

MACHINE BOLTS - 5/16" X 1-3/4" Length w/ lock nuts

WOOD POSTS (4" x 6")

LAG SCREWS - 3/8" X 3" (NO STRINGERS ON BACK OF SIGN)  
3/8" X 4" (STRINGERS ON BACK OF SIGN)

SQUARE STEEL POSTS (2" x 2")

MACHINE BOLTS - 3/8" X 3-1/4" Length w/ nuts (NO STRINGER ON BACK OF SIGN)  
3/8" X 5" Length w/ nuts (STRINGERS ON BACK OF SIGN)

RIVETS - 9/32" (6605-9-6) BULB-TITE, TRI-FOLD, ALUMINUM BODY/MANDREL  
O.D. FLANGE .720-.765 INCH, GRIP RANGE .042-.375 INCH

WASHERS (ALL POSTS) -

1-1/4" O.D. X 3/8" I.D. X 1/16" STEEL

1-1/4" O.D. X 3/8" I.D. X .080 NYLON

\* Two different fastening systems are shown for illustration purposes. On any individual sign, either one or the other system shall be used. Actual number of fasteners per sign varies with the sign area, but normally there are two. For a single post installation, all signs greater than 9 sq. ft. require the use of 3 fasteners.


# ATTACHMENT OF SIGNS TO POSTS

WISCONSIN DEPT OF TRANSPORTATION


APPROVED Matthew R. Rauch  
For State Traffic Engineer

DATE 4/1/2020 PLATE NO. A4-8.9

**2 1/4 " SQUARE  
12 GAUGE  
PERFORATED  
GALVANIZED FINISH**



**2 1/2" SQUARE  
12 GAUGE  
OMNI-DIRECTIONAL  
PERFORATED  
SOIL STABILIZING SLEEVE  
GALVANIZED FINISH**



LENGTH SHOWN ON MISC. QTY'S  
 18" DIA SCHEDULE 40 PVC BOX-OUT  
 TELESCOPE PIECES FLUSH AT TOP  
 2" STEEL TUBULAR SQUARE UPPER SECTION  
 ALL HOLES  $\frac{7}{16}$ " SPACED 1" C-C ALL FOUR SIDES  
 $\frac{3}{8}$ " ZINC PLATED CORNER ANCHOR BOLT AND NUT  
 2" GRAVEL OR DIRT  
 $\frac{3}{8}$ " ZINC PLATED ANCHOR BOLT AND NUT  
 2" SQUARE X 18" (SOIL STABILIZING SLEEVE)  
 2" SQUARE X 36"  
 SEE SIGN PLATE A4-8 FOR BOLT WASHER, & NUT MATERIAL  
 SIGN

LENGTH SHOWN ON MISC. QTY'S

TELESCOPE PIECES FLUSH AT TOP

2" STEEL TUBULAR SQUARE UPPER SECTION

ALL HOLES  $\frac{7}{16}$ " SPACED 1" C-C ALL FOUR SIDES

$\frac{3}{8}$ " ZINC PLATED CORNER ANCHOR BOLT AND NUT

1"

$\frac{3}{8}$ " ZINC PLATED ANCHOR BOLT AND NUT


2 1/2" SQUARE X 18" (SOIL STABILIZING SLEEVE)

2 1/4" SQUARE X 36"

SIGN

SEE SIGN PLATE A4-8 FOR BOLT WASHER, & NUT MATERIAL

3/8" ZINC PLATED CORNER  
ANCHOR BOLT AND NUT



DIRECTION  
OF TRAFFIC

SECTION A-A

Area of Sign Installation (Sq. Ft.)	Number of Required Posts
9 or less	1
Greater than 9 less than or equal to 18	2
Greater than 18 less than or equal to 27	3

TUBULAR STEEL  
SIGN POST  
A4-9

WISCONSIN DEPT OF TRANSPORTATION


APPROVED Matthew R Rauch

for State Traffic Engineer

DATE 2/05/15 PLATE NO. A4-9.9

PROJECT NO:	HWY:	COUNTY:	SHEET NO:	E
-------------	------	---------	-----------	---

7



GENERAL NOTES

1. All 4 x 6 Wood Posts shall be modified by having two 1½" diameter holes drilled perpendicular to the roadway centerline.

7

4 X 6 WOOD POST MODIFICATIONS

WISCONSIN DEPT OF TRANSPORTATION




APPROVED *Chester J. Spang*  
for State Traffic Engineer

DATE 3/27/97 PLATE NO. A4-11.2


PROJECT NO:	HWY:	COUNTY:	SHEET NO:	E
-------------	------	---------	-----------	---

BANDING

SINGLE SIGN



WASHER PLACEMENT





WASHERS (ALL POSTS) -  
1-1/4" O.D. X 3/8" I.D. X 1/16" STEEL  
1-1/4" O.D. X 3/8" I.D. X .080 NYLON  
FOR ALL TYPE H SIGNS

GENERAL NOTES

1. Any sign over 3 feet in width shall use the V-Block banding method. See A5-10 standard plate.
2. Signs 3 feet or greater in height shall have three bracket bands installed. Signs less than 3 feet in height shall have two bracket bands installed.
3. Banding and assembly bracket shall be stainless steel. All bands shall be 3/4" in width and 0.025" thickness.
4. ALL SIGN MOUNTING BOLTS AND WASHERS SHALL BE EITHER:
  - a. Hot dip or mechanically galvanized in accordance with ASTM Designation: A 153, Class D
  - b. Electro-galvanized in accordance with ASTM designation: B 633, Type III, SC 3


"J" ASSEMBLY



STANDARD SIGN  
SIGN BANDING DETAILS


WISCONSIN DEPT OF TRANSPORTATION

APPROVED *Matthew R. Rauch*  
for State Traffic Engineer  
DATE 6/10/19 PLATE NO. A5-9.4



VIEW FROM  
BACK

VIEW FROM SIDE



VIEW FROM TOP

## GENERAL NOTES

1. WOOD 4"X6" POST MATERIAL SHALL CONFORM TO 507.2.2 OF THE WISDOT STANDARD SPECIFICATIONS
2. BLOCK BANDING AND CLIPS SHALL BE STAINLESS STEEL,  $\frac{3}{4}$ " WIDTH AND 0.025" THICKNESS
3. SIGNS 3' OR GREATER IN HEIGHT SHALL UTILIZE 3 BLOCK BANDS. SIGNS UNDER 3' IN HEIGHT SHALL UTILIZE 2 BLOCK BANDS
4. ACTUAL NUMBER OF FASTENERS PER SIGN VARIES WITH THE SIGN AREA, BUT NORMALLY THERE ARE TWO. FOR SIGNS GREATER THAN 9 S.F. 3 FASTENERS SHALL BE USED.
5. ALL SIGN MOUNTING BOLTS AND WASHERS SHALL BE EITHER:
  - a. Hot dip or mechanically galvanized in accordance with ASTM Designation: A 153, Class D
  - b. Electro-galvanized in accordance with ASTM Designation : B 633, TYPE III, SC 3
6. ALL BOLTS SHALL HAVE HEXAGONAL HEADS.
7. STEEL WASHERS SHALL BE  $\frac{1}{4}$ " O.D. X  $\frac{3}{8}$ " I.D. X  $\frac{1}{16}$ "
8. NYLON WASHERS SHALL BE  $\frac{1}{4}$ " O.D. X  $\frac{3}{8}$ " I.D. X .080 FOR TYPE H OR TYPE F FACE SIGN

✱ LAG BOLTS SHALL BE  $\frac{3}{8}$ " X  $2\frac{1}{2}$ "

BLOCK BANDING DETAIL  
( V-BLOCK OPTION )

WISCONSIN DEPT OF TRANSPORTATION

APPROVED *Matthew R. Rauch*  
for State Traffic Engineer





DATE 4/19/2022 PLATE NO. A5-10.3

PROJECT NO:

SHEET NO:

E









NOTES

1. Sign is Type II - Type H Reflective
2. Color:  
Background - White & Black  
Message - Black
3. Message Series - see Note 4
4. Message Series E for 1 letter.  
Message Series D for 2 letters unless  
message is too big then Series C.  
Message Series C for 3 letters unless  
message is too big then Series B.
5. Substitute appropriate letters & optically  
center to achieve proper balance.


[illegible]

CTH MARKER	
M1-5A FOR ASSEMBLIES	
WISCONSIN DEPT OF TRANSPORTATION	
APPROVED	<u>Matthew R Rauch</u> For State Traffic Engineer
DATE 11/8/2022	PLATE NO. M1-5A.9

PROJECT NO:	HWY:	COUNTY:		SHEET NO:	<b>E</b>
-------------	------	---------	--	-----------	----------



- NOTES**
- Signs are Type II - Type H Reflective except as Shown
  - Color:  
Background - See note 4  
Message - See note 4
  - Corners may be square or rounded when base material is plywood but borders shall be rounded as shown. When base material is metal, the corners and borders shall be rounded.
  - M6-1 and M6-2 Background - White  
Message - Black  
MB6-1 and MB6-2 Background - Blue  
Message - White  
MK6-1 and MK6-2 Background - Green  
Message - White  
MM6-1 and MM6-2 Background - White  
Message - Green  
MN6-1 and MN6-2 Background - Brown  
Message - White  
M06-1 and M06-2 Background - Orange - Type F Reflective  
Message - Black  
MP6-1 and MP6-2 Background - White  
Message - Blue  
MR6-1 and MR6-2 Background - Brown  
Message - Yellow



SIZE	A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q	R	S	T	U	V	W	X	Y	Z	Area sq. ft.	
1																												
2S	21		1 1/2	3/8	3/8		7 1/2	7 1/8	5 5/8	5	4 1/4	5 1/4	3	2 5/8	1/2							1/2						3.06
2M	21		1 1/2	3/8	3/8		7 1/2	7 1/8	5 5/8	5	4 1/4	5 1/4	3	2 5/8	1/2							1/2						3.06
3	30		1 7/8	1/2	5/8		10 3/4	10 1/4	8	7 1/4	6	7 1/2	4 1/4	3 3/4	3/4							1/2						6.25
4	30		1 7/8	1/2	5/8		10 3/4	10 1/4	8	7 1/4	6	7 1/2	4 1/4	3 3/4	3/4							1/2						6.25
5	30		1 7/8	1/2	5/8		10 3/4	10 1/4	8	7 1/4	6	7 1/2	4 1/4	3 3/4	3/4							1/2						6.25

PROJECT NO:

HWY:

COUNTY:

SHEET NO:

E


STANDARD SIGN  
M6-1 & M6-2  
SERIES

WISCONSIN DEPT OF TRANSPORTATION

APPROVED *Matthew R. Rauch*  
For State Traffic Engineer

DATE 2/13/2023 PLATE NO. M6-1.16

7



NOTES

- 1. Sign is Type II - Type H Reflective - reference WIS DOT Standard Specification for HIGHWAY and STRUCTURE CONSTRUCTION latest edition.
- 2. Color:  
Background - Red  
Message - White
- 3. Message Series - C

7

R1-1

SIZE	A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q	R	S	T	U	V	W	X	Y	Z	Area sq. ft.
1	30				5/8	10	12 1/2	45°		12 3/4																	5.18
2S	30				5/8	10	12 1/2	45°		12 3/4																	5.18
2M	36				3/4	12	15	45°		15 3/8																	7.46
3	36				3/4	12	15	45°		15 3/8																	7.46
4	48				1	16	20	45°		20 1/2																	13.25
5	48				1	16	20	45°		20 1/2																	13.25
6	18				3/8	6	7 3/4	45°		7 3/4																	1.86
7	12				1/4	4	5	45°		5 1/8																	0.78



STANDARD SIGN

R1 - 1

WISCONSIN DEPT OF TRANSPORTATION

APPROVED *Matthew R. Rauch*  
for State Traffic Engineer

DATE 11/12/15 PLATE NO. R1-1.13



NOTES

1. Sign is Type II - Type F Reflective
2. Color:  
Background - Yellow  
Message - Black
3. Alternate colors of stripes as shown.

SIZE	A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q	R	S	T	U	V	W	X	Y	Z	Area sq. ft.
1																											
2S	12	36	1 1/2			4 3/8	3 1/2	5 5/8	45°	4	4																3.0
2M	12	36	1 1/2			4 3/8	3 1/2	5 5/8	45°	4	4																3.0
3	18	54	1 1/2			6	5 1/2	8 1/2	45°	6	6 9/16																6.75
4																											
5																											

STANDARD SIGN  
W5-52L & W5-52R

WISCONSIN DEPT OF TRANSPORTATION

APPROVED *Matthew R. Rauch*  
For State Traffic Engineer

DATE 3/4/2024 PLATE NO. W5-52.10

DESIGN DATA

**LIVE LOAD:**  
DESIGN LOADING: HL-93  
INVENTORY RATING FACTOR: RF = 1.17  
OPERATING RATING FACTOR: RF = 1.51  
WISCONSIN STANDARD PERMIT VEHICLE (WIS.-SPV): 250 (KIPS)

STRUCTURE IS DESIGNED FOR A FUTURE WEARING SURFACE OF 20 POUNDS PER SQUARE FOOT.

**MATERIAL PROPERTIES:**

CONCRETE MASONRY: \_\_\_\_\_ f'c = 4,000 P.S.I.  
SUPERSTRUCTURE \_\_\_\_\_ f'c = 3,500 P.S.I.  
ALL OTHER \_\_\_\_\_

BAR STEEL REINFORCEMENT: \_\_\_\_\_ fy = 60,000 P.S.I.  
GRADE 60 \_\_\_\_\_

**FOUNDATION DATA**

ABUTMENTS TO BE SUPPORTED ON CIP 10 3/4 x 0.25 PILING DRIVEN TO A REQUIRED DRIVING RESISTANCE OF 130 TONS ++ PER PILE AS DETERMINED BY THE MODIFIED GATES DYNAMIC FORMULA.  
ESTIMATED 100 FEET LONG PILES AT BOTH ABUTMENTS.

++ THE FACTORED AXIAL RESISTANCE OF PILES IN COMPRESSION USED FOR DESIGN IS THE REQUIRED DRIVING RESISTANCE MULTIPLIED BY A RESISTANCE FACTOR OF 0.5 USING MODIFIED GATES TO DETERMINE DRIVEN PILE CAPACITY.

**TRAFFIC VOLUME**

CTH E  
ADT = 1,190 (2045)  
R.D.S. = 50 M.P.H.

**HYDRAULIC DATA**

**100 YEAR FREQUENCY**

Q<sub>100</sub> = 246 C.F.S.  
VEL. = 2.50 F.P.S.  
HW<sub>100</sub> = EL. 797.46  
WATERWAY AREA = 98.4 SQ. FT.  
DRAINAGE AREA = 11.0 SQ. MI.  
ROADWAY OVERTOPPING = N/A  
SCOUR CRITICAL CODE = 5

**2 YEAR FREQUENCY**

Q<sub>2</sub> = 90 C.F.S.  
VEL. = 1.5 F.P.S.  
HW<sub>2</sub> = 796.50

**LIST OF DRAWINGS**

1. GENERAL PLAN
2. CROSS SECTION & QUANTITIES
3. SUBSURFACE EXPLORATION
4. SOUTH ABUTMENT
5. SOUTH ABUTMENT DETAILS
6. NORTH ABUTMENT
7. NORTH ABUTMENT DETAILS
8. SUPERSTRUCTURE
9. SUPERSTRUCTURE DETAILS
10. TUBULAR RAILING TYPE M

**STRUCTURE DESIGN CONTACTS:**

PATRICK BOLAND 608-588-7484  
AARON BONK 608-261-0261

THESE PLANS ARE BASED UPON STANDARD BRIDGE PLANS DEVELOPED AND MAINTAINED BY THE WISCONSIN DEPARTMENT OF TRANSPORTATION THROUGH THE USE OF THE WISDOT STANDARD BRIDGE DESIGN TOOL. THE UNDERSIGNED DESIGNER CERTIFIES THE ACCURACY OF THE BRIDGE TYPE, SIZE AND LOCATION, HYDRAULICS AND FOUNDATION SUPPORT, AND INFORMATION IN THE PLANS THAT IS NOT PART OF THE STANDARD PLANS SUPPLIED BY THE DEPARTMENT. THE DESIGNER FURTHER CERTIFIES THAT USE OF THE STANDARD BRIDGE DESIGN TOOL FOR DEVELOPMENT OF THIS PLAN IS CONSISTENT WITH THE GUIDANCE PROVIDED IN THE WISDOT BRIDGE MANUAL.



**JEWELL**

560 SUNRISE DRIVE  
SPRING GREEN, WI 53588  
OFFICE: (608) 588-7484  
www.JewellAssoc.com

STATE OF WISCONSIN  
DEPARTMENT OF TRANSPORTATION

ACCEPTED *[Signature]* SDR 11/05/24  
CHIEF STRUCTURES DESIGN ENGINEER DATE

**STRUCTURE B-69-0054**

CTH E OVER LITTLE SILVER CREEK

COUNTY WAUSAHA TOWN LEON

DESIGN SPEC. AASHTO LRFD BRIDGE DESIGN SPECIFICATION  
DESIGNED BY CTMP CK'D PTB DRAWN BY CTMP PLANS CK'D PTB

**GENERAL PLAN**

SHEET 1 OF 10

\* PROVIDE FOR THREE BEAM GUARD RAIL ATTACHMENT.



INDICATES WING NUMBER

VOIDS IN THE RIPRAP HEAVY SHALL BE FILLED WITH SELECT CRUSHED MATERIAL. COST OF THE SELECT CRUSHED MATERIAL IS PAID FOR UNDER BID ITEM "SELECT CRUSHED MATERIAL FOR TRAVEL CORRIDOR". ENTIRE SURFACE OF RIPRAP HEAVY TO BE COVERED.

ALLIANT ENERGY TO REMAIN


BRIGHTSPEED TO REMAIN

REMOVING STRUCTURE OVER WATERWAY DEBRIS CAPTURE B-69-0202, STEEL DECK GIRDER STRUCTURE  
26.5' OVERALL DECK WIDTH  
27.0' OVERALL LENGTH



**PLAN B-69-54**

SINGLE SPAN FLAT SLAB



**ELEVATION**

NORMAL TO LITTLE SILVER CREEK



PROTECTIVE SURFACE TREATMENT TO BE APPLIED TO ENTIRE EXPOSED TOP OF SLAB, INCLUDING THE SLAB EDGE AND 1'-0" UNDER THE SLAB, THE TOP AND EXTERIOR EXPOSED FACE OF WINGS AND FRONT FACE OF ABUTMENT TO 1'-0" PAST THE EDGE OF SLAB.

NO.	STATION	DESCRIPTION	ELEV.
1	8+53	3/4" IRON REBAR SET, 22.5' LT.	804.20
2	12+54	3/4" IRON REBAR SET, 34.8' RT.	799.89
3	10+32	3/4" IRON REBAR SET, 18.5' RT.	800.18
11	11+26	RAILROAD SPIKE SET IN POWER POLE, 31.8' LT.	796.81



THE RODENT SHIELD SHALL BE A PVC GRATE SIMILAR TO THIS DETAIL. THE GRATE IS COMMERCIALY AVAILABLE AS A FLOOR STRAINER. A PIPE COUPLING IS REQUIRED FOR THE ATTACHMENT OF THIS SHIELD TO THE EXPOSED END OF THE PIPE UNDERDRAIN. THE SHIELD SHALL BE FASTENED TO THE PIPE COUPLING WITH TWO OR MORE NO. 10 X 1-INCH STAINLESS STEEL SHEET METAL SCREWS.

NO.	DATE	REVISION		BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION				
<b>STRUCTURE      B-69-0054</b>				
DRAWN BY		CTMP	PLANS CK'D	PTB
<b>CROSS SECTION &amp; QUANTITIES</b>			SHEET 2 OF 10	




The diagram illustrates the required backfill structure for a bridge abutment. Key components and labels include:

- BRIDGE SUPERSTRUCTURE**: The top horizontal section of the bridge.
- ROADWAY PAVEMENT**: The surface layer above the subsurface.
- ROADWAY SUBSURFACE**: The layer below the pavement.
- ABUTMENT BACKFACE**: The vertical wall of the abutment.
- PAY LIMITS OF BACKFILL**: Indicated by a dashed line with a slope of 1.0 horizontal to 1.5 vertical.
- BACKFILL STRUCTURE TYPE A**: The specific backfill material and structure required.
- "GEOTEXTILE TYPE DF SCHEDULE A" LIMITS. EXTEND 2'-0" ABOVE BOTTOM OF ABUTMENT FOR THE ENTIRE ABUTMENT BODY LENGTH.**: A note specifying the geotextile requirements.
- 3'-0" REQ'D**: A dimension indicating the required height of the backfill structure.

**PIPE UNDERDRAIN WRAPPED (6-INCH). SLOPE 0.5% MIN. TO SUITABLE DRAINAGE. ATTACH RODENT SHIELD AT ENDS OF PIPE UNDERDRAIN.**



BID ITEM NUMBER	BID ITEMS	UNIT	SUPER	S. ABUT.	N. ABUT.	TOTALS
203.0270	REMOVING STRUCTURE OVER WATERWAY DEBRIS CAPTURE B-69-0202	EACH	---	---	---	1
206.1001	EXCAVATION FOR STRUCTURES BRIDGES B-69-0054	EACH	---	---	---	1
210.1500	BACKFILL STRUCTURE TYPE A	TON	---	165	165	330
502.0100	CONCRETE MASONRY BRIDGES	CY	85	28	28	141
502.3200	PROTECTIVE SURFACE TREATMENT	SY	167	15	15	197
505.0400	BAR STEEL REINFORCEMENT HS STRUCTURES	LB	---	2,330	2,330	4,660
505.0600	BAR STEEL REINFORCEMENT HS COATED STRUCTURES	LB	20,150	1,520	1,520	23,190
513.4061	RAILING TUBULAR TYPE M	LF	90	---	---	90
516.0500	RUBBERIZED MEMBRANE WATERPROOFING	SY	---	6	6	12
550.2104	PILING CIP CONCRETE 10 ¾ X 0.25-INCH	LF	---	700	700	1,400
606.0300	RIPRAP HEAVY	CY	---	55	55	110
612.0406	PIPE UNDERDRAIN WRAPPED 6-INCH	LF	---	75	75	150
645.0111	GEOTEXTILE TYPE DF SCHEDULE A	SY	---	48	48	96
645.0120	GEOTEXTILE TYPE HR	SY	---	95	90	185
SPV.0090.01	FLASHING STAINLESS STEEL	LF	75	---	---	75
SPV.0195.01	SELECT CRUSHED MATERIAL FOR TRAVEL CORRIDOR	TON	---	26	26	52
	NON-BID ITEMS					
	FILLER	SIZE	---	---	---	½", ¾"

THIS SHEET WAS CREATED BY THE WISDOT BUREAU OF STRUCTURES STANDARD BRIDGE DESIGN TOOL VERSION 1.1.0.0



<b>BORING NUMBER</b>	<b>DATE COMPLETED</b>	<b>NORTHING (Y)</b>	<b>EASTING (X)</b>
B-1	09/27/23	157,721.2	439,512.4
B-2	09/27/23	157,768.7	439,492.2


BORINGS & REPORT  
COMPLETED BY: ECS MIDWEST, LLC  
1280 PARKVIEW ROAD  
GREEN BAY, WI 54304



(1) UNCONFINED STRENGTH, AS DETERMINED BY A POCKET PENETROMETER (TSF)

(2) UNLESS OTHERWISE SPECIFIED, THE SPT 'N' VALUE IS BASED ON AASHTO T-206 STANDARD PENETRATION TEST. THE SPT 'N' VALUE PRESENTED HAS NOT BEEN CORRECTED FOR OVERBURDEN PRESSURE OR HAMMER EFFICIENCY.

## GROUND WATER ELEVATIONS




## ABBREVIATIONS

F-FINE    M-MEDIUM    C-COURSE    ST-SHELBY TUBE

## SUBSURFACE EXPLORATION FOR FOUNDATION DESIGN AND BIDDERS INFORMATION

BORINGS WERE COMPLETED AT POINTS APPROXIMATELY AS INDICATED ON THIS DRAWING TO OBTAIN INFORMATION CONCERNING THE CHARACTER OF SUBSURFACE MATERIALS FOUND AT THE SITE. BECAUSE THE INVESTIGATED DEPTHS ARE LIMITED AND THE AREA OF THE BORINGS IS VERY SMALL IN RELATION TO THE ENTIRE SITE, THE WISCONSIN DEPARTMENT OF TRANSPORTATION DOES NOT WARRANT SIMILAR SUBSURFACE CONDITIONS BELOW, BETWEEN, OR BEYOND THESE BORINGS. VARIATIONS IN SOIL CONDITIONS SHOULD BE EXPECTED AND FLUCTUATIONS IN GROUNDWATER LEVELS MAY OCCUR.

NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
<b>STRUCTURE B-69-0054</b>			
		DRAWN BY	PTB
		CTMP	PLANS CK'D.
<b>SUBSURFACE EXPLORATION</b>		SHEET 3 OF 10	



- A01** CONST. JOINT: KEYWAY FORMED BY A BEVELED 2X6.
- A06** SUPPORT ABUTMENT ON CIP 10% X 0.25 PILING, ESTIMATED 100 FT LONG WITH A REQUIRED DRIVING RESISTANCE OF 130 TONS PER PILE.
- A15** PIPE UNDERDRAIN WRAPPED (6-INCH), SLOPE 0.5% MIN. TO SUITABLE DRAINAGE. RODENT SHIELD REQUIRED.
- A17** ½" FILLER: SEAL ALL EXPOSED HORIZ. & VERT. SURFACES OF ½" FILLER WITH NON-STAINING GRAY NON-BITUMINOUS JOINT SEALER. (1" DEEP AND HOLD ½" BELOW SURFACE OF CONCRETE). EXTEND SEALER 3" BELOW GUTTER LINE AT INSIDE FACE.
- A19** 18" RUBBERIZED MEMBRANE WATERPROOFING. SEAL ALL HORIZ. & VERT. JOINTS AT BACKFACE.
- A22** A506 BARS SPACED @ 1'-0" CNTRS. MAY BE PLACED AFTER CONCRETE IS POURED BUT BEFORE INITIAL SET HAS TAKEN PLACE. (EMBED 1'-0" INTO CONC.)
- ALTERNATE THE POSITION OF THE 90° AND 180° HOOKS AT EACH VERTICAL LAYER OF TIES.
- ◇ VOIDS IN THE RIPRAP HEAVY SHALL BE FILLED WITH SELECT CRUSHED MATERIAL. COST OF THE SELECT CRUSHED MATERIAL IS PAID FOR UNDER BID ITEM "SELECT CRUSHED MATERIAL FOR TRAVEL CORRIDOR". ENTIRE SURFACE OF RIPRAP HEAVY TO BE COVERED.




NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
<b>STRUCTURE</b>		<b>B-69-0054</b>	
		DRAWN BY	PLANS CK'D PTE
<b>SOUTH ABUTMENT</b>		SHEET 4 OF 10	



BILL OF BARS


NOTE: THE FIRST OR FIRST TWO DIGITS OF THE BAR MARK SIGNIFIES THE BAR SIZE.

BAR MARK	COAT	NO. REQ'D.	LENGTH	BENT	BAR SERIES	LOCATION
A501		76	6'-0"	X		ABUT BODY STIRRUPS
A502		33	7'-9"	X		ABUT BODY STIRRUPS - TOP U-BAR
A503		9	37'-2"			ABUT BODY HORIZ. - F.F.
A804		18	24'-7"	X		ABUT BODY HORIZ. - B.F.
A405		30	3'-0"	X		ABUT BODY TIE BARS
A506	X	31	2'-0"			ABUT BODY DOWEL BARS
A407	X	56	10'-10"	X		WING STIRRUPS
A508	X	5	11'-7"	X		WING CORNER STIRRUPS
A509	X	18	11'-9"	X		WING LOWER HORIZ. - F.F.
A810	X	18	13'-3"	X		WING LOWER HORIZ. - B.F.
A411	X	4	10'-1"			WING UPPER HORIZ.
A412	X	4	7'-6"			WING UPPER HORIZ.
A413	X	4	5'-0"			WING UPPER HORIZ.
A414	X	4	9'-8"	X		WING TOP HORIZ.
A415	X	4	9'-4"	X		WING 1 UPPER HORIZ. CORNER
A416	X	4	7'-7"	X		WING 2 UPPER HORIZ. CORNER







WING 1 ELEVATION

SHOWING F.F. WING




WING 2 ELEVATION

SHOWING F.F. WING




WING 1 PLAN

SHOWING UPPER WING REINFORCEMENT




WING 2 PLAN

SHOWING UPPER WING REINFORCEMENT




WING 1 PLAN

SHOWING LOWER WING REINFORCEMENT  
WING 2 SIMILAR



CIP PILE DETAILS



SECTION THRU WING 1



TYPICAL BOTH WINGS

SECTION A-A

- A01 OPTIONAL CONST. JOINT: KEYWAY FORMED BY A BEVELED 2X6. PROVIDE 3/4" "V" GROOVE ON F.F. OF WINGWALL IF JOINT IS USED.
- A06 SUPPORT ABUTMENT ON CIP 10% X 0.25 PILING, ESTIMATED 100 FT LONG WITH A REQUIRED DRIVING RESISTANCE OF 130TONS PER PILE.
- A15 PIPE UNDERDRAIN WRAPPED (6-INCH). SLOPE 0.5% MIN. TO SUITABLE DRAINAGE. RODENT SHIELD REQUIRED.
- A19 18" RUBBERIZED MEMBRANE WATERPROOFING, ONLY IF OPTIONAL CONSTRUCTION JOINT IS USED. COST INCIDENTAL TO BID ITEM "CONCRETE MASONRY STRUCTURES".

NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
STRUCTURE B-69-0054			
DRAWN BY		CTMP	PLANS CK'D PTB
SOUTH ABUTMENT DETAILS		SHEET 5 OF 10	




- A01** CONST. JOINT: KEYWAY FORMED BY A BEVELED 2X6.
- A06** SUPPORT ABUTMENT ON CIP 10% X 0.25 PILING, ESTIMATED 100 FT LONG WITH A REQUIRED DRIVING RESISTANCE OF 130 TONS PER PILE.
- A15** PIPE UNDERDRAIN WRAPPED (6-INCH). SLOPE 0.5% MIN. TO SUITABLE DRAINAGE. RODENT SHIELD REQUIRED.
- A17** ½" FILLER: SEAL ALL EXPOSED HORIZ. & VERT. SURFACES OF ½" FILLER WITH NON-STAINING GRAY NON-BITUMINOUS JOINT SEALER. (1" DEEP AND HOLD ½" BELOW SURFACE OF CONCRETE). EXTEND SEALER 3" BELOW GUTTER LINE AT INSIDE FACE.
- A19** 18" RUBBERIZED MEMBRANE WATERPROOFING. SEAL ALL HORIZ. & VERT. JOINTS AT BACKFACE.
- A22** B506 BARS SPACED @ 1'-0" CNTRS. MAY BE PLACED AFTER CONCRETE IS POURED BUT BEFORE INITIAL SET HAS TAKEN PLACE. (EMBED 1'-0" INTO CONC.)
-  ALTERNATE THE POSITION OF THE 90° AND 180° HOOKS AT EACH VERTICAL LAYER OF TIES.
-  VOIDS IN THE RIPRAP HEAVY SHALL BE FILLED WITH SELECT CRUSHED MATERIAL. COST OF THE SELECT CRUSHED MATERIAL IS PAID FOR UNDER BID ITEM "SELECT CRUSHED MATERIAL FOR TRAVEL CORRIDOR". ENTIRE SURFACE OF RIPRAP HEAVY TO BE COVERED.

NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
<b>STRUCTURE</b>		<b>B-69-0054</b>	
		DRAWN BY	PLANS CK'D PTE
<b>NORTH ABUTMENT</b>		SHEET 6 OF 10	

BILL OF BARS


NOTE: THE FIRST OR FIRST TWO DIGITS OF THE BAR MARK SIGNIFIES THE BAR SIZE.

BAR MARK	COAT	NO. REQ'D.	LENGTH	BENT	BAR SERIES	LOCATION
B501		76	6'-0"	X		ABUT BODY STIRRUPS
B502		33	7'-9"	X		ABUT BODY STIRRUPS - TOP U-BAR
B503		9	37'-2"			ABUT BODY HORIZ. - F.F.
B804		18	24'-7"	X		ABUT BODY HORIZ. - B.F.
B405		30	3'-0"	X		ABUT BODY TIE BARS
B506	X	31	2'-0"			ABUT BODY DOWEL BARS
B407	X	56	10'-10"	X		WING STIRRUPS
B508	X	5	11'-7"	X		WING CORNER STIRRUPS
B509	X	18	11'-9"	X		WING LOWER HORIZ. - F.F.
B810	X	18	13'-3"	X		WING LOWER HORIZ. - B.F.
B411	X	4	10'-1"			WING UPPER HORIZ.
B412	X	4	7'-6"			WING UPPER HORIZ.
B413	X	4	5'-0"			WING UPPER HORIZ.
B414	X	4	9'-8"	X		WING TOP HORIZ.
B415	X	4	9'-4"	X		WING 3 UPPER HORIZ. CORNER
B416	X	4	7'-7"	X		WING 4 UPPER HORIZ. CORNER




WING 3 ELEVATION

SHOWING F.F. WING




WING 3 PLAN

SHOWING UPPER WING REINFORCEMENT




WING 3 PLAN

SHOWING LOWER WING REINFORCEMENT  
WING 4 SIMILAR




CIP PILE DETAILS

THIS SHEET WAS CREATED BY THE WISDOT BUREAU OF STRUCTURES STANDARD BRIDGE DESIGN TOOL VERSION 1.1.0.0




WING 4 ELEVATION

SHOWING F.F. WING



WING 4 PLAN

SHOWING UPPER WING REINFORCEMENT




SECTION THRU WING 3

TYPICAL BOTH WINGS

SECTION A-A

- A01 OPTIONAL CONST. JOINT: KEYWAY FORMED BY A BEVELED 2X6. PROVIDE 3/4" "V" GROOVE ON F.F. OF WINGWALL IF JOINT IS USED.
- A06 SUPPORT ABUTMENT ON CIP 10" X 0.25 PILING, ESTIMATED 100 FT LONG WITH A REQUIRED DRIVING RESISTANCE OF 130TONS PER PILE.
- A15 PIPE UNDERDRAIN WRAPPED (6-INCH). SLOPE 0.5% MIN. TO SUITABLE DRAINAGE. RODENT SHIELD REQUIRED.
- A19 18" RUBBERIZED MEMBRANE WATERPROOFING, ONLY IF OPTIONAL CONSTRUCTION JOINT IS USED. COST INCIDENTAL TO BID ITEM "CONCRETE MASONRY STRUCTURES".




NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
STRUCTURE B-69-0054			
DRAWN BY		CTMP	PLANS CK'D PTB
NORTH ABUTMENT DETAILS		SHEET 7 OF 10	

SCALE =



NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
<b>STRUCTURE</b>		<b>B-69-0054</b>	
		DRAWN BY	PLANS CK'D
		CTMP	PTB
<b>SUPERSTRUCTURE</b>		SHEET 8 OF 10	



CAMBER AND SLAB THICKNESS DIAGRAM


CAMBER SHOWN IS BASED ON 3 TIMES DEAD LOAD DEFLECTIONS. CAMBER SPANS AS SHOWN TO PROVIDE FOR DEAD LOAD DEFLECTION AND FUTURE CREEP. CAMBER DOES NOT INCLUDE ALLOWANCE FOR FORM SETTLEMENT. PARAPETS PLACED ON TOP OF THE SLAB SHALL BE POURED AFTER FALSEWORK HAS BEEN RELEASED, EXCEPT FOR STAGED CONSTRUCTION.

TO DETERMINE FALSEWORK ELEVATION AT EDGE OF SLAB, CROWN OR REFERENCE LINE FOLLOW THIS PROCEDURE:

LESS	TOP OF SLAB ELEVATION AT FINAL GRADE
PLUS	SLAB THICKNESS
PLUS	CAMBER
PLUS	FORM SETTLEMENT/DEFLECTION DUE TO PLACEMENT OF SLAB CONCRETE (TO BE COMPUTED BY THE CONTRACTOR)
EQUALS	TOP OF SLAB FALSEWORK ELEVATION

TOP OF SLAB ELEVATIONS

LOCATION	C/L BRG. S. ABUT.	1/10 PT.	2/10 PT.	3/10 PT.	4/10 PT.	5/10 PT.	6/10 PT.	7/10 PT.	8/10 PT.	9/10 PT.	C/L BRG. N. ABUT.
W. EDGE OF DECK	800.38	800.34	800.31	800.29	800.27	800.25	800.24	800.23	800.23	800.24	800.24
CROWN OR R/L	800.74	800.70	800.66	800.63	800.60	800.58	800.56	800.55	800.54	800.54	800.54
E. EDGE OF DECK	800.50	800.45	800.41	800.37	800.33	800.30	800.28	800.26	800.25	800.24	800.23



STAINLESS STEEL FLASHING DETAIL

NOTES:

THE BID ITEM "FLASHING STAINLESS STEEL" SHALL INCLUDE PROVIDING AND INSTALLING THE STAINLESS STEEL FLASHING, SILICONE CAULK, 3/16" CONCRETE SCREWS, AND CLEANING THE EDGE OF DECK PRIOR TO ATTACHMENT OF THE FLASHING.


FLASHING TO BE INSTALLED AFTER APPLICATION OF PROTECTIVE SURFACE TREATMENT.

CONCRETE SCREWS SHALL BE 410 STAINLESS STEEL.


EXTEND FLASHING TO F.F. OF ABUTMENT.

TOP OF FLASHING TO BEGIN APPROXIMATELY 1" BELOW TOP OF SLAB SURFACE.

THE FLASHING IS TO BE A CONSTANT HEIGHT BASED ON THE THINNEST SLAB DEPTH OVER THE BRIDGE LENGTH.



S505



S608

S609

BILL OF BARS

NOTE: THE FIRST OR FIRST TWO DIGITS OF THE BAR MARK SIGNIFIES THE BAR SIZE.

BAR MARK	COAT	NO. REQ'D.	LENGTH	BENT	BAR SERIES	LOCATION
S1001	X	73	42'-3"			SLAB BOTTOM LONGITUDINAL
S702	X	43	32'-1"			SLAB BOTTOM TRANSVERSE
S503	X	43	32'-1"			SLAB TOP TRANSVERSE
S504	X	21	42'-3"			SLAB TOP LONGITUDINAL
S505	X	62	7'-4"	X		ABUTMENT DIAPHRAGM STIRRUPS
S506	X	4	32'-1"			ABUTMENT DIAPHRAGM LONGITUDINAL
S607	X	48	6'-0"			SLAB TOP LONGIT. UNDER RAIL POSTS
S608	X	16	4'-8"	X		SLAB TOP LONGIT. UNDER RAIL END POSTS
S609	X	32	11'-3"	X		SLAB TOP HOOKS UNDER RAIL POSTS

SURVEY TOP OF SLAB ELEVATIONS

LOCATION	ABUTMENT	5/10 PT.	ABUTMENT
W. GUTTER			
CROWN OR R/L			
E. GUTTER			

PRIOR TO RELEASING SLAB FALSEWORK, TAKE TOP OF SLAB ELEVATIONS AT THE C/L OF ABUTMENTS, THE C/L OF PIERS AND AT 5/10 PTS. TO VERIFY CAMBER. TAKE ELEVATIONS ALONG GUTTER LINES AND CROWN OR R/L. RECORD THE ELEVATIONS IN THE ABOVE TABLE FOR THE "AS BUILT" PLANS.

NOTES

FILL IN THE TABLE OF "SURVEY TOP OF SLAB ELEVATIONS" FOR EACH SPAN ON AS BUILT PLANS.

TOP TRANSVERSE BARS IN SLAB SHALL BE SUPPORTED BY INDIVIDUAL BAR CHAIRS AT APPROXIMATELY 3'-0" CENTERS EACH WAY. BOTTOM LONGITUDINAL BARS SHALL BE SUPPORTED BY CONTINUOUS BAR CHAIRS AT APPROXIMATELY 4'-0" CENTERS.

ALL SLAB THICKNESS DIMENSIONS ARE MINIMUM. ANY TOLERANCES NECESSARY TO CORRECT CONSTRUCTION DISCREPANCIES ARE TO BE PLUS (+).


NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
STRUCTURE B-69-0054			
		DRAWN BY	PLANS CK'D PTB
SUPERSTRUCTURE DETAILS		SHEET 9 OF 10	

LEGEND


- 1 W6 x 25 WITH 1 1/2" x 1 1/2" HORIZ. SLOTS ON EACH SIDE OF POST FOR BOLT NO. 6. CUT BOTTOM OF POST TO MATCH CROSS SLOPE OF ROADWAY. PLACE POST VERTICAL. PLACE POSTS NORMAL TO GRADE LINE.
- 2 PLATE 1 3/4" x 11 3/4" x 1'-8" WITH 1 7/16" OVERSIZED HOLES FOR ANCHOR BOLTS NO. 3. WELD TO NO. 1 AS SHOWN.
- 3 ASTM A449 - 1 5/8" DIA. ANCHOR BOLTS WITH NUT AND HARDENED WASHER (ALL GALVANIZED). 5 REQ'D. PER POST. THREAD 3" AND PLACE NORMAL TO PLATE NO. 2. CHAMFER TOP OF BOLTS BEFORE THREADING. USE 1'-9" LONG IN ABUTMENT WINGS. AT POSTS ON CONCRETE SLAB SUPERSTRUCTURES WHERE THE SLAB THICKNESS IS > 16" USE 1'-3" LONG. USE 10 3/4" LONG AT ALL OTHER LOCATIONS. (AN EQUIVALENT THREADED ROD WITH NUTS AND HARDENED WASHERS MAY BE SUBSTITUTED FOR ANCHOR BOLTS IN WINGS IF REQ'D. FOR CONSTRUCTIBILITY.)
- 4 5/8" x 11" x 1'-8" ANCHOR PLATE (GALVANIZED) WITH 1 3/16" DIA. HOLES FOR ANCHOR BOLTS NO. 3.
- 5 TS 5 x 4 x 0.25 STRUCTURAL TUBING. ATTACH TO NO. 1 WITH NO. 6.
- 5A TS 5 x 5 x 0.25 STRUCTURAL TUBING. ATTACH TO NO. 1 WITH NO. 6.
- 6 7/8" DIA. A325 SLOTTED ROUND HEAD BOLT WITH NUT, 3/16" x 1 5/8" x 1 5/8" MIN. WASHER, AND LOCK WASHER (2 REQ'D. AT EACH RAIL TO POST LOCATION).
- 7 SPLICE SLEEVE FABRICATED FROM 1/4" PLATE. PROVIDE "SLIDING FIT".
- 8 3/8" x 3 5/8" x 2'-4" PLATE. 2 PER RAIL. USED IN NO. 5 & 5A.
- 8A 3/8" x 2 5/8" x 2'-4" PLATE USED IN NO. 5, 3/8" x 3 5/8" x 2'-4" PLATE USED IN NO. 5A. 2 PER RAIL.
- 9 7/8" DIA. A325 ROUND HEAD BOLT WITH NUT, WASHER, AND LOCK WASHER. USE 1 5/16" x 1 1/4" LONGIT. SLOTTED HOLES IN PLATE NO. 10A AT FIELD JOINTS AND 1 5/16" x 2 1/4" MIN. LONGIT. SLOTTED HOLES AT EXP. JOINTS IN PLATE NO. 8A. PROVIDE 1 5/16" DIA. ROUND HOLES IN TUBES NO. 5 AND NO. 5A.
- 10 1/2" THK. BACK-UP PLATE WITH 2 - 7/8" x 1 1/2" THREADED SHOP WELDED STUDS (NO. 12). BOLT TO RAIL AS SHOWN IN DETAIL. REQUIRED AT THRIE BEAM GUARD RAIL ATTACHMENTS ONLY. PLACE SYMMETRICALLY ABOUT TUBES NO. 5A.
- 11 1" DIA. HOLES IN PLATE NO. 10 & TUBES NO. 5A FOR 7/8" DIA. A325 BOLTS WITH HEX NUTS AND WASHERS. 6 HOLES IN TUBES AND PLATE NO. 10.
- 12 7/8" DIA. x 1 1/2" LONG THREADED SHOP WELDED STUDS (2 REQ'D).
- 13 3/8" x 8" x 1'-6" PLATE. BOLT TO RAIL AS SHOWN IN DETAIL. REQ'D. AT THRIE BEAM GUARD RAIL ATTACHMENTS ONLY. PLACE SYM. ABOUT TUBES NO. 5A.
- 14 7/8" DIA. x 2" LONG A325 HEX BOLT WITH NUT AND WASHER (5 REQ'D.).
- 15 1" DIA. HOLES IN TUBES NO. 5A FOR 7/8" DIA. A325 ROUND HEAD BOLT WITH NUT, WASHER AND LOCK WASHER (4 REQ'D.). 4 HOLES IN TUBES.

GENERAL NOTES


1. BID ITEM SHALL BE "RAILING TUBULAR TYPE M" WHICH INCLUDES ALL ITEMS SHOWN.
2. RAIL POST AND BASE PLATES SHALL CONFORM TO THE REQUIREMENTS OF ASTM A709 GRADE 50. HOLLOW RAILING STRUCTURAL TUBING SHALL CONFORM TO THE REQUIREMENTS OF ASTM A500 GRADE B OR C WITH A CERTIFIED FY = 50 KSI. ANCHOR PLATES, AND SPLICE TUBE PLATES SHALL CONFORM TO THE REQUIREMENTS OF ASTM A709 GRADE 36.
3. THE NUT SECURING THE POST BASE PLATE TO THE CONCRETE SHALL BE TIGHTENED TO A SNUG FIT AND GIVEN AN ADDITIONAL 1/2 TURN.
4. RAILS SHALL BE CONTINUOUS OVER A MINIMUM OF THREE (3) POSTS WITHOUT SPLICES WHERE POSSIBLE.
5. ENDS OF TUBE SECTIONS SHALL BE SAWED. GRIND SMOOTH EXPOSED EDGES. ALL CUT ENDS SHALL BE TRUE AND SMOOTH.
6. WELD IS THE SAME ON BOTH FLANGES. FLANGE WELD DOES NOT REQUIRE MAGNETIC PARTICLE TESTING.
7. FILL BOLT SLOT OPENINGS IN POST SHIMS AND PLATE NO. 2 AND CAULK AROUND PERIMETER OF PLATE NO. 2 WITH NON-STAINING GRAY NON-BITUMINOUS JOINT SEALER. STEEL POST SHIMS MAY BE USED UNDER POSTS WHERE REQ'D. FOR ALIGNMENT.
8. POST BASE PLATES SHALL BE FLAT WITH ALL SURFACES SMOOTH AND FREE FROM WARP AND ALL EDGES SMOOTH, STRAIGHT AND VERTICAL. ALL PLATE CUTS SHALL BE MACHINE OR MACHINE FLAME CUT.
9. ALL MATERIAL SHALL BE GALVANIZED AFTER FABRICATION. PRIOR TO GALVANIZING, ALL STEEL RAILING POSTS & STEEL TUBING SHALL BE GIVEN A NO. 6 BLAST CLEANING BY SSPC SPECIFICATIONS.




SECTION THRU RAILING ON DECK




FIELD ERECTION JOINT DETAIL




SHOP RAIL SPLICE DETAIL  
LOCATION MUST BE SHOWN ON SHOP DRAWINGS




SECTION B-B



ANCHOR BOLTS




SECTION THRU POST WEB




SECTION THRU RAIL  
NOTE: CONNECTIONS AT LOWER RAILS SHOWN. CONNECTIONS AT TOP RAIL SIMILAR.


TYPICAL RAIL TO POST CONNECTIONS



TOP VIEW AT END POST  
THRIE BEAM RAIL ATTACHMENT




SECTION C-C




SECTION D-D


DETAIL AT END POST  
THRIE BEAM RAIL ATTACHMENT




PART ELEVATION OF RAILING




SECTION A-A



ANCHOR PLATE  
AT BEAM GUARD ATTACHMENT



BACK-UP PLATE DETAIL  
AT BEAM GUARD ATTACHMENT



ANCHOR PLATE  
AT RAIL TO DECK CONNECTION


POST SHIM  
DETAIL

NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
STRUCTURE B-69-0054			
DRAWN BY		CTMP	PLANS CK'D PTB
TUBULAR STEEL RAILING TYPE 'M'		SHEET 10 OF 10	


EARTHWORK-CTH E

STATION	AREA (SF)		INCREMENTAL VOL (CY)			CUMMULATIVE VOLUME (CY)			
	CUT	FILL	CUT NOTE 1	FILL	FILL (25%) NOTE 2	CUT 1.00 NOTE 1	FILL	FILL (25%) NOTE 2	MASS ORDINATE NOTE 3
8+80	62	0	0	0	0	0	0	0	0
9+00	102	0	50	0	0	50	0	0	50
9+50	56	41	60	0	0	111	0	0	111
10+00	47	41	146	39	49	256	39	49	208
10+50	47	41	96	76	95	352	115	144	208
10+51	47	41	90	79	99	442	194	243	199
10+93	49	9	13	3	4	454	197	246	208
11+00	49	9	74	21	27	528	218	273	255
11+50	29	14	55	23	28	583	241	301	282
12+00	31	11	27	7	9	610	248	310	300
12+30	13	1	0	0	0	610	248	310	300
COLUMN TOTALS =			610	248	310				300

NOTES:	
1 - CUT	CUT INCLUDES SALVAGED/UNUSABLE PAVEMENT MATERIAL
2 - FILL 25%	(UNEXPANDED FILL)*1.25
3 - MASS ORDINATE	CUT + ROCK (10%) +REDUCED MARSH (60%) - FILL (25%)







PROJECT NO: 6987-02-70


HWY: CTH E


COUNTY: WAUSHARA


CROSS SECTIONS: MAINLINE


SHEET

E










9

9



## Notes



## ***Wisconsin Department of Transportation***

Dedicated people creating transportation solutions  
through innovation and exceptional service.

<http://www.dot.wisconsin.gov>