

FEBRUARY 2026
ORDER OF SHEETS

Section No. 1 Title
 Section No. 2 Typical Sections and Details
 Section No. 3 Estimate of Quantities
 Section No. 4 Right of Way Plat
 Section No. 5 Plan and Profile
 Section No. 6 Standard Detail Drawings
 Section No. 7 Sign Plates
 Section No. 8 Structure Plans
 Section No. 9 Computer Earthwork Data
 Section No. 9 Cross Sections

TOTAL SHEETS = 56



DESIGN DESIGNATION 9826-00-00

A.A.D.T. (2026) = <100
 A.A.D.T. (2046) = <100
 D.H.V. = 10
 D.D. = 50/50
 T. = 5%
 DESIGN SPEED = 15 MPH
 ESALS = 36,500

CONVENTIONAL SYMBOLS

PLAN	PROFILE
CORPORATE LIMITS	GRADE LINE
PROPERTY LINE	ORIGINAL GROUND
LOT LINE	MARSH OR ROCK PROFILE (To be noted as such)
LIMITED HIGHWAY EASEMENT	SPECIAL DITCH
EXISTING RIGHT OF WAY	GRADE ELEVATION
PROPOSED OR NEW R/W LINE	CULVERT (Profile View)
SLOPE INTERCEPT	UTILITIES
REFERENCE LINE	ELECTRIC
EXISTING CULVERT	FIBER OPTIC
PROPOSED CULVERT (Box or Pipe)	GAS
COMBUSTIBLE FLUIDS	SANITARY SEWER
MARSH AREA	STORM SEWER
WOODED OR SHRUB AREA	TELEPHONE
	WATER
	UTILITY PEDESTAL
	POWER POLE
	TELEPHONE POLE

STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION


PLAN OF PROPOSED IMPROVEMENT

T KIMBALL, TOWN PARK DRIVE

W BR MONTREAL RIVER BRIDGE B-26-0047

LOC STR
IRON COUNTYSTATE PROJECT NUMBER
9826-00-70

R-1-E → R-2-E

STRUCTURE B-26-0047
STA 9+96.00END PROJECT
STA 11+21.25
Y = 383908.72
X = 723052.73

SCALE 0 1 MI

TOTAL NET LENGTH OF CENTERLINE = 0.047 MI

HORIZONTAL POSITIONS SHOWN ON THIS PLAN ARE WISCONSIN COORDINATE REFERENCE SYSTEM (WISCRS), IRON COUNTY, NAD83 (2011), IN U.S. SURVEY FEET. POSITIONS SHOWN ARE GRID COORDINATES, GRID BEARINGS, AND GRID DISTANCES. GRID DISTANCES ARE THE SAME AS GROUND DISTANCES.

ELEVATIONS ARE REFERENCED TO NAVD 88 (2012). GPS DERIVED ELEVATIONS ARE BASED ON GEODID 18.

STATE PROJECT	FEDERAL PROJECT	
	PROJECT	CONTRACT
9826-00-70	_____	_____

ACCEPTED FOR

Town of Kimball
 10/20/2025 *R. E. L.*
 (Date) (Signature)
 Howy Chairman

ORIGINAL PLANS PREPARED BY
AYRES



STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION

PREPARED BY
 Surveyor: AYRES ASSOCIATES INC
 Designer: AYRES ASSOCIATES INC
 Project Manager: MICHAEL GRAJE, PE
 Regional Examiner: NC REGION
 Regional Supervisor: DANIEL ERVA, PE

APPROVED FOR THE DEPARTMENT
 DATE: 10/28/2025 *M. D. P.*
 (Signature)

UTILITIES CONTACTS

XCEL ENERGY
MITCHELL ANDERSON
1751 LIBERTY ST
IRONWOOD, MI 49938
PHONE: 906-767-5127
CELL: 906-364-9448
EMAIL: mitch.d.anderson@xcelenergy.com

WISCONSIN DNR LIAISON

JON SIMONSEN
WDNR
107 SUTLIFF AVENUE
RHINELANDER, WI 54501
PHONE: 715-367-1936
EMAIL: jonathan.simonson@wisconsin.gov

DESIGN PROJECT MANAGER

MIKE GRAGE, PE
WISDOT NC REGION
510 N. HANSON LAKE ROAD
RHINELANDER, WI 54501
PHONE: 715-365-5705
EMAIL: michael.grage@dot.wi.gov

GENERAL NOTES

THE LOCATIONS OF EXISTING UTILITY INSTALLATIONS AS SHOWN ON THE PLANS ARE APPROXIMATE.
THERE MAY BE OTHER UTILITY INSTALLATIONS WITHIN THE PROJECT AREA THAT ARE NOT SHOWN.

FILL EXPANSION FACTOR IS 30%

NO TREES OR SHRUBS ARE TO BE REMOVED WITHOUT THE APPROVAL OF THE ENGINEER.

RIGHT OF WAY INFORMATION SHOWN ON THE PLANS IS APPROXIMATE.

EROSION CONTROL FEATURES AS SHOWN IN THE PLANS ARE AT APPROXIMATE LOCATIONS. EXACT LOCATIONS
WILL BE DETERMINED BY THE CONTRACTOR'S EROSION CONTROL IMPLEMENTATION PLAN (ECIP) AND
APPROVED BY THE ENGINEER. MAINTAIN EROSION CONTROL MEASURES UNTIL SUCH A TIME AS THE ENGINEER
DETERMINES THE MEASURE IS NO LONGER NECESSARY.

SEED MIXTURE NO. 20 AND SEEDING TEMPORARY SHALL BE USED IN THE PROJECT AND SHALL BE PLACED
AS SHOWN IN THE PLANS AND/OR DIRECTED BY THE ENGINEER.

ASPHALTIC SURFACE SHALL BE CONSTRUCTED WITH A 2" UPPER LAYER AND A 2" LOWER LAYER.
ASPHALTIC SURFACE SHALL USE 12.5 mm NOMINAL AGGREGATE SIZE.

THE PROPOSED SHOULDER WIDTH SHOWN IN THE TYPICAL SECTIONS ARE MINIMUM WIDTH. PERPETUATE
EXISTING SHOULDERS THAT ARE WIDER THAN WHAT IS SHOWN IN THE TYPICAL SECTIONS.

SAWCUTS, AS SHOWN ON THE PLANS, ARE SUGGESTED LOCATIONS AND MAY BE ADJUSTED AT THE DISCRETION
OF THE ENGINEER TO BETTER SUIT FIELD CONDITIONS.

TRAFFIC CONTROL DEVICES SHALL BE ADJUSTED TO FIT FIELD CONDITIONS AS DIRECTED BY THE ENGINEER.

DO NOT DRIVE OR STORE EQUIPMENT, OR STORE CONSTRUCTION MATERIALS IN ENVIRONMENTALLY SENSITIVE
AREAS, WETLANDS OR WATERWAYS.

DISTURBED AREAS WITHIN THE RIGHT OF WAY, EXCEPT THE AREAS WITHIN THE FINISHED SUBGRADE
SHOULDER POINTS ARE TO BE SEADED AND EITHER MULCHED OR EROSION MATTED AS DIRECTED BY
THE ENGINEER.

ELEVATIONS SHOWN ON THIS PLAN ARE REFERENCED TO THE NORTH AMERICAN VERTICAL DATUM
(NAVD) 1988.

THE DEPARTMENT OF TRANSPORTATION WILL FURNISH THE CONTRACTOR WITH A MONUMENT TO BE
INSTALLED BY THE CONTRACTOR AS DIRECTED BY THE ENGINEER.

RUNOFF COEFFICIENT TABLE

LAND USE:	HYDROLOGIC SOIL GROUP											
	A			B			C			D		
	SLOPE RANGE (PERCENT)		SLOPE RANGE (PERCENT)		SLOPE RANGE (PERCENT)		SLOPE RANGE (PERCENT)		SLOPE RANGE (PERCENT)		SLOPE RANGE (PERCENT)	
0-2	2-6	6 & OVER	0-2	2-6	6 & OVER	0-2	2-6	6 & OVER	0-2	2-6	6 & OVER	0-2
ROW CROPS:	.08	.16	.22	.12	.20	.27	.15	.24	.33	.19	.28	.38
	.22	.30	.38	.26	.34	.44	.30	.37	.50	.34	.41	.56
MEDIAN STRIPTURF:	.19	.20	.24	.19	.22	.26	.20	.23	.30	.20	.25	.30
	.24	.26	.30	.25	.28	.33	.26	.30	.37	.27	.32	.40
SIDE SLOPETURF:			.25			.27			.28			.30
			.32			.34			.36			.38
PAVEMENT:												
ASPHALT:												.70 - .95
CONCRETE:												.80 - .95
BRICK:												.70 - .80
DRIVES, WALKS:												.75 - .85
ROOFS:												.75 - .95
GRAVEL ROADS, SHOULDERS:												.40 - .60

TOTAL PROJECT AREA = 0.397 ACRES

TOTAL AREA EXPECTED TO BE DISTURBED BY CONSTRUCTION ACTIVITIES = 0.290 ACRES

PROJECT NO: 9826-00-70

HWY: TOWN PARK DRIVE

COUNTY: IRON



GENERAL NOTES

SHEET



E

2

2




*THE ASPHALT SURFACE LANE SHALL TAPER FROM 13.25' WIDE AT THE ENDS OF THE WINGS TO 10' WIDE AT 50' FROM THE END OF THE BRIDGE AND MATCH EXISTING AT THE ENDS OF THE PROJECT.



2

2



PROJECT NO: 9826-00-70

HWY: TOWN PARK DRIVE

COUNTY: IRO

ALIGNMENT CONTROLS

SHEET

FILE NAME : I:\42\42-1435.00 - IRON CO, TN KIMBALL, TOWN PARK DRIVE\C3D\Sheets\020401-AC.DWG
LAYOUT NAME - AlignTies

PILOT DATE : 10/8/2025 3:06 P

PILOT BY: PEDERSON, CARM


PLOT SCALE : 1 IN:50 FT

1

1

2

2



NOTES:
FOR DRIVEWAY DETAILS
FOR NW QUADRANT, SEE
"INTERSECTION DETAIL" SHEET

FOR PIPE INFORMATION, SEE
PLAN AND PROFILE SHEET

PLAN

STRUCTURE B-26-0047

PE (NW)

C/L OF DRIVEWAY

EXISTING C/L OF TOWN PARK DRIVE (WEST BOUND LANE)

EXISTING R/W

STA 10+73.34, 12' RT

STA 10+21.25, 15.25' RT

STA 10+62.49, 20' RT

STA 10+93, RT CONSTRUCT PE

STA 11+21.25, 12' RT

STA 11+21.25, 20' RT

DITCH FLOW LINE

SLOPE INTERCEPT - TYP

BASE AGGREGATE SHOULDER - TYP

PROPOSED C/L OF TOWN PARK DRIVE

PE (NE)

13.25'

10+00

12'

20+00

11+00

52'

12'


12'

DETAILS
PLAN, SEE
DETAIL SHEET.


INFORMATION, SEE
SHEET.

EXISTING C/L OF
TOWN PARK DRIVE
(EAST BOUND LANE)

PLAN




TYPICAL CROSS SECTION



TYPICAL CROSS SECTION

PRIVATE ENTRANCE DETAILS


PROJECT NO: 9826-00-70	HWY: TOWN PARK DRIVE	COUNTY: IRON	CONSTRUCTION DETAILS	SHEET 5 E
FILE NAME : I:\42\42-1435.00 - IRON CO, TN KIMBALL, TOWN PARK DRIVE\C3D\Sheets\021001-CD.DWG	PLOT DATE : 10/9/2025 6:55 AM	PLOT BY : PEPIN, STEFFANIE	PLOT NAME :	PLOT SCALE : 1 IN:20 FT



SUPERELEVATION DIAGRAM

2

2



PROJECT NO: 9826-00-70

HWY: TOWN PARK DRIV

COUNTY: IR

INTERSECTION DET

SHEET

E

FILE NAME : I:\42\42-1435.00 - IRON CO, TN KIMBALL, TOWN PARK DRIVE\C3D\SHEETS\021101-ID.DWG
LAYOUT NAME - INTERSECTION


PLOT DATE : 7/23/2025 9:05

PLOT BY : PEDERSON, CAR

PLOT NA

PLOT SCALE : 1 IN:20 FT


WISDOT/CADD SHEET 42



NOTE:
FOR PIPE INFORMATION, SEE
PLAN AND PROFILE SHEET.

LEGEND

- EROSION MAT CLASS II (TYPE C)
- SILT FENCE
- RIP RAP
- SLOPE INTERCEPT
- COFFERDAM (SEE STRUCTURE PLAN)
- ▲ TEMPORARY DITCH CHECK



Estimate Of Quantities

9826-00-70

Line	Item	Item Description	Unit	Total	Qty
0002	201.0205	Grubbing	STA	1.000	1.000
0004	203.0100	Removing Small Pipe Culverts	EACH	1.000	1.000
0006	203.0270	Removing Structure Over Waterway Debris Capture (structure) 01. P-26-0903	EACH	1.000	1.000
0008	205.0100	Excavation Common	CY	199.000	199.000
0010	205.0200	Excavation Rock	CY	5.000	5.000
0012	206.1001	Excavation for Structures Bridges (structure) 01. B-26-0047	EACH	1.000	1.000
0014	206.5001	Cofferdams (structure) 01. B-26-0047	EACH	1.000	1.000
0016	210.1500	Backfill Structure Type A	TON	230.000	230.000
0018	213.0100	Finishing Roadway (project) 01. 9826-00-70	EACH	1.000	1.000
0020	305.0110	Base Aggregate Dense 3/4-Inch	TON	115.000	115.000
0022	305.0120	Base Aggregate Dense 1 1/4-Inch	TON	345.000	345.000
0024	455.0605	Tack Coat	GAL	43.000	43.000
0026	465.0105	Asphaltic Surface	TON	140.000	140.000
0028	502.0100	Concrete Masonry Bridges	CY	153.000	153.000
0030	502.3200	Protective Surface Treatment	SY	195.000	195.000
0032	505.0400	Bar Steel Reinforcement HS Structures	LB	2,580.000	2,580.000
0034	505.0600	Bar Steel Reinforcement HS Coated Structures	LB	23,470.000	23,470.000
0036	513.4061	Railing Tubular Type M	LF	106.000	106.000
0038	516.0500	Rubberized Membrane Waterproofing	SY	12.000	12.000
0040	517.1015.S	Concrete Staining Multi-Color (structure) 01. B-26-0047	SF	345.000	345.000
0042	517.1050.S	Architectural Surface Treatment (structure) 01. B-26-0047	SF	345.000	345.000
0044	520.3312	Culvert Pipe Class III-A 12-Inch	LF	36.000	36.000
0046	606.0400	Riprap Extra-Heavy	CY	40.000	40.000
0048	612.0406	Pipe Underdrain Wrapped 6-Inch	LF	110.000	110.000
0050	614.0920	Salvaged Rail	LF	56.000	56.000
0052	618.0100	Maintenance and Repair of Haul Roads (project) 01. 9826-00-70	EACH	1.000	1.000
0054	619.1000	Mobilization	EACH	1.000	1.000
0056	624.0100	Water	MGAL	13.000	13.000
0058	625.0100	Topsoil	SY	160.000	160.000
0060	627.0200	Mulching	SY	200.000	200.000
0062	628.1504	Silt Fence	LF	525.000	525.000
0064	628.1520	Silt Fence Maintenance	LF	1,050.000	1,050.000
0066	628.1905	Mobilizations Erosion Control	EACH	4.000	4.000
0068	628.1910	Mobilizations Emergency Erosion Control	EACH	4.000	4.000
0070	628.2027	Erosion Mat Class II Type C	SY	40.000	40.000
0072	628.7504	Temporary Ditch Checks	LF	50.000	50.000
0074	629.0210	Fertilizer Type B	CWT	0.300	0.300
0076	630.0120	Seeding Mixture No. 20	LB	11.000	11.000
0078	630.0200	Seeding Temporary	LB	6.000	6.000
0080	630.0500	Seed Water	MGAL	6.000	6.000
0082	634.0614	Posts Wood 4x6-Inch X 14-FT	EACH	4.000	4.000
0084	637.2230	Signs Type II Reflective F	SF	12.000	12.000
0086	638.2102	Moving Signs Type II	EACH	1.000	1.000
0088	638.2602	Removing Signs Type II	EACH	4.000	4.000
0090	638.3000	Removing Small Sign Supports	EACH	4.000	4.000
0092	638.4000	Moving Small Sign Supports	EACH	1.000	1.000
0094	642.5001	Field Office Type B	EACH	1.000	1.000
0096	643.0420	Traffic Control Barricades Type III	DAY	725.000	725.000
0098	643.0705	Traffic Control Warning Lights Type A	DAY	1,125.000	1,125.000

Estimate Of Quantities

9826-00-70

Line	Item	Item Description	Unit	Total	Qty
0100	643.0900	Traffic Control Signs	DAY	485.000	485.000
0102	643.5000	Traffic Control	EACH	1.000	1.000
0104	645.0111	Geotextile Type DF Schedule A	SY	60.000	60.000
0106	645.0120	Geotextile Type HR	SY	80.000	80.000
0108	650.4500	Construction Staking Subgrade	LF	200.000	200.000
0110	650.5000	Construction Staking Base	LF	200.000	200.000
0112	650.6501	Construction Staking Structure Layout (structure) 01. B-26-0047	EACH	1.000	1.000
0114	650.9911	Construction Staking Supplemental Control (project) 01. 9826-00-70	EACH	1.000	1.000
0116	650.9920	Construction Staking Slope Stakes	LF	200.000	200.000
0118	690.0150	Sawing Asphalt	LF	14.000	14.000
0120	715.0502	Incentive Strength Concrete Structures	DOL	918.000	918.000
0122	999.2005.S	Maintaining Bird Deterrent System (station) 01. 10+00	EACH	1.000	1.000
0124	SPV.0060	Special 01. Moving Boulders	EACH	2.000	2.000
0126	SPV.0060	Special 02. Temporary Construction Access B-26-0047	EACH	1.000	1.000
0128	SPV.0180	Special 01. Infill Riprap - B-26-0047	SY	50.000	50.000

3

3

CLEARING & GRUBBING

STATION	TO	STATION	LOCATION	STA
9+33	-	10+40	MAINLINE	1
		TOTAL 0010		1

201.0205
GRUBBINGTOWN PARK DRIVE EARTHWORK SUMMARY

From/To Station	Location	Excavation	Excavation	Salvaged /	Unexpanded	Expanded Fill	Mass	Ordinate +/-
		Common (1)	Rock 205.0200	Unuseable Pavement Material (5)				
		Cut	Cut			Factor 1.30		
8+70.75 - 9+70.75	TOWN PARK DRIVE	50	2	0	20	25	24	24
10+21.25 - 11+21.25	TOWN PARK DRIVE	149	3	11	12	16	123	123
		TOTAL	199	5	11	41	147	147

FINISHING ROADWAY

LOCATION	213.0100.01 FINISHING ROADWAY (PROJECT) (01. 9826-00-70)
9826-00-70	1
TOTAL 0010	1

213.0100.01
FINISHING ROADWAY(PROJECT) (01. 9826-00-70)
EACH

1) Excavation Common is the Cut. Item number 205.0100.

2) Expanded Fill. Factor = 1.30; Expanded Fill = Unexpanded Fill * Fill Factor

3) The Mass Ordinate + or - Qty calculated for the Division. Plus quantity indicates an excess of material on the project.

4) All quantities shown in CY.

5) Salvaged/unuseable pavement material

BASE AGGREGATE DENSE

STATION	TO	STATION	LOCATION	TON	TON
				305.0110 BASE AGGREGATE DENSE 3/4-INCH	305.0120 BASE AGGREGATE DENSE 1 1/4-INCH
8+70.75	-	9+70.75	TOWN PARK DRIVE	85	140
10+21.25	-	11+21.25	TOWN PARK DRIVE	30	205

ASPHALTIC SURFACE

STATION	TO	STATION	LOCATION	GAL	TON
				455.0605 TACK COAT	465.0105 ASPHALTIC SURFACE
8+70.75	-	9+70.75	TOWN PARK DRIVE	17	55
10+21.25	-	11+21.25	TOWN PARK DRIVE	26	85

TOTAL 0010 43 140

CULVERT PIPE

STATION	LOCATION	CULVERTS	INCH
200+72.33	DRIVEWAY	1	36
TOTAL 0010		1	36

ALL ITEMS ON THIS SHEET
ARE CATEGORY 0010
UNLESS OTHERWISE NOTED

MAINTENANCE AND REPAIR OF HAUL ROAD

SALVAGED RAIL

614.0920
SALVAGED RA

STATION	TO	STATION	LOCATION	LF
8+70.75	-	9+70.75	MAINLINE	28
10+21.25	-	11+21.25	MAINLINE	28
			TOTAL 0010	56

618.0100.01
MAINTENANCE AND REPAIR C
HAUL ROADS (PROJECT) (011
9826-00-70)

MOBILIZATION

619.1000
MOBILIZATION

CATEGORY	LOCATION	EACH	LOCATION	EACH
0030	PROJECT LIMITS	1	PROJECT LIMITS	1
TOTAL 0030		1	TOTAL 0010	1

WATER

624.0100
WATER

LOCATION	MGAL
COMPACTION	7
DUST CONTROL	6
TOTAL 0010	13

EROSION CONTROL ITEM

628.1504	628.1520	628.2027	628.7504
SILT FENCE	SILT FENCE	EROSION MAT	TEMPORARY
SILT FENCE	MAINTENANCE	CLASS II TYPE C	DITCH CHECKS
15	15	15	15

STATION	TO	STATION	LOCATION	SET FENCE	MAINTENANCE	CLASS TYPE	DITCH CHECKS
				LF	LF	SY	LF
8+70.75	-	9+70.75	TOWN PARK DRIVE	205	410	30	--
10+21.25	-	11+21.25	TOWN PARK DRIVE	215	430	--	30
			UNDISTRIBUTED	105	210	10	20
TOTAL 0010				525	1,050	40	50

MOBILIZATIONS EROSION CONTROL

628.1905 628.1910

LOCATION	MOBILIZATIONS		MOBILIZATIONS	
	EROSION CONTROL	EACH	EMERGENCY EROSION CONTROL	EACH
PROJECT LIMITS		4		4
TOTAL 0010				4

RESTORATION ITEM

625.0100 627.0200 629.0210 630.0120 630.0200 630.0500
SEEDING MIXTURE SEEDING

STATION	TO	STATION	LOCATION	TOPSOIL SY	MULCHING SY	FERTILIZER TYPE B CWT	NO. 20 LB	TEMPORARY LB	SEED WATER MGAL
8+70.75	-	9+70.75	TOWN PARK DRIVE	55	60	0.1	4	2	2
10+21.25	-	11+21.25	TOWN PARK DRIVE	90	125	0.1	6	3	3
			UNDISTRIBUTED	15	15	0.1	1	1	1
				TOTAL 0010	160	200	0.3	11	6

ALL ITEMS ON THIS SHEET
ARE CATEGORY 0010
UNLESS OTHERWISE NOTED

SIGNS TYPE II

STATION	LOCATION	SIGN CODE	SIGN SIZE (INCHES)	634.0614	637.2230	638.2102	638.2602	638.3000	638.4000	FIELD OFFICE TYPE B	
				POSTS WOOD 4X6- INCH X 14-FT	SIGNS TYPE II REFLECTIVE F SF	MOVING SIGNS TYPE II EACH	MOVING SIGNS TYPE II EACH	MOVING SMALL SIGN SUPPORTS EACH	MOVING SMALL SIGN SUPPORTS EACH	642.5001	FIELD OFFICE TYPE B EACH
9+45	LT	KIMBALL TOWN PARK SIGN		--	--	1	--	--	1	PROJECT LIMITS	1
9+70	LT	W5-52L	12x36	1	3	--	--	--	--		
9+70	RT	W5-52R	12x36	1	3	--	--	--	--	TOTAL 0010	1
9+86	LT	W5-52L	12x36	--	--	--	1	1	--		
9+86	RT	W5-52R	12x36	--	--	--	1	1	--		
10+14	LT	W5-52L	12x36	--	--	--	1	1	--		
10+14	RT	W5-52R	12x36	--	--	--	1	1	--		
10+22	LT	W5-52L	12x36	1	3	--	--	--	--		
10+22	RT	W5-52R	12x36	1	3	--	--	--	--		
TOTAL 0010				4	12	1	4	4	1		

TRAFFIC CONTROL

LOCATION	DURATION	643.0420	643.0705	643.0900	643.5000
		TRAFFIC CONTROL BARRICADES	TRAFFIC CONTROL WARNING LIGHTS TYPE A	TRAFFIC CONTROL SIGNS	TRAFFIC CONTROL
PER SDD 15C02	70	9	630	14	980
UNDISTRIBUTED	--	95	--	145	--
				65	420
					1
TOTAL 0010		725	1,125	485	1

ALL ITEMS ON THIS SHEET
ARE CATEGORY 0010
UNLESS OTHERWISE NOTED

3

3

CONSTRUCTION STAKING

				650.4500 CONSTRUCTION STAKING SUBGRADE	650.5000 CONSTRUCTION STAKING BASE	650.9920 CONSTRUCTION STAKING SLOPE STAKES
STATION	TO	STATION	LOCATION	LF	LF	LF
8+70.75	-	9+70.75	MAINLINE	100	100	100
10+21.25	-	11+21.25	MAINLINE	100	100	100
TOTAL 0010				200	200	200

CONSTRUCTION STAKING STRUCTURE LAYOUT

650.6501.01 CONSTRUCTION STAKING STRUCTURE LAYOUT (STRUCTURE) (01. B-26-0047)	CATEGORY	STATION	LOCATION	EACH
	0020	9+96	MAINLINE	1
	TOTAL 0020			1

CONSTRUCTION STAKING SUPPLEMENTAL CONTROL

650.9911.01 CONSTRUCTION STAKING SUPPLEMENTAL CONTROL (PROJECT) (01. 9826-00-70)	
PROJECT	EACH
9826-00-70	1
TOTAL 0010	1

SAWING ASPHALT

690.0150 SAWING ASPHALT	STATION	LOCATION	LF
	200+50	DRIVEWAY	14
TOTAL 0010			14

MAINTAINING BIRD DETERRENT SYSTEM

999.2005.S.01 MAINTAINING BIRD DETERRENT SYSTEM (STATION) (01. 10+00)	LOCATION	EACH
	P-26-0903	1
TOTAL 0010		1


MOVING BOULDERS


SPV.0060.01 SPECIAL (01. MOVING BOULDERS)				
STATION	TO	STATION	LOCATION	EACH
10+34	-	10+38	MAINLINE	2
TOTAL 0010				2

TEMPORARY CONSTRUCTION ACCESS B-26-0047

SPV.0060.02 SPECIAL (02. TEMPORARY CONSTRUCTION ACCESS B-26-0047)	LOCATION	EACH
	PROJECT LIMITS	1
TOTAL 0010		1


ALL ITEMS ON THIS SHEET
ARE CATEGORY 0010
UNLESS OTHERWISE NOTED





5

5



PROJECT NO: 9826-00-70

HWY: TOWN PARK DRIVE

COUNTY: IRON


PLAN AND PROFILE:

SHEET

16

Standard Detail Drawing List


08D21-01	DRIVEWAYS WITHOUT CURB & GUTTER
08E08-03	TYPICAL INSTALLATIONS OF EROSION BALES / TEMPORARY DITCH CHECKS
08E09-06	SILT FENCE
12A03-10	NAME PLATE (STRUCTURES)
13C19-03	HMA LONGITUDINAL JOINTS
15C02-09A	BARRICADES AND SIGNS FOR MAINLINE CLOSURES
15C02-09B	BARRICADES AND SIGNS FOR VARIOUS CLOSURES
15C06-12	SIGNING & MARKING FOR TWO LANE BRIDGES
15C11-10B	CHANNELIZING DEVICES DRUMS, CONES, BARRICADES AND VERTICAL PANELS



PLAN VIEW
(UNPAVED SHOULDER ON HIGHWAY)

PLAN VIEW
(PAVED SHOULDER ON HIGHWAY)

RURAL DRIVEWAY INTERSECTION DETAIL
(NO CURB AND GUTTER OR SIDEWALK)




IN CUT

IN FILL

TYPICAL CROSS SECTION FOR
PRIVATE DRIVE OR FIELD ENTRANCE
AGGREGATE SURFACE

** SLOPE CAN VARY WITH
SPEED. SEE 11-45-30.6.2


POSTED SPEED MPH	MAX. SLOPE
<35	4:1
≥ 35 TO < 60	6:1
≥ 60	10:1




IN CUT

IN FILL


TYPICAL CROSS SECTION FOR
PRIVATE DRIVE OR FIELD ENTRANCE
ASPHALTIC SURFACE




TYPICAL DRIVEWAY PROFILES



SECTION A-A



PLAN VIEW




FRONT ELEVATION

TEMPORARY DITCH CHECK USING EROSION BALES ①

GENERAL NOTES


DETAILS OF CONSTRUCTION, MATERIALS AND WORKMANSHIP NOT SHOWN ON THIS DRAWING SHALL CONFORM TO THE PERTINENT REQUIREMENTS OF THE STANDARD SPECIFICATIONS AND THE APPLICABLE SPECIAL PROVISIONS.

① TEMPORARY DITCH CHECKS EITHER EROSION BALES OR MANUFACTURED SHALL BE PAID FOR UNDER THE BID ITEM OF TEMPORARY DITCH CHECK. THE DEPARTMENT WILL NOT PAY FOR TEMPORARY DITCH CHECKS CONSTRUCTED OF A SINGLE ROW OF EROSION BALES.




PLAN VIEW

WHEN ALTERING THE DIRECTION OF FLOW



PLAN VIEW



FRONT ELEVATION


WHEN EXISTING GROUND SLOPES AWAY FROM FILL SLOPE

EROSION BALES FOR SHEET FLOW


TYPICAL INSTALLATIONS OF EROSION BALES / TEMPORARY DITCH CHECKS

STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION


APPROVED
6/04/02 /S/ Beth Cann
DATE CHIEF ROADWAY DEVELOP 19
FHWA




PLAN VIEW
TYPICAL APPLICATION OF SILT FENCE



SILT FENCE AT MEDIAN SURFACE DRAINS



SILT FENCE




JOINING TWO LENGTHS OF SILT FENCE^⑤


GENERAL NOTES

DETAILS OF CONSTRUCTION NOT SHOWN ON THIS DRAWING SHALL CONFORM TO THE PERTINENT REQUIREMENTS OF THE STANDARD SPECIFICATIONS AND APPLICABLE SPECIAL PROVISIONS.

- ① HORIZONTAL BRACE REQUIRED WITH 2" X 4" WOODEN FRAME OR EQUIVALENT AT TOP OF POSTS.
- ② FOR MANUAL INSTALLATIONS THE TRENCH SHALL BE A MINIMUM OF 4" WIDE & 6" DEEP TO BURY AND ANCHOR THE GEOTEXTILE FABRIC. FOLD MATERIAL TO FIT TRENCH AND BACKFILL & COMPACT TRENCH WITH EXCAVATED SOIL.
- ③ WOOD POSTS SHALL BE A MINIMUM SIZE OF 1/8" X 1/8" OF OAK OR HICKORY.
- ④ SILT FENCE TO EXTEND ACROSS THE TOP OF THE PIPE.
- ⑤ CONSTRUCT SILT FENCE FROM A CONTINUOUS ROLL IF POSSIBLE BY CUTTING LENGTHS TO AVOID JOINTS. IF A JOINT IS NECESSARY USE ONE OF THE FOLLOWING TWO METHODS; A) OVERLAP THE END POSTS AND TWIST, OR ROTATE, AT LEAST 180 DEGREES, B) HOOK THE END OF EACH SILT FENCE LENGTH.



TRENCH DETAIL



SILT FENCE TIE BACK
(WHEN REQUIRED BY THE ENGINEER)


SILT FENCE	
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION	
APPROVED	/S/ Beth Cannon
4-29-05	DATE
CHIEF ROADWAY DEVELOP 20	
FHWA	

GENERAL NOTES


NAME PLATES TO BE INSTALLED ON BRIDGES, CULVERTS, AND RETAINING WALLS SHALL CONFORM TO THE REQUIREMENTS OF SECTION 502.3.11 OF THE STANDARD SPECIFICATIONS.

THE BRIDGE NUMBER AND YEAR BUILT SHOWN ON THIS DRAWING ARE EXAMPLES ONLY. SEE CONSTRUCTION PLANS FOR INDIVIDUAL NUMBERING AND YEAR BUILT.



- ① EPOXY RESIN SHALL BE FROM AN APPROVED MANUFACTURER AND USED IN ACCORDANCE WITH MANUFACTURER'S RECOMMENDATIONS.
- ② REHABILITATION OF AN EXISTING STRUCTURE SHOULD USE THE DATE OF ORIGINAL STRUCTURE CONSTRUCTION.



TYPICAL NAME PLATE
(BRIDGES, CULVERTS, AND RETAINING WALLS)




NUMBERING DESIGNATION
MULTI-UNIT STRUCTURES



ALTERNATE LUG
(FOR ATTACHMENT TO PRECAST STRUCTURES)

NAME PLATE (STRUCTURES)	
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION	
APPROVED	
3/26/10	/S/ Scot Beck
DATE	CHIEF STRUCTURAL DEVELOP 21
FHWA	



**TYPICAL PAVEMENT CROSS SECTION
NOTCHED WEDGE JOINT**

GENERAL NOTES


IN ADDITION TO THE DETAILS PROVIDED IN THIS DRAWING, CONFORM TO STANDARD SPECIFICATION 450.3.2.8 FOR WHEN A NOTCHED WEDGE JOINT IS REQUIRED AND FOR GENERAL JOINT CONSTRUCTION REQUIREMENTS.

FOR ALL LONGITUDINAL JOINTS, ENSURE THE PAVER SCREED OVERLAPS THE PREVIOUSLY PLACED PAVEMENT BY $1'' \pm 0.5''$ AND THE HOT SIDE OF THE JOINT REMAINS HIGHER THAN THE COLD SIDE BY APPROXIMATELY $0.1''$ AFTER FINAL COMPACTION. (IT WILL BE FLUSH WHEN PAVING IN ECHELON.)


ONLY REMOVE THE LONGITUDINAL NOTCHED WEDGE JOINT FOR SMA PAVEMENT OR AS DIRECTED BY THE ENGINEER TO ADDRESS SPECIFIC LENGTHS OF JOINT DAMAGED BY TRAFFIC.

WHEN MILLING BACK OR REMOVING ANY LONGITUDINAL JOINT, LIMIT THE MATERIAL REMOVED TO $2''$ FROM THE TOP NOTCH OR FROM THE VERTICAL JOINT EDGE ON THE COLD SIDE OF THE JOINT.


USE LONGITUDINAL MILLED JOINT AS PLANS SHOW OR AS THE ENGINEER DIRECTS.



**TYPICAL PAVEMENT CROSS SECTION
VERTICAL JOINT**



OVERLAP DETAIL (TYPICAL)




**TYPICAL PAVEMENT CROSS SECTION
VERTICAL JOINT (MILLED)**

HMA LONGITUDINAL JOINTS

STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION


APPROVED
November 2020 /S/ Steven Hefel
DATE
FHWA

HMA PAVEMENT ENGIN 22



DETAIL A
MAINLINE CLOSURE WITH POSTED DETOUR

WORK ZONE GREATER THAN OR EQUAL TO $\frac{1}{2}$ MILE FROM
DETOUR ROUTE (1000 FEET IF URBAN)



DETAIL C
MAINLINE CLOSURE, NO POSTED DETOUR

SEE SDD 15C2-SHEET "b"
FOR GENERAL NOTES
AND FOOTNOTES ① THROUGH ⑦

SPEED LIMIT (MPH)	"STOP AHEAD" ADVANCE WARNING DISTANCE (FT)
25	200
30	200
35	350
40	350
45	500
50	550
55	750

BARRICADES AND SIGNS FOR MAINLINE CLOSURES

STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION

APPROVED _____
May 2023 _____ /S/ Andrew Heidtke
DATE WORK ZONE ENGINEER 23
/A

GENERAL NOTES

THE EXACT NUMBER, LOCATION, AND SPACING OF ALL SIGNS AND BARRICADES SHALL BE ADJUSTED TO FIT FIELD CONDITIONS AS APPROVED BY THE ENGINEER.

ANY SIGNS TEMPORARY OR EXISTING, WHICH CONFLICT WITH TRAFFIC CONTROL "IN USE", SHALL BE REMOVED OR COVERED AS NEEDED AND AS APPROVED BY THE ENGINEER.

THE SPACING BETWEEN TRAFFIC CONTROL SIGNS SHOULD BE ADJUSTED TO NOT CONFLICT WITH AND SHOULD PROVIDE A DESIRABLE MINIMUM OF 200 FEET CLEARANCE TO EXISTING SIGNS THAT WILL REMAIN IN PLACE.

BARRICADES THAT MUST BE MOVED FOR A WORK OPERATION SHALL BE IMMEDIATELY RE-ESTABLISHED UPON COMPLETION OF THE OPERATION, OR FOR CONTINUING OPERATIONS, AT THE END OF EACH WORKING DAY.

SIGNS THAT WILL BE IN PLACE LESS THAN 7 CONTINUOUS DAYS AND NIGHTS MAY BE MOUNTED ON PORTABLE SUPPORTS.

ALL TYPE III BARRICADES SHALL HAVE RAILS REFLECTORIZED ON BOTH FACES. STRIPES SHALL BE PROPERLY SLOPED DOWN TOWARD THE TRAFFIC SIDE OR AS SHOWN IN THE ROAD CLOSURE BARRICADE DETAIL "D" FOR FULL ROAD CLOSURES.

TYPE "A" LOW - INTENSITY FLASHING WARNING LIGHTS SHALL BE VISIBLE ON BOTH SIDES OF THE BARRICADE.

THE R11 - 2, R11 - 3, M4 - 9, R11 - 4, AND R10 - 61 SIGNS PLACED ON THE BARRICADES SHALL COVER NO MORE THAN THE TOP RAIL. THE SIGNS SHALL NOT COVER ANY PORTION OF THE MIDDLE RAIL OR BOTTOM RAILS.

"WO" AND "MO" SIGNS ARE THE SAME AS "W" AND "M" SIGNS EXCEPT THE BACKGROUND IS ORANGE.

ALL SIGNS SHALL BE 48" X 48" UNLESS OTHERWISE NOTED BELOW:

R11 - 2 SHALL BE 48" X 30"

R11 - 3 SHALL, R11 - 4 AND R10 - 61 SHALL BE 60" X 30"

M4 - 9 SHALL BE 30" X 24"

M3 - X SHALL BE 24" X 12" (36" X 18" IF NEEDED TO MATCH EXISTING SIGNS)


M4 - 8 SHALL BE 24" X 12" (36" X 18" IF NEEDED TO MATCH EXISTING SIGNS)

M1 - 4, M1 - 5A AND M1 - 6 SHALL BE 24" X 24" (36" X 36" IF NEEDED TO MATCH EXISTING SIGNS)

M05 - 1 AND M06 - 1 SHALL BE 21" X 21" (30" X 30" IF NEEDED TO MATCH EXISTING SIGNS)


D1 - X SHALL BE AS SHOWN ON SPECIFIC PROJECT SIGNING DETAIL SHEETS.

R1 - 1 SHALL BE 36" X 36"



DETAIL D
ROAD CLOSURE BARRICADE DETAIL
APPROACH VIEW

6



DETAIL E
LANE CLOSURE BARRICADE DETAIL
APPROACH VIEW

SEE SDD 15C2 - SHEET "a" FOR LEGEND


- ① TWO WARNING LIGHTS SHALL BE PROVIDED ON THE CENTER BARRICADE AND A MINIMUM OF ONE WARNING LIGHT SHALL BE PROVIDED ON EACH OF THE OTHER BARRICADES WITHIN THE ROADWAY LIMITS. SPACING OF THE WARNING LIGHTS SHALL BE UNIFORM TO THE EDGE OF ROADWAY AS SHOWN (APPROX. 8 FOOT LIGHT SPACING).
- ② THESE SIGNS AND BARRICADES ARE NOT REQUIRED IF ROAD CLOSURE BEGINS AT AN INTERSECTION.
- ③ FOR ROAD CLOSURE WITHOUT LOCAL ACCESS TO PROJECT, SEE ROAD CLOSURE BARRICADE DETAIL "D".
- ④ FOR ROAD CLOSURE WITH LOCAL ACCESS TO PROJECT, SEE ROAD CLOSURE BARRICADE DETAIL "E".
- ⑤ FOR BRIDGE OR CULVERT REPLACEMENTS, SUBSTITUTE "BRIDGE OUT" INSTEAD OF "ROAD CLOSED" ON R11 - 2 AND R11 - 3 SIGNS.
- ⑥ INSTALL DETOUR AND COMMUNITY GUIDE SIGNS AND ARROWS ONLY IF SPECIFIED IN THE CONTRACT. IF THERE ARE EXISTING ROUTE MARKER ASSEMBLIES THAT WILL REMAIN IN PLACE, ADJUST THE LOCATION OF THE DETOUR ROUTE SIGNS TO CORRESPOND WITH THE EXISTING ASSEMBLIES. MODIFY EXISTING SIGNS WHERE POSSIBLE. SEE SPECIFIC PROJECT DETOUR SIGNING DETAIL SHEETS. IF DETOUR SIGNS ARE BEING INSTALLED BY OTHERS, PLACE THE CONTRACTED TRAFFIC CONTROL SIGNS TO ALLOW FOR PLACEMENT OF ALL WARNING, DETOUR AND GUIDE SIGNS AS SHOWN.
- ⑦ "EAST" CARDINAL DIRECTION MARKERS AND RIGHT TURN ARROWS ARE SHOWN. USE OTHER CARDINAL DIRECTIONS AND ARROWS AS APPROPRIATE.

BARRICADES AND SIGNS FOR VARIOUS CLOSURES


STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION

APPROVED
May 2023
DATE
FHWA

/S/ Andrew Heidke
WORK ZONE ENGINEER 24

**SITUATION 1**

WARRANTING CRITERIA:
BRIDGE WIDTH IS AT LEAST 16 FEET BUT LESS THAN 24 FEET.

**SITUATION 2**

WARRANTING CRITERIA:
1. BRIDGE WIDTH IS AT LEAST 24 FEET AND
2. BRIDGE SHOULDER WIDTH IS LESS THAN 6 FEET

GENERAL NOTES

DETAILS OF TRAFFIC CONTROL DEVICES AND INSTALLATION NOT SHOWN ON THE DRAWING SHALL CONFORM TO THE PERTINENT REQUIREMENTS OF THE STANDARD SPECIFICATIONS, THE SPECIAL PROVISIONS, AND THE MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES.

LOCATE W5-52 SIGN POST(S) BEHIND GUARDRAIL WHEN PRESENT.

PLACE THE EDGE OF THE W-52 SIGN IN LINE WITH FACE OF CURB OR PARAPET.

ON BRIDGE ONLY PROJECTS, PLACE 300 FEET OF EDGELINE.

OMIT EDGELINES ON ROADWAYS WITHOUT EXISTING EDGELINES.

① OMIT ON ONE-WAY TRAVELED WAYS.

LEGEND

Ⓐ SIGN ON PERMANENT SUPPORT

→ DIRECTION OF TRAFFIC


DISTANCE TABLE

POSTED OR 85TH PERCENTILE SPEED	DISTANCE "A"
25	150'
30	200'
35	250'
40	300'
45	400'
50	550'
55	700'


**SIGNING AND MARKING
FOR TWO LANE BRIDGES**

STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION


APPROVED
May 2023 /S/ Jeannie Silver
DATE
FHWA
Statewide Pavement Marking Engineer

**DRUM**


BALLAST WIDTHS
RANGE FROM 24"-36"

**42" CONE**


DO NOT USE IN TAPERS
 $\frac{1}{2}$ SPACING OF DRUMS
 BALLAST WIDTHS
RANGE FROM 14"-20"

**VERTICAL PANEL**

THE STRIPES SHALL SLOPE DOWNWARD TO
THE TRAFFIC SIDE FOR CHANNELIZATION.

**TYPE II BARRICADE**

FOR RAILS LESS THAN 36" LONG, 4" WIDE STRIPES
MAY BE USED. ALL STRIPES SHALL SLOPE DOWNWARD
TO THE TRAFFIC SIDE FOR CHANNELIZATION.

**TYPE III BARRICADE**

IF SIGN MOUNTED, DO NOT COVER MORE THAN 50% OF THE TOP
TWO RAILS OR 33% OF THE TOTAL AREA OF THE THREE RAILS.

* IF USED FOR A PERMANENT APPLICATION USE RED SHEETING.

GENERAL NOTES


- ① REFLECTIVE SHEETING SHALL FOLLOW THE REQUIREMENTS IN THE APPROVED PRODUCTS LISTING FOR SIGN SHEETING.
- ② LOCATION OF WARNING LIGHTS WHEN SHOWN ON THE PLAN.

CHANNELIZING DEVICES DRUMS, CONES, BARRICADES AND VERTICAL PANELS


STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION

APPROVED
November 2022 /S/ Andrew Heidtke
DATE FHWA
WORK ZONE ENGINEER 26

URBAN AREA




RURAL AREA (See Note 2)



GENERAL NOTES

1. Signs wider than 4 feet or 20 sq.ft or larger, shall be mounted on multiple posts. Refer to plate A4-4.
2. If signs are mounted on or behind barrier wall, see A4-10 sign plate.
3. The Double Arrow sign (W12-1D) shall be mounted at a height of 2'-3" (±) 3". The Chevron sign (W1-8), Roundabout Chevron panel (R6-4B), Enhanced Reference Markers, Clearance Markers (W5-52), Mile Markers (D10 series), In Road Object Markers (W5-54) & End of Road Markers (W5-56) shall be mounted at a height of 4'-3" (±) 3".
4. For expressways and freeways, mounting height is 7'-3" (±) 3" or 6'-3" (±) 3" depending upon existence of a sub-sign.
5. Minimum mounting height for signs mounted on traffic signal poles is 5'-3" (±) 3".
6. Offset distance shall be consistent with existing signs or consistent throughout length of project.
7. Folding signs shall be mounted at a height of 5'-3" (±) 3" or as directed by the Engineer.

2' Min - 4' Max (See Note 5)



White Edgeline Location



** The existence of curb and gutter does not in itself mandate the vertical clearance illustrated. That height is typically measured where there is sidewalk adjacent to the roadway or parking is permitted. In the absence of sidewalk vertical clearance is measured from the top of the curb. Offset of signs is measured from the flow line.

POST EMBEDMENT DEPTH

Area of Sign Installation (Sq. Ft.)	D (Min)
20 or Less	4'
Greater than 20	5'


* 6 feet from edge of a paved shoulder or 12 feet from the edge of pavement (edge line location) or 2 feet from outside edge of gravel, whichever is greater unless directed by project engineer.

TYPICAL INSTALLATION
OF PERMANENT TYPE II
SIGNS ON SINGLE POSTS

WISCONSIN DEPT OF TRANSPORTATION


APPROVED *Matthew P. Rauch*
for State Traffic Engineer

DATE 12/6/23 PLATE NO. A4-3.23




ELEVATION VIEW

DETAIL OF WOOD 4 X 6 SIGN POST IN BOX-OUT



ELEVATION VIEW

DETAIL OF STEEL 2 X 2 SIGN POST IN BOX-OUT



PLAN VIEW

FOR NEW CONCRETE/ASPHALT INSTALLATIONS

SIGN POST
BOX-OUTS
A4-3B

WISCONSIN DEPT OF TRANSPORTATION

APPROVED
Matthew P. Rauch
for State Traffic Engineer
DATE 1/27/14 PLATF 28 A4-3B.1

PROJECT NO:

HWY:



COUNTY:

SHEET NO:




E

GENERAL NOTES

- For 3 or 4 post installations, individual post spacing shall be greater than 3'-6".
- See tables below for required number of posts.
- For expressways and freeways, mounting height is 7'-3" (\pm 3") or 6'-3" (\pm 3") depending upon existence of sub-sign.
- The (\pm) tolerance for mounting height is 3 inches.
- J-Assemblies are considered to be one sign for mounting height.
- Offset distance shall be consistent with existing signs or consistent throughout length of project.
- Folding signs shall be mounted at a height of 5'-3" (\pm 3") or as directed by the engineer.
- The Double Arrow sign (W12-1) shall be mounted at a height of 2'-3" (\pm 3"). The Chevron sign (W1-8), Roundabout Chevron panel (R6-4B), Clearance Markers (W5-52), Mile Markers (D10 series), In Road Object Markers (W5-54) & End of Road Markers (W5-56) shall be mounted at a height of 4"-3" (\pm 3").



RURAL AREA (See Note 3)



* 6 feet from edge of a paved shoulder or 12 feet from the edge of pavement (edge line location) or 2 feet from outside edge of gravel, whichever is greater unless directed by project engineer.

** The existence of curb and gutter does not in itself mandate the vertical clearance illustrated. That height is typically measured where there is sidewalk adjacent to the roadway or parking is permitted. In the absence of sidewalk vertical clearance is measured from the top of the curb. Offset of signs is measured from the flow line.

*** See A4-3 sign plate for signs 4' or less in width and less than 20 S.F. in area.

SIGN SHAPE OTHER THAN DIAMOND (TWO POSTS REQUIRED)

L	E
Greater than 48"	12"
Less than 60"	
60" to 108"	L/5

SIGN SHAPE OTHER THAN DIAMOND (THREE POSTS REQUIRED)

L	E
Greater than 108" to 144"	12"

POST EMBEDMENT DEPTH

Area of Sign Installation (Sq. Ft.)	D (Min)
20 or Less	4'
Greater than 20	5'

TYPICAL INSTALLATION OF TYPE II SIGNS ON MULTIPLE POSTS

WISCONSIN DEPT OF TRANSPORTATION

APPROVED

Matthew R. Rauch
for State Traffic Engineer

DATE 12/6/23 PLATE NO. A4-4.16


PROJECT NO:

HWY:


COUNTY:

SHEET NO: 29

E



SIGN SHALL BE MOUNTED TO PROJECT
ABOVE THE TOP OF THE POST



Nuts, bolts and lags used for mounting signs shall have hexagonal heads and shall be either :

- a. Hot dip galvanized in accordance with ASTM Designation: A 153, Class D, or SC 3
- b. Electro-galvanized in accordance with ASTM Designation :B 633, TYPE III, SC 3.

Threads on bolts and nuts shall be manufactured with sufficient allowance for the cadmium plate or galvanized coating to permit the nuts to run freely on the bolts.

STRINGER BOLTING TO ALUMINUM SIGNS (SEE SIGN PLATE A4-18)

MACHINE BOLTS - $\frac{5}{16}$ " X 1-3/4" Length w/ lock nuts

WOOD POSTS (4" x 6")

LAG SCREWS - $\frac{3}{8}$ " X 3" (NO STRINGERS ON BACK OF SIGN)
 $\frac{3}{8}$ " X 4" (STRINGERS ON BACK OF SIGN)

SQUARE STEEL POSTS (2" x 2")

MACHINE BOLTS - $\frac{3}{8}$ " X 3-1/4" Length w/ nuts (NO STRINGER ON BACK OF SIGN)
 $\frac{3}{8}$ " X 5" Length w/ nuts (STRINGERS ON BACK OF SIGN)

RIVETS - $\frac{9}{32}$ " (6605-9-6) BULB-TITE, TRI-FOLD, ALUMINUM BODY/MANDREL

O.D. FLANGE .720-.765 INCH, GRIP RANGE .042-.375 INCH

WASHERS (ALL POSTS) -

1-1/4" O.D. X $\frac{3}{8}$ " I.D. X $\frac{1}{16}$ " STEEL

1-1/4" O.D. X $\frac{3}{8}$ " I.D. X .080 NYLON

* Two different fastening systems are shown for illustration purposes. On any individual sign, either one or the other system shall be used. Actual number of fasteners per sign varies with the sign area, but normally there are two. For a single post installation, all signs greater than 9 sq. ft. require the use of 3 fasteners.


ATTACHMENT OF SIGNS TO POSTS

WISCONSIN DEPT OF TRANSPORTATION


APPROVED *Matthew R Rauch*
for State Traffic Engineer

DATE 4/1/2020 PLATE NO. A4-8.9


TELESCOPIC TUBING ANCHORS TWO PIECE SYSTEM



DETAIL OF TUBULAR STEEL SIGN POST (IN Poured CONCRETE OR ASPHALT)



DETAIL OF TUBULAR STEEL SIGN POST (IN LOCATIONS OTHER THAN Poured CONCRETE OR ASPHALT)



Area of Sign Installation (Sq. Ft.)	Number of Required Posts
9 or less	1
Greater than 9 less than or equal to 18	2
Greater than 18 less than or equal to 27	3

Signs wider than 3 feet or larger than 9 sq. ft shall be mounted on multiple posts (see above table).

**TUBULAR STEEL
SIGN POST**
A4-9

WISCONSIN DEPT OF TRANSPORTATION

APPROVED
Matthew P. Rauch

for State Traffic Engineer

DATE 2/05/15 PLATI 31 14-9.9



PROJECT NO:

HWY:

COUNTY:

SHEET NO:

E



SIDE VIEW

GENERAL NOTES

1. All 4 x 6 Wood Posts shall be modified by having two $1\frac{1}{2}$ " diameter holes drilled perpendicular to the roadway centerline.

4 X 6 WOOD POST
MODIFICATIONS

WISCONSIN DEPT OF TRANSPORTATION

APPROVED

Cheska J. Sprey
for State Traffic Engineer

DATE 3/27/97

PLATE NO. A4-11.2

PROJECT NO:

HWY:




COUNTY:

BANDING


GENERAL NOTES

1. Any sign over 3 feet in width shall use the V-Block banding method. See A5-10 standard plate.
2. Signs 3 feet or greater in height shall have three bracket bands installed. Signs less than 3 feet in height shall have two bracket bands installed.
3. Banding and assembly bracket shall be stainless steel. All bands shall be $\frac{3}{4}$ " in width and 0.025" thickness.
4. ALL SIGN MOUNTING BOLTS AND WASHERS SHALL BE EITHER:
 - a. Hot dip or mechanically galvanized in accordance with ASTM Designation: A 153, Class D
 - b. Electro-galvanized in accordance with ASTM designation: B 633, Type III, SC 3

SINGLE SIGN




WASHER PLACEMENT



WASHERS (ALL POSTS) -
 1-1/4" O.D. X $\frac{3}{8}$ " I.D. X $\frac{1}{16}$ " STEEL
 1-1/4" O.D. X $\frac{3}{8}$ " I.D. X .080 NYLON
 FOR ALL TYPE H SIGNS

"J" ASSEMBLY




STANDARD SIGN SIGN BANDING DETAILS

WISCONSIN DEPT OF TRANSPORTATION

APPROVED


 for State Traffic Engineer
 DATE 6/10/19 PLATE NO. A5-9.4



GENERAL NOTES

1. WOOD 4"X6" POST MATERIAL SHALL CONFORM TO 507.2.2 OF THE WisDOT STANDARD SPECIFICATIONS
2. BLOCK BANDING AND CLIPS SHALL BE STAINLESS STEEL, $\frac{3}{4}$ " WIDTH AND 0.025" THICKNESS
3. SIGNS 3' OR GREATER IN HEIGHT SHALL UTILIZE 3 BLOCK BANDS. SIGNS UNDER 3' IN HEIGHT SHALL UTILIZE 2 BLOCK BANDS
4. ACTUAL NUMBER OF FASTENERS PER SIGN VARIES WITH THE SIGN AREA, BUT NORMALLY THERE ARE TWO. FOR SIGNS GREATER THAN 9 S.F. 3 FASTENERS SHALL BE USED.
5. ALL SIGN MOUNTING BOLTS AND WASHERS SHALL BE EITHER:
 - a. Hot dip or mechanically galvanized in accordance with ASTM Designation: A 153, Class D
 - b. Electro-galvanized in accordance with ASTM Designation : B 633, TYPE III, SC 3
6. ALL BOLTS SHALL HAVE HEXAGONAL HEADS.
7. STEEL WASHERS SHALL BE $1\frac{1}{4}$ " O.D. X $\frac{3}{8}$ " I.D. X $\frac{1}{16}$ "
8. NYLON WASHERS SHALL BE $1\frac{1}{4}$ " O.D. X $\frac{3}{8}$ " I.D. X .080 FOR TYPE H OR TYPE F FACE SIGN

※ LAG BOLTS SHALL BE $\frac{3}{8}$ " X $2\frac{1}{2}$ "





BLOCK BANDING DETAIL
(V-BLOCK OPTION)

WISCONSIN DEPT OF TRANSPORTATION

APPROVED *Matthew R Rauch*
for State Traffic Engineer
DATE 4/19/2022 PLATE NO. A5-10.3

7



NOTES

1. Sign is Type II - Type F Reflective
2. Color:
Background - Yellow
Message - Black
3. Alternate colors of stripes as shown.

SIZE	A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q	R	S	T	U	V	W	X	Y	Z	Area sq. ft.
1																											
2S	12	36	1 1/2			4 3/8	3 1/2	5 5/8	45°	4	4															3.0	
2M	12	36	1 1/2			4 3/8	3 1/2	5 5/8	45°	4	4															3.0	
3	18	54	1 1/2			6	5 1/2	8 1/2	45°	6	6 9/16															6.75	
4																											
5																											

PROJECT NO:

HWY:

COUNTY:

STANDARD SIGN

W5-52L & W5-52R


WISCONSIN DEPT OF TRANSPORTATION

APPROVED *Matthew R Rauch*

for State Traffic Engineer

DATE 3/4/2024 PLATE NO. W5-52.10

SHEET NO: 35 E




TYPICAL SECTION THRU BRIDGE

TOTAL ESTIMATED QUANTITIES

BID ITEM NUMBER	BID ITEMS	UNIT	SUPER	W ABUT.	E ABUT.	TOTALS
203.0270	REMOVING STRUCTURE OVER WATERWAY DEBRIS CAPTURE (P-26-903)	EACH	---	---	---	1
206.1001	EXCAVATION FOR STRUCTURES BRIDGES B-26-47	EACH	---	---	---	1
206.5001	COFFERDAMS (B-26-47)	EACH	---	---	---	1
210.1500	BACKFILL STRUCTURE TYPE A	TON	---	120	110	230
502.0100	CONCRETE MASONRY BRIDGES	CY	112.3	22.1	18.3	153
502.3200	PROTECTIVE SURFACE TREATMENT	SY	180	10	5	195
505.0400	BAR STEEL REINFORCEMENT HS STRUCTURE	LB	---	1,290	1,290	2,580
505.0600	BAR STEEL REINFORCEMENT HS COATED STRUCTURES	LB	21,510	1,140	820	23,470
513.4061	RAILING TUBULAR TYPE M	LF	106	---	---	106
516.0500	RUBBERIZED MEMBRANE WATERPROOFING	SY	---	6	6	12
517.1015.S	CONCRETE STAINING MULTI-COLOR B-26-47	SF	--	190	155	345
517.1050.S	ARCHITECTURAL SURFACE TREATMENT B-26-47	SF	---	190	155	345
606.0400	RIPRAP EXTRA-HEAVY	CY	---	20	20	40
612.0406	PIPE UNDERDRAIN WRAPPED 6-INCH	LF	---	60	50	110
645.0111	GEOTEXTILE TYPE DF SCHEDULE A	SY	---	35	25	60
645.0120	GEOTEXTILE TYPE HR	SY	---	35	45	80
SPV.0180	INFILL RIPRAP B-26-47	SY	---	---	---	50
NON-BID ITEMS						
	FILLER	SIZE	---	---	---	1/2", 3/4"

BENCH MARK

NO.	STATION	DESCRIPTION	ELEV.
50	12+19	SURVEY SPIKE IN 18" MAPLE, ON C/L	1218.27
51	9+82	CHIS. 'X' IN ABUTMENT, 8' RT	1211.26
52	8+66	120 'D' SPIKE IN ROOT OF 36" OAK, 15' LT	1213.11



PROFILE GRADE LINE

(TOWN PARK DRIVE)

GENERAL NOTES

DRAWINGS SHALL NOT BE SCALED.

BAR STEEL REINFORCEMENT SHALL BE EMBEDDED 2" CLEAR UNLESS OTHERWISE SHOWN OR NOTED.

THE FIRST OR FIRST TWO DIGITS OF THE BAR MARK SIGNIFIES THE BAR SIZE.

BEVEL EXPOSED EDGES OF CONCRETE 3/4" UNLESS OTHERWISE NOTED.

THE UPPER LIMITS OF "EXCAVATION FOR STRUCTURES BRIDGES B-26-47" SHALL BE THE EXISTING GROUNDLINE.

EXCAVATION OF ALL MATERIAL, INCLUDING ROCK, SHALL BE PAID FOR UNDER THE "EXCAVATION FOR STRUCTURES BRIDGES B-26-47" BID ITEM. ALL EXCAVATION SHALL BE CLEANED BY HAND AND INSPECTED TO VERIFY THE SURFACE IS FREE OF LOOSE RUBBLE AND SOIL PRIOR TO CONCRETE PLACEMENT.

THE SURFACE OF BEDROCK MAY BE IRREGULAR AT THE ABUTMENT LOCATIONS. ADJUSTMENT OF THE ABUTMENT HEIGHT WILL BE ALLOWED AND SHALL BE SUBJECT TO THE APPROVAL OF THE ENGINEER. REPORT ELEVATIONS OF THE BEDROCK TO THE ENGINEER ONCE IT IS EXPOSED.

PROTECTIVE SURFACE TREATMENT TO BE APPLIED AS SHOWN IN DETAIL ON SHEET 3 AND APPLY TO ENTIRE EXPOSED TOP OF SLAB, THE TOP AND EXTERIOR EXPOSED FACE OF WINGS, AND FRONT FACE OF ABUTMENT TO 1'-0" PAST THE EDGE OF SLAB.


AT THE BACK FACE OF ABUTMENT ALL VOLUME WHICH CANNOT BE PLACED BEFORE ABUTMENT CONSTRUCTION AND IS NOT OCCUPIED BY THE NEW STRUCTURE SHALL BE BACKFILLED WITH STRUCTURE BACKFILL TYPE A.

EXCAVATION BELOW THE ABUTMENT AND ABUTMENT BEDDING MATERIALS REQUIRES ENGINEER APPROVAL. GEOTEXTILE SHALL BE SET AT THE BOTTOM OF EXCAVATION AND EXTEND 2'-0" ABOVE BOTTOM OF ABUTMENT.

THE QUANTITY FOR BACKFILL STRUCTURE IS CALCULATED BASED ON THE DETAIL SHOWN IN THE PLANS, AND MAY NOT REFLECT ACTUAL PLACED QUANTITIES. "BACKFILL STRUCTURE TYPE A" REQUIRED DIRECTLY BEHIND ABUTMENTS AND ABUTMENT WINGS FOR 3 FEET. BACKFILL PLACED BEYOND PAY LIMITS OR EXCEEDING PLAN QUANTITIES SHALL BE INCIDENTAL TO EXCAVATION FOR STRUCTURES.

SLAB FALSEWORK SHALL BE SUPPORTED ON PILES OR THE SUBSTRUCTURE UNLESS AN ALTERNATE METHOD IS APPROVED BY THE ENGINEER.

EXISTING SUBSTRUCTURE LOCATIONS ARE BASED ON SURVEY. EXTENT OF BELOW GRADE SUBSTRUCTURES ARE NOT KNOWN. REMOVE EXISTING SUBSTRUCTURE AS NEEDED TO BUILD NEW SUBSTRUCTURE. COST OF SUBSTRUCTURE REMOVAL IS CONSIDERED INCIDENTAL TO "REMOVING STRUCTURE OVER WATERWAY DEBRIS CAPTURE" BID ITEM.




RODENT SHIELD DETAIL

* DIMENSIONS ARE APPROXIMATE. THE GRATE IS SIZED TO FIT INTO A PIPE COUPLING. ORIENT SO SLOTS ARE VERTICAL.

THE RODENT SHIELD, PIPE COUPLING AND SCREWS SHALL BE CONSIDERED INCIDENTAL TO THE BID ITEM "PIPE UNDERDRAIN WRAPPED 6-INCH".

THE RODENT SHIELD SHALL BE A PVC GRATE SIMILAR TO THIS DETAIL. THE GRATE IS COMMERCIALLY AVAILABLE AS A FLOOR STRAINER. A PIPE COUPLING IS REQUIRED FOR THE ATTACHMENT OF THIS SHIELD TO THE EXPOSED END OF THE PIPE UNDERDRAIN. THE SHIELD SHALL BE FASTENED TO THE PIPE COUPLING WITH TWO OR MORE NO. 10 X 1-INCH STAINLESS STEEL SHEET METAL SCREWS.

NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
STRUCTURE B-26-47			
DRAWN BY JMC/CLP PLANS CK'D JMC			
TYPICAL SECTION, QUANTITIES AND NOTES			
SHEET 2 OF 14			
37			




FORMLINER DETAILS


SECTION THRU FORMLINER

STRUCTURAL CONCRETE CAN ONLY BE ASSUMED TO THIS LINE. PROVIDE ADDITIONAL STRUCTURE SIZE AS NECESSARY TO MAINTAIN MINIMUM FULL STRUCTURAL CONCRETE DIMENSIONS AS INDICATED ON THE STANDARDS.

THE SPECIAL PROVISION FOR THE BID ITEM, ARCHITECTURAL SURFACE TREATMENT B-26-47 TO BE SIMILAR PATTERN TO B-26-32 (DUPONT ROAD OVER MONTREAL RIVER, 6.8 MILES NORTH EAST).




PROTECTIVE SURFACE TREATMENT DETAIL




ABUTMENT BACKFILL DIAGRAM

L = ABUTMENT BODY LENGTH AT BACKFACE (FT)
 H = AVERAGE ABUTMENT FILL HEIGHT (FT)
 $H1$ = WING 1 HEIGHT AT TIP (FT)
 $H2$ = WING 2 HEIGHT AT TIP (FT)
 W = WING LENGTH (FT)
 EF = EXPANSION FACTOR (1.20 FOR CY BID ITEMS AND 1.00 FOR TON BID ITEMS)
 V_{CF} = $(L)(3.0')(H) + (L)(0.5)(1.5H)(H) + (3')(0.5)(H1+H2+H+H)(W)$
 V_{CY} = $V_{CF}(EF)/27$
 V_{TON} = $V_{CY}(2.0)$

NOTE:
THE BACKFILL QUANTITY WAS CALCULATED BASED ON THE STANDARD FORMULA. IF BEDROCK OCCUPIES SPACE BEHIND THE ABUTMENTS THE QUANTITY WILL BE REDUCED.



BACKFILL STRUCTURE LIMITS ABUTMENT PLAN WITH WING



TYPICAL SECTION THRU ABUTMENT

BACKFILL PAY LIMITS. BACKFILL BEYOND PAY LIMITS SHALL BE INCIDENTAL TO EXCAVATION FOR STRUCTURES. LIMITS OF EXCAVATION SHALL BE DETERMINED BY THE CONTRACTOR.

PIPE UNDERDRAIN WRAPPED (6-INCH). SLOPED 0.5% MIN. TO SUITABLE DRAINAGE. ATTACH RODENT SHIELD AT ENDS OF PIPE UNDERDRAIN.

NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
STRUCTURE B-26-47			
DRAWN BY	JMC/CLP	PLANS CK'D	JMC
STRUCTURE DETAILS			
SHEET 3 OF 14		38	

BORING #	DATE COMPLETED	NORTHING (Y)	EASTING (X)
B-01	10/24/2024	383838.91	722924.44
B-02	10/25/2024	383827.68	722935.09
HA-01	10/24/2024	383871.53	722959.70
HA-02	10/24/2024	383867.15	722963.82
BORINGS COMPLETED BY: ECS MIDWEST, LLC			
REPORT COMPLETED BY: ECS MIDWEST, LLC			
ALL COORDINATES REFERENCED TO WCCS NAD 83(91) IRON COUNTY			


STATE PROJECT NUMBER

9826-00-70

MATERIAL SYMBOLS

ASPHALT	TOPSOIL	PEAT
CONCRETE	FILL	GRAVEL
SAND	CLAY	SILT
BOULDERS OR COBBLES	LIMESTONE	BEDROCK (UNKNOWN)
SHALE	SANDSTONE	IGNEOUS/META

LEGEND OF BORING



(1) UNCONFINED STRENGTH, AS DETERMINED BY A POCKET PENETROMETER (TSF)

(2) UNLESS OTHERWISE, SPECIFIED THE SPT 'N' VALUE IS BASED ON AASHTO T-206, STANDARD PENETRATION TEST. THE SPT 'N' VALUE PRESENTED HAS NOT BEEN CORRECTED FOR OVERBURDEN PRESSURE OR HAMMER EFFICIENCY.

GROUND WATER ELEVATION

- ▽ AT TIME OF DRILLING
- ▼ END OF DRILLING
- AFTER DRILLING

ABBREVIATIONS

F-FINE M-MEDIUM C-COARSE ST-SHELBY TUBE

SUBSURFACE EXPLORATION FOR FOUNDATION DESIGN AND BIDDERS INFORMATION

BORINGS WERE COMPLETED AT POINTS APPROXIMATELY AS INDICATED ON THIS DRAWING TO OBTAIN INFORMATION CONCERNING THE CHARACTER OF SUBSURFACE MATERIALS FOUND AT THE SITE. BECAUSE THE INVESTIGATED DEPTHS ARE LIMITED AND THE AREA OF THE BORINGS IS VERY SMALL IN RELATION TO THE ENTIRE SITE, THE WISCONSIN DEPARTMENT OF TRANSPORTATION DOES NOT WARRANT SIMILAR SUBSURFACE CONDITIONS BELOW, BETWEEN, OR BEYOND THESE BORINGS. VARIATIONS IN SOIL CONDITIONS SHOULD BE EXPECTED AND FLUCTUATIONS IN GROUNDWATER LEVELS MAY OCCUR.

NO.	DATE	REVISION	BY
-----	------	----------	----


STATE OF WISCONSIN

DEPARTMENT OF TRANSPORTATION

STRUCTURE B-26-47

DRAWN BY	PLANS CK'D	JMC
----------	------------	-----

SHEET 4 OF 14	39
---------------	----



8

8

140

1140

1230

1220

1210

1200

1190

1180

1170

1160

1150

1140

HAND AUGER #1, EL. 1210.8
STA. 9+69.5, 4' LT. C/LHAND AUGER #2, EL. 1211.1
STA. 9+69.5, 12' RT. C/L

GRADE

EL. 1205.78

EL. 1207.41

EXISTING GROUNDLINE

BORING #1, EL. 1213.6
STA. 10+20, 3' LT. C/L

25

PS

%

100

50

%

18

%

100

50

%

18

%

100

50

%

18

%

100

50

%

18

%

100

50

%

18

%

100

50

%

18

%

100

50

%

18

%

100

50

%

18

%

100

50

%

18

%

100

50

%

18

%

100

50

%

18

%

100

50

%

18

%

100

50

%

18

%

100

50

%

18

%

100

50

%

18

%

100

50

%

18

%

100

50

%

18

%

100

50

%

18

%

100

50

%

18

%

100

50

%

18

%

100

50

%

18

%

100

50

%

18

%

100

50

%

18

%

100

50

%


18

%


100

50


%



ELEVATION LOOKING DOWNSTATION



PLAN



BAR STEEL LAYOUT

⚠ ELEVATION IS APPROXIMATE. CONSTRUCT ABUTMENT AND WINGS TO REACH SOLID ROCK, KEY IN A MIN. 6" INTO SOLID ROCK. BOTTOM OF ABUTMENT AND WINGS TO BE APPROXIMATELY LEVEL. MAX. ABUTMENT HEIGHT AT C/L OF TOWN PARK DRIVE TO BE 4'-3 1/4".

NOTE: ABUTMENTS WITH SHALLOW FOOTINGS TO BE SUPPORTED BY SOUND ROCK WITH A REQUIRED FACTOR BEARING RESISTANCE OF 20,000 PSE

A15 PIPE UNDERDRAIN WRAPPED (6-INCH), SLOPE 0.5%
MIN. TO SUITABLE DRAINAGE. RODENT SHIELD
REQUIRED, AN 8" DIA. HOLE IN ABUTMENT IS REQ'D.
LOCATE TO MISS. REINF. STEEL


(A17) $\frac{1}{2}$ " FILLER: SEAL ALL EXPOSED HORIZ. & VERT. SURFACES OF $\frac{1}{2}$ " FILLER WITH NON-STAINING GRAY NON-BITUMINOUS JOINT SEALER. (1" DEEP AND HOLD $\frac{1}{8}$ " BELOW SURFACE OF CONCRETE). EXTEND

A19 18" RUBBERIZED MEMBRANE WATERPROOFING.
SEAL ALL HORIZ. & VERT. JOINTS AT BACKFACE.

■ ALTERNATE THE POSITION OF THE 90° AND 180° HOOKS AT EACH VERTICAL LAYER OF TIES.

- ◆ ADDITIONAL LAP ALLOWED IF BEDROCK IS HIGHER ELEVATION.
- ▼ FORMLINER - SEE SHEET 3 FOR DETAILS.


NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
STRUCTURE B-26-47			
DRAWN BY		PLANS CLP CK'D JMC	
WEST ABUTMENT		SHEET 5 OF 14 40	



WING 1 ELEVATION


△ ELEVATION IS APPROXIMATE. CONSTRUCT ABUTMENT AND WINGS TO REACH SOLID ROCK, KEY IN A MIN. 6" INTO SOLID ROCK. BOTTOM OF ABUTMENT AND WINGS TO BE APPROXIMATELY LEVEL. MAX. ABUTMENT HEIGHT AT C/L OF TOWN PARK DRIVE TO BE 4'-3 3/4".

WING 1 SHOWN, WING 2 SIMILAR
SHOWING F.F. WING




WING 1 PLAN

WING 1 SHOWN, WING 2 SIMILAR
SHOWING UPPER WING REINFORCEMENT



WING 1 PLAN

WING 1 SHOWN, WING 2 SIMILAR
SHOWING LOWER WING REINFORCEMENT



SECTION THRU WING 1

NOTE:

ABUTMENTS WITH SHALLOW FOOTINGS TO BE SUPPORTED BY SOUND ROCK WITH A REQUIRED FACTOR BEARING RESISTANCE OF 20,000 PSF.

(A01) OPTIONAL CONST. JOINT: KEYWAY FORMED BY A BEVELED 2X6. PROVIDE $\frac{3}{4}$ " "V" GROOVE ON F.F. OF WINGWALL IF JOINT IS USED.

(A15) PIPE UNDERDRAIN WRAPPED (6-INCH). SLOPE 0.5% MIN. TO SUITABLE DRAINAGE. RODENT SHIELD REQUIRED.


(A17) $\frac{1}{2}$ " FILLER: SEAL ALL EXPOSED HORIZ. & VERT. SURFACES OF $\frac{1}{2}$ " FILLER WITH NON-STAINING GRAY NON-BITUMINOUS JOINT SEALER. (1" DEEP AND HOLD $\frac{1}{8}$ " BELOW SURFACE OF CONCRETE). EXTEND SEALER 3" BELOW GUTTER LINE AT INSIDE FACE.

(A19) 18" RUBBERIZED MEMBRANE WATERPROOFING, ONLY IF OPTIONAL CONSTRUCTION JOINT IS USED. COST INCIDENTAL TO BID ITEM "CONCRETE MASONRY STRUCTURES".

◆ ADDITIONAL LAP ALLOWED IF BEDROCK IS HIGHER ELEVATION.

▼ FORMLINER - SEE SHEET 3 FOR DETAILS.

NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
STRUCTURE B-26-47			
DRAWN BY CLP PLANS CK'D JMC			
WEST ABUTMENT WING DETAILS	SHEET 6 OF 14		41



SECTION THRU BODY

NOTE:
ABUTMENTS WITH SHALLOW FOOTINGS TO BE SUPPORTED BY SOUND ROCK WITH A REQUIRED FACTOR BEARING RESISTANCE OF 20,000 PSF.

(A15) PIPE UNDERDRAIN WRAPPED (6-INCH). SLOPE 0.5% MIN. TO SUITABLE DRAINAGE. RODENT SHIELD REQUIRED. AN 8" DIA. HOLE IN WALL IS REQ'D. LOCATE TO MISS REINF. STEEL.

(A19) 18" RUBBERIZED MEMBRANE WATERPROOFING, ONLY IF OPTIONAL CONSTRUCTION JOINT IS USED. COST INCIDENTAL TO BID ITEM "CONCRETE MASONRY STRUCTURES".

■ ALTERNATE THE POSITION OF THE 90° AND 180° HOOKS AT EACH VERTICAL LAYER OF TIES.

◆ ADDITIONAL LAP ALLOWED IF BEDROCK IS HIGHER ELEVATION.


▼ FORMLINER - SEE SHEET 3 FOR DETAILS.

BILL OF BARS

NOTE: THE FIRST OR FIRST TWO DIGITS OF THE BAR MARK SIGNIFIES THE BAR SIZE.


BAR MARK	COAT	NO. REQ'D.	LENGTH	BENT	BAR SERIES	LOCATION
A501		64	7'-7"	X		ABUT BODY STIRRUPS - U-BAR
A402		24	2'-11"	X		ABUT BODY TIE BARS
A503		11	31'-0"			ABUT BODY HORIZ. - F.F.
A504		14	20'-9"	X		ABUT BODY HORIZ. - B.F.
A405		18	3'-9"	X		ABUT. BODY TOP @ NOTCH VERT.
A406		2	26'-2"			ABUT. BODY TOP @ NOTCH HORIZ.
A407	X	12	7'-2"	X		WINGS 1 & 2 U-BAR
A408	X	30	9'-4"	X		WINGS 1 & 2 U-BAR - LOWER
A409	X	30	9'-4"	X		WINGS 1 & 2 U-BAR - UPPER
A510	X	14	14'-9"	X		WINGS 1 & 2 LOWER HORIZ - F.F.
A511	X	14	16'-5"	X		WINGS 1 & 2 LOWER HORIZ. - B.F.
A412	X	4	12'-4"			WINGS 1 & 2 UPPER HORIZ. E.F.
A413	X	4	10'-2"			WINGS 1 & 2 UPPER HORIZ. E.F.
A414	X	4	7'-8"			WINGS 1 & 2 UPPER HORIZ. E.F.
A415	X	4	5'-2"			WINGS 1 & 2 UPPER HORIZ. E.F.
A416	X	4	13'-6"	X		WINGS 1 & 2 UPPER DIAG. E.F.
A417	X	10	8'-2"	X		WINGS 1 & 2 TOP HORIZ. CORNER
A418	X	12	6'-3"	X		WINGS 1 & 2 TOP VERT. CORNER
A419	X	8	2'-6"			BODY - PIPE UNDERDRAIN OPENING

BENDING DIMENSIONS ARE OUT TO OUT OF BARS.




A501, A405, A407


A408, A409




A402, A504, A510, A511



A416




A417



A418


NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
STRUCTURE B-26-47			
DRAWN BY	CLP	PLANS CK'D	JMC
WEST ABUTMENT BILL OF BARS			
SHEET 7 OF 14		42	




ELEVATION

LOOKING DOWNSTATION

⚠ ELEVATION IS APPROXIMATE. CONSTRUCT ABUTMENT AND WINGS TO REACH SOLID ROCK, KEY IN A MIN. 6" INTO SOLID ROCK. BOTTOM OF ABUTMENT AND WINGS TO BE APPROXIMATELY LEVEL. MAX. ABUTMENT HEIGHT AT C/L OF TOWN PARK DRIVE TO BE 5'-9 1/4"



PLAN



BAR STEEL LAYOUT

NOTE: ABUTMENTS WITH SHALLOW FOOTINGS TO BE SUPPORTED BY SOUND ROCK WITH A REQUIRED FACTOR BEARING RESISTANCE OF 20,000 PSF.

A15 PIPE UNDERDRAIN WRAPPED (6-INCH). SLOPE 0.5%
MIN. TO SUITABLE DRAINAGE. RODENT SHIELD
REQUIRED. AN 8" DIA. HOLE IN ABUTMENT IS REQ'D.
LOCATE TO MISS. PEINE, STEEL.

A17 $\frac{1}{2}$ " FILLER: SEAL ALL EXPOSED HORIZ. & VERT. SURFACES OF $\frac{1}{2}$ " FILLER WITH NON-STAINING GRAY NON-BITUMINOUS JOINT SEALER. (1" DEEP AND HOLD $\frac{1}{6}$ " BELOW SURFACE OF CONCRETE). EXTEND SEALER 2" BELOW CHUTTER LINE AT INSIDE FACE.

A19 18" RUBBERIZED MEMBRANE WATERPROOFING.
SEAL ALL HORIZ. & VERT. JOINTS AT BACKFACE


■ APPROXIMATE POSITION OF THE 200 AND 1000

 **ALTERNATE THE POSITION OF THE SWING HOOKS AT EACH VERTICAL LAYER OF TIES.**

HIGHER ELEVATION.

▼ FORMLINER - SEE SHEET 3 FOR DETAILS.


NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
STRUCTURE B-26-47			
EAST ABUTMENT		DRAWN BY	PLANS CLP CK'D
		SHEET 8 OF 14 43	



⚠ ELEVATION IS APPROXIMATE. CONSTRUCT ABUTMENT AND WINGS TO REACH SOLID ROCK, KEY IN A MIN. 6" INTO SOLID ROCK. BOTTOM OF ABUTMENT AND WINGS TO BE APPROXIMATELY LEVEL. MAX. ABUTMENT HEIGHT AT C/L OF TOWN PARK DRIVE TO BE 5'-9 1/4".


WING 3 ELEVATION

SHOWING F.F. WING




WING 3 PLAN

SHOWING UPPER WING REINFORCEMENT



WING 3 PLAN

SHOWING LOWER WING REINFORCEMENT



FILL OVER EXCAVATED AREA WITH CONCRETE. FILL MATERIAL TO BE INCIDENTAL TO "EXCAVATION FOR STRUCTURES BRIDGES B-26-47"

SECTION THRU WING 3

NOTE:

ABUTMENTS WITH SHALLOW FOOTINGS TO BE SUPPORTED BY SOUND ROCK WITH A REQUIRED FACTOR BEARING RESISTANCE OF 20,000 PSF.

(A01) OPTIONAL CONST. JOINT: KEYWAY FORMED BY A BEVELED 2X6. PROVIDE 3/4" "V" GROOVE ON F.F. OF WINGWALL IF JOINT IS USED.

(A15) PIPE UNDERDRAIN WRAPPED (6-INCH). SLOPE 0.5% MIN. TO SUITABLE DRAINAGE. RODENT SHIELD REQUIRED.


(A17) 1/2" FILLER: SEAL ALL EXPOSED HORIZ. & VERT. SURFACES OF 1/2" FILLER WITH NON-STAINING GRAY NON-BITUMINOUS JOINT SEALER. (1" DEEP AND HOLD 1/2" BELOW SURFACE OF CONCRETE). EXTEND SEALER 3" BELOW GUTTER LINE AT INSIDE FACE.

(A19) 18" RUBBERIZED MEMBRANE WATERPROOFING, ONLY IF OPTIONAL CONSTRUCTION JOINT IS USED. COST INCIDENTAL TO BID ITEM "CONCRETE MASONRY STRUCTURES".

◆ ADDITIONAL LAP ALLOWED IF BEDROCK IS HIGHER ELEVATION.

▼ FORMLINER - SEE SHEET 3 FOR DETAILS.


NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
STRUCTURE B-26-47			
DRAWN BY CLP PLANS CK'D JMC			
EAST ABUTMENT	SHEET 9 OF 14		
WING 3 DETAILS	44		



WING 4 ELEVATION


SHOWING F.F. WING

△ ELEVATION IS APPROXIMATE. CONSTRUCT ABUTMENT AND WINGS TO REACH SOLID ROCK, KEY IN A MIN. 6" INTO SOLID ROCK. BOTTOM OF ABUTMENT AND WINGS TO BE APPROXIMATELY LEVEL. MAX. ABUTMENT HEIGHT AT C/L OF TOWN PARK DRIVE TO BE 5'-9 1/4".




WING 4 PLAN

SHOWING UPPER WING REINFORCEMENT



WING 4 PLAN

SHOWING LOWER WING REINFORCEMENT



SECTION THRU WING 4

FILL OVER EXCAVATED AREA WITH CONCRETE. FILL MATERIAL TO BE INCIDENTAL TO "EXCAVATION FOR STRUCTURES BRIDGES B-26-47"

NOTE:
ABUTMENTS WITH SHALLOW FOOTINGS TO BE SUPPORTED BY SOUND ROCK WITH A REQUIRED FACTOR BEARING RESISTANCE OF 20,000 PSF.

(A01) OPTIONAL CONST. JOINT: KEYWAY FORMED BY A BEVELED 2X6. PROVIDE 3/4" "V" GROOVE ON F.F. OF WINGWALL IF JOINT IS USED.

(A15) PIPE UNDERDRAIN WRAPPED (6-INCH). SLOPE 0.5% MIN. TO SUITABLE DRAINAGE. RODENT SHIELD REQUIRED.

(A17) 1/2" FILLER: SEAL ALL EXPOSED HORIZ. & VERT. SURFACES OF 1/2" FILLER WITH NON-STAINING GRAY NON-BITUMINOUS JOINT SEALER. (1" DEEP AND HOLD 1/2" BELOW SURFACE OF CONCRETE). EXTEND SEALER 3" BELOW GUTTER LINE AT INSIDE FACE.

(A19) 18" RUBBERIZED MEMBRANE WATERPROOFING, ONLY IF OPTIONAL CONSTRUCTION JOINT IS USED. COST INCIDENTAL TO BID ITEM "CONCRETE MASONRY STRUCTURES".

△ ADDITIONAL LAP ALLOWED IF BEDROCK IS HIGHER ELEVATION.

▼ FORMLINER - SEE SHEET 3 FOR DETAILS.

NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
STRUCTURE B-26-47			
DRAWN BY CLP PLANS CK'D JMC			
EAST ABUTMENT WING 4 DETAILS	SHEET 10 OF 14		45


BILL OF BARS

NOTE: THE FIRST OR FIRST TWO DIGITS OF THE BAR MARK SIGNIFIES THE BAR SIZE.


BAR MARK	COAT	NO. REQ'D.	LENGTH	BENT	BAR SERIES	LOCATION
B501	64	7'-7"	X			ABUT BODY STIRRUPS - U-BAR
B402	24	2'-11"	X			ABUT BODY TIE BARS
B503	11	31'-0"				ABUT BODY HORIZ. - F.F.
B504	14	20'-9"	X			ABUT BODY HORIZ. - B.F.
B405	18	3'-9"	X			ABUT. BODY TOP @ NOTCH VERT.
B406	2	26'-2"				ABUT. BODY TOP @ NOTCH HORIZ.
B407	X	10	9'-10"	X		WING 3 U-BAR - LOWER
B408	X	10	9'-10"	X		WING 3 U-BAR - UPPER
B509	X	7	8'-9"	X		WING 3 LOWER HORIZ. - F.F.
B510	X	7	10'-5"	X		WING 3 LOWER HORIZ. - B.F.
B411	X	6	7'-2"			WING 3 UPPER HORIZ. E.F.
B412	X	2	6'-6"			WING 3 UPPER HORIZ. E.F.
B413	X	2	7'-3"	X		WING 3 UPPER DIAG. E.F.
B414	X	5	8'-2"	X		WING 3 HORIZ. CORNER
B415	X	6	6'-3"	X		WING 3 TOP VERT. CORNER
B416	X	10	9'-10"	X		WING 4 U-BAR - LOWER
B417	X	10	9'-10"	X		WING 4 U-BAR - UPPER
B518	X	7	8'-9"	X		WING 4 LOWER HORIZ. - F.F.
B519	X	7	10'-5"	X		WING 4 LOWER HORIZ. - B.F.
B420	X	10	7'-2"			WING 4 UPPER HORIZ. E.F.
B421	X	5	8'-2"	X		WING 4 HORIZ. CORNER
B422	X	6	6'-3"	X		WING 4 TOP VERT. CORNER
B423	X	20	5'-0"			ABUTMENT VERT.
B424	X	8	2'-6"			BODY - PIPE UNDERDRAIN OPENING

BENDING DIMENSIONS ARE OUT TO OUT OF BARS.


★ LAP WITH B501 IF HEIGHT OF ABUTMENT EXCEEDS 5'. MAINTAIN 1'-4" MIN. LAP, BAR CAN BE CUT AS NECESSARY.




B504, B509, B510
B518, B519




B501, B405, B407
B408, B416, B417




B413



B414, B421



B415, B422



SECTION THRU BODY

NOTE:

ABUTMENTS WITH SHALLOW FOOTINGS TO BE SUPPORTED BY SOUND ROCK WITH A REQUIRED FACTOR BEARING RESISTANCE OF 20,000 PSF.

(A15) PIPE UNDERDRAIN WRAPPED (6-INCH). SLOPE 0.5% MIN. TO SUITABLE DRAINAGE. RODENT SHIELD REQUIRED. AN 8" DIA. HOLE IN WALL IS REQ'D. LOCATE TO MISS REINF. STEEL.


(A19) 18" RUBBERIZED MEMBRANE WATERPROOFING, ONLY IF OPTIONAL CONSTRUCTION JOINT IS USED. COST INCIDENTAL TO BID ITEM "CONCRETE MASONRY STRUCTURES".

ALTERNATE THE POSITION OF THE 90° AND 180° HOOKS AT EACH VERTICAL LAYER OF TIES.

ADDITIONAL LAP ALLOWED IF BEDROCK IS HIGHER ELEVATION.

FORMLINER - SEE SHEET 3 FOR DETAILS.

NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
STRUCTURE B-26-47			
DRAWN BY	CLP	PLANS CK'D	JMC
EAST ABUTMENT BILL OF BARS			
SHEET 11 OF 14		46	



TYPICAL SECTION THRU BRIDGE

TOP TRANSVERSE BARS IN SLAB SHALL BE SUPPORTED BY INDIVIDUAL BAR CHAIRS AT 3'-0" CENTERS EACH WAY. BOTTOM LONGITUDINAL BARS SHALL BE SUPPORTED BY CONTINUOUS BAR CHAIRS AT APPROXIMATELY 4'-0" CENTERS.

ALL SLAB THICKNESS DIMENSIONS ARE MINIMUM. ANY TOLERANCE NECESSARY TO CORRECT CONSTRUCTION DISCREPANCIES ARE TO BE PLUS (+).

* $\frac{3}{4}$ " V-GROOVE. EXTEND V-GROOVE TO 6" FROM F.F. OF ABUT.


V-GROOVES ARE REQUIRED.

BILL OF BARS

NOTE: THE FIRST OR FIRST TWO DIGITS OF THE BAR MARK SIGNIFIES THE BAR SIZE.

BAR MARK	COAT	NO. REQ'D.	LENGTH	BENT	BAR SERIES	LOCATION
S1101	X	58	43'-5"			SLAB LONG. BOT.
S502	X	87	26'-2"			SLAB TRANS. BOT.
S503	X	87	26'-2"			SLAB TRANS. TOP
S404	X	72	26'-3"			SLAB LONG. TOP
S505	X	54	8'-1"	X		SLAB @ ABUT. DIAPHRAGM STIRRUPS
S506	X	4	26'-2"			SLAB @ ABUT. DIAPHRAGM TRANS.
S407	X	54	3'-4"	X		SLAB @ ABUT. NOTCH
S408	X	4	26'-2"			SLAB @ ABUT. NOTCH
S609	X	40	11'-3"	X		SLAB @ RAIL POSTS
S610	X	64	6'-0"			SLAB @ INT. RAIL POSTS
S611	X	16	4'-8"	X		SLAB @ END RAIL POSTS

BENDING DIMENSIONS ARE OUT TO OUT OF BARS.



CAMBER AND SLAB THICKNESS DIAGRAM

CAMBER SHOWN IS BASED ON 3 TIMES DEAD LOAD DEFLECTIONS. CAMBER SPANS AS SHOWN TO PROVIDE FOR DEAD LOAD DEFLECTION AND FUTURE CREEP. CAMBER DOES NOT INCLUDE ALLOWANCE FOR FORM SETTLEMENT.

TO DETERMINE FALSEWORK ELEVATION AT EDGE OF SLAB, CROWN OR REFERENCE LINE FOLLOW THIS PROCEDURE:

TOP OF SLAB ELEVATION AT FINAL GRADE
 LESS SLAB THICKNESS
 PLUS CAMBER
 PLUS FORM SETTLEMENT/DEFLECTION DUE TO PLACEMENT OF SLAB CONCRETE (TO BE COMPUTED BY THE CONTRACTOR)
 EQUALS TOP OF SLAB FALSEWORK ELEVATION

TOP OF SLAB ELEVATIONS



LOCATION	C/L W. ABUT.	$\frac{1}{10}$ PT.	$\frac{2}{10}$ PT.	$\frac{3}{10}$ PT.	$\frac{4}{10}$ PT.	$\frac{5}{10}$ PT.	$\frac{6}{10}$ PT.	$\frac{7}{10}$ PT.	$\frac{8}{10}$ PT.	$\frac{9}{10}$ PT.	C/L E. ABUT.
N. EDGE OF SLAB	1212.20	1212.36	1212.53	1212.69	1212.85	1213.02	1213.18	1213.34	1213.51	1213.67	1213.83
C/L OF TOWN PARK DRIVE	1212.46	1212.63	1212.79	1212.95	1213.12	1213.28	1213.45	1213.61	1213.77	1213.94	1214.10
S. EDGE OF SLAB	1212.20	1212.36	1212.53	1212.69	1212.85	1213.02	1213.18	1213.34	1213.51	1213.67	1213.83

SURVEY TOP OF SLAB ELEVATIONS

	ABUTMENT	5/10 PT.	ABUTMENT
N. EDGE OF SLAB			
C/L OF TOWN PARK DRIVE			
S. EDGE OF SLAB			

PRIOR TO RELEASING SLAB FORMWORK, TAKE TOP OF SLAB ELEVATIONS AT THE C/L OF SUBSTRUCTURES, AND AT 5/10 PTS. TO VERIFY CAMBER. TAKE ELEVATIONS ALONG EDGE OF SLAB AND C/L. RECORD ELEVATIONS IN THE TABLE ABOVE FOR THE "AS BUILT" PLANS.

NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
STRUCTURE B-26-47			
DRAWN BY	CLP	PLANS CK'D	JMC
SUPERSTRUCTURE		SHEET 12 OF 14	
		47	



NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
STRUCTURE B-26-47			
		DRAWN BY	PLANS CLP CK'D JMC
SUPERSTRUCTURE PLAN		SHEET 13 OF 14 48	

TOWN PARK DRIVE COMPUTER EARTHWORK

Station	Distance	Area (SF)			Incremental Vol (CY) (Unadjusted)			Cumulative Vol (CY)		Mass Ordinate	
		Cut	Unuseable Pavement Material	Fill	Salvaged /			Cut	Fill		
					Cut	Unuseable Pavement Material	Fill				
					Note 1	Note 4	Note 2	Note 5		Note 3	
8+71	--	15.9	0.0	0.0							
8+75	4.25	17.2	0.0	0.0	3	0	0	3	0	3	
9+00	25.00	20.9	0.0	0.0	18	0	0	20	0	20	
9+21	20.75	16.7	0.0	0.0	14	0	0	35	0	35	
9+25	4.25	15.7	0.0	0.0	3	0	0	37	0	37	
9+50	25.00	7.1	0.0	3.4	11	0	2	48	2	46	
9+60.75	10.75	1.0	0.0	41.2	2	0	9	49	14	36	
9+70.75	10.00	0.3	0.0	8.2	0	0	9	50	25	24	
BRIDGE	--	--	--	--	--	--	--	--	--	--	
10+21.25	--	3	0.0	8	--	--	--	--	--	--	
10+31.25	10.00	40	0.0	10	8	0	3	58	30	28	
10+50	18.75	45.5	0.0	0.0	30	0	4	88	35	53	
10+71	21.25	25.0	3.5	0.0	65	6	5	146	41	105	
10+75	3.75	24.3	3.3	0.0	3	0	0	149	41	108	
11+00	25.00	24.5	3.0	0.0	23	3	0	169	41	128	
11+21	21.25	26.5	0.0	0.0	20	1	0	188	41	147	
					199	11	32				


1) Excavation Common is the Cut. Item number 205.0100.

2) Expanded Fill. Factor = 1.30; Expanded Fill = Unexpanded Fill * Fill Factor

3) The Mass Ordinate + or - Qty calculated for the Division. Plus quantity indicates an excess of material on the project.

4) All quantities shown in CY.

5) Salvaged/unuseable pavement material



PROJECT NO: 9826-00-70

HWY: TOWN PARK DRIVE

COUNTY: IRON

CROSS SECTIONS: TOWN PARK DRIVE

SHEET

1

FILE NAME : I:\42\42-1435.00 - IRON CO, TN KIMBALL, TOWN PARK DRIVE\C3D\DSGN\CRDR\CRDR_TOWN PARK DRIVE.DWG
LAYOUT NAME - 01


PLOT DATE : 10/6/2025 11:04 AM

PLOT BY : PEPIN, STEFFAN


PLOT NAME :


PLOT SCALE : 1 IN:10 FT HORZ. / 1 IN:10 FT VERT.


1/ISDOT/CADD\$ SHEET 49




STRUCTURE B-26-0047









Wisconsin Department of Transportation

Dedicated people creating transportation solutions
through innovation and exceptional service.

<http://www.dot.wisconsin.gov>