

MARCH 2026

ORDER OF SHEETS

Section No. 1 Title
 Section No. 2 Typical Sections and Details
 Section No. 3 Estimate of Quantities
 Section No. 3 Miscellaneous Quantities
 Section No. 4 Right of Way Plat
 Section No. 5 Plan and Profile
 Section No. 6 Standard Detail Drawings
 Section No. 7 Sign Plates
 Section No. 8 Structure Plans
 Section No. 9 Computer Earthwork Data
 Section No. 9 Cross Sections

TOTAL SHEETS = 48



36

DESIGN DESIGNATION 9833-03-02
 A.A.D.T. (2026) = <100
 A.A.D.T. (2046) = <100
 D.H.V. = 10
 D.D. = 50/50
 T. = 5%
 DESIGN SPEED = 55 MPH
 ESALS = 36,500

CONVENTIONAL SYMBOLS

PLAN	PROFILE
CORPORATE LIMITS	GRADE LINE
PROPERTY LINE	ORIGINAL GROUND
LOT LINE	MARSH OR ROCK PROFILE (To be noted as such)
LIMITED HIGHWAY EASEMENT	SPECIAL DITCH
EXISTING RIGHT OF WAY	GRADE ELEVATION
PROPOSED OR NEW R/W LINE	CULVERT (Profile View)
SLOPE INTERCEPT	
REFERENCE LINE	
EXISTING CULVERT	ELECTRIC
PROPOSED CULVERT (Box or Pipe)	FIBER OPTIC
COMBUSTIBLE FLUIDS	GAS
MARSH AREA	SANITARY SEWER
WOODED OR SHRUB AREA	STORM SEWER
	TELEPHONE
	WATER
	UTILITY PEDESTAL
	POWER POLE
	TELEPHONE POLE

STATE OF WISCONSIN
 DEPARTMENT OF TRANSPORTATION

PLAN OF PROPOSED IMPROVEMENT

TACKLEY, RANGE LINE ROAD

BLACK BROOK BRIDGE B-34-0066

LOC STR
LANGLADE COUNTY

STATE PROJECT NUMBER
9833-03-72

BEGIN PROJECT
 STA 9+28.75
 Y = 355527.25
 X = 589112.60

STRUCTURE B-34-0066
 STA 10+00

END PROJECT
 STA 10+71.25
 Y = 355532.90
 X = 589254.99



SCALE 0 1 MI

TOTAL NET LENGTH OF CENTERLINE = 0.027 MI

HORIZONTAL POSITIONS SHOWN ON THIS PLAN ARE WISCONSIN COORDINATE REFERENCE SYSTEM (WISCRS), LANGLADE COUNTY, NAD83 (2011), IN U.S. SURVEY FEET. POSITIONS SHOWN ARE GRID COORDINATES, GRID BEARINGS, AND GRID DISTANCES. GRID DISTANCES ARE THE SAME AS GROUND DISTANCES.


ELEVATIONS ARE REFERENCED TO NAVD 88 (2012). GPS DERIVED ELEVATIONS ARE BASED ON GEOD 18.

STATE PROJECT	FEDERAL PROJECT	
	PROJECT	CONTRACT
9833-03-72		

ACCEPTED FOR
 Town _____ of Ackley
 10/20/25
 (Date) (Signature)

Rick Bina
 (Town Chairman)

ORIGINAL PLANS PREPARED BY
AYRES



STATE OF WISCONSIN
 DEPARTMENT OF TRANSPORTATION

PREPARED BY
 Surveyor AYRES ASSOCIATES INC
 Designer AYRES ASSOCIATES INC
 Project Manager NATHAN WAITE
 Regional Examiner NC REGION
 Regional Supervisor DAN ERVA, PE

APPROVED FOR THE DEPARTMENT
 DATE: 10/29/2025
 (Signature)

UTILITIES CONTACTS

WISCONSIN PUBLIC SERVICE (WPS)
ELECTRICITY
DON LUTZOW
P.O. BOX 1166
WAUSAU, WI 54402-1166
PHONE: 715-848-7487
CELL: 507-848-4211
EMAIL: donald.lutzow@wisconsinpublicservice.com

WISCONSIN DNR LIAISON

WENDY HENNIGES
NORTH CENTRAL REGION
107 SUTLIFF AVENUE
RHINELANDER, WI 54501
PHONE: 715-365-8916
EMAIL: wendy.henniges@wisconsin.gov

LANGLADE COUNTY

BRIAN BRAUN
HIGHWAY COMMISSIONER
1521 ARCTIC STREET
ANTIGO, WI 54409
PHONE: 715-627-6272
EMAIL: bbraun@co.langlade.wi.us

TOWN OF ACKLEY

RICK BINA, CHAIRMAN
TOWN OF ACKLEY
W11529 RANGE LINE ROAD
ANTIGO, WI 54409
PHONE: 715-216-0155
EMAIL: ackleychairman@gmail.com

DESIGN PROJECT MANAGER

NATHAN WAITE
NORTH CENTRAL REGION
510 HANSON LAKE ROAD
RHINELANDER, WI 54501
PHONE: 715-365-5762
EMAIL: Nathaniel.Waite@dot.wi.gov

DESIGN PROJECT LEADER

STEFFANIE PEPIN, PE
AYRES ASSOCIATES
700 PILGRIM WAY, SUITE 180
GREEN BAY, WI 54304
PHONE: 906-421-2346
EMAIL: pepins@AyresAssociates.com

GENERAL NOTES

THE LOCATIONS OF EXISTING AND PROPOSED UTILITY INSTALLATIONS AS SHOWN ON THE PLANS ARE APPROXIMATE. THERE MAY BE OTHER UTILITY INSTALLATIONS WITHIN THE PROJECT AREA THAT ARE NOT SHOWN.

FILL EXPANSION FACTOR IS 30%

NO TREES OR SHRUBS ARE TO BE REMOVED WITHOUT THE APPROVAL OF THE ENGINEER.

RIGHT OF WAY INFORMATION SHOWN ON THE PLANS IS APPROXIMATE.

EROSION CONTROL FEATURES AS SHOWN IN THE PLANS ARE AT APPROXIMATE LOCATIONS. EXACT LOCATIONS WILL BE DETERMINED BY THE CONTRACTOR'S EROSION CONTROL IMPLEMENTATION PLAN (ECIP) AND APPROVED BY THE ENGINEER. MAINTAIN EROSION CONTROL MEASURES UNTIL SUCH A TIME AS THE ENGINEER DETERMINES THE MEASURE IS NO LONGER NECESSARY.

SEED MIXTURE NO. 20 AND SEEDING TEMPORARY SHALL BE USED IN THE PROJECT AND SHALL BE PLACED AS SHOWN IN THE PLANS AND/OR DIRECTED BY THE ENGINEER.

THE PROPOSED SHOULDER WIDTH SHOWN IN THE TYPICAL SECTIONS ARE MINIMUM WIDTH. PERPETUATE EXISTING SHOULDERS THAT ARE WIDER THAN WHAT IS SHOWN IN THE TYPICAL SECTIONS.

TRAFFIC CONTROL DEVICES SHALL BE ADJUSTED TO FIT FIELD CONDITIONS AS DIRECTED BY THE ENGINEER.

DO NOT DRIVE OR STORE EQUIPMENT, OR STORE CONSTRUCTION MATERIALS IN ENVIRONMENTALLY SENSITIVE AREAS, WETLANDS OR WATERWAYS.

THE DEPARTMENT OF TRANSPORTATION WILL FURNISH THE CONTRACTOR WITH A MONUMENT TO BE INSTALLED BY THE CONTRACTOR AS DIRECTED BY THE ENGINEER.

DISTURBED AREAS WITHIN THE RIGHT OF WAY, EXCEPT THE AREAS WITHIN THE FINISHED SUBGRADE SHOULDER POINTS ARE TO BE SEDED AND EITHER MULCHED OR EROSION MATTED AS DIRECTED BY THE ENGINEER.

ASPHALTIC SURFACE WAS DESIGNED WITH A 2" UPPER LAYER AND A 2" LOWER LAYER. ASPHALTIC SURFACE SHALL USE 12.5 mm NOMINAL AGGREGATE SIZE.

SAWCUTS, AS SHOWN ON THE PLANS, ARE SUGGESTED LOCATIONS AND MAY BE ADJUSTED AT THE DISCRETION OF THE ENGINEER TO BETTER SUIT FIELD CONDITIONS.

RUNOFF COEFFICIENT TABLE

LAND USE:	HYDROLOGIC SOIL GROUP											
	A			B			C			D		
	SLOPE RANGE (PERCENT)		SLOPE RANGE (PERCENT)	SLOPE RANGE (PERCENT)		SLOPE RANGE (PERCENT)	SLOPE RANGE (PERCENT)		SLOPE RANGE (PERCENT)	SLOPE RANGE (PERCENT)		SLOPE RANGE (PERCENT)
0-2	2-6	6 & OVER	0-2	2-6	6 & OVER	0-2	2-6	6 & OVER	0-2	2-6	6 & OVER	
ROW CROPS:	.08	.16	.22	.12	.20	.27	.15	.24	.33	.19	.28	.38
	.22	.30	.38	.26	.34	.44	.30	.37	.50	.34	.41	.56
MEDIAN STRIPTURF:	.19	.20	.24	.19	.22	.26	.20	.23	.30	.20	.25	.30
	.24	.26	.30	.25	.28	.33	.26	.30	.37	.27	.32	.40
SIDE SLOPETURF:			.25			.27			.28			.30
			.32			.34			.36			.38
PAVEMENT:												
ASPHALT:												.70 - .95
CONCRETE:												.80 - .95
BRICK:												.70 - .80
DRIVES, WALKS:												.75 - .85
ROOFS:												.75 - .95
GRAVEL ROADS, SHOULDERS:												.40 - .60

TOTAL PROJECT AREA = 0.216 ACRES

TOTAL AREA EXPECTED TO BE DISTURBED BY CONSTRUCTION ACTIVITIES = 0.146 ACRES

PROJECT NO: 9833-03-72



HWY: RANGE LINE ROAD

COUNTY: LANGLADE

GENERAL NOTES


SHEET

E



2

2



PROJECT NO: 9833-03-72


HWY: RANGE LINE ROAD

COUNTY: LANGLADE

ALIGNMENT CONTROLS

SHEET

E



NOTES:
NO DISTURBANCE OR TOPSOIL STOCKPILING IS
ALLOWED OUTSIDE OF THE SLOPE INTERCEPTS.

WETLANDS EXIST IN THE PROJECT AREA.

MULCH TO BE PLACED ON SIDE SLOPES NOT PROTECTED
BY EROSION MAT.


MODIFIED TURBIDITY BARRIER INSTALLATION TO BE USED AROUND
THE EXISTING STRUCTURE AND TEMPORARILY ACROSS STREAM.
MODIFIED TURBIDITY BARRIER INSTALLATION MUST RESULT IN A
COMPLETE SEALING OFF OF THE WORK AREA (COMPLETELY STILL
WATER INSIDE THE TURBIDITY BARRIER - NO SIGNS OF FLOW) AND
SAND BAGS SHOULD BE PLACED IN A CONTINUAL FASHION, END TO
END, ALONG THE BOTTOM FLAP AND THE ENDS SHOULD BE
SECURED TIGHTLY AND ALSO SEALED WITH SAND BAGS.

* TEMPORARY TURBIDITY BARRIER (STAGE 1) FOR REMOVAL OF PIPE
CULVERTS.

IF, DURING CONSTRUCTION, TURBIDITY BARRIER DOES NOT
ADEQUATELY CONTAIN SEDIMENT, IMPERMEABLE BARRIERS TO
DIVERT FLOW MUST BE EMPLOYED.

LEGEND

- EROSION MAT CLASS II (TYPE C)
- SILT FENCE
- RIP RAP
- HIGHWATER EL. 1472.12
- SLOPE INTERCEPT
- TURBIDITY BARRIER
- TEMPORARY DITCH CHECK (UNDISTRIBUTED)
- SAND BAGS



Estimate Of Quantities

9833-03-72

Line	Item	Item Description	Unit	Total	Qty
0002	203.0220	Removing Structure (structure) 01. P-34-917	EACH	1.000	1.000
0004	205.0100	Excavation Common	CY	110.000	110.000
0006	206.1001	Excavation for Structures Bridges (structure) 01. B-34-66	EACH	1.000	1.000
0008	210.1500	Backfill Structure Type A	TON	230.000	230.000
0010	213.0100	Finishing Roadway (project) 01. 9833-03-72	EACH	1.000	1.000
0012	305.0110	Base Aggregate Dense 3/4-Inch	TON	20.000	20.000
0014	305.0120	Base Aggregate Dense 1 1/4-Inch	TON	170.000	170.000
0016	455.0605	Tack Coat	GAL	20.000	20.000
0018	465.0105	Asphaltic Surface	TON	70.000	70.000
0020	502.0100	Concrete Masonry Bridges	CY	140.000	140.000
0022	502.3200	Protective Surface Treatment	SY	177.000	177.000
0024	505.0400	Bar Steel Reinforcement HS Structures	LB	3,260.000	3,260.000
0026	505.0600	Bar Steel Reinforcement HS Coated Structures	LB	18,910.000	18,910.000
0028	513.4061	Railing Tubular Type M	LF	131.000	131.000
0030	516.0500	Rubberized Membrane Waterproofing	SY	18.000	18.000
0032	550.1100	Piling Steel HP 10-Inch X 42 Lb	LF	280.000	280.000
0034	606.0300	Riprap Heavy	CY	105.000	105.000
0036	612.0406	Pipe Underdrain Wrapped 6-Inch	LF	140.000	140.000
0038	618.0100	Maintenance and Repair of Haul Roads (project) 01. 9833-03-72	EACH	1.000	1.000
0040	619.1000	Mobilization	EACH	1.000	1.000
0042	624.0100	Water	MGAL	6.000	6.000
0044	625.0100	Topsoil	SY	145.000	145.000
0046	627.0200	Mulching	SY	210.000	210.000
0048	628.1504	Silt Fence	LF	245.000	245.000
0050	628.1520	Silt Fence Maintenance	LF	490.000	490.000
0052	628.1905	Mobilizations Erosion Control	EACH	4.000	4.000
0054	628.1910	Mobilizations Emergency Erosion Control	EACH	4.000	4.000
0056	628.2027	Erosion Mat Class II Type C	SY	50.000	50.000
0058	628.6005	Turbidity Barriers	SY	175.000	175.000
0060	628.7504	Temporary Ditch Checks	LF	50.000	50.000
0062	629.0210	Fertilizer Type B	CWT	0.300	0.300
0064	630.0120	Seeding Mixture No. 20	LB	11.000	11.000
0066	630.0200	Seeding Temporary	LB	8.000	8.000
0068	630.0500	Seed Water	MGAL	5.000	5.000
0070	634.0614	Posts Wood 4x6-Inch X 14-FT	EACH	4.000	4.000
0072	637.2230	Signs Type II Reflective F	SF	12.000	12.000
0074	638.2602	Removing Signs Type II	EACH	6.000	6.000
0076	638.3000	Removing Small Sign Supports	EACH	6.000	6.000
0078	642.5001	Field Office Type B	EACH	1.000	1.000
0080	643.0420	Traffic Control Barricades Type III	DAY	1,450.000	1,450.000
0082	643.0705	Traffic Control Warning Lights Type A	DAY	2,255.000	2,255.000
0084	643.0900	Traffic Control Signs	DAY	965.000	965.000
0086	643.5000	Traffic Control	EACH	1.000	1.000
0088	645.0111	Geotextile Type DF Schedule A	SY	50.000	50.000
0090	645.0120	Geotextile Type HR	SY	210.000	210.000
0092	650.4500	Construction Staking Subgrade	LF	100.000	100.000
0094	650.5000	Construction Staking Base	LF	100.000	100.000
0096	650.6501	Construction Staking Structure Layout (structure) 01. B-34-66	EACH	1.000	1.000
0098	650.9911	Construction Staking Supplemental Control (project) 01. 9833-03-72	EACH	1.000	1.000

Estimate Of Quantities

9833-03-72

Line	Item	Item Description	Unit	Total	Qty
0100	650.9920	Construction Staking Slope Stakes	LF	100.000	100.000
0102	690.0150	Sawing Asphalt	LF	43.000	43.000
0104	715.0502	Incentive Strength Concrete Structures	DOL	840.000	840.000

RANGE LINE ROAD EARTHWORK SUMMARY

From/To Station	Location	Excavation Common (1)	Salvaged / Unuseable Pavement Material (5)	Unexpanded Fill	Expanded Fill (2)	Mass Ordinate +/- (3)	Waste
		205.0100			Factor 1.30		
9+28.75 -9+78.75	RANGE LINE ROAD	53	11	4	5	37	37
10+21.25 -10+71.25	RANGE LINE ROAD	57	8	4	5	44	44
TOTAL		110	19	8	10		

FINISHING ROADWAY

213.0100.01	FINISHING ROADWAY
(PROJECT) (01. 9833-03-72)	
LOCATION	EACH
9833-03-72	1

1) Excavation Common is the Cut. Item number 205.0100.

2) Expanded Fill. Factor = 1.30; Expanded Fill = Unexpanded Fill * Fill Factor

3) The Mass Ordinate + or - Qty calculated for the Division. Plus quantity indicates an excess of material on the project.

4) All quantities shown in CY.

5) Salvaged/unuseable pavement material

BASE AGGREGATE DENSE

		305.0110	305.0120		
STATION	TO	STATION	LOCATION	TON	TON
9+28.75	-	9+78.75	RANGE LINE ROAD	10	85
10+21.25	-	10+71.25	RANGE LINE ROAD	10	85
TOTAL 0010		20	170		

ASPHALTIC SURFACE

		455.0605	465.0105		
STATION	TO	STATION	LOCATION	TACK COAT	ASPHALTIC
9+28.75	-	9+78.75	RANGE LINE ROAD	10	35
10+21.25	-	10+71.25	RANGE LINE ROAD	10	35
TOTAL 0010		20	70		

MAINTENANCE AND REPAIR OF HAUL ROADS

618.0100.01	
MAINTENANCE AND REPAIR	
OF HAUL ROADS (PROJECT)	
(01. 9833-03-72)	
CATEGORY	LOCATION
0030	EACH
PROJECT LIMITS	1
TOTAL 0030	1

MOBILIZATION

619.1000	
MOBILIZATION	
LOCATION	EACH
PROJECT LIMITS	1
TOTAL 0010	1

WATER

624.0100	
WATER	
LOCATION	MGAL
COMPACTI	3
DUST CONTROL	3
TOTAL 0010	6

ALL ITEMS ON THIS SHEET
ARE CATEGORY 0010
UNLESS OTHERWISE NOTED

3

3

EROSION CONTROL ITEMS

STATION	TO	STATION	EROSION CONTROL STAGE	LOCATION	SILT FENCE LF	MAINTENANCE LF	628.1520 SILT FENCE	628.2027 EROSION MAT CLASS II TYPE C	628.6005 TURBIDITY BARRIERS	628.7504 TEMPORARY DITCH CHECKS
10+21.25	-	10+71.25	1	RANGE LINE ROAD	--	--	--	40	--	
9+28.75	-	9+78.75	2	RANGE LINE ROAD	95	190	20	75	--	
10+21.25	-	10+71.25	2	RANGE LINE ROAD	100	200	20	55	--	
				UNDISTRIBUTED	50	100	10	45	50	
TOTAL 0010					245	490	50	175	50	

MOBILIZATIONS EROSION CONTROL

LOCATION	628.1905 MOBILIZATIONS EROSION CONTROL EACH	628.1910 MOBILIZATIONS EMERGENCY EROSION CONTROL EACH
PROJECT LIMITS	4	4
TOTAL 0010	4	4

RESTORATION ITEMS

STATION	TO	STATION	LOCATION	TOPSOIL SY	MULCHING SY	FERTILIZER TYPE B CWT	630.0120 SEEDING MIXTURE NO. 20 LB	630.0200 SEEDING TEMPORARY LB	630.0500 SEED WATER MGAL
9+28.75	-	9+78.75	RANGE LINE ROAD	55	80	0.1	4	3	2
10+21.25	-	10+71.25	RANGE LINE ROAD	60	85	0.1	5	3	2
			UNDISTRIBUTED	30	45	0.1	2	2	1
TOTAL 0010				145	210	0.3	11	8	5

SIGNS TYPE II

STATION	LOCATION	SIGN CODE	SIGN SIZE (INCHES)	634.0614 POSTS WOOD 4X6- INCH X 14-FT EACH	637.2230 SIGNS TYPE II REFLECTIVE F SF	638.2602 REMOVING SIGNS TYPE II EACH	638.3000 REMOVING SMALL SIGN SUPPORTS EACH	REMARKS	LOCATION	EACH
9+61	RT	R12-1	--	--	--	1	1	WEIGHT LIMIT 16 TONS	PROJECT LIMITS	1
9+68	LT	W5-52L	12x36	1	3	--	--	OBJECT MARKER		
9+68	RT	W5-52R	12x36	1	3	--	--	OBJECT MARKER	TOTAL 0010	1
9+73	LT	W5-52L	--	--	--	1	1	OBJECT MARKER		
9+74	RT	W5-52R	--	--	--	1	1	OBJECT MARKER		
10+29	RT	W5-52R	--	--	--	1	1	OBJECT MARKER		
10+30	LT	W5-52L	--	--	--	1	1	OBJECT MARKER		
10+32	LT	W5-52L	12x36	1	3	--	--	OBJECT MARKER		
10+32	RT	W5-52R	12x36	1	3	--	--	OBJECT MARKER		
10+43	LT	R12-1	--	--	--	1	1	WEIGHT LIMIT 16 TONS		
TOTAL 0010				4	12	6	6			

ALL ITEMS ON THIS SHEET
ARE CATEGORY 0010
UNLESS OTHERWISE NOTED

3

3

<u>TRAFFIC CONTROL</u>										<u>CONSTRUCTION STAKING</u>						
LOCATION	DURATION	TRAFFIC CONTROL	643.0420	643.0705	643.0900	643.5000	CONSTRUCTION STAKING	650.4500	CONSTRUCTION STAKING	650.5000	CONSTRUCTION STAKING	650.9920	CONSTRUCTION STAKING	650.9920	CONSTRUCTION STAKING	650.9920
			TYPE	BARRICADES	WARNING LIGHTS	TRAFFIC CONTROL			SIGNS	TRAFFIC CONTROL	STAKE SUBGRADE		STAKING BASE	STAKING SLOPE	STAKES	
LOCATION	DURATION	TRAFFIC CONTROL	III	TRAFFIC CONTROL	TYPE A	TRAFFIC CONTROL	SIGNS	TRAFFIC CONTROL	STATION	TO	STATION	LOCATION	LF	LF	LF	LF
LOCATION	DURATION	TRAFFIC CONTROL	DAY	TRAFFIC CONTROL	DAY	TRAFFIC CONTROL	DAY	TRAFFIC CONTROL	STATION	TO	STATION	LOCATION	LF	LF	LF	LF
PER SDD 15C02	70	18	1,260	28	1,960	12	840	--	9+28.75	-	9+78.75	RANGE LINE ROAD	50	50	50	50
UNDISTRIBUTED	--	--	190	--	295	--	125	1	10+21.25	-	10+71.25	RANGE LINE ROAD	50	50	50	50
TOTAL 0010			1,450		2,255		965	1				TOTAL 0010	100	100	100	100

CONSTRUCTION STAKING STRUCTURE LAYOUT

CATEGORY	STATION	LOCATION	650.6501.01
			CONSTRUCTION STAKING
		STRUCTURE LAYOUT	
		(STRUCTURE) (01. B-34-0066)	
0020	10+00	MAINLINE	1
TOTAL 0020			1



CONSTRUCTION STAKING SUPPLEMENTAL CONTROL

PROJECT	650.9911.01
	CONSTRUCTION STAKING
	SUPPLEMENTAL CONTROL (PROJECT)
	(01. 9833-03-72)
9833-03-72	1
TOTAL 0010	1

SAWING ASPHALT

STATION	LOCATION	690.0150
		SAWING ASPHALT
9+28.75	MAINLINE	21
10+71.25	MAINLINE	22
TOTAL 0010		43


ALL ITEMS ON THIS SHEET
ARE CATEGORY 0010
UNLESS OTHERWISE NOTED




PROJECT NO: 9833-03-72 HWY: RANGE LINE ROAD COUNTY: LANGLADE PLAN AND PROFILE: SHEET E

Standard Detail Drawing List


08E08-03	TYPI CAL I NSTALLATI ONS OF EROSI ON BALES / TEMPORARY DITCH CHECKS
08E09-06	SI LT FENCE
08E11-02	TURBI DI TY BARRI ER
12A03-10	NAME PLATE (STRUCTURES)
13C19-03	HMA LONGI TUDI NAL JOI NTS
15C02-09A	BARRI CADES AND SIGNS FOR MAI NLINE CLOSURES
15C02-09B	BARRI CADES AND SIGNS FOR VARIOUS CLOSURES
15C06-12	SIGNING & MARKING FOR TWO LANE BRIDGES
15C11-10B	CHANNELIZING DEVICES DRUMS, CONES, BARRI CADES AND VERTICAL PANELS



SECTION A-A



PLAN VIEW




FRONT ELEVATION

TEMPORARY DITCH CHECK USING EROSION BALES ①

GENERAL NOTES


DETAILS OF CONSTRUCTION, MATERIALS AND WORKMANSHIP NOT SHOWN ON THIS DRAWING SHALL CONFORM TO THE PERTINENT REQUIREMENTS OF THE STANDARD SPECIFICATIONS AND THE APPLICABLE SPECIAL PROVISIONS.

① TEMPORARY DITCH CHECKS EITHER EROSION BALES OR MANUFACTURED SHALL BE PAID FOR UNDER THE BID ITEM OF TEMPORARY DITCH CHECK. THE DEPARTMENT WILL NOT PAY FOR TEMPORARY DITCH CHECKS CONSTRUCTED OF A SINGLE ROW OF EROSION BALES.




PLAN VIEW

WHEN ALTERING THE DIRECTION OF FLOW



PLAN VIEW



FRONT ELEVATION


WHEN EXISTING GROUND SLOPES AWAY FROM FILL SLOPE

EROSION BALES FOR SHEET FLOW


TYPICAL INSTALLATIONS OF EROSION BALES / TEMPORARY DITCH CHECKS

STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION


APPROVED
6/04/02 /S/ Beth Cannestra
DATE CHIEF ROADWAY DEVELOPMENT ENGINEER
FHWA




PLAN VIEW
TYPICAL APPLICATION OF SILT FENCE



SILT FENCE AT MEDIAN SURFACE DRAINS



SILT FENCE




JOINING TWO LENGTHS OF SILT FENCE^⑤


GENERAL NOTES

DETAILS OF CONSTRUCTION NOT SHOWN ON THIS DRAWING SHALL CONFORM TO THE PERTINENT REQUIREMENTS OF THE STANDARD SPECIFICATIONS AND APPLICABLE SPECIAL PROVISIONS.

- ① HORIZONTAL BRACE REQUIRED WITH 2" X 4" WOODEN FRAME OR EQUIVALENT AT TOP OF POSTS.
- ② FOR MANUAL INSTALLATIONS THE TRENCH SHALL BE A MINIMUM OF 4" WIDE & 6" DEEP TO BURY AND ANCHOR THE GEOTEXTILE FABRIC. FOLD MATERIAL TO FIT TRENCH AND BACKFILL & COMPACT TRENCH WITH EXCAVATED SOIL.
- ③ WOOD POSTS SHALL BE A MINIMUM SIZE OF 1/8" X 1/8" OF OAK OR HICKORY.
- ④ SILT FENCE TO EXTEND ACROSS THE TOP OF THE PIPE.
- ⑤ CONSTRUCT SILT FENCE FROM A CONTINUOUS ROLL IF POSSIBLE BY CUTTING LENGTHS TO AVOID JOINTS. IF A JOINT IS NECESSARY USE ONE OF THE FOLLOWING TWO METHODS; A) OVERLAP THE END POSTS AND TWIST, OR ROTATE, AT LEAST 180 DEGREES, B) HOOK THE END OF EACH SILT FENCE LENGTH.




TRENCH DETAIL




SILT FENCE TIE BACK
(WHEN REQUIRED BY THE ENGINEER)


SILT FENCE	
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION	
APPROVED 4-29-05 DATE	/S/ Beth Cannestra CHIEF ROADWAY DEVELOPMENT ENGINEER FHWA




SECTION B - B

**TURBIDITY BARRIER - FLOAT ALTERNATIVE
CAUTION - SEE NOTE 6**


SECTION A - A

TURBIDITY BARRIER - STANDARD POST INSTALLATION
TURBIDITY BARRIER PLACEMENT DETAILS


PLAN VIEW




PLAN VIEW

GENERAL NOTES


DETAILS OF CONSTRUCTION, MATERIALS AND WORKMANSHIP NOT SHOWN ON THIS DRAWING SHALL CONFORM TO THE PERTINENT REQUIREMENTS OF THE STANDARD SPECIFICATIONS AND THE APPLICABLE SPECIAL PROVISIONS.

TURBIDITY BARRIER MAY BE REMOVED AT THE ENGINEERS DISCRETION, WHEN PERMANENT EROSION CONTROL MEASURES HAVE BEEN ESTABLISHED.

- ① DRIVEN STEEL POSTS, PIPES, OR CHANNELS. LENGTH SHALL BE SUFFICIENT TO SECURELY SUPPORT BARRIER AT HIGH WATER ELEVATIONS.
- ② SAND BAGS TO BE USED AS ADDITIONAL BALLAST WHEN ORDERED BY THE ENGINEER TO MEET ADVERSE FIELD CONDITIONS. SPACE AS APPROPRIATE FOR SITE CONDITIONS.
- ③ WHEN BARRIER HEIGHT "H" EXCEEDS 8 FEET, POST SPACING MAY NEED TO BE DECREASED.
- ④ IN WATERWAYS SUBJECT TO FLUCTUATING WATER ELEVATIONS, PROVISIONS SHOULD BE MADE TO ALLOW THE WATER TO EQUALIZE ON EACH SIDE OF THE BARRIER. THIS MAY BE ACCOMPLISHED BY LEAVING A PORTION OF THE BARRIER OPEN ON THE UPSTREAM END.
- ⑤ ESTIMATED HIGH WATER ELEVATION DURING CONSTRUCTION PERIOD. MINIMUM BARRIER HEIGHT SHALL BE 2' GREATER THAN EITHER THE Q2 ELEVATION OR THE ESTIMATED HIGH WATER ELEVATION DURING CONSTRUCTION, WHICHEVER IS GREATER.
- ⑥ FLOAT ALTERNATIVE WILL ONLY BE ALLOWED WITH WRITTEN APPROVAL OF THE ENGINEER, AND IS MEANT FOR LOCATIONS WHERE BEDROCK PREVENTS THE INSTALLATION OF POSTS.
- ⑦ ALLOW SUFFICIENT SLACK VERTICALLY AND HORIZONTALLY SO THAT SEDIMENT BUILD UP WILL NOT SEPARATE OR LOWER THE TURBIDITY BARRIER.
- ⑧ USE AS DIRECTED BY COAST GUARD OR DNR PERMIT WHEN WORKING IN NAVIGABLE WATERWAYS.



PLAN VIEW




SECTION C - C

**TURBIDITY BARRIER DETAIL SHOWING
TYPICAL PLACEMENT AT STRUCTURES**
TURBIDITY BARRIER

STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION

APPROVED
6/4/02 /S/ Beth Cannestra
DATE CHIEF ROADWAY DEVELOPMENT
FHWA ENGINEER



TYPICAL NAME PLATE


NUMBERING DESIGNATION MULTI-UNIT STRUCTURES

GENERAL NOTES

NAME PLATES TO BE INSTALLED ON BRIDGES, CULVERTS, AND RETAINING WALLS SHALL CONFORM TO THE REQUIREMENTS OF SECTION 502.3.11 OF THE STANDARD SPECIFICATIONS.


THE BRIDGE NUMBER AND YEAR BUILT SHOWN ON THIS DRAWING ARE EXAMPLES ONLY. SEE CONSTRUCTION PLANS FOR INDIVIDUAL NUMBERING AND YEAR BUILT.

- ① EPOXY RESIN SHALL BE FROM AN APPROVED MANUFACTURER AND USED IN ACCORDANCE WITH MANUFACTURER'S RECOMMENDATIONS.
- ② REHABILITATION OF AN EXISTING STRUCTURE SHOULD USE THE DATE OF ORIGINAL STRUCTURE CONSTRUCTION.



SECTION A-A

ALTERNATE LUG



ALTERNATE LUG

**REINFORCED CONCRETE FORMS
(FOR ATTACHMENT TO PRECAST STRUCTURES)**


**NAME PLATE
(STRUCTURES)**

**STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION**

APPROVED

3/26/10 /S/ Scot Becker

CHIEF STRUCTURAL DEVELOPMENT ENGINEER



**TYPICAL PAVEMENT CROSS SECTION
NOTCHED WEDGE JOINT**

GENERAL NOTES


IN ADDITION TO THE DETAILS PROVIDED IN THIS DRAWING, CONFORM TO STANDARD SPECIFICATION 450.3.2.8 FOR WHEN A NOTCHED WEDGE JOINT IS REQUIRED AND FOR GENERAL JOINT CONSTRUCTION REQUIREMENTS.

FOR ALL LONGITUDINAL JOINTS, ENSURE THE PAVER SCREED OVERLAPS THE PREVIOUSLY PLACED PAVEMENT BY $1'' \pm 0.5''$ AND THE HOT SIDE OF THE JOINT REMAINS HIGHER THAN THE COLD SIDE BY APPROXIMATELY $0.1''$ AFTER FINAL COMPACTION. (IT WILL BE FLUSH WHEN PAVING IN ECHELON.)


ONLY REMOVE THE LONGITUDINAL NOTCHED WEDGE JOINT FOR SMA PAVEMENT OR AS DIRECTED BY THE ENGINEER TO ADDRESS SPECIFIC LENGTHS OF JOINT DAMAGED BY TRAFFIC.

WHEN MILLING BACK OR REMOVING ANY LONGITUDINAL JOINT, LIMIT THE MATERIAL REMOVED TO $2''$ FROM THE TOP NOTCH OR FROM THE VERTICAL JOINT EDGE ON THE COLD SIDE OF THE JOINT.


USE LONGITUDINAL MILLED JOINT AS PLANS SHOW OR AS THE ENGINEER DIRECTS.



**TYPICAL PAVEMENT CROSS SECTION
VERTICAL JOINT**



OVERLAP DETAIL (TYPICAL)




**TYPICAL PAVEMENT CROSS SECTION
VERTICAL JOINT (MILLED)**

HMA LONGITUDINAL JOINTS

STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION

APPROVED	November 2020	/S/ Steven Hefel
DATE		
FHWA		
HMA PAVEMENT ENGINEER		



DETAIL A MAINLINE CLOSURE WITH POSTED DETOUR

WORK ZONE GREATER THAN OR EQUAL TO $\frac{1}{2}$ MILE FROM DETOUR ROUTE (1000 FEET IF URBAN)

DETAIL B MAINLINE CLOSURE WITH POSTED DETOUR

WORK ZONE LESS THAN $\frac{1}{2}$ MILE FROM DETOUR ROUTE (1000 FEET IF URBAN)

LEGEND

- SIGN ON PERMANENT SUPPORT
- + TYPE III BARRICADE
- || TYPE III BARRICADE WITH ATTACHED SIGN
- TYPE "A" WARNING LIGHT (FLASHING)



WORK AREA



FLAGS, 16" X 16" MIN. (ORANGE)




M1 - 5A



M05 - 1



M06 - 1



DETAIL C MAINLINE CLOSURE, NO POSTED DETOUR

SPEED LIMIT (MPH)	"STOP AHEAD" ADVANCE WARNING DISTANCE (FT)
25	200
30	200
35	350
40	350
45	500
50	550
55	750

SEE SDD 15C2-SHEET "b"
FOR GENERAL NOTES
AND FOOTNOTES ① THROUGH ⑦

BARRICADES AND SIGNS FOR MAINLINE CLOSURES

STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION

APPROVED
May 2023 /S/ Andrew Heidke
DATE
FHWA
WORK ZONE ENGINEER

GENERAL NOTES

THE EXACT NUMBER, LOCATION, AND SPACING OF ALL SIGNS AND BARRICADES SHALL BE ADJUSTED TO FIT FIELD CONDITIONS AS APPROVED BY THE ENGINEER.

ANY SIGNS TEMPORARY OR EXISTING, WHICH CONFLICT WITH TRAFFIC CONTROL "IN USE", SHALL BE REMOVED OR COVERED AS NEEDED AND AS APPROVED BY THE ENGINEER.

THE SPACING BETWEEN TRAFFIC CONTROL SIGNS SHOULD BE ADJUSTED TO NOT CONFLICT WITH AND SHOULD PROVIDE A DESIRABLE MINIMUM OF 200 FEET CLEARANCE TO EXISTING SIGNS THAT WILL REMAIN IN PLACE.

BARRICADES THAT MUST BE MOVED FOR A WORK OPERATION SHALL BE IMMEDIATELY RE-ESTABLISHED UPON COMPLETION OF THE OPERATION, OR FOR CONTINUING OPERATIONS, AT THE END OF EACH WORKING DAY.

SIGNS THAT WILL BE IN PLACE LESS THAN 7 CONTINUOUS DAYS AND NIGHTS MAY BE MOUNTED ON PORTABLE SUPPORTS.

ALL TYPE III BARRICADES SHALL HAVE RAILS REFLECTORIZED ON BOTH FACES. STRIPES SHALL BE PROPERLY SLOPED DOWN TOWARD THE TRAFFIC SIDE OR AS SHOWN IN THE ROAD CLOSURE BARRICADE DETAIL "D" FOR FULL ROAD CLOSURES.

TYPE "A" LOW - INTENSITY FLASHING WARNING LIGHTS SHALL BE VISIBLE ON BOTH SIDES OF THE BARRICADE.

THE R11 - 2, R11 - 3, M4 - 9, R11 - 4, AND R10 - 61 SIGNS PLACED ON THE BARRICADES SHALL COVER NO MORE THAN THE TOP RAIL. THE SIGNS SHALL NOT COVER ANY PORTION OF THE MIDDLE RAIL OR BOTTOM RAILS.

"WO" AND "MO" SIGNS ARE THE SAME AS "W" AND "M" SIGNS EXCEPT THE BACKGROUND IS ORANGE.

ALL SIGNS SHALL BE 48" X 48" UNLESS OTHERWISE NOTED BELOW:

R11 - 2 SHALL BE 48" X 30"

R11 - 3 SHALL, R11 - 4 AND R10 - 61 SHALL BE 60" X 30"

M4 - 9 SHALL BE 30" X 24"

M3 - X SHALL BE 24" X 12" (36" X 18" IF NEEDED TO MATCH EXISTING SIGNS)


M4 - 8 SHALL BE 24" X 12" (36" X 18" IF NEEDED TO MATCH EXISTING SIGNS)

M1 - 4, M1 - 5A AND M1 - 6 SHALL BE 24" X 24" (36" X 36" IF NEEDED TO MATCH EXISTING SIGNS)

M05 - 1 AND M06 - 1 SHALL BE 21" X 21" (30" X 30" IF NEEDED TO MATCH EXISTING SIGNS)


D1 - X SHALL BE AS SHOWN ON SPECIFIC PROJECT SIGNING DETAIL SHEETS.

R1 - 1 SHALL BE 36" X 36"



DETAIL D
ROAD CLOSURE BARRICADE DETAIL
APPROACH VIEW

6



DETAIL E
LANE CLOSURE BARRICADE DETAIL
APPROACH VIEW

SDD 15C02 - 09b

SEE SDD 15C2 - SHEET "a" FOR LEGEND


- ① TWO WARNING LIGHTS SHALL BE PROVIDED ON THE CENTER BARRICADE AND A MINIMUM OF ONE WARNING LIGHT SHALL BE PROVIDED ON EACH OF THE OTHER BARRICADES WITHIN THE ROADWAY LIMITS. SPACING OF THE WARNING LIGHTS SHALL BE UNIFORM TO THE EDGE OF ROADWAY AS SHOWN (APPROX. 8 FOOT LIGHT SPACING).
- ② THESE SIGNS AND BARRICADES ARE NOT REQUIRED IF ROAD CLOSURE BEGINS AT AN INTERSECTION.
- ③ FOR ROAD CLOSURE WITHOUT LOCAL ACCESS TO PROJECT, SEE ROAD CLOSURE BARRICADE DETAIL "D".
- ④ FOR ROAD CLOSURE WITH LOCAL ACCESS TO PROJECT, SEE ROAD CLOSURE BARRICADE DETAIL "E".
- ⑤ FOR BRIDGE OR CULVERT REPLACEMENTS, SUBSTITUTE "BRIDGE OUT" INSTEAD OF "ROAD CLOSED" ON R11 - 2 AND R11 - 3 SIGNS.
- ⑥ INSTALL DETOUR AND COMMUNITY GUIDE SIGNS AND ARROWS ONLY IF SPECIFIED IN THE CONTRACT. IF THERE ARE EXISTING ROUTE MARKER ASSEMBLIES THAT WILL REMAIN IN PLACE, ADJUST THE LOCATION OF THE DETOUR ROUTE SIGNS TO CORRESPOND WITH THE EXISTING ASSEMBLIES. MODIFY EXISTING SIGNS WHERE POSSIBLE. SEE SPECIFIC PROJECT DETOUR SIGNING DETAIL SHEETS. IF DETOUR SIGNS ARE BEING INSTALLED BY OTHERS, PLACE THE CONTRACTED TRAFFIC CONTROL SIGNS TO ALLOW FOR PLACEMENT OF ALL WARNING, DETOUR AND GUIDE SIGNS AS SHOWN.
- ⑦ "EAST" CARDINAL DIRECTION MARKERS AND RIGHT TURN ARROWS ARE SHOWN. USE OTHER CARDINAL DIRECTIONS AND ARROWS AS APPROPRIATE.

BARRICADES AND SIGNS FOR VARIOUS CLOSURES

STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION


APPROVED
May 2023
DATE
/S/ Andrew Heidtke
FHWA
WORK ZONE ENGINEER

SDD 15C02 - 09b



SITUATION 1

WARRANTING CRITERIA:
BRIDGE WIDTH IS AT LEAST 16 FEET BUT LESS THAN 24 FEET.



SITUATION 2

WARRANTING CRITERIA:
1. BRIDGE WIDTH IS AT LEAST 24 FEET AND
2. BRIDGE SHOULDER WIDTH IS LESS THAN 6 FEET

GENERAL NOTES

DETAILS OF TRAFFIC CONTROL DEVICES AND INSTALLATION NOT SHOWN ON THE DRAWING SHALL CONFORM TO THE PERTINENT REQUIREMENTS OF THE STANDARD SPECIFICATIONS, THE SPECIAL PROVISIONS, AND THE MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES.

LOCATE W5-52 SIGN POST(S) BEHIND GUARDRAIL WHEN PRESENT.

PLACE THE EDGE OF THE W-52 SIGN IN LINE WITH FACE OF CURB OR PARAPET.

ON BRIDGE ONLY PROJECTS, PLACE 300 FEET OF EDGELINE.

OMIT EDGELINES ON ROADWAYS WITHOUT EXISTING EDGELINES.

① OMIT ON ONE-WAY TRAVELED WAYS.

LEGEND

Ⓐ SIGN ON PERMANENT SUPPORT

→ DIRECTION OF TRAFFIC


DISTANCE TABLE

POSTED OR 85TH PERCENTILE SPEED	DISTANCE "A"
25	150'
30	200'
35	250'
40	300'
45	400'
50	550'
55	700'


SIGNING AND MARKING FOR TWO LANE BRIDGES

STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION


APPROVED
May 2023 /S/ Jeannie Silver
DATE
Statewide Pavement Marking Engineer
FHWA

**DRUM**


BALLAST WIDTHS
RANGE FROM 24"-36"

**42" CONE**


DO NOT USE IN TAPERS
 $\frac{1}{2}$ SPACING OF DRUMS
 BALLAST WIDTHS
RANGE FROM 14"-20"

**VERTICAL PANEL**

THE STRIPES SHALL SLOPE DOWNWARD TO
THE TRAFFIC SIDE FOR CHANNELIZATION.

**TYPE II BARRICADE**

FOR RAILS LESS THAN 36" LONG, 4" WIDE STRIPES
MAY BE USED. ALL STRIPES SHALL SLOPE DOWNWARD
TO THE TRAFFIC SIDE FOR CHANNELIZATION.

**TYPE III BARRICADE**

IF SIGN MOUNTED, DO NOT COVER MORE THAN 50% OF THE TOP
TWO RAILS OR 33% OF THE TOTAL AREA OF THE THREE RAILS.

* IF USED FOR A PERMANENT APPLICATION USE RED SHEETING.

GENERAL NOTES


- ① REFLECTIVE SHEETING SHALL FOLLOW THE REQUIREMENTS IN THE APPROVED PRODUCTS LISTING FOR SIGN SHEETING.
- ② LOCATION OF WARNING LIGHTS WHEN SHOWN ON THE PLAN.

CHANNELIZING DEVICES DRUMS, CONES, BARRICADES AND VERTICAL PANELS


STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION

APPROVED
November 2022 /S/ Andrew Heidtke
DATE FHWA
WORK ZONE ENGINEER

URBAN AREA




RURAL AREA (See Note 2)




GENERAL NOTES

1. Signs wider than 4 feet or 20 sq.ft or larger, shall be mounted on multiple posts. Refer to plate A4-4.
2. If signs are mounted on or behind barrier wall, see A4-10 sign plate.
3. The Double Arrow sign (W12-1D) shall be mounted at a height of 2'-3" (±) 3". The Chevron sign (W1-8), Roundabout Chevron panel (R6-4B), Enhanced Reference Markers, Clearance Markers (W5-52), Mile Markers (D10 series), In Road Object Markers (W5-54) & End of Road Markers (W5-56) shall be mounted at a height of 4'-3" (±) 3".
4. For expressways and freeways, mounting height is 7'-3" (±) 3" or 6'-3" (±) 3" depending upon existence of a sub-sign.
5. Minimum mounting height for signs mounted on traffic signal poles is 5'-3" (±) 3".
6. Offset distance shall be consistent with existing signs or consistent throughout length of project.
7. Folding signs shall be mounted at a height of 5'-3" (±) 3" or as directed by the Engineer.

2' Min - 4' Max (See Note 5)



White Edgeline Location



** The existence of curb and gutter does not in itself mandate the vertical clearance illustrated. That height is typically measured where there is sidewalk adjacent to the roadway or parking is permitted. In the absence of sidewalk vertical clearance is measured from the top of the curb. Offset of signs is measured from the flow line.

POST EMBEDMENT DEPTH

Area of Sign Installation (Sq. Ft.)	D (Min)
20 or Less	4'
Greater than 20	5'

* 6 feet from edge of a paved shoulder or 12 feet from the edge of pavement (edge line location) or 2 feet from outside edge of gravel, whichever is greater unless directed by project engineer.

TYPICAL INSTALLATION
OF PERMANENT TYPE II
SIGNS ON SINGLE POSTS

WISCONSIN DEPT OF TRANSPORTATION

APPROVED *Matthew P. Rauch*
for State Traffic Engineer

DATE 12/6/23 PLATE NO. A4-3.23


PROJECT NO:

HWY:

COUNTY:

SHEET NO:

E




ELEVATION VIEW

DETAIL OF WOOD 4 X 6 SIGN POST IN BOX-OUT


NOTES:

1. ALL MATERIAL TO BE APPROVED BY ENGINEER PRIOR TO INSTALLATION
2. SEE SIGN PLATE A4-8 FOR SIGN HARDWARE REQUIREMENTS
3. 18 INCH X 18 INCH SQUARE BOX-OUTS MAY BE USED FOR INSTALLATIONS IN EXISTING CONCRETE OR ASPHALT LOCATIONS.



ELEVATION VIEW

DETAIL OF STEEL 2 X 2 SIGN POST IN BOX-OUT



PLAN VIEW

FOR NEW CONCRETE/ASPHALT INSTALLATIONS



**SIGN POST
BOX-OUTS
A4-3B**

WISCONSIN DEPT OF TRANSPORTATION




APPROVED
Matthew P. Rauch
for State Traffic Engineer
DATE 1/27/14 PLATE NO. A4-3B.1

GENERAL NOTES

- For 3 or 4 post installations, individual post spacing shall be greater than 3'-6".
- See tables below for required number of posts.
- For expressways and freeways, mounting height is 7'-3" (\pm 3") or 6'-3" (\pm 3") depending upon existence of sub-sign.
- The (\pm) tolerance for mounting height is 3 inches.
- J-Assemblies are considered to be one sign for mounting height.
- Offset distance shall be consistent with existing signs or consistent throughout length of project.
- Folding signs shall be mounted at a height of 5'-3" (\pm 3") or as directed by the engineer.
- The Double Arrow sign (W12-1) shall be mounted at a height of 2'-3" (\pm 3"). The Chevron sign (W1-8), Roundabout Chevron panel (R6-4B), Clearance Markers (W5-52), Mile Markers (D10 series), In Road Object Markers (W5-54) & End of Road Markers (W5-56) shall be mounted at a height of 4"-3" (\pm 3").



RURAL AREA (See Note 3)



* 6 feet from edge of a paved shoulder or 12 feet from the edge of pavement (edge line location) or 2 feet from outside edge of gravel, whichever is greater unless directed by project engineer.

** The existence of curb and gutter does not in itself mandate the vertical clearance illustrated. That height is typically measured where there is sidewalk adjacent to the roadway or parking is permitted. In the absence of sidewalk vertical clearance is measured from the top of the curb. Offset of signs is measured from the flow line.

*** See A4-3 sign plate for signs 4' or less in width and less than 20 S.F. in area.

SIGN SHAPE OTHER THAN DIAMOND (TWO POSTS REQUIRED)

L	E
Greater than 48"	12"
Less than 60"	
60" to 108"	L/5

SIGN SHAPE OTHER THAN DIAMOND (THREE POSTS REQUIRED)

L	E
Greater than 108" to 144"	12"

POST EMBEDMENT DEPTH

Area of Sign Installation (Sq. Ft.)	D (Min)
20 or Less	4'
Greater than 20	5'

TYPICAL INSTALLATION OF TYPE II SIGNS ON MULTIPLE POSTS

WISCONSIN DEPT OF TRANSPORTATION

APPROVED

Matthew R. Rauch
for State Traffic Engineer

DATE 12/6/23 PLATE NO. A4-4.16


PROJECT NO:

HWY:


COUNTY:

SHEET NO:

E



SIGN SHALL BE MOUNTED TO PROJECT
ABOVE THE TOP OF THE POST



Nuts, bolts and lags used for mounting signs shall have hexagonal heads and shall be either :

- a. Hot dip galvanized in accordance with ASTM Designation: A 153, Class D, or SC 3
- b. Electro-galvanized in accordance with ASTM Designation :B 633, TYPE III, SC 3.

Threads on bolts and nuts shall be manufactured with sufficient allowance for the cadmium plate or galvanized coating to permit the nuts to run freely on the bolts.

STRINGER BOLTING TO ALUMINUM SIGNS (SEE SIGN PLATE A4-18)

MACHINE BOLTS - $\frac{5}{16}$ " X 1-3/4" Length w/ lock nuts

WOOD POSTS (4" x 6")

LAG SCREWS - $\frac{3}{8}$ " X 3" (NO STRINGERS ON BACK OF SIGN)
 $\frac{3}{8}$ " X 4" (STRINGERS ON BACK OF SIGN)

SQUARE STEEL POSTS (2" x 2")

MACHINE BOLTS - $\frac{3}{8}$ " X 3-1/4" Length w/ nuts (NO STRINGER ON BACK OF SIGN)
 $\frac{3}{8}$ " X 5" Length w/ nuts (STRINGERS ON BACK OF SIGN)

RIVETS - $\frac{9}{32}$ " (6605-9-6) BULB-TITE, TRI-FOLD, ALUMINUM BODY/MANDREL

O.D. FLANGE .720-.765 INCH, GRIP RANGE .042-.375 INCH

WASHERS (ALL POSTS) -

1-1/4" O.D. X $\frac{3}{8}$ " I.D. X $\frac{1}{16}$ " STEEL

1-1/4" O.D. X $\frac{3}{8}$ " I.D. X .080 NYLON

* Two different fastening systems are shown for illustration purposes. On any individual sign, either one or the other system shall be used. Actual number of fasteners per sign varies with the sign area, but normally there are two. For a single post installation, all signs greater than 9 sq. ft. require the use of 3 fasteners.


ATTACHMENT OF SIGNS TO POSTS

WISCONSIN DEPT OF TRANSPORTATION

APPROVED *Matthew R Rauch*
for State Traffic Engineer

DATE 4/1/2020 PLATE NO. A4-8.9


**TELESCOPIC TUBING ANCHORS
TWO PIECE SYSTEM**



7

DETAIL OF TUBULAR STEEL SIGN POST

(IN Poured CONCRETE OR ASPHALT)



LENGTH SHOWN ON MISC. QTY'S

SEE SIGN PLATE A4-8 FOR BOLT WASHER, & NUT MATERIAL

2" STEEL TUBULAR SQUARE UPPER SECTION

ALL HOLES 7/16" SPACED 1" C-C ALL FOUR SIDES

3/8" ZINC PLATED CORNER ANCHOR BOLT AND NUT

2 1/2" GRAVEL OR DIRT

TELESCOPE PIECES FLUSH AT TOP

18" DIA SCHEDULE 40 PVC BOX-OUT

36"

18"

13"

4"

10"

2 1/2"

3 1/2"

18"

2 1/2" SQUARE X 18" (SOIL STABILIZING SLEEVE)

2 1/4" SQUARE X 36"

4" x 10" x 10 GA. STEEL PLATE (CUT AS SHOWN) WELDED TO ALL FOUR CORNERS OF TELESPAR TUBE

ALL HOLES 7/16" SPACED 1" C-C ALL FOUR SIDES

1" width

1/8" thickness

1" height

10" height

2 1/2" height

3 1/2" height

18" height

2 1/2" height

36" height

2 1/4" width

1" height

1/8" thickness

1" width

1/8" thickness

1" height

10" height

2 1/2" height

3 1/2" height

18" height

2 1/2" height

36" height

2 1/4" width

1" height

1/8" thickness

1" width

1/8" thickness

1" height

10" height

2 1/2" height

3 1/2" height

18" height

2 1/2" height

36" height

2 1/4" width

1" height

1/8" thickness

1" width

1/8" thickness

1" height

10" height

2 1/2" height

3 1/2" height

18" height

2 1/2" height

36" height

2 1/4" width

1" height

1/8" thickness

1" width

1/8" thickness

1" height

10" height

2 1/2" height

3 1/2" height

18" height

2 1/2" height

36" height

2 1/4" width

1" height

1/8" thickness

1" width

1/8" thickness

1" height

10" height

2 1/2" height

3 1/2" height

18" height

2 1/2" height

36" height

2 1/4" width

1" height

1/8" thickness

1" width

1/8" thickness

1" height

10" height

2 1/2" height

3 1/2" height

18" height

2 1/2" height

36" height

2 1/4" width

1" height

1/8" thickness

1" width

1/8" thickness

1" height

10" height

2 1/2" height

3 1/2" height

18" height

2 1/2" height

36" height

2 1/4" width

1" height

1/8" thickness

1" width

1/8" thickness

1" height

10" height

2 1/2" height

3 1/2" height

18" height

2 1/2" height

36" height

2 1/4" width

1" height

1/8" thickness

1" width

1/8" thickness

1" height

10" height

2 1/2" height

3 1/2" height

18" height

2 1/2" height

36" height

2 1/4" width

1" height

1/8" thickness

1" width

1/8" thickness

1" height

10" height

2 1/2" height

3 1/2" height

18" height

2 1/2" height

36" height

2 1/4" width

1" height

1/8" thickness

1" width

1/8" thickness

1" height

10" height

2 1/2" height

3 1/2" height

18" height

2 1/2" height

36" height

2 1/4" width

1" height

1/8" thickness

1" width

1/8" thickness

1" height



10" height

2 1/2" height

3 1/2" height

18" height

2 1/2" height



SIDE VIEW

GENERAL NOTES

1. All 4 x 6 Wood Posts shall be modified by having two $1\frac{1}{2}$ " diameter holes drilled perpendicular to the roadway centerline.

4 X 6 WOOD POST
MODIFICATIONS

WISCONSIN DEPT OF TRANSPORTATION

APPROVED

Cheska J. Sprey
for State Traffic Engineer

DATE 3/27/97

PLATE NO. A4-11.2

PROJECT NO:

HWY:

COUNTY:

SHEET NO:




E

GENERAL NOTES


1. Any sign over 3 feet in width shall use the V-Block banding method. See A5-10 standard plate.
2. Signs 3 feet or greater in height shall have three bracket bands installed. Signs less than 3 feet in height shall have two bracket bands installed.
3. Banding and assembly bracket shall be stainless steel. All bands shall be $\frac{3}{4}$ " in width and 0.025" thickness.
4. ALL SIGN MOUNTING BOLTS AND WASHERS SHALL BE EITHER:
 - a. Hot dip or mechanically galvanized in accordance with ASTM Designation: A 153, Class D
 - b. Electro-galvanized in accordance with ASTM designation: B 633, Type III, SC 3

BANDING

SINGLE SIGN




WASHER PLACEMENT



WASHERS (ALL POSTS) -
 1-1/4" O.D. X $\frac{3}{8}$ " I.D. X $\frac{1}{16}$ " STEEL
 1-1/4" O.D. X $\frac{3}{8}$ " I.D. X .080 NYLON
 FOR ALL TYPE H SIGNS

"J" ASSEMBLY



STANDARD SIGN SIGN BANDING DETAILS

WISCONSIN DEPT OF TRANSPORTATION

APPROVED

Matthew P. Rauch
for State Traffic Engineer

DATE 6/10/19 PLATE NO. A5-9.4


PROJECT NO:

HWY:

COUNTY:

SHEET NO:


E



GENERAL NOTES

1. WOOD 4"X6" POST MATERIAL SHALL CONFORM TO 507.2.2 OF THE WisDOT STANDARD SPECIFICATIONS
2. BLOCK BANDING AND CLIPS SHALL BE STAINLESS STEEL, $\frac{3}{4}$ " WIDTH AND 0.025" THICKNESS
3. SIGNS 3' OR GREATER IN HEIGHT SHALL UTILIZE 3 BLOCK BANDS. SIGNS UNDER 3' IN HEIGHT SHALL UTILIZE 2 BLOCK BANDS
4. ACTUAL NUMBER OF FASTENERS PER SIGN VARIES WITH THE SIGN AREA, BUT NORMALLY THERE ARE TWO. FOR SIGNS GREATER THAN 9 S.F. 3 FASTENERS SHALL BE USED.
5. ALL SIGN MOUNTING BOLTS AND WASHERS SHALL BE EITHER:
 - a. Hot dip or mechanically galvanized in accordance with ASTM Designation: A 153, Class D
 - b. Electro-galvanized in accordance with ASTM Designation : B 633, TYPE III, SC 3
6. ALL BOLTS SHALL HAVE HEXAGONAL HEADS.
7. STEEL WASHERS SHALL BE $1\frac{1}{4}$ " O.D. X $\frac{3}{8}$ " I.D. X $\frac{1}{16}$ "
8. NYLON WASHERS SHALL BE $1\frac{1}{4}$ " O.D. X $\frac{3}{8}$ " I.D. X .080 FOR TYPE H OR TYPE F FACE SIGN

※ LAG BOLTS SHALL BE $\frac{3}{8}$ " X $2\frac{1}{2}$ "





BLOCK BANDING DETAIL
(V-BLOCK OPTION)

WISCONSIN DEPT OF TRANSPORTATION

APPROVED *Matthew R Rauch*
for State Traffic Engineer
DATE 4/19/2022 PLATE NO. A5-10.3

7



NOTES

1. Sign is Type II - Type F Reflective
2. Color:
Background - Yellow
Message - Black
3. Alternate colors of stripes as shown.

SIZE	A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q	R	S	T	U	V	W	X	Y	Z	Area sq. ft.
1																											
2S	12	36	1 1/2			4 3/8	3 1/2	5 5/8	45°	4	4															3.0	
2M	12	36	1 1/2			4 3/8	3 1/2	5 5/8	45°	4	4															3.0	
3	18	54	1 1/2			6	5 1/2	8 1/2	45°	6	6 9/16															6.75	
4																											
5																											

PROJECT NO:

HWY:

COUNTY:

STANDARD SIGN

W5-52L & W5-52R

WISCONSIN DEPT OF TRANSPORTATION

APPROVED *Matthew R Rauch*

For State Traffic Engineer

DATE 3/4/2024 PLATE NO. W5-52.10

SHEET NO:



E

□ INDICATES WING NUMBER

* PROVIDE FOR THREE BEAM GUARD RAIL ATTACHMENT.

STATE PROJECT NUMBER

9833-03-72



DESIGN DATA

LIVE LOAD:

DESIGN LOADING: HL-93
INVENTORY RATING: RF = 1.11
OPERATING RATING: RF = 1.43
WISCONSIN STANDARD PERMIT VEHICLE (WIS-SPV): 250 (KIPS)

STRUCTURE IS DESIGNED FOR A FUTURE WEARING SURFACE OF 20 POUNDS PER SQUARE FOOT.

MATERIAL PROPERTIES:

CONCRETE MASONRY:
SUPERSTRUCTURE $f_c' = 4,000$ PSI
ALL OTHER $f_c' = 3,500$ PSI

BAR STEEL REINFORCEMENT:
GRADE 60 $f_y = 60,000$ PSI

FOUNDATION DATA

ABUTMENTS TO BE SUPPORTED ON HP 10x42 STEEL PILING DRIVEN TO A REQUIRED DRIVING RESISTANCE OF 180 TONS ** PER PILE AS DETERMINED BY THE MODIFIED GATES DYNAMIC FORMULA.
ESTIMATED 35'-0" LONG AT WEST ABUTMENT.
ESTIMATED 35'-0" LONG AT EAST ABUTMENT.

**THE FACTORED AXIAL RESISTANCE OF PILES IN COMPRESSION USED FOR DESIGN IS THE REQUIRED DRIVING RESISTANCE MULTIPLIED BY A RESISTANCE FACTOR OF 0.5 USING MODIFIED GATES TO DETERMINE PILE CAPACITY.

HYDRAULIC DATA

100-YEAR FREQUENCY:

$Q_{100} = 690$ C.F.S.
 $V_{100} = 3.6$ F.P.S.
 $HW_{100} = EL. 1474.03$
WATERWAY AREA = 193 SQ. FT.
DRAINAGE AREA = 11 SQ. MI.
ROADWAY OVERTOPPING = N/A
SCOUR CRITICAL CODE = 5

2-YEAR FREQUENCY:

$Q_2 = 190$ C.F.S.
 $V_2 = 1.4$ F.P.S.
 $HW_2 = EL. 1472.12$

TRAFFIC DATA

FEATURE ON: RANGE LINE ROAD

ADT = <100 (2026)
ADT = <100 (2046)
R.D.S. = 55 MPH

LIST OF DRAWINGS:

- GENERAL PLAN
- TYPICAL SECTION, QUANTITIES AND NOTES
- STRUCTURE DETAILS
- SUBSURFACE EXPLORATION
- WEST ABUTMENT
- WEST ABUTMENT WING DETAILS
- WEST ABUTMENT PILE LAYOUT AND BILL OF BARS
- EAST ABUTMENT
- EAST ABUTMENT WING DETAILS
- EAST ABUTMENT PILE LAYOUT AND BILL OF BARS
- SUPERSTRUCTURE
- SUPERSTRUCTURE PLAN
- TUBULAR RAILING STEEL TYPE "M"



STRUCTURE DESIGN CONTACTS:
AARON BONK 608-261-0261
KRISTOFER OLSON 920-498-1200

NO.	DATE	REVISION	BY
ORIGINAL PLANS PREPARED BY			
AYRES 700 Pilgrim Way, Suite 180 Green Bay, WI 54304 www.AyresAssociates.com			
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
ACCEPTED	<i>JLR</i>	12/01/25	DATE
STRUCTURE B-34-66			
RANGE LINE ROAD OVER BLACK BROOK			
COUNTY	TOWN	ACKLEY	
DESIGN SPEC. AASHTO LRFD BRIDGE DESIGN SPECIFICATION			
DESIGNED BY	DESIGN CK'D	DRAWN BY	PLANS CK'D
JMC	SAP	JMC	KRO
SHEET 1 OF 13			
GENERAL PLAN			

I.D.

DATE:

TOTAL ESTIMATED QUANTITIES

BID ITEM NUMBER	BID ITEMS	UNIT	SUPER	W ABUT.	E ABUT.	TOTALS
203.0220	REMOVING STRUCTURE P-34-917	EACH	---	---	---	1
206.1001	EXCAVATION FOR STRUCTURES BRIDGES B-34-66	EACH	---	---	---	1
210.1500	BACKFILL STRUCTURE TYPE A	TON	---	115	115	230
502.0100	CONCRETE MASONRY BRIDGES	CY	82.7	28.4	28.4	140
502.3200	PROTECTIVE SURFACE TREATMENT	SY	159	9	9	177
505.0400	BAR STEEL REINFORCEMENT HS STRUCTURES	LB	---	1,630	1,630	3,260
505.0600	BAR STEEL REINFORCEMENT HS COATED STRUCTURES	LB	16,190	1,360	1,360	18,910
513.4061	RAILING TUBULAR TYPE M	LF	131	---	---	131
516.0500	RUBBERIZED MEMBRANE WATERPROOFING	SY	---	9	9	18
550.1100	PILING STEEL HP 10-INCH X 42 LB	LF	---	140	140	280
606.0300	RIPRAP HEAVY	CY	---	60	45	105
612.0406	PIPE UNDERDRAIN WRAPPED 6 - INCH	LF	---	70	70	140
645.0111	GEOTEXTILE TYPE DF SCHEDULE A	SY	---	25	25	50
645.0120	GEOTEXTILE TYPE HR	SY	---	115	95	210
	NON-BID ITEMS					
	FILLER	SIZE	---	---	---	1/2", 3/4"

GENERAL NOTES

DRAWINGS SHALL NOT BE SCALED.

BAR STEEL REINFORCEMENT SHALL BE EMBEDDED 2" CLEAR UNLESS OTHERWISE SHOWN OR NOTED.

THE FIRST OR FIRST TWO DIGITS OF THE BAR MARK SIGNIFIES THE BAR SIZE.

BEVEL EXPOSED EDGES OF CONCRETE 3/4" UNLESS OTHERWISE NOTED.

THE UPPER LIMITS OF "EXCAVATION FOR STRUCTURES BRIDGES B-34-66" SHALL BE THE EXISTING GROUNDLINE.

AT THE BACK FACE OF ABUTMENT ALL VOLUME WHICH CANNOT BE PLACED BEFORE ABUTMENT CONSTRUCTION AND IS NOT OCCUPIED BY THE NEW STRUCTURE SHALL BE BACKFILLED WITH STRUCTURE BACKFILL TYPE A.

EXCAVATION BELOW THE ABUTMENT AND ABUTMENT BEDDING MATERIALS REQUIRES ENGINEER APPROVAL. GEOTEXTILE SHALL BE SET AT THE BOTTOM OF EXCAVATION AND EXTEND 2'-0" ABOVE BOTTOM OF ABUTMENT.

THE QUANTITY FOR BACKFILL STRUCTURE IS CALCULATED BASED ON THE DETAIL SHOWN IN THE PLANS.


THE SLOPE OF THE FILL IN FRONT OF THE ABUTMENTS SHALL BE COVERED WITH HEAVY RIPRAP AND GEOTEXTILE TYPE "HR" TO THE EXTENT SHOWN ON SHEET 1 AND THE ABUTMENT DETAILS.

SLAB FALSEWORK SHALL BE SUPPORTED ON PILES OR THE SUBSTRUCTURE, UNLESS AN ALTERNATE METHOD IS APPROVED BY THE ENGINEER.


PROTECTIVE SURFACE TREATMENT TO BE APPLIED TO ENTIRE EXPOSED TOP OF SLAB, THE TOP AND EXTERIOR EXPOSED FACE OF WINGS AND FRONT FACE OF ABUTMENT TO 1'-0" PAST THE EDGE OF SLAB.

AT ABUTMENTS, CONCRETE POURED UNDER WATER WILL BE ALLOWED AND SHALL BE DONE IN ACCORDANCE WITH SECTION 502.3.5.3 OF THE STANDARD SPECIFICATIONS.

EXISTING PIPE AND HEADWALL LOCATIONS ARE BASED ON SURVEY. EXTENT OF BELOW GRADE FEATURES ARE NOT KNOWN. REMOVE EXISTING STRUCTURE AS NEEDED TO BUILD NEW SUBSTRUCTURE. COST OF BELOW GRADE REMOVAL IS CONSIDERED INCIDENTAL TO "REMOVING STRUCTURE" BID ITEM.




TYPICAL SECTION THRU BRIDGE



ABUTMENT BACKFILL DIAGRAM

L = OUT TO OUT OF ABUTMENT BODY INCLUDING WINGS (FT)
 H = AVERAGE ABUTMENT FILL HEIGHT (FT)
 EF = EXPANSION FACTOR (1.20 FOR CY BID ITEMS AND 1.00 FOR TON BID ITEMS)
 V_{CF} = $(L)(3.0')(H) + (L)(0.5)(1.5H)(H)$
 V_{CY} = $V_{CF}(EF)/27$
 V_{TON} = $V_{CY}(2.0)$




TYPICAL SECTION THRU ABUTMENT

▲ BACKFILL PAY LIMITS. BACKFILL BEYOND PAY LIMITS SHALL BE INCIDENTAL TO EXCAVATION FOR STRUCTURES. LIMITS OF EXCAVATION SHALL BE DETERMINED BY THE CONTRACTOR.

■ PIPE UNDERDRAIN WRAPPED (6-INCH). SLOPE 0.5% MIN. TO SUITABLE DRAINAGE. ATTACH RODENT SHIELD AT ENDS OF PIPE UNDERDRAIN.

★ FOR BOTTOM OF ABUTMENTS LOCATED BELOW NORMAL WATER, PLACE DRAIN ABOVE NORMAL WATER. SEE BRIDGE MANUAL 12.6.1 FOR ADDITIONAL GUIDANCE.

NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
STRUCTURE B-34-66			
DRAWN BY	JMC	PLANS CK'D	SAP
TYPICAL SECTION, QUANTITIES AND NOTES			SHEET 2 OF 13




RODENT SHIELD DETAIL

* DIMENSIONS ARE APPROXIMATE. THE GRATE IS SIZED TO FIT INTO A PIPE COUPLING. ORIENT SO SLOTS ARE VERTICAL.

THE RODENT SHIELD, PIPE COUPLING AND SCREWS SHALL BE CONSIDERED INCIDENTAL TO THE BID ITEM "PIPE UNDERDRAIN WRAPPED 6-INCH".


THE RODENT SHIELD SHALL BE A PVC GRATE SIMILAR TO THIS DETAIL. THE GRATE IS COMMERCIALLY AVAILABLE AS A FLOOR STRAINER. A PIPE COUPLING IS REQUIRED FOR THE ATTACHMENT OF THIS SHIELD TO THE EXPOSED END OF THE PIPE UNDERDRAIN. THE SHIELD SHALL BE FASTENED TO THE PIPE COUPLING WITH TWO OR MORE NO. 10 X 1-INCH STAINLESS STEEL SHEET METAL SCREWS.




PROTECTIVE SURFACE TREATMENT DETAIL

NOTE: PLACE RIPRAP HEAVY AS SHOWN ON GENERAL PLAN SHEET

PLACE RIPRAP HEAVY EVEN WITH TOP OF WING, 2 FEET FROM THE WING TIP.



TYPICAL FILL SECTION AT WING TIPS



'HP' PILE DETAILS

NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
STRUCTURE B-34-66			
	DRAWN BY	PLANS CK'D	SAP
STRUCTURE DETAILS			SHEET 3 OF 13

BORING #	DATE COMPLETED	NORTHING (Y)	EASTING (X)
B-01	MARCH 3, 2025	355538.19	589140.32
B-02	MARCH 10, 2025	355525.55	589219.20
BORINGS COMPLETED BY: ECS MIDWEST, LLC			
REPORT COMPLETED BY: ECS MIDWEST, LLC			
ALL COORDINATES REFERENCED TO WCCS NAD 83(91) LANGLADE COUNTY			


STATE PROJECT NUMBER

9833-03-72

MATERIAL SYMBOLS

ASPHALT	TOPSOIL	PEAT
CONCRETE	FILL	GRAVEL
SAND	CLAY	SILT
BOULDERS OR COBBLES	LIMESTONE	BEDROCK (UNKNOWN)
SHALE	SANDSTONE	IGNEOUS/META

LEGEND OF BORING



(1) UNCONFINED STRENGTH, AS DETERMINED BY A POCKET PENETROMETER (TSF)

(2) UNLESS OTHERWISE SPECIFIED, THE SPT 'N' VALUE IS BASED ON AASHTO T-206, STANDARD PENETRATION TEST. THE SPT 'N' VALUE PRESENTED HAS NOT BEEN CORRECTED FOR OVERBURDEN PRESSURE OR HAMMER EFFICIENCY.

GROUND WATER ELEVATION

- ▽ AT TIME OF DRILLING
- ▼ END OF DRILLING
- ▼ AFTER DRILLING

ABBREVIATIONS

F-FINE M-MEDIUM C-COARSE ST-SHELBY TUBE

SUBSURFACE EXPLORATION FOR FOUNDATION DESIGN AND BIDDERS INFORMATION

BORINGS WERE COMPLETED AT POINTS APPROXIMATELY AS INDICATED ON THIS DRAWING TO OBTAIN INFORMATION CONCERNING THE CHARACTER OF SUBSURFACE MATERIALS FOUND AT THE SITE. BECAUSE THE INVESTIGATED DEPTHS ARE LIMITED AND THE AREA OF THE BORINGS IS VERY SMALL IN RELATION TO THE ENTIRE SITE, THE WISCONSIN DEPARTMENT OF TRANSPORTATION DOES NOT WARRANT SIMILAR SUBSURFACE CONDITIONS BELOW, BETWEEN, OR BEYOND THESE BORINGS. VARIATIONS IN SOIL CONDITIONS SHOULD BE EXPECTED AND FLUCTUATIONS IN GROUNDWATER LEVELS MAY OCCUR.



NO. DATE REVISION BY


STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION

STRUCTURE B-34-66

DRAWN BY JMC PLANS CK'D SAP


SUBSURFACE EXPLORATION SHEET 4 OF 13






ELEVATION

(LOOKING WEST)



PLAN



SECTION THRU BODY

(A01) CONST. JOINT: KEYWAY FORMED BY A BEVELED 2 x 6.

(A06) SUPPORT ABUTMENT ON HP 10 x 42 STEEL PILING, ESTIMATED 35'-0" LONG WITH A REQUIRED DRIVING RESISTANCE OF 180 TONS PER PILE.



(A15) PIPE UNDERDRAIN WRAPPED (6-INCH). SLOPE 0.5% MIN. TO SUITABLE DRAINAGE. RODENT SHIELD REQUIRED.

(A17) 1/2" FILLER (INCLUDED IN WING LENGTH): SEAL ALL EXPOSED HORIZ. & VERT. SURFACES OF 1/2" FILLER WITH NON-STAINING GRAY NON-BITUMINOUS JOINT SEALER. (1" DEEP AND HOLD 1/2" BELOW SURFACE OF CONCRETE). EXTEND SEALER 3" BELOW GUTTER LINE AT INSIDE FACE.

(A19) 18" (RMW) RUBBERIZED MEMBRANE WATERPROOFING SEAL ALL HORIZ. & VERT. JOINTS AT BACKFACE.

(A22) BARS @ 1'-0" CTRS. BETWEEN BEAM SEATS. MAY BE PLACED AFTER CONCRETE IS POURED BUT BEFORE INITIAL SET HAS TAKEN PLACE. (EMBED 1'-0" INTO CONC.)

NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
STRUCTURE B-34-66			
DRAWN BY	CLP	PLANS CK'D	SAP
WEST ABUTMENT			
SHEET 5 OF 13			

**SECTION A**

(A03) OPTIONAL CONST. JOINT: KEYWAY FORMED BY BEVELED 2 x 6. (18" RMW @ B.F. & $\frac{3}{4}$ " "V" GROOVE @ F.F. IF JOINT IS USED).

(A17) $\frac{1}{2}$ " FILLER (INCLUDED IN WING LENGTH): SEAL ALL EXPOSED HORIZ. & VERT. SURFACES OF $\frac{1}{2}$ " FILLER WITH NON-STAINING GRAY NON-BITUMINOUS JOINT SEALER. (1" DEEP AND HOLD $\frac{1}{2}$ " BELOW SURFACE OF CONCRETE). EXTEND SEALER 3" BELOW GUTTER LINE AT INSIDE FACE.

(A19) 18" (RMW) RUBBERIZED MEMBRANE WATERPROOFING SEAL ALL HORIZ. & VERT. JOINTS AT BACKFACE.

NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
STRUCTURE B-34-66			
DRAWN BY CLP PLANS CK'D SAP			
WEST ABUTMENT WING DETAILS		SHEET 6 OF 13	




BILL OF BARS


NOTE: THE FIRST OR FIRST TWO DIGITS OF THE BAR MARK SIGNIFIES THE BAR SIZE.

BAR MARK	COAT	NO. REQ'D.	LENGTH	BENT	BAR SERIES	LOCATION
A401		4	28'-0"	X		BODY @ PILES
A402		8	2'-3"			BODY @ PILES
A503		35	14'-2"	X		BODY VERT.
A604		11	28'-2"			BODY HORIZ.
A805		7	30'-0"	X		BODY HORIZ. @ B.F.
A506	X	27	2'-0"			BODY DOWELS
A507	X	20	15'-8"	X		WINGS 1 & 2 VERT.
A508	X	12	12'-2"			WINGS 1 & 2 HORIZ. F.F.
A609	X	16	11'-11"			WINGS 1 & 2 HORIZ. B.F. & TOP
A610	X	28	9'-6"	X		WINGS 1 & 2 VERT.
A411	X	10	9'-7"			WINGS 1 & 2 HORIZ. E.F.
A612	X	4	9'-7"			WINGS 1 & 2 HORIZ. E.F. TOP
A413	X	6	4'-7"			BODY VERT. END @ WINGS 1 & 2

BENDING DIMENSIONS ARE OUT TO OUT OF BARS.



A805



A610




A503, A507

Diagram illustrating the bridge structure and foundation details. The bridge is 28'-6" wide, supported by four H-piles (1, 2, 3, 4) with a total width of 28'-6". The distance between the centers of piles 1 and 2 is 11'-0", and between piles 3 and 4 is 11'-0". The bridge deck is supported by four H-piles (1, 2, 3, 4). The vertical height of the bridge is 12'-6". The diagram shows the centerline of the range line road and the centerline of the west abutment. Foundation details include A507, A508, A609, A805, A401, A402, A413, A06, A604, and STA. 9+80.00. Pile spacing dimensions are 2'-6", 7'-10", 3'-11", 3'-11", 7'-10", and 2'-6". A503 bar spacing and space to miss pile dimensions are also provided.

PILE LAYOUT

**(A06) SUPPORT ABUTMENT ON HP 10 X 42 STEEL PILING,
ESTIMATED 35'-0" LONG WITH A REQUIRED DRIVING
RESISTANCE OF 180 TONS PER PILE.**

NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
STRUCTURE B-34-66			
WEST ABUTMENT PILE LAYOUT AND BILL OF BARS		DRAWN BY CLP CK'D SAP	
		SHEET 7 OF 13	



(A01) CONST. JOINT: KEYWAY FORMED BY A BEVELED 2 x 6.

(A06) SUPPORT ABUTMENT ON HP 10 x 42 STEEL PILING, ESTIMATED 35'-0" LONG WITH A REQUIRED DRIVING RESISTANCE OF 180 TONS PER PILE.


(A15) PIPE UNDERDRAIN WRAPPED (6-INCH), SLOPE 0.5% MIN. TO SUITABLE DRAINAGE. RODENT SHIELD REQUIRED.

(A17) 1/2" FILLER (INCLUDED IN WING LENGTH): SEAL ALL EXPOSED HORIZ. & VERT. SURFACES OF 1/2" FILLER WITH NON-STAINING GRAY NON-BITUMINOUS JOINT SEALER. (1" DEEP AND HOLD 1/8" BELOW SURFACE OF CONCRETE). EXTEND SEALER 3" BELOW GUTTER LINE AT INSIDE FACE.

(A19) 18" (RMW) RUBBERIZED MEMBRANE WATERPROOFING SEAL ALL HORIZ. & VERT. JOINTS AT BACKFACE.

(A22) BARS @ 1'-0" CTRS. BETWEEN BEAM SEATS. MAY BE PLACED AFTER CONCRETE IS POURED BUT BEFORE INITIAL SET HAS TAKEN PLACE. (EMBED 1'-0" INTO CONC.).


NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
STRUCTURE B-34-66			
DRAWN BY	CLP	PLANS CK'D	SAP
EAST ABUTMENT			
SHEET 8 OF 13			




(A03) OPTIONAL CONST. JOINT: KEYWAY FORMED BY BEVELED 2 x 6. (18" RMW @ B.F. & $\frac{3}{4}$ " "V" GROOVE @ F.F. IF JOINT IS USED).

(A17) $\frac{1}{2}$ " FILLER (INCLUDED IN WING LENGTH): SEAL ALL EXPOSED HORIZ. & VERT. SURFACES OF $\frac{1}{2}$ " FILLER WITH NON-STAINING GRAY NON-BITUMINOUS JOINT SEALER. (1" DEEP AND HOLD $\frac{1}{2}$ " BELOW SURFACE OF CONCRETE). EXTEND SEALER 3" BELOW GUTTER LINE AT INSIDE FACE.

(A19) 18" (RMW) RUBBERIZED MEMBRANE WATERPROOFING SEAL ALL HORIZ. & VERT. JOINTS AT BACKFACE.



NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
STRUCTURE B-34-66			
DRAWN BY	CLP	PLANS CK'D	SAP
EAST ABUTMENT WING DETAILS			SHEET 9 OF 13




PILE LAYOUT

BILL OF BARS

NOTE: THE FIRST OR FIRST TWO DIGITS OF THE BAR MARK SIGNIFIES THE BAR SIZE.

BAR MARK	COAT	NO. REQ'D.	LENGTH	BENT	BAR SERIES	LOCATION
B401		4	28'-0"	X		BODY @ PILES
B402		8	2'-3"			BODY @ PILES
B503		35	14'-2"	X		BODY VERT.
B604		11	28'-2"			BODY HORIZ.
B805		7	30'-0"	X		BODY HORIZ. @ B.F.
B506	X	27	2'-0"			BODY DOWELS
B507	X	20	15'-8"	X		WINGS 3 & 4 VERT.
B508	X	12	12'-2"			WINGS 3 & 4 HORIZ. F.F.
B609	X	16	11'-11"			WINGS 3 & 4 HORIZ. B.F. & TOP
B610	X	28	9'-6"	X		WINGS 3 & 4 VERT.
B411	X	10	9'-7"			WINGS 3 & 4 HORIZ. E.F.
B612	X	4	9'-7"			WINGS 3 & 4 HORIZ. E.F. TOP
B413	X	6	4'-7"			BODY VERT. END @ WINGS 3 & 4


BENDING DIMENSIONS ARE OUT TO OUT OF BARS.




B401



B805




B503, B507




B610

(A06) SUPPORT ABUTMENT ON HP 10 X 42 STEEL PILING,
ESTIMATED 35'-0" LONG WITH A REQUIRED DRIVING
RESISTANCE OF 180 TONS PER PILE.

NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
STRUCTURE B-34-66			
DRAWN BY CLP PLANS CK'D SAP			
EAST ABUTMENT PILE LAYOUT AND BILL OF BARS		SHEET 10 OF 13	



TYPICAL SECTION THRU BRIDGE



CAMBER AND SLAB THICKNESS DIAGRAM

CAMBER SHOWN IS BASED ON 3 TIMES DEAD LOAD DEFLECTIONS. CAMBER SPANS AS SHOWN TO PROVIDE FOR DEAD LOAD DEFLECTION AND FUTURE CREEP. CAMBER DOES NOT INCLUDE ALLOWANCE FOR FORM SETTLEMENT.

TO DETERMINE FALSEWORK ELEVATION AT EDGE OF SLAB, CROWN OR REFERENCE LINE FOLLOW THIS PROCEDURE:

LESS	TOP OF SLAB ELEVATION AT FINAL GRADE
PLUS	SLAB THICKNESS
PLUS	CAMBER
EQUALS	FORM SETTLEMENT/DEFLECTION DUE TO PLACEMENT OF SLAB CONCRETE (TO BE COMPUTED BY THE CONTRACTOR)
	TOP OF SLAB FALSEWORK ELEVATION

TOP OF SLAB ELEVATIONS

LOCATION	C/L W. ABUT.	1/10 PT.	2/10 PT.	3/10 PT.	4/10 PT.	5/10 PT.	6/10 PT.	7/10 PT.	8/10 PT.	9/10 PT.	C/L E. ABUT.
N. EDGE OF SLAB	1475.31	1475.32	1475.32	1475.32	1475.32	1475.33	1475.33	1475.33	1475.33	1475.33	1475.34
C/L OF RANGE LINE ROAD	1475.60	1475.60	1475.60	1475.61	1475.61	1475.61	1475.61	1475.61	1475.62	1475.62	1475.62
S. EDGE OF SLAB	1475.31	1475.32	1475.32	1475.32	1475.32	1475.33	1475.33	1475.33	1475.33	1475.33	1475.34

TOP TRANSVERSE BARS IN SLAB SHALL BE SUPPORTED BY INDIVIDUAL BAR CHAIRS AT 3'-0" CENTERS EACH WAY. BOTTOM LONGITUDINAL BARS SHALL BE SUPPORTED BY CONTINUOUS BAR CHAIRS AT APPROXIMATELY 4'-0" CENTERS.

ALL SLAB THICKNESS DIMENSIONS ARE MINIMUM. ANY TOLERANCE NECESSARY TO CORRECT CONSTRUCTION DISCREPANCIES ARE TO BE PLUS (+).

* 3/4" V-GROOVE. EXTEND V-GROOVE TO 6" FROM F.F. OF ABUT.


V-GROOVES ARE REQUIRED.

BILL OF BARS


NOTE: THE FIRST OR FIRST TWO DIGITS OF THE BAR MARK SIGNIFIES THE BAR SIZE.

BAR MARK	COAT	NO. REQ'D.	LENGTH	BENT	BAR SERIES	LOCATION
S1001	X	62	37'-0"			SLAB LONG. BOT.
S502	X	64	28'-2"			SLAB TRANS. BOT.
S503	X	64	28'-2"			SLAB TRANS. TOP
S404	X	32	42'-2"			SLAB LONG. TOP
S505	X	58	7'-6"	X		SLAB @ ABUT. DIAPHRAGM STIRRUPS
S506	X	4	28'-2"			SLAB @ ABUT. DIAPHRAGM TRANS.
S607	X	32	11'-3"	X		SLAB @ RAIL POSTS
S608	X	48	6'-0"			SLAB @ INT. RAIL POSTS
S609	X	16	4'-8"	X		SLAB @ END RAIL POSTS


BENDING DIMENSIONS ARE OUT TO OUT OF BARS.



S505



S607




S609

SURVEY TOP OF SLAB ELEVATIONS

	W. ABUTMENT	5/10 PT.	E. ABUTMENT
N. EDGE OF SLAB			
C/L OF RANGE LINE ROAD			
S. EDGE OF SLAB			


PRIOR TO RELEASING SLAB FORMWORK, TAKE TOP OF SLAB ELEVATIONS AT THE C/L OF ABUTMENTS, AND AT 5/10 PTS. TO VERIFY CAMBER. TAKE ELEVATIONS ALONG EDGE OF SLAB AND C/L. RECORD ELEVATIONS IN THE TABLE ABOVE FOR THE "AS BUILT" PLANS.

NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
STRUCTURE B-34-66			
DRAWN BY	CLP	PLANS CK'D	SAP
SUPERSTRUCTURE SHEET 11 OF 13			



PLAN

█ PLACE BELOW AND TIE TO TOP MAT OF STEEL



LONGITUDINAL SECTION

DIMENSIONS ARE GIVEN PARALLEL TO C, ROADWAY UNLESS OTHERWISE NOTED

MEASURED NORMAL TO THE C/L OF ABUTMENT.
DIMENSIONS ARE TYPICAL FOR BOTH ABUTMENTS

A22 A506, B506 BARS SPACED @ 1'-0" CNTRS. MAY BE PLACED AFTER CONCRETE IS POURED BUT BEFORE INITIAL SET HAS TAKEN PLACE. (EMBED 1'-0" INTO CONC.)




NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
STRUCTURE B-34-66			
SUPERSTRUCTURE PLAN	DRAWN BY	PLANS CLP CK'D	SAP
	SHEET 12 OF 13		

RANGE LINE ROAD COMPUTER EARTHWORK

Station	Distance	Area (SF)			Incremental Vol (CY) (Unadjusted)			Cumulative Vol (CY)		Mass Ordinate	
		Cut	Unuseable Pavement Material	Fill	Salvaged /			Expanded			
					Cut	Unuseable Pavement Material	Fill	Cut	Fill		
					Note 1	Note 4	Note 2	Note 5		Note 3	
9+29	--	28.2	5.2	0.0							
9+50	21.25	29.1	6.0	1.0	23	4	0	18	1	18	
9+68.75	18.75	30.2	6.6	6.4	21	4	3	34	4	31	
9+78.75	10.00	25.3	6.2	0.0	10	2	1	42	5	37	
BRIDGE	--	--	--	--	--	--	--	--	--	--	
10+21.25	--	27	4.1	0	--	--	--	--	--	--	
10+31.25	10.00	32	4.5	4	11	2	1	52	6	45	
10+50	18.75	31.3	4.1	2.3	22	3	2	70	9	61	
10+71	21.25	30.0	3.7	0.0	24	3	1	91	10	81	
					110	19	8				

- 1) Excavation Common is the Cut. Item number 205.0100.
- 2) Expanded Fill. Factor = 1.30; Expanded Fill = Unexpanded Fill * Fill Factor
- 3) The Mass Ordinate + or - Qty calculated for the Division. Plus quantity indicates an excess of material on the project.
- 4) All quantities shown in CY.
- 5) Salvaged/unuseable pavement material

STRUCTURE B-34-0066



PROJECT NO: 9833-03-72


HWY: RANGE LINE ROAD

COUNTY: LANGLADE


CROSS SECTIONS: RANGE LINE ROAD

SHEET

E



Notes



Wisconsin Department of Transportation

Dedicated people creating transportation solutions
through innovation and exceptional service.

<http://www.dot.wisconsin.gov>